



New Jersey Board of Public Utilities
New Jersey Clean Energy Program™
Protocols to Measure Resource Savings

**Revisions to
FY2016 Protocols**

Release Date: May 10, 2018
[Board Agenda Date: June 22, 2018]

New Jersey's Clean Energy Program Protocols

Style Definition: TOC 1

Style Definition: TOC 2

Style Definition: TOC 3

Style Definition: TOC 4

Style Definition: TOC 5

Style Definition: TOC 6

Style Definition: TOC 7

Style Definition: TOC 8

Style Definition: TOC 9

Style Definition: Table Text: Font: Times New Roman, 12 pt, Bold, Space Before: 6 pt, After: 3 pt

Formatted: Different first page header

Table of Contents

Formatted

Introduction.....	5
Purpose.....	5
Types of Protocols.....	6
Algorithms.....	8
Data and Input Values.....	10
Baseline Estimates.....	10
Resource Savings in Current and Future Program Years.....	11
Prospective Application of the Protocols.....	11
Resource Savings.....	11
<i>Electric.....</i>	<i>11</i>
<i>Natural Gas.....</i>	<i>12</i>
<i>Other Resources.....</i>	<i>13</i>
Post Implementation Review.....	13
Adjustments to Energy and Resource Savings.....	13
<i>Coincidence with Electric System Peak.....</i>	<i>13</i>
<i>Measure Retention and Persistence of Savings.....</i>	<i>13</i>
<i>Interaction of Energy Savings.....</i>	<i>13</i>
Calculation of the Value of Resource Savings.....	14
Transmission and Distribution System Losses.....	14
<i>Electric Loss Factor.....</i>	<i>14</i>
<i>Gas Loss Factor.....</i>	<i>14</i>
Calculation of Clean Air Impacts.....	15
Measure Lives.....	15
Protocols for Program Measures.....	15
Residential Electric HVAC.....	16
Protocols.....	16
<i>Central Air Conditioner (A/C) & Air Source Heat Pump (ASHP).....</i>	<i>16</i>
<i>Ground Source Heat Pumps (GSHP).....</i>	<i>17</i>
<i>GSHP Desuperheater.....</i>	<i>17</i>
<i>Furnace High Efficiency Fan.....</i>	<i>17</i>
<i>Solar Domestic Hot Water (augmenting electric resistance DHW).....</i>	<i>17</i>
<i>Heat Pump Hot Water (HPHW).....</i>	<i>17</i>
<i>Drain Water Heat Recovery (DWHR).....</i>	<i>18</i>
<i>Combined space and water heating (Combo).....</i>	<i>23</i>
Residential Gas HVAC.....	24
Protocols.....	24
<i>Space Heaters.....</i>	<i>24</i>
<i>Water Heaters.....</i>	<i>26</i>
Residential Low Income Program.....	29
Protocols.....	29
<i>Efficient Lighting.....</i>	<i>29</i>
<i>Hot Water Conservation Measures.....</i>	<i>30</i>
<i>Efficient Refrigerators.....</i>	<i>34</i>
<i>Air Sealing.....</i>	<i>35</i>
<i>Duct Sealing and Repair.....</i>	<i>35</i>
<i>Insulation Up Grades.....</i>	<i>36</i>
<i>Thermostat Replacement.....</i>	<i>36</i>
<i>Heating and Cooling Equipment Maintenance Repair/Replacement.....</i>	<i>36</i>

<i>Other “Custom” Measures</i>	37
Residential New Construction Program	41
Protocols.....	41
<i>Single-Family, Multi-Single and Low-Rise Multifamily Building Shell</i>	41
Multifamily High Rise (MFHR) Protocols	45
<i>Multifamily High Rise (MFHR)</i>	45
ENERGY STAR Products Program	47
<i>ENERGY STAR Appliances, ENERGY STAR Lighting, ENERGY STAR Windows, and ENERGY STAR Audit</i>	47
ENERGY STAR Appliances	47
Protocols.....	47
<i>ENERGY STAR Refrigerators—CEE Tier 1</i>	47
<i>ENERGY STAR Refrigerators—CEE Tier 2</i>	47
<i>ENERGY STAR Clothes Washers—CEE Tier 1</i>	47
<i>ENERGY STAR Clothes Washers—CEE Tier 2</i>	47
<i>ENERGY STAR Set Top Boxes</i>	48
<i>Advanced Power Strip—Tier 1</i>	48
<i>Advanced Power Strip—Tier 2</i>	48
<i>ENERGY STAR Electric Clothes Dryers—Tier 1</i>	48
<i>ENERGY STAR Gas Clothes Dryers—Tier 1</i>	48
<i>ENERGY STAR 2014 Emerging Technology Award Electric Clothes Dryers—Tier 2</i>	48
<i>ENERGY STAR 2014 Emerging Technology Award Gas Clothes Dryers—Tier 2</i>	49
<i>ENERGY STAR Room AC—Tier 1</i>	49
<i>ENERGY STAR Room AC—Tier 2</i>	49
<i>ENERGY STAR Room Air Purifier</i>	49
<i>ENERGY STAR Freezer</i>	50
<i>ENERGY STAR Soundbar</i>	50
Residential ENERGY STAR Lighting.....	55
Home Energy Reporting System.....	63
Protocols.....	63
<i>Home Energy Reporting System</i>	63
Refrigerator/Freezer Retirement Program.....	63
Protocols.....	63
Home Performance with ENERGY STAR Program	65
Commercial and Industrial Energy Efficient Construction	66
C&I Electric Protocols.....	66
<i>Baselines and Code Changes</i>	66
<i>Building Shell</i>	66
<i>Performance Lighting</i>	66
<i>Prescriptive Lighting</i>	69
<i>Lighting Controls</i>	71
<i>Motors</i>	72
<i>Electric HVAC Systems</i>	77
<i>Fuel Use Economizers</i>	81
<i>Dual Enthalpy Economizers</i>	81
<i>Electric Chillers</i>	82
<i>Variable-Frequency Drives</i>	85
<i>Air Compressors with Variable-Frequency Drives</i>	86
<i>New and Retrofit Kitchen Hoods with Variable-Frequency Drives</i>	87
<i>Commercial Refrigeration Measures</i>	91

C&I Construction Gas Protocols.....	95
<i>Gas Chillers</i>	95
<i>Gas Fired Desiccants</i>	97
<i>Gas Booster Water Heaters</i>	98
<i>Water Heaters</i>	99
<i>This prescriptive measure targets solely the use of smaller scale domestic water heaters (50 gallons or less per unit) in all commercial facilities. Larger gas water heaters are treated under the custom measure path. The measurement of energy savings for C&I gas water heaters is based on algorithms with key variables (i.e., energy factor) provided by manufacturer data.</i>	99
<i>Prescriptive Boilers</i>	101
<i>Fuel Use Economizers</i>	106
Distributed Energy Resource (DER) Program.....	107
Protocols.....	107
<i>Distributed Generation</i>	107
<i>Energy Savings</i>	107
<i>Emission Reductions</i>	107
<i>Sustainable Biomass</i>	109
Pay for Performance Program.....	110
Protocols.....	110
Direct Install Program.....	114
Protocols.....	114
Electric HVAC Systems.....	114
Motors.....	115
Variable Frequency Drives.....	115
Refrigeration Measures.....	116
Gas Space and Water Heating Measures.....	122
<i>Gas Furnaces and Boilers</i>	122
Small Commercial Boilers.....	122
<i>Gas and Propane Infrared Heating</i>	122
<i>Gas Water Heating</i>	123
Food Service Measures.....	123
Occupancy Controlled Thermostats.....	133
Dual-Enthalpy Economizers.....	134
Electronic Fuel Use Economizers.....	136
Low Flow Devices.....	137
Demand Control Ventilation Using CO ₂ Sensors.....	138
Pipe Insulation.....	139
<i>Lighting and Lighting Controls</i>	140
C&I Large Energy Users Incentive Program.....	141
Protocols.....	141
C&I Customer Tailored Energy Efficiency Pilot Program.....	141
Protocols.....	141
Renewable Energy Program Protocols.....	142
SREC Registration Program (SRP).....	142
Renewable Non-SRP.....	142
Renewable Electric Storage.....	142
Appendix A – Measure Lives.....	143
Introduction.....	7

<u>Purpose</u>	7
<u>Types of Protocols</u>	8
<u>Algorithms</u>	11
<u>Data and Input Values</u>	13
<u>Baseline Estimates</u>	13
<u>Resource Savings in Current and Future Program Years</u>	14
<u>Prospective Application of the Protocols</u>	14
<u>Resource Savings</u>	15
<i>Electric</i>	15
<i>Natural Gas</i>	16
<i>Other Resources</i>	16
<u>Adjustments to Energy and Resource Savings</u>	16
<i>Coincidence with Electric System Peak</i>	16
<i>Interaction of Energy Savings</i>	17
<u>Calculation of the Value of Resource Savings</u>	17
<u>Transmission and Distribution System Losses</u>	18
<i>Electric Loss Factor</i>	18
<i>Gas Loss Factor</i>	18
<u>Calculation of Clean Air Impacts</u>	18
<u>Measure Lives</u>	19
<u>Protocols Revision History</u>	20
<u>Protocols for Program Measures</u>	20
<u>Residential Electric HVAC</u>	21
<u>Protocols</u>	21
<i>Central Air Conditioner (A/C) & Air Source Heat Pump (ASHP) & Mini-split (AC or HP)</i>	21
<i>Ground Source Heat Pumps (GSHP)</i>	24
<i>GSHP Desuperheater [Inactive 2017, Not Reviewed]</i>	24
<i>Furnace High Efficiency Fan</i>	24
<i>Solar Domestic Hot Water (augmenting electric resistance DHW) [Inactive 2017, Not Reviewed]</i>	25
<i>Heat Pump Hot Water (HPHW)</i>	25
<i>Drain Water Heat Recovery (DWHR) [Inactive 2017, Not Reviewed]</i>	25
<u>Residential Gas HVAC</u>	33
<u>Protocols</u>	33
<i>Furnaces</i>	33
<i>Boilers</i>	37
<i>Combination Boilers</i>	39
<i>Boiler Reset Controls</i>	41
<i>Stand Alone Storage Water Heaters</i>	42
<i>Instantaneous Water Heaters</i>	44
<u>Residential Low Income Program</u>	46
<u>Protocols</u>	46
<i>Efficient Lighting</i>	46
<i>Hot Water Conservation Measures</i>	48
<i>Water heater pipe wrap</i>	53
<i>Efficient Refrigerators</i>	54
<i>Air Sealing</i>	54
<i>Furnace/Boiler Replacement</i>	55
<i>Duct Sealing and Repair</i>	55
<i>Insulation Upgrades</i>	55

<i>Thermostat Replacement</i>	56
<i>Heating and Cooling Equipment Maintenance Repair/Replacement</i>	56
<i>Gas HVAC Repairs</i>	56
<i>Other “Custom” Measures</i>	58
Residential New Construction Program	63
Protocols.....	63
<i>Single-Family, Multi-Single (townhomes), Low-Rise Multifamily</i>	63
<i>Multifamily High Rise (MFHR)</i>	68
ENERGY STAR Energy Efficient Products	71
Protocols.....	71
<i>ENERGY STAR Appliances</i>	71
<i>Residential ENERGY STAR Lighting</i>	80
Appliance Recycling Program	88
Protocols.....	88
Home Performance with ENERGY STAR Program	96
Commercial and Industrial Energy Efficient Construction	98
Protocols.....	98
C&I Electric Protocols	98
<i>Performance Lighting</i>	98
<i>Prescriptive Lighting</i>	103
<i>Refrigerated Case LED Lights</i>	107
<i>Specialty LED Fixtures</i>	109
<i>Lighting Controls</i>	112
<i>Motors [Inactive 2017, Not Reviewed]</i>	114
<i>Electronically Commutated Motors for Refrigeration</i>	118
<i>Electric HVAC Systems</i>	122
<i>Fuel Use Economizers</i>	129
<i>Dual Enthalpy Economizers</i>	130
<i>Occupancy Controlled Thermostats</i>	132
<i>Electric Chillers</i>	136
<i>Variable Frequency Drives</i>	141
<i>Variable Speed Air Compressors</i>	144
<i>New and Retrofit Kitchen Hoods with Variable Frequency Drives</i>	146
<i>Energy Efficient Glass Doors on Vertical Open Refrigerated Cases</i>	151
<i>Aluminum Night Covers</i>	155
<i>Walk-in Cooler/Freezer Evaporator Fan Control</i>	156
<i>Cooler and Freezer Door Heater Control</i>	159
<i>Medium Temperature (Cooler) Door Heater Control</i>	160
<i>Electric Defrost Control</i>	161
<i>Novelty Cooler Shutoff</i>	162
Food Service Measures Protocols	164
<i>Electric and Gas Combination Oven/Steamer</i>	164
<i>Electric and Gas Convection Ovens, Gas Conveyor and Rack Ovens, Steamers, Fryers, and Griddles</i>	168
<i>Insulated Food Holding Cabinets</i>	173
<i>Commercial Dishwashers</i>	175
<i>Commercial Refrigerators and Freezers</i>	177
<i>Commercial Ice Machines</i>	178
C&I Gas Protocols	181
<i>Gas Chillers</i>	181

<i>Gas Fired Dessicants</i>	187
<i>Gas Booster Water Heaters</i>	187
<i>Stand Alone Storage Water Heaters</i>	189
<i>Instantaneous Gas Water Heaters</i>	194
<i>Prescriptive Boilers</i>	198
<i>Prescriptive Furnaces</i>	202
<i>Infrared Heaters</i>	205
<i>Electronic Fuel Use Economizers</i>	207
Combined Heat & Power Program	209
Protocols.....	209
<i>Distributed Generation</i>	209
<i>Energy Savings Impact</i>	210
<i>Emission Reductions</i>	210
<i>CHP Emissions Reduction Associated with PJM Grid</i>	210
<i>Sustainable Biomass Biopower</i>	212
Pay for Performance Program	213
Protocols.....	213
Direct Install Program	218
Protocols.....	218
<i>Electric HVAC Systems</i>	218
<i>Motors [Inactive 2017, Not Reviewed]</i>	219
<i>Variable Frequency Drives</i>	220
<i>Refrigeration Measures</i>	220
<i>Vending Machine Controls</i>	221
<i>Gas Water Heating Measures</i>	229
<i>Gas Space Heating Measures</i>	230
<i>Small Commercial Boilers [Inactive 2017, Not Reviewed]</i>	231
<i>Gas, Oil, and Propane Furnaces</i>	231
<i>Infrared Heating</i>	232
<i>Programmable Thermostats</i>	233
<i>Boiler Reset Controls</i>	246
<i>Dual Enthalpy Economizers</i>	248
<i>Electronic Fuel-Use Economizers (Boilers, Furnaces, AC)</i>	248
<i>Demand-Controlled Ventilation Using CO₂ Sensors</i>	249
<i>Low Flow Faucet Aerators, Showerheads, and Pre-rinse Spray Valves</i>	252
<i>Pipe Insulation</i>	258
<i>Lighting and Lighting Controls</i>	261
C&I Large Energy Users Incentive Program	262
Protocols.....	262
C&I Customer-Tailored Energy Efficiency Pilot Program	262
Protocols.....	262
Renewable Energy Program Protocols	263
SREC Registration Program (SRP).....	263
Appendix A Measure Lives	264

New Jersey Clean Energy Program Protocols to Measure Resource Savings

Introduction

These protocols have been developed to measure resource savings, including electric energy capacity, natural gas, and other resource savings, and to measure electric energy and capacity from renewable energy and distributed generation systems. -Specific protocols for determination of the resource savings or generation from each program are presented for each eligible measure and technology.

Formatted: Space Before: 6 pt, After: 6 pt

These protocols use measured and customer data as input values in industry-accepted algorithms. -The data and input values for the algorithms come from the program application forms or from standard values. -The standard input values are based on the recent impact evaluations and best available measured or industry data applicable for the New Jersey programs when impact evaluations are not available.

Formatted: Space Before: 6 pt, After: 6 pt

Purpose

These protocols were developed for the purpose of determining energy and resource savings for technologies and measures supported by New Jersey's Clean Energy Program. -The protocols will be updated from time to time to reflect the addition of new programs, modifications to existing programs, and the results of future program evaluations. -The protocols will be used consistently statewide to assess program impacts and calculate energy and resource savings to:

Formatted: Space Before: 6 pt, After: 6 pt

1. Report to the Board on program performance
2. Provide inputs for planning and cost-effectiveness calculations
3. Provide information to regulators and program administrators for determining eligibility for administrative performance incentives (to the extent that such incentives are approved by the BPU)
4. Assess the environmental benefits of program implementation

Formatted: Space Before: 6 pt, After: 6 pt

Resource savings to be measured include electric energy (kWh) and capacity (kW) savings, natural gas savings (therms), and savings of other resources (oil, propane, water, and maintenance), where applicable. -In turn, these resource savings will be used to determine avoided environmental emissions. -The Protocols are also utilized to support preliminary estimates of the electric energy and capacity from renewable energy and distributed generation systems and the associated environmental benefits. -Note,

Formatted: Space Before: 6 pt, After: 6 pt

however, that renewable energy protocols are different from those required for REC certification in the state of New Jersey.

The protocols in this document focus on the determination of the per unit savings for the energy efficiency measures, and the per unit generation for the renewable energy or distributed generation measures, included in the current programs approved by the Board. The number of adopted units to which these per unit savings or avoided generation apply are captured in the program tracking and reporting process, supported by market assessments for some programs. -The unit count will reflect the direct participation and, through market assessments, the number of units due to market effects in comparison to a baseline level of adoptions. -The protocols report gross savings and generation only. -Free riders and free drivers are not addressed in these Protocols. - Further research in this area is planned.

Formatted: Space Before: 6 pt, After: 6 pt

The outputs of the Protocols are used to support:

- Regulatory ~~Reporting~~reporting
- Cost ~~Effectiveness Analysis~~effectiveness analysis
- Program ~~Evaluation~~evaluation
- Performance ~~Incentives~~incentives for the ~~Market Managers~~market managers

Formatted: Space Before: 6 pt, After: 6 pt

These Protocols provide the methods to measure per unit savings for program tracking and reporting. -An annual evaluation plan prepared by the ~~Center for Energy, Economic and Environmental Policy (CEEEP)~~NJCEP Evaluation Contractor outlines the plans for assessing markets including program progress in transforming markets, and to update key assumptions used in the Protocols to assess program energy impacts. -Reporting provides formats and definitions to be used to document program expenditures, participation rates, and program impacts, including energy and resource savings. -The program tracking systems, that support program evaluation and reporting, will track and record the number of units adopted due to the program, and assist in documenting the resource savings using the per unit savings values in the Protocols. -Cost benefit analyses prepared by ~~CEEEP and other evaluation contractors~~NJCEP Evaluation Contractors assesses the impact of programs, including market effects, and their relationship to costs in a multi-year analysis.

Formatted: Space Before: 6 pt, After: 6 pt

Types of Protocols

In general, energy and demand savings will be measured using measured and customer data as input values in algorithms in the protocols, tracking systems, and information from the program application forms, worksheets, and field tools.

Formatted: Space Before: 6 pt, After: 6 pt

The following table summarizes the spectrum of protocols and approaches to be used for measuring energy and resource savings. -No one protocol approach will serve all programs and measures.

Formatted: Space Before: 6 pt, After: 6 pt

|

Summary of Protocols and Approaches

Type of Measure	Type of Protocol	General Approach	Examples
1.- Standard prescriptive measures	Standard formula and standard input values	Number of installed units times standard savings/unit	Residential lighting (number of units installed times standard savings/unit)
2.- Measures with important variations in one or more input values (e.g., delta watts, efficiency level, capacity, load, etc.)	Standard formula with one or more site-specific input values	Standard formula in the protocols with one or more input values coming from the application form, worksheet, or field tool (e.g., delta watts, efficiency levels, unit capacity, site-specific load)	<p>Some prescriptive lighting measures (delta watts on the application form times standard operating hours in the protocols)</p> <p>Residential Electric HVAC (change in efficiency level times site-specific capacity times standard operating hours)</p> <p>Field screening tools that use site-specific input values</p> <p>Customer On-Site Renewable Energy</p>
3.- Custom or site-specific measures, or measures in complex comprehensive jobs	Site-specific analysis	Greater degree of site-specific analysis, either in the number of site-specific input values, or in the use of special engineering algorithms, including building simulation programs	<p>Custom</p> <p>Industrial process</p> <p>Complex comprehensive jobs (P4P)</p> <p>CHP</p> <p>Customer-Tailored Pilot</p>

Formatted: Font: Not Bold

Formatted: Space Before: 6 pt, After: 3 pt

Formatted: Space After: 1 pt

Formatted Table

Formatted: Space After: 2 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Three or four systems will work together to ensure accurate data on a given measure:

Formatted: Space Before: 6 pt, After: 6 pt

1. The application form that the customer or customer's agent submits with basic information.
2. Application worksheets and field tools with more detailed site-specific data, input values, and calculations (for some programs).
3. Program tracking systems that compile data and may do some calculations.
4. Protocols that contain algorithms and rely on standard or site-specific input values based on measured data. -Parts or all of the protocols may ultimately be implemented within the tracking system, the application forms and worksheets, and the field tools.

Formatted: Space Before: 3 pt, After: 3 pt

Algorithms

The algorithms that have been developed to calculate the energy and or demand savings are driven by a change in efficiency level for the installed measure compared to a baseline level of efficiency. -This change in efficiency is reflected in both demand and energy savings for electric measures and energy savings for gas. ~~Following are the basic algorithms.~~

Formatted: Space Before: 6 pt, After: 6 pt

~~Electric Demand Savings = $\Delta kW = kW_{\text{baseline}} - kW_{\text{energy efficient measure}}$~~

~~Electric Energy Savings = $\Delta kW \times EFLH$~~

~~Electric Peak Coincident Demand Savings = $\Delta kW \times \text{Coincidence Factor}$~~

~~Gas Energy Savings = $\Delta Btuh \times EFLH$~~

~~Where: —~~

~~EFLH = Equivalent Full Load Hours of operation for the installed measure. Total annual energy use (kWh) of an end use over a range of operating conditions divided by the connected full load of the end use in kW.~~

~~$\Delta Btuh = Btuh_{\text{baseline input}} - Btuh_{\text{energy efficient measure input}}$~~

~~Other resource savings will be calculated as appropriate.~~

Specific algorithms for each of the program measures may incorporate additional factors to reflect specific conditions associated with a program or measure. -This may include factors to account for coincidence of multiple installations, or interaction between different measures.

Formatted: Space Before: 6 pt, After: 6 pt

When building simulation software programs are used to develop savings estimates for several measures in a comprehensive project, as in the Pay for Performance Program, the specific algorithms used are inherent in the software and account for interaction among measures by design. Detailed Simulation Guidelines have been developed for the Pay for Performance Program and are included in the Pay for Performance Program Guidelines. These Guidelines should be followed when building simulation is used to develop savings estimates. ~~As stated in the Guidelines, simulation software must be compliant with ASHRAE 90.1 2004 Section 11 or Appendix G.~~

Formatted: Space Before: 6 pt, After: 6 pt

Data and Input Values

The input values and algorithms in the protocols and on the program application forms are based on the best available and applicable data for the New Jersey programs. -The input values for the algorithms come from the program application forms or from standard values based on measured or industry data.

Formatted: Space Before: 6 pt, After: 6 pt

Many input values, including site-specific data, come directly from the program application forms, worksheets, and field tools. -Site-specific data on the application forms are used for measures with important variations in one or more input values (e.g., delta watts, efficiency level, capacity, etc.).

Formatted: Space Before: 6 pt, After: 6 pt

Standard input values are based on the best available measured or industry data, including metered data, measured data from prior evaluations (applied prospectively), field data and program results, and standards from industry associations. -The standard values for most commercial and industrial measures are based on recent impact evaluations of New Jersey Programs.

Formatted: Space Before: 6 pt, After: 6 pt

For the standard input assumptions for which metered or measured data were not available, the input values (e.g., Δ watts, Δ efficiency, equipment capacity, operating hours, coincidence factors) were based on the best available industry data or standards. -These input values were based on a review of literature from various industry organizations, equipment manufacturers, and suppliers.

Formatted: Space Before: 6 pt, After: 6 pt

For larger, comprehensive projects, as in the Pay for-Performance Program, measurement and verification (M&V) protocols are followed to better estimate site-specific energy use for the pre- and post-retrofit conditions. -Guidelines for developing an M&V plan and protocols to follow for conducting M&V are included in the Pay for Performance Program Guidelines, available on the NJ Office of Clean Energy website at www.njcleanenergy.com. -These guidelines and protocols should be followed when M&V is conducted to determine energy use for either the pre- or post-retrofit period.

Formatted: Space Before: 6 pt, After: 6 pt

Program evaluation will be used to assess key data and input values to either confirm that current values should continue to be used or update the values going forward.

Formatted: Space Before: 6 pt, After: 6 pt

Baseline Estimates

For most efficiency programs and measures, the Δ kW, Δ kWh, and gas energy savings values are based on the energy use of standard new products vs. the high efficiency products promoted through the programs. -The approach used for the new programs encourages residential and business consumers to purchase and install high efficiency equipment vs. new standard efficiency equipment. -The baseline estimates used in the

Formatted: Space Before: 6 pt, After: 6 pt

protocols are documented in the baseline studies or other market information. -Baselines will be updated to reflect changing codes, practices and market transformation effects.

For the Direct Install and Low Income programs, some Δ kW, Δ kWh, and gas energy savings values are based on high efficiency equipment versus existing equipment, where the programs specifically target early retirement or upgrades that would not otherwise occur. -Protocols for the Direct Install Program include degradation tables to calculate the efficiency of the replaced unit.

Formatted: Space Before: 6 pt, After: 6 pt

The Pay for Performance Program is a comprehensive program that requires participants to implement energy efficiency improvements that will achieve a minimum of 15% reduction in total source energy consumption. -Due to the building simulation and measurement and verification (M&V) requirements associated with this Program, the baseline is the existing energy consumption of the facility, as reported through the U.S. EPA's Portfolio Manager benchmarking software.

Formatted: Space Before: 6 pt, After: 6 pt

Renewable energy and distributed generation program protocols assume that any electric energy or capacity produced by a renewable energy or distributed generation system displaces electric energy and capacity from the PJM grid.

Formatted: Space Before: 6 pt, After: 6 pt

Resource Savings in Current and Future Program Years

The Protocols support tracking and reporting the following categories of energy and resource savings:

Formatted: Space Before: 6 pt, After: 6 pt

1. Savings or generation from installations that were completed in the program year and prior program years due to the program's direct participation and documented market effects.
2. Savings or generation from program participant future adoptions due to program commitments.
3. Savings or generation from future adoptions due to market effects.

Formatted: Space Before: 3 pt, After: 3 pt

Prospective Application of the Protocols

The protocols will be applied prospectively. -The input values are from the program application forms and standard input values (based on measured data including metered data and evaluation results). -The protocols will be updated periodically based on evaluation results and available data, and then applied prospectively for future program years.

Resource Savings

Electric

Protocols have been developed to determine the electric energy and coincident peak demand savings.

Annual Electric energy savings are calculated and then allocated separately by season (summer and winter) and time of day (on-peak and off-peak). -Summer coincident peak demand savings are calculated using a demand savings protocol for each measure that includes a coincidence factor. -Application of this coincidence factor converts the demand savings of the measure, which may not occur at time of system peak, to demand savings that is expected to occur during the Summer On-Peak period. -These periods for energy savings and coincident peak demand savings are defined as:

	Energy Savings	Coincident Peak Demand Savings
Summer	May through September	June through August
Winter	October through April	NA
On Peak (Monday - Friday)	8:00 a.m. to 8:00 p.m.	12:00 p.m. to 8:00 p.m.
Off Peak	M-F 8:00 p.m. to 8:00 a.m. All day weekends and holidays	NA

The time periods for energy savings and coincident peak demand savings were chosen to best fit the seasonal avoided cost patterns for electric energy and capacity that were used for the energy efficiency program cost effectiveness purposes. -For energy, the summer period May through September was selected based on the pattern of avoided costs for energy at the PJM level. -In order to keep the complexity of the process for calculating energy savings benefits to a reasonable level by using two time periods, the knee periods for spring and fall were split approximately evenly between the summer and winter periods.

For capacity, the summer period June through August was selected to match the highest avoided costs time period for capacity. -The experience in PJM and New Jersey has been that nearly all system peak events occur during these three months. -Coincidence factors are used to calculate energy efficiency factors on peak demand. -Renewable energy and distributed generation systems are assumed to be operating coincident with the PJM system peak. -This assumption will be assessed in the impact evaluation.

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Keep with next, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Font: Bold

Formatted: Space After: 1 pt

Formatted Table

Formatted: Font: Bold

Formatted: Space After: 2 pt

Formatted: Font: Bold

Formatted: Space After: 2 pt

Formatted: Font: Bold

Formatted: Space After: 2 pt

Formatted: Font: Bold

Formatted: Space After: 2 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Natural Gas

Protocols have been developed to determine the natural gas energy savings on a seasonal basis. -The seasonal periods are defined as:

Summer = April through September

Winter = October through March

The time periods for gas savings were chosen to best fit the seasonal avoided gas cost pattern that was used for calculating energy efficiency program benefits for cost effectiveness purposes. -However, given the changing seasonal cost patterns for gas supply, different time periods may be more appropriate to reflect a current outlook for the seasonal pattern, if any, at the time that the avoided cost benefits are calculated. -The seasonal factors used in the following protocols that correspond to the above time periods reflect either base load or heating load usage. -In the case of base load, one twelfth of the annual use is allocated to each month. - In the case of heating load, the usage is prorated to each month based on the number of normal degree-days in each month. -This approach makes it relatively easy to calculate new seasonal factors to best match different avoided cost patterns.

Other Resources

Some of the energy savings measures also result in environmental benefits and the saving of other resources. -Environmental impacts are quantified based on statewide conversion factors supplied by the NJDEP for electric, gas, and oil energy savings. Where identifiable and quantifiable these other key resource savings, such as oil, will be estimated. -Oil and propane savings are the major resources that have been identified. - If other resources are significantly impacted, they will be included in the resource savings estimates.

Post-Implementation Review

~~Program administrators will review application forms and tracking systems for all measures and conduct field inspections on a sample of installations. For some programs and jobs (e.g., custom, large process, large and complex comprehensive design), post-installation review and on-site verification of a sample of application forms and installations will be used to ensure the reliability of site-specific savings estimates.~~

Adjustments to Energy and Resource Savings

Coincidence with Electric System Peak

Coincidence factors are used to reflect the portion of the connected load savings or generation that is coincident with the electric system peak.

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space After: 0 pt

Formatted: Space Before: 6 pt

Measure Retention and Persistence of Savings

~~The combined effect of measure retention and persistence is the ability of installed measures to maintain the initial level of energy savings or generation over the measure life. Measure retention and persistence effects were accounted for in the metered data that were based on C&I installations over an eight year period. As a result, some protocols incorporate retention and persistence effects in the other input values. For other measures, if the measure is subject to a reduction in savings or generation over time, the reduction in retention or persistence is accounted for using factors in the calculation of resource savings (e.g., in-service rates for residential lighting measures, degradation of photovoltaic systems).~~

Interaction of Energy Savings

Interaction of energy savings is accounted for in certain programs as appropriate. For all other programs and measures, interaction of energy savings is zero.

Formatted: Space Before: 6 pt, After: 6 pt

For the Residential New Construction program, the interaction of energy savings is accounted for in the home energy rating tool that compares the efficient building to the baseline or reference building and calculates savings.

Formatted: Space Before: 6 pt, After: 6 pt

For the Residential and Commercial and Industrial Efficient Construction program, the energy savings for lighting is increased by an amount specified in the protocol to account for HVAC interaction.

For commercial and industrial custom measures, interaction where relevant is accounted for in the site-specific analysis. In the Pay for Performance Program, interaction is addressed by the building simulation software program.

Formatted: Space Before: 6 pt, After: 6 pt

Calculation of the Value of Resource Savings

The calculation of the value of the resources saved is not part of the protocols. The protocols are limited to the determination of the per unit resource savings in physical terms.

Formatted: Space Before: 6 pt, After: 6 pt

In order to calculate the value of the energy savings for reporting and other purposes, the energy savings are determined at the customer level and then increased by the amount of the transmission and distribution losses to reflect the energy savings at the system level. The energy savings at the system level are then multiplied by the appropriate avoided costs to calculate the value of the benefits.

Formatted: Space Before: 6 pt, After: 6 pt

System Savings = (Savings at Customer) ~~X~~ (T&D Loss Factor)

Value of Resource Savings = (System Savings) ~~X~~ (System Avoided Costs + Environmental Adder) + (Value of Other Resource Savings)

The value of the benefits for a particular measure will also include the value of the water, oil, maintenance and other resource savings where appropriate. -Maintenance savings will be estimated in annual dollars levelized over the life of the measure.

Formatted: Space Before: 6 pt

Transmission and Distribution System Losses

The protocols calculate the energy savings at the customer level. -These savings need to be increased by the amount of transmission and distribution system losses in order to determine the energy savings at the system level. -The following loss factors multiplied by the savings calculated from the protocols will result in savings at the supply level.

Electric Loss Factor

The electric loss factor applied to savings at the customer meter is ~~1.076081~~^{1,2} for both energy and demand. -The electric system loss factor was developed to be applicable to statewide programs. -~~Therefore, average system losses at the margin based on a 10 year (2001 to 2010) average of the New Jersey state electricity supply and disposition dataset from the U.S. Energy Information Administration (EIA).~~

Gas Loss Factor

The gas loss factor is 1.0. -The gas system does not have losses in the same sense that the electric system does. - All of the gas gets from the “city gate” (delivery point to the distribution system) to the point of use except for unaccounted for gas (such as theft), gas lost due to system leakage or loss of gas that is purged when necessary to make system repairs. -Since none of these types of “losses” is affected by a decrease in gas use due to energy efficiency at the customer, there are no losses for which to make any adjustment. Therefore, a system loss factor of 1.0 is appropriate for gas energy efficiency savings.

Formatted: Space Before: 6 pt, After: 6 pt

These electric and gas loss factors reflect losses at the margin and are a consensus of the electric and gas utilities.

Formatted: Space Before: 6 pt, After: 6 pt

Calculation of Clean Air Impacts

The amount of air emission reductions resulting from the energy savings are calculated using the energy savings at the system level and multiplying them by factors developed by ~~the New Jersey Department of Environmental Protection (NJDEP).~~ Pennsylvania-New Jersey-Maryland Interconnection (PJM) for electric emissions and US EPA for natural gas emissions.

Formatted: Space Before: 6 pt, After: 6 pt

¹ JPC&L, Summary of reconciliation factors January 1, 2017 – December 31, 2017.

² PSE&G Rate Class & Loss Factor Information

System average marginal on-peak air electric emissions reduction factors provided by the NJDEPPJM are³:

Formatted: Space Before: 6 pt, After: 6 pt

Electric Emissions Factors

Formatted: Table Caption, Left

Emissions Product	Jan 2001-June 2002	July 2003-February 2014	March 2014-Present
CO₂ Emission s Product	1.1 lbs 2014 Lbs per kWh saved	1,520 lbs 2015 Lbs per MWh saved	2016, 111.79 lbs Lbs per MWh saved
NO _x CO ₂	6.42 lbs per metric ton of CO ₂ saved 1.646	2.8 lbs per MWh saved 1.647	0.95 lbs per MWh saved 1.617
NO _x	1.74	1.80	1.48
SO ₂	10.26 lbs per metric ton of CO ₂ saved 5.2	6.5 lbs per MWh saved 3.34	2.21 lbs per MWh saved 1.73
Hg	0.00005 lbs per metric ton of CO ₂ saved	0.0000356 lbs per MWh saved	2.11 mg per MWh saved

Formatted Table

Formatted: Font: 12 pt

Formatted: Table Header

Formatted: Table Header

Formatted: Table Header

Formatted: Table Header

Formatted: Centered, Space After: 2 pt

Formatted Table

Formatted: Centered, Space After: 2 pt

System natural gas emissions reduction factors provided by US EPA are⁴:

Natural Gas Emissions Factors

Formatted: Table Caption, Left, Space Before: 6 pt

Emissions Product	Jan 2001-June 2002	Current
CO ₂	NA	118 Lbs/MMBtu
NO _x	NA	0.0092 lbs per therm saved 0.12 Lbs/MMBtu
SO ₂		0.0006 Lbs/MMBtu

Deleted Cells

Formatted: Table Header, Left

Formatted Table

Formatted: Space After: 2 pt

Deleted Cells

Formatted: Space After: 2 pt

All factors are provided by the NJ Department of Environmental Protection and are on an average system basis. They will be updated as new factors become available.

Measure Lives

Measure lives are provided in Appendix A for informational purposes and for use in other applications such as reporting lifetime savings or in benefit cost studies that span more than one year. -The Pay for Performance Program uses the measure lives as included in Appendix A to determine measure-level and project-level cost effectiveness.

³ PJM report; "2012-2016 CO₂, SO₂ and NO_x Emission Rates," March 2017. <http://www.pjm.com/-/media/library/reports-notice/special-reports/20170317-2016-emissions-report.ashx?la=en>

⁴ US EPA AP-42: AP-42, Compilation of Air Pollutant Emission Factors, 5th Edition, Chapter 1.4 Natural Gas Combustion <https://www3.epa.gov/ttnchie1/ap42/ch01/final/c01s04.pdf>.

Protocols Revision History

Revision History of Protocols

<u>Date Issued</u>	<u>Reviewer</u>	<u>Comments</u>
<u>October 2017</u>	<u>ERS</u>	<u>See ERS Memo, NJCEP Protocols - Comparative Measure Life Study and Summary of Measure Changes to NJCEP Protocols, September 5, 2017. Updated October 16, 2017, January 12, 2018.</u>
<u>May 2018</u>	<u>Program Administrator in consultation with Board Staff</u>	<u>Revisions to the January 12, 2018 version issued by ERS to reflect discussions at Utility Working Group Meetings, additional comments from Rate Counsel and further review of public comments.</u>

Protocols for Program Measures

The following pages present measure or project-specific protocols.- In those instances where measures are applicable to more than one program, the measures apply to all such programs unless otherwise specified.

Formatted: Space Before: 6 pt, After: 6 pt

Residential Electric HVAC

Protocols

The measurement plan for residential high efficiency cooling and heating equipment is based on algorithms that determine a central air conditioners or heat pump’s cooling/heating energy use and peak demand. -Input data is based both on fixed assumptions and data supplied from the high efficiency equipment rebate application form. -The algorithms also include the calculation of additional energy and demand savings due to the required proper sizing of high efficiency units.

The savings will be allocated to summer/winter and on-peak/off-peak time periods based on load shapes from measured data and industry sources. -The allocation factors are documented below in the input value table.

The protocols applicable for this program measure the energy savings directly related to the more efficient hardware installation. -Estimates of energy savings due to the proper sizing of the equipment are also included.

The following is an explanation of the algorithms used and the nature and source of all required input data.

Central Air Conditioner (A/C) & Air Source Heat Pump (ASHP) & Mini-split (AC or HP)

Algorithms

Central Air Conditioner (A/C) & Air Source Heat Pump (ASHP)

Cooling Energy ~~Consumption~~ and Peak Demand Savings—Central A/C & ASHP (High Efficiency Equipment Only):

$$\text{Energy Impact Savings (kWh)} = \frac{\text{CAPY}}{(1/\text{SEER}_b - 1/\text{SEER}_q) \times \text{EFLH}_c} = \text{Tons} * 12 \text{ kBtuh/Ton} *$$

$$\text{Peak Demand Impact Savings (kW)} = \frac{\text{CAPY}}{1/\text{EER}_b} \times \text{Tons} * 12 \text{ kBtuh/Ton} * (1/\text{EER}_b - 1/\text{EER}_q) \times \text{CF}$$

Heating Energy Savings —(ASHP and Mini-Split):

$$\text{Energy Impact Savings (kWh)} = \frac{\text{CAPY}}{(1/\text{HSPF}_b - 1/\text{HSPF}_q) \times \text{EFLH}_h} = \text{Tons} * 12 \text{ kBtuh/Ton} *$$

Cooling Proper Sizing and Quality Installation Verification (QIV):

Formatted: Keep with next

Formatted

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: English (U.S.)

Formatted: Font: Not Italic

Formatted: Indent: Left: 0"

Formatted: Font: Not Italic

Formatted: None, Indent: Left: 0"

Formatted: None, Indent: Left: 0", First line: 0"

Formatted: None, Indent: Left: 0"

Formatted: Indent: Left: 0"

Formatted: Font: Not Italic

Formatted: Normal, Indent: First line: 0"

Formatted: Font: Not Italic

Formatted: Indent: Left: 0"

Energy Savings *for Proper Sizing and QIV*
 $(kWh_p = kWh_q / yr) = kWh_q * ESF$

Formatted: Font: Not Italic

Formatted: Indent: Left: 0"

Cooling Demand Energy Savings for Proper Sizing and QIV

Formatted: Indent: Left: 0", First line: 0"

Formatted: Font: Not Italic

$kW_p = (kW/yr) = kW_q * DSF$

Formatted: Font: Not Italic

~~Cooling Energy Consumption and Demand Savings—Central A/C & ASHP~~

During Existing System Maintenance):

~~Energy Impact Savings (kWh) = ((CAPY/(1000 X)Savings (kWh/yr) = (Tons * 12 kBtuh/Ton * SEER_m)) X) * EFLH_c) X * MF~~

~~Peak Demand Impact Savings (kW) = ((CAPY/(1000 X) = (Tons * 12 kBtuh/Ton * EER_m)) X) * CF) X * MF~~

~~Cooling Energy Consumption and Demand Savings – Central A/C & ASHP – (Duct Sealing):~~

~~Energy Impact Savings (kWh) = (CAPY / (1000 X) / yr) = (Tons * 12 kBtuh/Ton * SEER_g) X) * EFLH_c X * DuctSF~~

~~Peak Demand Impact Savings (kW) = ((CAPY / (1000 X) (Tons * 12 kBtuh/Ton * EER_g) X) * CF) X * DuctSF~~

Ground Source Heat Pumps (GSHP)

Algorithms

~~Cooling Energy (kWh) Savings = CAPY/1000 X (kWh/yr) = Tons * 12 kBtuh/Ton * (1/(EER_{g,b} X * GSER) - (1/ (EER_g X * GSER))) X * EFLH_c~~

~~Peak Demand Savings (kW) = Tons * 12 kBtuh/Ton * (1/EER_{g,b} - (1/ (EER_g * GSPK))) * CF~~

~~Heating Energy Savings (kWh) Savings = CAPY/1000 X/yr) = Tons * 12 kBtuh/Ton * (1/(COP_{g,b} X * GSOP) - (1/ (COP_g X * GSOP))) X * EFLH_h~~

~~Peak Demand Impact (kW) = CAPY/1000 X (1/EER_{g,b} - (1/ (EER_g X GSPK))) X CF~~

GSHP Desuperheater [Inactive 2017, Not Reviewed]

Energy (kWh) Savings = EDSH

Peak Demand Impact (kW) = PDSH

Furnace High Efficiency Fan

Algorithms

Formatted: Font: Not Bold, Not Italic

Formatted: Font: Not Bold, Not Italic

Formatted: Indent: Left: 0"

Formatted: Subscript

Formatted: Subscript

Formatted: Font: Not Bold, Not Italic

Formatted: Font: Not Bold, Not Italic

Formatted: Indent: Left: 0"

Formatted: Subscript

Formatted: Subscript

Formatted: English (U.S.)

Formatted: Font: Not Bold, English (U.S.)

Formatted: Font: Not Bold

Formatted: None, Indent: Left: 0.25"

Formatted: Font: 8 pt, Raised by 3 pt, Kern at 18 pt

Formatted: None, Indent: Left: 0"

Formatted: Indent: Left: 0.25"

Formatted: Heading 3, Indent: Left: 0"

Formatted: Indent: Left: 0"

Formatted: Indent: Left: 0"

Formatted: Heading 3

Formatted: English (U.S.)

Formatted: Font: Not Bold

$$\text{Heating Energy (kWh) Savings} = \frac{((\text{CAPY}_q \times \text{EFLH}_{HT}) / 100,000 \text{ BTU/therm})}{\text{kWh/yr}} = (\text{Cap}_q / 3.412 \text{ kWh/Btu}) * \text{EFLH}_h * \text{FFS}_{HT}$$

Formatted: Indent: Left: 0.25", First line: 0"

$$\text{Cooling Energy (kWh) Savings (kWh/yr)} = \text{FFS}_{CL}$$

Formatted: Subscript

Formatted: Indent: Left: 0"

Solar Domestic Hot Water (augmenting electric resistance DHW) [Inactive 2017, Not Reviewed]

Formatted: Keep with next

Formatted: Indent: Left: 0"

$$\text{Heating Energy (kWh) Savings} = \text{ESav}_{SDHW}$$

$$\text{Peak Demand Impact (kW)} = \text{DSav}_{SDHW} * \text{CF}_{SDHW}$$

Formatted: Indent: Left: 0", First line: 0.25"

Heat Pump Hot Water (HPHW)

$$\text{Heating Energy (kWh) Savings (kWh/yr)} = \text{ESav}_{HPHW}$$

Formatted: Don't keep with next

Formatted: Indent: Left: 0", Don't keep with next

$$\text{Peak Demand Impact Savings (kW)} = \text{DSav}_{HPHW} * \text{CF}_{HPHW}$$

Formatted: Indent: Left: 0", First line: 0", Don't keep with next

Formatted: Indent: Left: 0", First line: 0.25"

Formatted: Subscript

Drain Water Heat Recovery (DWHR) [Inactive 2017, Not Reviewed]

$$\text{Heating Energy (kWh) Savings} = \text{ESav}_{DWHR}$$

Formatted: Indent: Left: 0"

$$\text{Peak Demand Impact (kW)} = \text{DSav}_{DWHR} * \text{CF}_{DWHR}$$

Formatted: Indent: Left: 0", First line: 0.25"

Definition of Terms

CAPY_{Tons} = The rated cooling capacity (output) of the central air conditioner or heat pump unit being installed. -This data is obtained from the Application Form based on the model number.

Formatted: Space Before: 3 pt, After: 3 pt

SEER_b = The Seasonal Energy Efficiency Ratio of the Baseline Unit.

Formatted: Space Before: 3 pt, After: 3 pt

SEER_q = The Seasonal Energy Efficiency Ratio of the qualifying unit being installed. This data is obtained from the Application Form based on the model number.

Formatted: Space Before: 3 pt, After: 3 pt

SEER_m = The Seasonal Energy Efficiency Ratio of the Unit receiving maintenance

Formatted: Space Before: 3 pt, After: 3 pt

EER_m = The Energy Efficiency Ratio of the Unit receiving maintenance

EER_b = The Energy Efficiency Ratio of the Baseline Unit.

Formatted: Space Before: 3 pt, After: 3 pt

EER_q = The Energy Efficiency Ratio of the unit being installed. This data is obtained from the Application Form based on the model number.

Formatted: Space Before: 3 pt, After: 3 pt

$EER_{g,q}$ = The EER of the ground source heat pump being installed. - Note that EERs of GSHPs are measured differently than EERs of air source heat pumps (focusing on entering water temperatures rather than ambient air temperatures). -The equivalent SEER of a GSHP can be estimated by multiplying EER_g by 1.02.

Formatted: Space Before: 3 pt, After: 3 pt

$EER_{g,b}$ = The EER of a baseline ground source heat pump

Formatted: Space Before: 3 pt, After: 3 pt

GSER = The factor to determine the SEER of a GSHP based on its EER.

Formatted: Space Before: 3 pt, After: 3 pt

EFLH = The Equivalent Full Load Hours of operation for the average unit- (cooling or heating)

Formatted: Space Before: 3 pt, After: 3 pt

ESF = The Energy Savings Factor or the assumed saving due to proper sizing and proper installation.

Formatted: Space Before: 3 pt, After: 3 pt

MF = The Maintenance Factor or assumed savings due to completing recommended maintenance on installed cooling equipment.

Formatted: Space Before: 3 pt, After: 3 pt

DuctSF = The Duct Sealing Factor or the assumed savings due to proper sealing of all cooling ducts

Formatted: Space Before: 3 pt, After: 3 pt

CF = The coincidence factor which equates the installed unit's connected load to its demand at time of system peak.

Formatted: Space Before: 3 pt, After: 3 pt

DSF = The Demand Savings Factor or the assumed peak demand capacity saved due to proper sizing and proper installation.

Formatted: Space Before: 3 pt, After: 3 pt

$HSPF_b$ = The Heating Seasonal Performance Factor of the Baseline Unit.

Formatted: Space Before: 3 pt, After: 3 pt

$HSPF_q$ = The Heating Seasonal Performance Factor of the unit being installed. This data is obtained from the Application Form.

Formatted: Space Before: 3 pt, After: 3 pt

$COP_{g,q}$ = Coefficient of Performance of a GSHP

Formatted: Space Before: 3 pt, After: 3 pt

$COP_{g,b}$ = Baseline Coefficient of Performance of a GSHP

Formatted: Space Before: 3 pt, After: 3 pt

GSOP = The factor to determine the HSPF of a GSHP based on its COP.

Formatted: Space Before: 3 pt, After: 3 pt

GSPK = The factor to convert EER_g to the equivalent EER of an air conditioner to enable comparisons to the baseline unit.

Formatted: Space Before: 3 pt, After: 3 pt

EDSH = Assumed savings per desuperheater.

PDSH = Assumed peak demand savings per desuperheater.

ESav_{SDHW} = Assumed energy savings per installed solar domestic hot water system with electric resistance heater backup.

DSav_{SDHW} = Assumed demand savings per installed solar domestic hot water system with electric resistance heater backup.

Formatted: Space Before: 3 pt, After: 3 pt

~~CAP_{YY}~~~~Cap_q~~ = Output capacity of the qualifying heating unit in BTUs/hour

Formatted: Space Before: 3 pt, After: 3 pt

~~EFLH_{HT}~~~~EFLH~~ = The Equivalent Full Load Hours of operation for the average heating unit

Formatted: Space Before: 3 pt, After: 3 pt

FFS_{HT} = Furnace fan savings (heating mode)

Formatted: Space Before: 3 pt, After: 3 pt

FFS_{CL} = Furnace fan savings (cooling mode)

Formatted: Space Before: 3 pt, After: 3 pt

~~kWh_p~~ = Annual kWh due to proper sizing

kWh_q = Annual kWh usage post-program

Formatted: Space Before: 3 pt, After: 3 pt

~~kW_p~~ = Annual kW due to proper sizing

kW_q = Annual kW usage post-program

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{HPHW} = Assumed energy savings per installed heat pump water heater.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{HPHW} = Assumed demand savings per installed heat pump water heater.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{DWHR} = Assumed energy savings per installed drain water heat recovery unit in a household with an electric water heater.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{DWHR} = Assumed demand savings per installed drain water heat recovery unit in a household with an electric water heater.

Formatted: Space Before: 3 pt, After: 3 pt

The 1000 used in the denominator is used to convert watts to kilowatts.

A summary of the input values and their data sources follows:

Summary of Inputs

Residential Electric HVAC

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>CAPY</u> Tons	Variable	<u>Rated Capacity, Tons</u>	Rebate Application
SEER _b	Fixed	<u>Split Systems (A/C-Baseline)</u> = 13 <u>ASHP-Baseline Split Systems (HP)</u> = 14 <u>Single Package (A/C) = 14</u> <u>Single Package (HP) = 14</u>	1a
SEER _q	Variable		Rebate Application
SEER _m	Fixed	10.13	15.1
EER _b	Fixed	Baseline = 11.3	2
EER _q	Fixed	= (11.3/13) * SEER _q	2
EER _g	Variable		Rebate Application
EER _{g,b}	Fixed	11.2	28.12
EER _m	Fixed	8.69	19.2
GSER	Fixed	1.02	3
<u>EFLH</u> / <u>EFLH_{c or h}</u>	Fixed	<u>Cooling = 600 Hours</u> <u>Heating = 965 Hours</u>	4.11
ESF	Fixed	9.2%	22.10
DSF	Fixed	9.2%	22.10
kWh _q	Variable		Rebate Application
kW _q	Variable		Rebate Application
MF	Fixed	10%	20.3
DuctSF	Fixed	18%	14.13
CF	Fixed	70.69%	6.4
DSF	Fixed	2.9%	7.5

Formatted: Keep with next

Formatted: Table Text, Left

Formatted: Table Header, Don't keep with next

Formatted Table

Formatted: Table Header

Formatted: Table Header, Indent: Left: 0"

Formatted: Subscript

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Component	Type	Value	Source
HSPF _b	Fixed	Baseline = 88.2 Split Systems (HP) = 8.2 Single Package (HP) = 8.0	81
HSPF _q	Variable		Rebate Application
COP _g	Variable		Rebate Application
COP _{g,b}	Fixed	2.9	28 12
GSOP	Fixed	3.413	96
GSPK	Fixed	0.8416	40 3
EDSH	Fixed	1842 kWh	44 3
PDSH	Fixed	0.34 kW	42 3
ESav _{SDHW}	Fixed	3100 kWh	21 14
DSav _{SDHW}	Fixed	0.426 kW	21 14
CF _{SDHW}	Fixed	20%	21 14
ESav_{HPHW} ESAV_{HP} HW	Fixed	1687 kWh	23 15
DSav _{HPHW}	Fixed	0.37 kW	24 16
CF _{HPHW}	Fixed	70%	24 16
ESav_{DWHR} ESAV_D WHR	Fixed	1457 kWh	26, 23 15, 18
DSav _{DWHR}	Fixed	0.142 kW	27 19
CF _{DWHR}	Fixed	20%	27 19
Cooling – CAC Time Period Allocation Factors	Fixed	Summer/On-Peak 64.9% Summer/Off-Peak 35.1% Winter/On-Peak 0% Winter/Off-Peak 0%	43 7
Cooling – ASHP Time Period Allocation Factors	Fixed	Summer/On-Peak 59.8% Summer/Off-Peak 40.2% Winter/On-Peak 0% Winter/Off-Peak 0%	43 7
Cooling – GSHP Time Period Allocation Factors	Fixed	Summer/On-Peak 51.7% Summer/Off-Peak 48.3% Winter/On-Peak 0% Winter/Off-Peak 0%	43 7
Heating – ASHP & GSHP Time Period Allocation Factors	Fixed	Summer/On-Peak 0.0% Summer/Off-Peak 0.0% Winter/On-Peak 47.9% Winter/Off-Peak 52.1%	43 7

Formatted: Table Header, Don't keep with next

Formatted: Table Header

Formatted: Table Header, Indent: Left: 0"

Formatted Table

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Subscript

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Subscript

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Centered, Space After: 2 pt

Formatted: Subscript

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Subscript

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Subscript

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt, Don't keep with next

Formatted: Centered, Space After: 2 pt

Formatted

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Formatted: Centered, Space After: 2 pt

Component	Type	Value	Source
GSHP Desuperheater Time Period Allocation Factors	Fixed	Summer/On-Peak 4.5% Summer/Off-Peak 4.2% Winter/On-Peak 43.7% Winter/Off-Peak 47.6%	137
SDHW Time Period Allocation Factors	Fixed	Summer/On-Peak 27.0% Summer/Off-Peak 15.0% Winter/On-Peak 42.0% Winter/Off-Peak 17.0%	214
HPWH Time Period Allocation Factors	Fixed	Summer/On-Peak 21% Summer/Off-Peak 22% Winter/On-Peak 28% Winter/Off-Peak 29%	2517
DWHR Time Period Allocation Factors	Fixed	Summer/On-Peak 27.0% Summer/Off-Peak 15.0% Winter/On-Peak 42.0% Winter/Off-Peak 17.0%	214
Cap _{yq}	Variable		Rebate Application
EFLH_{HT}	Fixed	965 hours	16
F _{FSHT}	Fixed	0.5 kWh	178
F _{FSCL}	Fixed	105 kWh	189

Sources:

- ~~1. a Survey of New Jersey HVAC equipment distributors, CLEAResult, March 2016~~
- ~~b Federal Register, 76 FR 37408, June 27, 2011~~
1. US Government Publishing Office, June 2017, *Electronic Code of Federal Regulations – Title 10, Chapter II, Subchapter D, Part 430, Subpart C, §430.32*. Available at: https://www.ecfr.gov/cgi-bin/text-idx?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.
2. Average EER for SEER 13 units. The same EER to SEER ratio used for SEER 13 units applied to SEER 10 units. $EER_m = (11.3/13) * 10$.
3. VEIC estimate. -Extrapolation of manufacturer data.
- ~~4. VEIC estimate. NEEP, Mid-Atlantic Technical Reference Manual, V7, May 2017.~~
- ~~4.1. Consistent with analysis of PEPCo and LIPA, and conservative relative to ARI.~~
- ~~5. Xenergy, "New Jersey Residential HVAC Baseline Study", (Xenergy, Washington, D.C., November 16, 2001).~~
- ~~6. NEEP, Mid-Atlantic Technical Reference Manual, May 2010.~~
- ~~7.5. Xenergy, "New Jersey Residential HVAC Baseline Study", (Xenergy, Washington, D.C., November 16, 2001) Table E-8.~~

- Formatted: Table Header, Don't keep with next
- Formatted: Table Header
- Formatted: Table Header, Indent: Left: 0"
- Formatted Table
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt
- Formatted: Centered, Space After: 2 pt

- Formatted: Space After: 3 pt
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Tab stops: 2.19", Left
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

~~8. Federal Register, Vol. 66, No. 14, Monday, January 22, 2001/ Rules and Regulations, p. 7170-7200.~~

~~9-6. Engineering calculation, HSPF/COP=3.413~~

~~10. VEIC Estimate. Extrapolation of manufacturer data.~~

~~11. VEIC estimate, based on PEPCo assumptions.~~

~~12. VEIC estimate, based on PEPCo assumptions.~~

~~13-7. Time period allocation factors used in cost-effectiveness analysis.~~

~~14. Northeast Energy Efficiency Partnerships, Inc., "Benefits of HVAC Contractor Training", (February 2006): Appendix C Benefits of HVAC Contractor Training: Field Research Results 03-STAC-01~~

~~15. Minimum Federal Standard for new Central Air Conditioners between 1990 and 2006~~

~~16. NJ utility analysis of heating customers, annual gas heating usage~~

~~8. "Review of Emerging HVAC Technologies and Practices" 03-STAC-01 Emerging Technologies Report, October 2005, John Proctor, PE, p. 46.~~

~~17-9. Scott Pigg (Energy Center of Wisconsin), "Electricity Use by New Furnaces: -A Wisconsin Field Study", Technical Report 230-1, October 2003.~~

~~10. KEMA, NI Clean Energy Program Energy Impact Evaluation Protocol Review. 2009.~~

~~11. VEIC Estimate. Consistent with analysis of PEPCo and LIPA, and conservative relative to ARI.~~

~~18. Ibid., p. 34. ARI charts suggest there are about 20% more full load cooling hours in NJ than southern WI. Thus, average cooling savings in NJ are estimated at 95 to 115~~

~~12. AHRI directory; baseline values are the least efficient "Geothermal - Water-to -Air Heat Pumps" active in the directory, downloaded May 18, 2015.~~

~~13. NEEP, "Benefits of HVAC Contractor Training," Appendix C, February 2006.~~

~~19. The same EER to SEER ratio used for SEER 13 units applied to SEER 10 units. $EER_m = (11.3/13) * 10$~~

~~20. VEIC estimate. Conservatively assumes less savings than for QIV because of the retrofit context~~

~~21-14. Energy savings are estimated based on 2008 SRCC OG300 ratings for a typical 2 panel system with solar storage tank in Newark, NJ with electric DHW backup. Demand savings are estimated based on an estimated electric DHW demand of 2.13kW with 20% CF. Load shape and coincidence factors were developed by VEIC from ASHRAE Standard 90.2 Hot Water Draw Profile and NREL Red Book insulation data for Newark, NJ.~~

~~22-1. KEMA, NJ Clean Energy Program Energy Impact Evaluation Protocol Review. 2009.~~

~~23-15. Table 1. (Page 2) From "Heat Pump Water Heaters Evaluation of Field Installed Performance." Steven Winter Associates, Inc. (2012). http://www.ma-eeac.org/Docs/8.1_EMV%20Page/2012/2012%20Residential%20Studies/MA%20RR&LI%20-~~

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Tab stops: 2.19", Left

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

%202011%20HPWH%20Field%20Evaluation%20Report%20FINAL%206_26_2012.pdf

24.16. VEIC Estimate based upon range derived from FEMP Federal Technology Alert: S9508031.3a (http://www1.eere.energy.gov/femp/pdfs/FTA_res_heat_pump.pdf)

Formatted: Default Paragraph Font

25.17. “Electrical Use, Efficiency, and Peak Demand of Electric Resistance, Heat Pump, Desuperheater, and Solar Hot Water Systems”,
<http://www.fsec.ucf.edu/en/publications/html/FSEC-PF-215-90/>

Formatted: Default Paragraph Font

26.18. 30% savings (from Zaloum, C. Lafrance, M. Gusdorf, J. “Drain Water Heat Recovery Characterization and Modeling” Natural Resources Canada. 2007. Savings vary due to a number of factors including make, model, installation-type, and household behaviors.) multiplied by standard electric resistance water heating baseline annual usage of 4,857 kWh cited in source #23 above.

27.19. Demand savings are estimated based on electric DHW demand of 2.13kW and 20% CF as in cited source #21 adjusting for the proportional difference of 30% savings relative to the 70% solar fraction: $0.426 * 0.3 / 0.9 = 0.142$.

~~28. AHRI directory. Baseline values are the least efficient “Geothermal—Water to—Air Heat Pumps” active in the directory, downloaded May 18, 2015.~~

Combined space and water heating (Combo)

~~Participants installing a qualifying boiler or furnace and a qualifying water heater at the same time earn a special incentive. For savings calculations, there is no special consideration. The heating system savings are calculated according to the appropriate algorithm and the water heating savings are calculated separately according to the system type.~~

Residential Gas HVAC

Protocols

The following ~~two algorithms~~ sections detail savings calculations for gas space heating and gas water heating equipment in residential applications. They are to be used to determine gas energy savings between baseline standard units and the high efficiency units promoted in the program. ~~The input values are based on data on typical customers supplied by the gas utilities, an analysis by the Federal Energy Management Program (FEMP), and customer information on the application form, confirmed with manufacturer data. The energy values are in therms.~~

Furnaces

This section provides energy savings algorithms for qualifying gas and oil furnaces installed in residential settings. The input values are based on the specifications of the actual equipment being installed, federal equipment efficiency standards, and the most recent impact evaluation of the residential Warm and Cool Advantage programs (2009).

This measure applies to replacement of failed equipment or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by IECC 2015, which is the current residential code adopted by the state of New Jersey.

Algorithms

Space Heaters

Algorithms

$$\text{Gas Fuel Savings} = \left[\left(\text{Cap}_{y_q} (\text{MMBtu}/\text{yr}) = \text{Cap}_{in} * \text{EFLH}_h * \left(\frac{\text{AFUE}_q}{\text{AFUE}_b} \right) - \left(\text{Cap}_{y_q} / \text{AFUE}_q \right) \right) * \text{EFLH} / 100,000 \text{ BTUs}/\text{therm} \right]$$

$$\text{Low Income Gas Savings} = \left[\left(\text{Cap}_{y_q} / \text{AFUE}_{Li} \right) - \left(\text{Cap}_{y_q} / 1 \right) / \text{AFUE}_q \right] * \text{EFLH} / 100,000 \text{ BTUs}/\text{therm}$$

$$\text{Gas Savings due to duct sealing} = \left(\text{Cap}_{avg} * \text{AFUE}_{avg} \right) * \text{EFLH} * \left(\text{DuctSF}_w / 100,000 \text{ BTUs}/\text{therm} \right)$$

$$\text{Average Heating Use (therms)} = \left(\text{Cap}_{avg} / \text{AFUE}_{avg} \right) * \text{EFLH} / 100,000 \text{ BTUs}/\text{therm}$$

$$\text{EFLH} = \left(\text{Average Heating Use} * \text{AFUE}_{avg} * 100,000 \text{ BTUs}/\text{therm} \right) / \text{Cap}_{avg}$$

$$\text{Oil Savings for a qualifying boiler} = \text{OsavBOILER}$$

$$\text{Oil Savings} = \left[\left(\text{Cap}_{y_q} / \text{AFUE}_b \right) - \left(\text{Cap}_{y_q} / \text{AFUE}_q \right) \right] * \text{EFLH} / 100,000 \text{ BTUs}/\text{therm}$$

$$\text{Circulator Pumps Savings (kWh)} = \text{Hours} * \left(\text{Watts}_{Base} - \text{Watts}_{EE} \right) / 1000 \text{ kBTu/MMBtu}$$

Formatted: Font: Bold

Formatted: Heading 4

Formatted: Font: Not Bold, English (U.S.)

Formatted: Font: Not Bold

Formatted: Indent: Left: 0.25", Space Before: 6 pt

Definition of Variables

~~Cap_{y,q} = Output~~ ~~Cap_{in} = Input~~ capacity of qualifying unit ~~output~~ in ~~BTUs~~ ~~kBtu~~/hour

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

~~Cap_{y,t} = Output capacity of the typical heating unit output in Btus/hour~~

~~Cap_{y,avg} = Output capacity of the average heating unit output in Btus/hour~~

~~EFLH~~ ~~EFLH_t~~ = The Equivalent Full Load Hours of operation per year for the average unit: during the heating season

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

~~DuctSF_h = The Duct Sealing Factor or the assumed savings due to proper sealing of all heating ducts~~

~~AFUE_{avg} = Annual Fuel Utilization Efficiency of the average furnace or boiler~~

~~AFUE_q = Annual Fuel Utilization Efficiency of the qualifying baseline-furnace or boiler~~

Formatted: English (U.S.)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

~~AFUE_b = Annual Fuel Utilization Efficiency of the baseline furnace or boiler~~

Formatted: English (U.S.)

~~AFUE_{LI} = Annual Fuel Utilization Efficiency of the Low Income Program-replaced furnace or boiler.~~

~~Average Heating Usage = The weighted average annual heating usage (therms) of typical New Jersey heating customers~~

~~Watts_{Base} = Baseline-connected kW~~

~~Watts_{EE} = Efficient-connected kW~~

Space Heating

Component	Type	Value	Source
Cap_{y,q}	Variable		Application
Cap_{y,t}	Fixed	CAP_{Y,Q}	1
DuctSF_h	Fixed	13%	5
AFUE_{avg}	Variable		Application
AFUE_q	Variable		Application
AFUE_b	Fixed	Gas Furnaces: 80% Gas Boilers: Water— 82% Steam—80% Oil Boilers: Water—	2

Component	Type	Value	Source
		84% Steam—82% Electric Resistance Heating—35%	
AFUE _{LI}	Variable		Application or utility estimates
EFLH ⁵	Fixed	965 hours	3
Avg. Heating Usage	Fixed	860 therms	5
Time Period Allocation Factors	Fixed	Summer = 12% Winter = 88%	4
WattsBase	Fixed	87.8	8
WattsEE	Fixed	14.4	8
Hours	Fixed	2350	9

meeting current federal equipment

Sources:

1. NJ Residential HVAC Baseline Study
2. Federal minimum standards as of 2015.
3. NJ utility analysis of heating customers, annual gas heating usage
4. Prorated based on 12% of the annual degree days falling in the summer period and 88% of the annual degree days falling in the winter period.
5. Northeast Energy Efficiency Partnerships, Inc., “Benefits of HVAC Contractor Training”, (February 2006): Appendix C Benefits of HVAC Contractor Training: Field Research Results 03-STAC-01
6. KEMA, *NJ Clean Energy Program Energy Impact Evaluation Protocol Review*, 2009.
7. Electric resistance heat calculated by determining the overall fuel cycle efficiency by dividing the average PJM heat rate (9,642 BTU per kWh) by the BTUs per kWh (3,413 BTU per kWh), giving a 2.83 BTU_{in} per BTU_{out}.
8. Efficiency Vermont Technical Reference Manual
9. Boiler run hours, based on Efficiency Vermont TRM methodology, where boilers have EFLH of 810 and the circ pump run hours are 1973. Therefore for NJ with 965 EFLH, the run hours can be estimated as $965 * 1973 / 810 = 2350$

Formatted: English (U.S.)

Formatted: Body Text Indent 3, Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt, No bullets or numbering

Water Heaters

Algorithms

Gas Savings = $((EF_q - EF_b) / EF_q) \times \text{Baseline Water Heater Usage}$

Formatted: Font: Not Bold

Formatted: Heading 3

~~Gas Savings (Solar DHW) = GsavSHW~~

Formatted: Font: Bold, Italic

⁵ Residential Gas Measures EFLH are subject to change barring the results of impact evaluations.

Gas Savings (Drain Water Heat Recover) = GsavDWHR * Baseline Water Heater Usage

Formatted: Normal

Definition of Variables

EF_q = Energy factor of the qualifying energy efficient water heater.

Note: For qualifying units not rated with an Energy Factor, the estimated EF_q shall be used:

Est. EF_q = Q_{out}/Q_{in}
 = 41,094⁶ / (41,094/TE + Volume*SLratio*24hours)

Where: TE = Thermal (or Recovery) Efficiency of the unit as a percentage

Volume = Volume of storage water heater, in gallons.

SLratio = Average ratio of rated standby losses water heater (BTU loss per hour for > 90% TE units less than 130 Gallons = 9.73⁷)

Gas & Propane Tankless Water Heaters[†]: EF_b = 0.82 - (0.0019 * Gallons of Capacity)

Gas & Propane Storage or Power Vented Water Heaters[†]:

55 gallons or less: EF_b = 0.675 - (0.0015 * Gallons of Capacity)

56 gallons or more: EF_b = 0.8012 - (0.00078 * Gallons of Capacity)

Summary of Inputs

Furnace Assumptions

Baseline Water Heater Usage = Annual usage of the baseline water heater, in therms.

GsavSHW = Gas savings, in therms, for a solar hot water installation augmented by a new gas hot water heater.

GsavDWHR = Gas savings, as a percentage, for a drain water heat recovery installation in a home with a gas hot water heater.

Water Heaters

Component	Type	Value	Source
EF _q Cap _{in}	Variable		Application Form, confirmed with Manufacturer Data

Formatted: Table Header, Left

Formatted Table

Formatted: Space After: 2 pt

⁶Based upon the test conditions of the DOE test protocol for residential water heaters, the amount of energy delivered is equal to 64.3 gallons * density of water (8.3lb/gal) * Specific heat of water (1 BTU/lb-F) and the temperature rise of 77degF (135F-58F).

⁷Based upon February, 2012 query of ARHI/GAMA database <http://cafs.ahrinet.org/gama-cafs/sdpsearch/search.jsp?table=CWH>

Component	Type	Value	Source
$TEEFLH_t$	<u>Fixed</u> Variable	<u>965 hours</u>	Application Form, confirmed with Manufacturer Data 1
$AFUE_q$ Stdy	Variable		Application Form, confirmed with Manufacturer Data
EF_t	Variable	For Electric Resistance (only): 35%	Application Form, confirmed with Manufacturer Data
$AFUE_t$ Baseline Water Heater Usage	Fixed	180 therms Weatherized gas: 81% Weatherized oil: 78% Mobile home gas: 80% Mobile home oil: 75% Non-weatherized gas: 80% Non-weatherized oil: 83%	2
Time Period Allocation Factors	Fixed	Summer = 50% Winter = 50%	3
$GSavSHW$	Fixed	130.27	4
$GSavDWHR$	Fixed	30%	5

Sources:

1. NJ utility analysis of heating customers, annual gas usage.
2. US Government Publishing Office, June 2017, *Electronic Code of Federal Regulations – Title 10, Chapter II, Subchapter D, Part 430, Subpart C, §430.32*; available at: https://www.ecfr.gov/cgi-bin/text-id.x?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.

Boilers

This section provides energy savings algorithms for qualifying boilers installed in residential settings. The input values are based on the specifications of the actual equipment being installed, federal equipment efficiency standards, and the most recent impact evaluation of the residential Warm and Cool Advantage programs (2009).

This measure applies to replacement of failed equipment or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by IECC 2015, which is the current residential code adopted by the state of New Jersey.

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = \text{Cap}_{in} * \text{EFLH}_h * ((\text{AFUE}_q / \text{AFUE}_b) - 1) / 1000 \text{ kBTu/MMBtu}$$

Definition of Variables

Cap_{in} = Input capacity of qualifying unit in kBtu/hour

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season in hours

AFUE_q = Annual Fuel Utilization Efficiency of the qualifying boiler

AFUE_b = Annual Fuel Utilization Efficiency of the baseline boiler

Summary of Inputs

Space Heating Boiler Assumptions

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Cap_{in}</u>	<u>Variable</u>		<u>Application</u>
<u>EFLH_h</u>	<u>Fixed</u>	<u>965 hours</u>	<u>1</u>
<u>AFUE_q</u>	<u>Variable</u>		<u>Application</u>
<u>AFUE_b</u>	<u>Fixed</u>	<u>Gas fired boiler – 82%</u> <u>Oil fired boiler – 84%</u>	<u>2</u>

Sources

1. NJ utility analysis of heating customers, annual gas usage..
2. US Government Publishing Office, June 2017, Electronic Code of Federal Regulations – Title 10, Chapter II, Subchapter D, Part 430, Subpart C, §430.32; available at: https://www.ecfr.gov/cgi-bin/text-id.x?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.

Formatted: Normal

Formatted: Font: Bold

Formatted: Normal

Formatted: Font: Not Bold

Combination Boilers

This section provides energy savings algorithms for qualifying gas combination boilers installed in residential settings. A combination boiler is defined as a boiler that provides domestic hot water and space heating. The input values are based on the specifications of the actual equipment being installed, federal equipment efficiency standards, DOE2.2 simulations completed by the New York State Joint Utilities and regional estimates of average baseline water heating energy usage.

This measure assumes the existing boiler system has failed or is at end of useful life and is replaced with a combination boiler. The baseline boiler unit has an efficiency as required by IECC 2015, which is the current residential code adopted by the state of New Jersey. For the water heating component, this measure assumes that the baseline water heater is a storage water heater, and customers replacing existing tankless water heaters are not eligible.

Note, that as of June 12, 2017, the Federal Trade Commission has published a final rule updating the EnergyGuide label to reflect recent changes by the Department of Energy to the Code of Federal Regulations regarding the use of uniform energy factor (UEF) rather than the traditional energy factor (EF)⁸ for consumer and commercial water heaters. The UEF is newest measure of water heater overall efficiency. The higher the UEF value is, the more efficient the water heater. UEF is determined by the Department of Energy's test method outlined in 10 CFR Part 430, Subpart B, Appendix E.⁹

Algorithms

1. Federal EPACK Standard Table II.1, revised April 16, 2015
2. KEMA. *NJ Clean Energy Program Energy Impact Evaluation Protocol Review: 2009.*
3. Prorated based on 6 months in the summer period and 6 months in the winter period.

Fuel Savings (MMBtu/yr) = MMBtu/yr Boiler Fuel Savings + MMBtu/yr DHW Fuel Savings

MMBtu Boiler Fuel Savings/yr = Cap_{in} * EFLH_h * ((AFUE_q/AFUE_b)-1) / 1,000
kBtu/MMBTU

MMBtu DHW Fuel Savings/yr = (1 - (UEF_b / UEF_q)) × Baseline Water Heater Usage

Cap_{in} = Input capacity of qualifying unit in kBtu/hr

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season

⁸ The final ruling on this change is available at:

https://energy.gov/sites/prod/files/2016/12/f34/WH_Conversion_Final%20Rule.pdf.

⁹ https://www.energystar.gov/products/water_heaters/residential_water_heaters_key_product_criteria

Formatted: Normal (Web)

Formatted: Font: Bold

AFUE_q = Annual fuel utilization efficiency of the qualifying boiler
AFUE_b = Annual fuel utilization efficiency of the baseline boiler
UEF_a = Uniform energy factor of the qualifying energy efficient water heater.
UEF_b = Uniform energy factor of the baseline water heater. In New Jersey the 2015 International Energy Conservation Code (IECC) generally defines the residential energy efficiency code requirements, but the IECC does not include residential service water heating provisions, leaving federal equipment efficiency standards to define baseline.
Baseline Water Heater Usage = Annual usage of the baseline water heater^{derived}

Summary of Inputs

Combination Boiler Assumptions

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Cap_{in}</u>	<u>Variable</u>		<u>Application</u>
<u>EFLH_h</u>	<u>Fixed</u>	<u>965 hours</u>	<u>1</u>
<u>AFUE_q</u>	<u>Variable</u>		<u>Application</u>
<u>AFUE_b</u>	<u>Fixed</u>	<u>Gas fired boiler – 82%</u> <u>Oil fired boiler – 84%</u>	<u>2</u>
<u>UEF_b</u>	<u>Fixed</u>	<u>Storage Water Heater – 0.657</u>	<u>2</u>
<u>UEF_q</u>	<u>Fixed</u>	<u>0.87</u>	<u>3</u>
<u>Baseline Water Heater Usage</u>	<u>Fixed</u>	<u>23.6 MMBtu/yr</u>	<u>4</u>

The referenced federal standards for the baseline UEF are dependent on both draw pattern and tank size. A weighted average baseline UEF was calculated with a medium draw pattern from the referenced federal standards and water heating equipment market data from the Energy Information Association 2009 residential energy consumption survey for NJ¹⁰ assuming tank sizes of 30 gallons for small units, 40 gallons for medium units, and 55 gallons for large units.

Sources US DOE estimates for the SEEARP (ENERGY STAR@

1. NJ utility analysis of heating customers, annual gas usage..
2. US Government Publishing Office, June 2017, Electronic Code of Federal Regulations – Title 10, Chapter II, Subchapter D, Part 430, Subpart C, §430.32; available at: https://www.ecfr.gov/cgi-bin/text-idc?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.

¹⁰ Available at: <https://www.eia.gov/consumption/residential/data/2009/hc/hc8.8.xls>

3. Minimum UEF for instantaneous (tankless) water heaters from Energy Star
https://www.energystar.gov/products/water_heaters/residential_water_heaters_key_product_criteria.

4. US Energy Information Association, 2009 Residential Energy Consumption Survey Data¹¹; available at:
<https://www.eia.gov/consumption/residential/data/2009/c&e/ce3.2.xlsx>

Formatted: Font: Italic

Boiler Reset Controls

The following algorithm details savings for installation of boiler reset control on residential boilers. Energy savings are realized through a better control of boiler water temperature. Through the use of software settings, boiler reset controls use outside or return water temperature to control boiler firing and in turn the boiler water temperature.

The input values are based on data supplied by the utilities and customer information on the application form, confirmed with manufacturer data. Unit savings are based on study results.

$$\text{Fuel Savings (MMBtu/yr)} = (\% \text{ Savings}) * (\text{EFLH}_h * \text{Cap}_{in}) / 1,000 \text{ kBtu/MMBtu}$$

Formatted: Indent: Left: 0", First line: 0"

Definition of Variables

% Savings = Estimated percentage reduction in heating load due to boiler reset controls

Formatted: (none)

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season

Formatted: Level 4, Keep with next

Cap_{in} = Input capacity of qualifying unit in kBtu/hr

Summary of Inputs

Boiler Reset Control Assumptions

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>% Savings</u>	<u>Fixed</u>	<u>5%</u>	<u>1</u>
<u>EFLH_h</u>	<u>Fixed</u>	<u>965 hours</u>	<u>2</u>
<u>Cap_{in}</u>	<u>Variable</u>		<u>Application</u>

Sources

Formatted: Font: Not Bold

1. GDS Associates, Inc., Natural Gas Energy Efficiency Potential in Massachusetts, 2009, p. 38, Table 6-4, http://ma-eeac.org/wordpress/wp-content/uploads/5_Natural-Gas-EE-Potential-in-MA.pdf.

2. NJ utility analysis of heating customers, annual gas usage..

¹¹ Data for 2015 will be available in 2018.

4. Stand Alone Storage Water Heaters: Final Criteria Analysis

Formatted: Heading 3, No bullets or numbering

This section provides energy savings algorithms for qualifying stand alone storage hot water heaters installed in residential settings. This measure assumes that the baseline water heater is a code storage water heater. The input values are based on federal equipment efficiency standards and regional estimates of average baseline water heating energy usage.

Note, that as of June 12, 2017, the Federal Trade Commission has published a final rule updating the EnergyGuide label to reflect recent changes by the Department of Energy to the Code of Federal Regulations regarding the use of uniform energy factor (UEF) rather than the traditional energy factor (EF)¹² for consumer and commercial water heaters. The UEF is newest measure of water heater overall efficiency. The higher the UEF value is, the more efficient the water heater. UEF is determined by the Department of Energy’s test method outlined in 10 CFR Part 430, Subpart B, Appendix E.¹³

Algorithms

Formatted: Heading 4

Fuel Savings (MMBtu/yr) = (1 – (UEF_b / UEF_q)) × Baseline Water Heater Usage

Formatted: Font: Bold

Formatted: No underline

Definition of Variables

Formatted: Heading 4

UEF_q = Uniform energy factor of the qualifying energy efficient water heater.

UEF_b = Uniform energy factor of the baseline water heater. In New Jersey the 2015 International Energy Conservation Code (IECC) generally defines the residential energy efficiency code requirements, but the IECC does not include residential service water heating provisions, leaving federal equipment efficiency standards to define baseline.

Baseline Water Heater Usage = Annual usage of the baseline water heater

Summary of Inputs

Storage Water Heater

<u>Component</u>	<u>Type</u>	<u>Value^a</u>	<u>Sources</u>
<u>UEF_q</u>	<u>Variable</u>		<u>Application</u>
<u>UEF_b</u>	<u>Variable</u>	<u>If gas & less than 55 gal: UEF_b = 0.6483–(0.0017×V)</u> <u>If gas & more than 55 gal: UEF_b = 0.7897–(0.0004×V)</u>	<u>1</u>
<u>Baseline Water</u>	<u>Fixed</u>	<u>23.6 MMBtu/yr</u>	<u>2</u>

¹² The final ruling on this change is available at: https://energy.gov/sites/prod/files/2016/12/f34/WH_Conversion_Final%20Rule.pdf

¹³ https://www.energystar.gov/products/water_heaters/residential_water_heaters_key_product_criteria

<u>Component</u>	<u>Type</u>	<u>Value^a</u>	<u>Sources</u>
<u>Heater Usage</u>			

^a V refers to volume of the installed storage water heater tank in gallons

[▲] The referenced federal standards for the baseline UEF are dependent on both draw pattern and tank size. The baseline UEF formulas shown in the table above are associated with medium draw patterns.

Formatted: Underline

Sources

1. US Government Publishing Office, June 2017, *Electronic Code of Federal Regulations – Title 10, Part 430, Subpart C*; available at: https://www.ecfr.gov/cgi-bin/text-idx?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.
2. US Energy Information Association, *2009 Residential Energy Consumption Survey Data¹⁴*; available at: <https://www.eia.gov/consumption/residential/data/2009/c&e/ce3.2.xlsx>.

¹⁴ Data for 2015 will be available in 2018.

Instantaneous Water Heaters

This section provides energy savings algorithms for qualifying instantaneous hot water heaters installed in residential settings. This measure assumes that the baseline water heater is either a code stand alone storage water heater, or an code instantaneous water heater. The input values are based on federal equipment efficiency standards and regional estimates of average baseline water heating energy usage.

Note, that as of June 12, 2017, the Federal Trade Commission has published a final rule updating the EnergyGuide label to reflect recent changes by the Department of Energy to the Code of Federal Regulations regarding the use of uniform energy factor (UEF) rather than the traditional energy factor (EF)¹⁵ for consumer and commercial water heaters. The UEF is newest measure of water heater overall efficiency. The higher the UEF value is, the more efficient the water heater. UEF is determined by the Department of Energy’s test method outlined in 10 CFR Part 430, Subpart B, Appendix E.¹⁶

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = (1 - (\text{UEF}_b / \text{UEF}_q)) \times \text{Baseline Water Heater Usage}$$

Definition of Variables

UEF_q = Uniform energy factor of the qualifying energy efficient water heater.

UEF_b = Uniform energy factor of the baseline water heater. In New Jersey the 2015 International Energy Conservation Code (IECC) generally defines the residential energy efficiency code requirements, but the IECC does not include residential service water heating provisions, leaving federal equipment efficiency standards to define baseline.

Baseline Water Heater Usage = Annual usage of the baseline water heater

Summary of Inputs

Instantaneous Water Heaters

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>UEF_q</u>	<u>Variable</u>		<u>Application</u>
<u>UEF_b</u>	<u>Variable</u>	<u>Storage water heater – 0.657</u> <u>Instantaneous water heater – 0.81</u>	<u>1</u>
<u>Baseline Water Heater Usage</u>	<u>Fixed</u>	<u>23.6 MMBtu/yr</u>	<u>2</u>

Formatted: English (U.S.)

Formatted: Don't keep lines together

Formatted: Underline, (none)

Formatted: Indent: First line: 0.25", Don't keep lines together

¹⁵ The final ruling on this change is available at:

https://energy.gov/sites/prod/files/2016/12/f34/WH_Conversion_Final%20Rule.pdf

¹⁶ https://www.energystar.gov/products/water_heaters/residential_water_heaters_key_product_criteria

The referenced federal standards for the baseline UEF are dependent on both draw pattern and tank size. A weighted average baseline UEF was calculated with a medium draw pattern from the referenced federal standards and water heating equipment market data from the Energy Information Association 2009 residential energy consumption survey for NJ¹⁷ assuming tank sizes of 30 gallons for small units, 40 gallons for medium units, and 55 gallons for large units.

Sources Zaloum, C. Lafrance, M. GUSDORF, J. “Drain Water Heat Recovery Characterization and Modeling” Natural Resources Canada. 2007. Savings vary due to a number of factors including make, model, installation type, and household behaviors.

1. US Government Publishing Office, June 2017, *Electronic Code of Federal Regulations – Title 10, Part 430, Subpart C*; available at: https://www.ecfr.gov/cgi-bin/text-idx?SID=2942a69a6328c23266612378a0725e60&mc=true&node=se10.3.430_132&rgn=div8.
2. US Energy Information Association, *2009 Residential Energy Consumption Survey Data*¹⁸; available at: <https://www.eia.gov/consumption/residential/data/2009/c&e/ce3.2.xlsx>.

5.

Formatted: No bullets or numbering

¹⁷ Available at: <https://www.eia.gov/consumption/residential/data/2009/hc/hc8.8.xls>

¹⁸ Data for 2015 will be available in 2018.

Residential Low Income Program

Protocols

The Protocols set out below are applicable to both the Comfort Partners component of the Low-income Program currently implemented by the State’s electric and gas utilities and the Weatherization Assistance component of the Low-income Program implemented by the New Jersey Department of Community Affairs (DCA).

Formatted: Space Before: 6 pt, After: 6 pt

The savings protocols for the low-income program are based upon estimated per unit installed savings. In some cases, such as lighting and refrigerators, the savings per unit estimate is based on direct observation or monitoring of the existing equipment being replaced. For other measures, for example air sealing and insulation, the protocols calculation is based on an average % savings of pre-treatment consumption.

Formatted: Space Before: 6 pt, After: 6 pt

Base Load Measures

Efficient Lighting

Savings from installation of screw-in CFLs, high performance fixtures, fluorescent torchieres, LEDs and LED nightlights are based on a straightforward algorithm that calculates the difference between existing and new wattage, and the average daily hours of usage for the lighting unit being replaced.

Formatted

Algorithm

Compact Fluorescent Screw In Lamp

$$\text{Electricity Impact Energy Savings (kWh/yr)} = ((\text{CFL}_{\text{watts}} \times (\text{CFL}_{\text{hours}} \times 365)) / 1000)$$

Formatted: Space Before: 3 pt, After: 3 pt

$$\text{Peak Demand Impact Savings (kW)} = (\text{CFL}_{\text{watts}} \times \text{Light CF})$$

Formatted: Space Before: 3 pt, After: 3 pt

Efficient Fixtures

$$\text{Electricity Impact Energy Savings (kWh/yr)} = ((\text{Fixt}_{\text{watts}} \times (\text{Fixt}_{\text{hours}} \times 365)) / 1000)$$

Formatted: Space Before: 3 pt, After: 3 pt

$$\text{Peak Demand Impact Savings (kW)} = (\text{Fixt}_{\text{watts}} \times \text{Light CF})$$

Formatted: Space Before: 3 pt, After: 3 pt

Efficient Torchieres

$$\text{Electricity Impact Energy Savings (kWh/yr)} = ((\text{Torch}_{\text{watts}} \times (\text{Torch}_{\text{hours}} \times 365)) / 1000)$$

Formatted: Space Before: 3 pt, After: 3 pt

Peak Demand ~~Impact~~Savings (kW) = (Torch_{watts}) ~~X~~* Light CF

Formatted: Space Before: 3 pt, After: 3 pt

LED Screw In Lamp

Formatted: Space Before: 3 pt, After: 3 pt

~~Electricity Impact~~Energy Savings (kWh/yr) = ((LED_{watts}) ~~X~~* (LED_{hours} ~~X~~* 365))/1000

Peak Demand ~~Impact~~Savings (kW) = (LED_{watts}) ~~X~~* Light CF

Formatted: Space Before: 3 pt, After: 3 pt

LED Nightlight

Formatted: Space Before: 3 pt, After: 3 pt

~~Electricity Impact~~Energy Savings (kWh/yr) = ((LEDN_{watts}) ~~X~~* (LEDN_{hours} ~~X~~* 365))/1000

Hot Water Conservation Measures

The protocols savings estimates are based on an average package of domestic hot water measures typically installed by low-income programs.

Low Flow Showerheads

Savings for low-flow showerhead measures are determined using the total change in flow rate (gallons per minute) from the baseline (existing) showerhead to the efficient showerhead.

Algorithms

Algorithms

~~Electricity Impact~~ Energy Savings (kWh/yr) = %Electric DHW * (GPM_base – GPM_ee) * kWh/ΔGPM

Peak ~~Electric~~-Demand ImpactSavings (kW) = Electricity Impact (kWh) * Demand Factor

Natural Gas Impact (therm) = %Gas DHW * (GPM_base – GPM_ee) * therm/ΔGPM

Definition of Variables

% Electric DHW = proportion of water heating supplied by electricity

~~Definition of Variables~~

~~% Electric DHW = proportion of water heating supplied by electricity~~

GPM_base = Flow rate of the baseline showerhead (gallons per minute)

GPM_ee = Flow rate of the efficient showerhead (gallons per minute)

kWh/ΔGPM = Electric energy savings of efficient showerhead per gallon per minute (GPM)

Demand Factor = energy to demand factor

%Gas DHW = proportion of water heating supplied by natural gas

Formatted: Page break before

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font: Bold

Formatted: Heading 4

Formatted: Space Before: 6 pt, After: 3 pt

Formatted: Underline

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 9 pt, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Indent: Left: 0", First line: 0"

Formatted: (none)

Formatted: Level 4, Keep with next

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

therm/ΔGPM = natural gas energy savings of efficient showerhead per gallon per minute (GPM)

Formatted: Space Before: 3 pt, After: 3 pt

Low Flow Showerheads

Component	Type	Value	Sources
% Electric DHW	Variable	Electric DHW = 100% Unknown = 13%	1
% Gas DHW	Variable	Natural Gas DHW = 100% Unknown = 81%	1
GPM_base	Variable	Rebate Application Unknown = 2.5	2
GPM_ee	Variable	Rebate Application Unknown = 1.5	2
kWh/ΔGPM	Fixed	SF = 360.1 MF = 336.9 Unknown = 390.1	3
therm/ΔGPM	Fixed	SF = 15.5 MF = 16.9 Unknown = 16.8	3, 4
Demand Factor	Fixed	0.00008013	3

Formatted: Font: Italic

Formatted: Table Caption

Formatted: Table Header, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Sources

1. Unknown hot water heating fuel assumption taken from 2009 RECS data for New Jersey. ~~See; see~~ Table HC8.8 Water Heating in U.S. Homes in Northeast Region, Divisions, and States.
2. Flow rate specification taken from rebate application. ~~Default; default~~ assumption for unknown flow rate taken from Pennsylvania Technical Reference Manual. ~~Effective, effective~~ June 2016, ~~pagesp.~~ 120ff. ~~Available; available~~ at <http://www.puc.pa.gov/pcdocs/1370278.docx>.
3. Default assumptions from Pennsylvania Technical Reference Manual (ibid).
4. Illinois Statewide Technical Reference Manual for Energy Efficiency, Version 4.0. ~~Effective, effective~~ June 1, 2015 ~~pages, pp.~~ 657ff. ~~Default; default~~ assumptions for housing demographic characteristics taken from PA TRM.

Formatted: Space After: 6 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Add space between paragraphs of the same style

Low Flow Faucet Aerators

Savings for low-flow faucet aerator measures are determined using the total change in flow rate (gallons per minute) from the baseline (existing) faucet to the efficient faucet.

Formatted: Space Before: 6 pt

Algorithms

Energy Savings Algorithm

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

$$\text{Electricity Impact (kWh/yr)} = \% \text{Electric DHW} * (\text{GPM}_{\text{base}} - \text{GPM}_{\text{ee}}) * \text{kWh}/\Delta\text{GPM}$$

Formatted: Heading 4, Space Before: 6 pt

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Peak ~~Electric~~-Demand ~~Impact~~Savings (kW) = Electricity Impact (kWh) * Demand Factor

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

$$\text{Natural Gas Impact (therm)} = \% \text{Gas DHW} * (\text{GPM}_{\text{base}} - \text{GPM}_{\text{ee}}) * \text{therm}/\Delta\text{GPM}$$

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Definition of Variables

Formatted: Underline

%Electric DHW = proportion of water heating supplied by electricity

Formatted: Normal

Definition of Variables

Formatted: Heading 4

~~%Electric DHW = proportion of water heating supplied by electricity~~

Formatted: Space Before: 3 pt, After: 3 pt

GPM_base = Flow rate of the baseline faucet (gallons per minute)

Formatted: Space Before: 3 pt, After: 3 pt

GPM_ee = Flow rate of the efficient faucet (gallons per minute)

Formatted: Space Before: 3 pt, After: 3 pt

kWh/ΔGPM = Electric energy savings of efficient faucet per gallon per minute (GPM)

Formatted: Space Before: 3 pt, After: 3 pt

Demand Factor = energy to demand factor

Formatted: Space Before: 3 pt, After: 3 pt

%Gas DHW = proportion of water heating supplied by natural gas

Formatted: Space Before: 3 pt, After: 3 pt

therm/ΔGPM = natural gas energy savings of efficient faucet per gallon per minute (GPM)

Formatted: Space Before: 3 pt, After: 3 pt

Low Flow Faucet Aerators

Formatted: Table Caption

Component	Type	Value	Source
			Source

Formatted: Table Header, Left

Formatted: Font: Not Italic

Component	Type	Value	Sources
%_Electric DHW	Variable	Electric DHW = 100% Unknown = 13%	1
%_Gas DHW	Variable	Natural Gas DHW = 100% Unknown = 81%	1
GPM_base	Variable	Rebate Application Unknown = 2.2	2
GPM_ee	Variable	Rebate Application Unknown = 1.5	2
kWh/ Δ GPM	Fixed	SF = 60.5 MF = 71.0 Unknown = 63.7	3
therm/ Δ GPM	Fixed	SF = 4.8 MF = 6.5 Unknown = 5.0	3, 4
Demand Factor	Fixed	0.00008013000134	3

Sources

Sources

1. Unknown hot water heating fuel assumption taken from 2009 RECS data for New Jersey. ~~See; see~~ Table HC8.8 Water Heating in U.S. Homes in Northeast Region, Divisions, and States.
2. Flow rate specification taken from rebate application. ~~Default; default~~ assumption for unknown flow rate taken from Pennsylvania Technical Reference Manual. ~~Effective; effective~~ June 2016, ~~pagespp.~~ 114ff. ~~Available; available~~ at <http://www.puc.pa.gov/pcdocs/1370278.docx>.
3. Default assumptions from Pennsylvania Technical Reference Manual (ibid).
4. Illinois Statewide Technical Reference Manual for Energy Efficiency, Version 4.0. ~~Effective, effective~~ June 1, 2015 ~~pages, pp.~~ 648ff. ~~Default; default~~ assumptions for housing demographic characteristics taken from PA TRM.

Formatted: Font: Not Italic

Formatted: Table Header, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Space After: 6 pt

Formatted: Space After: 6 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Add space between paragraphs of the same style

Term	Definition	Value
Vol _{Std}	Volume of standard water heater (gallons)	63.50
Vol _{Eff}	Volume of efficient water heater (gallons)	51.20
°F/hr _{Std}	Heat lost per hour from standard water heater tank	0.8
°F/hr _{Eff}	Heat lost per hour from efficient water heater tank	0.93
	Conversion factor: density of water (lbs./gallon)	8.33

*AHRI Database. **Data model look-ups of AHRI Certifications.

Water heater pipe wrap

This section provides energy savings algorithms for insulation on domestic hot water heater pipes. Un-insulated hot water carrying pipes lose considerable heat to outside air due to high thermal conductivity. In order to reduce this heat loss, pipes can be covered with a layer of insulation, which will reduce source heating demand, resulting in significant energy savings. The baseline case assumes un-insulated copper pipes and the qualifying condition assumes polyolefin (Polyethylene) Foam Tube insulation at 3/8" thick for 1/2" pipe and 1/2" thick for 3/4" pipe.

Algorithms

$$\text{Energy Savings (kWh/yr)} = AKW_w \times L$$

$$\text{Fuel Savings (Ccf/yr)} = ACCF_w \times L$$

Definition of Variables

AKW_w = Annual electric savings per linear foot of heating pipe insulation

ACCF_w = Annual gas savings per linear foot of heating pipe insulation

L = Length of heating pipe insulation in ft

Summary of Inputs

Water Heater Pipe Wrap

Component	Type	Value	Source
AKW _w	Variable	See Table Below	1
ACCF _w	Variable	See Table Below	1
L	Variable		Application

Insulation Savings by Pipe Diameter

Pipe Diameter (in)	AKW _w (kWh/ft)	ACCF _w (Ccf/ft)
--------------------	---------------------------	----------------------------

<u>Pipe Diameter (in)</u>	<u>AKW_w (kWh/ft)</u>	<u>ACCF_w (Ccf/ft)</u>
<u>0.50</u>	<u>10.4</u>	<u>0.55</u>
<u>0.75</u>	<u>15.9</u>	<u>0.85</u>

Sources

1. NAIMA, 3E Plus software tool, Version 4.0, Released 2005; available from: <https://insulationinstitute.org/tools-resources/free-3e-plus/>

Efficient Refrigerators

The eligibility for refrigerator replacement is determined by comparing monitored consumption for the existing refrigerator with the rated consumption of the eligible replacement. -Estimated savings are directly calculated based on the difference between these two values.- Note that in the case where an under-utilized or unneeded refrigerator unit is removed, and no replacement is installed, the Ref_{new} term of the equation will be zero.

Algorithm

$$\text{Electricity Impact Energy Savings (kWh/yr)} = \text{Ref}_{\text{old}} - \text{Ref}_{\text{new}}$$

$$\text{Peak Demand Savings (kW)} = (\text{Ref}_{\text{old}} - \text{Ref}_{\text{new}}) * (\text{Ref DF})$$

Space Conditioning Measures

When available, gas heat measure savings will be based on heating use. -If only total gas use is known, heating use will be estimated as total use less 300 therms.

Air Sealing

It is assumed that air sealing is the first priority among candidate space conditioning measures. -Expected percentage savings is based on previous experiences with measured savings from similar programs. -Note there are no summer coincident electric peak demand savings estimated at this time.

Algorithm

Algorithm

$$\text{Electricity Impact Energy Savings (kWh/yr)} = \text{ESC}_{\text{pre}} * 0.05$$

$$\text{MMBtu savings} = (\text{GHpre} * 0.05)$$

Formatted

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted

Formatted: Heading 4, Space Before: 6 pt

Furnace/Boiler Replacement

Quantification of savings due to furnace and boiler replacements implemented under the low-income program will be based on the algorithms presented in the Residential Gas HVAC section of these Protocols.

Duct Sealing and Repair

The second priority for homes with either Central Air Conditioning (CAC) or some other form of ducted distribution of electric space conditioning (electric furnace, gas furnace or heat pump) is ensuring integrity and effectiveness of the ducted distribution system.

Algorithm

Algorithm

With CAC

$$\text{Electricity Impact Energy Savings (kWh/yr)} = (\text{ECool}_{\text{pre}}) \times 0.10$$

$$\text{Peak Demand Impact Savings (kW)} = (\text{Ecool}_{\text{pre}} \times 0.10) / \text{EFLH} \times \text{AC CF}$$

$$\text{MMBtu savings} = (\text{GHpre} \times 0.02)$$

No CAC

$$\text{Electricity Impact Energy Savings (kWh/yr)} = (\text{ESC}_{\text{pre}}) \times 0.02$$

$$\text{MMBtu savings} = (\text{GHpre} \times 0.02)$$

Combined space and water heating (Combo)

~~Participants installing a qualifying boiler or furnace and a qualifying water heater at the same time earn a special incentive. For savings calculations, there is no special consideration. The heating system savings are calculated according to the appropriate algorithm and the water heating savings are calculated separately according to the system type.~~

Insulation Up-Grades Upgrades

For savings calculations, it is assumed that any applicable air sealing and duct sealing/repair have been done, thereby reducing the space conditioning load, before consideration of upgrading insulation. -Attic insulation savings are then projected on the basis of the “new” load. - Gas savings are somewhat greater, as homes with gas heat generally have less insulation.

Formatted: Heading 3, Tab stops: Not at

Formatted: Heading 3, None, Tab stops: Not at 0.5"

Formatted: Space Before: 18 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt

Formatted: Indent: First line: 0"

Formatted: Space Before: 0 pt

Algorithm

$$\text{Electricity Impact Energy savings (kWh/yr)} = (\text{ESC}_{\text{pre}}) \times 0.08$$

$$\text{MMBtu savings} = \text{GH}_{\text{pre}} \times 0.13$$

Thermostat Replacement

Thermostats are eligible for consideration as an electric space conditioning measure only after the first three priority items. -Savings projections are based on a conservative 3% of the “new” load after installation of any of the top three priority measures.

Algorithm

$$\text{Electricity Impact Energy Savings (kWh/yr)} = (\text{ESC}_{\text{pre}}) \times 0.03$$

$$\text{MMBtu savings} = (\text{GH}_{\text{pre}} \times 0.03)$$

Heating and Cooling Equipment Maintenance Repair/Replacement

Savings projections for heat pump charge and air flow correction. -Protocol savings account for shell measures having been installed that reduce the ~~pre-existing~~preexisting load.

Algorithm

Algorithm

$$\text{Electricity Impact Energy Savings (kWh/yr)} = (\text{ESC}_{\text{pre}}) \times 0.17$$

$$\text{Peak Demand Impact Savings (kW)} = (\text{Capy/EER} \times 1000) \times \text{HP CF} \times \text{DSF}$$

Gas HVAC Repairs

This section provides energy savings algorithms for existing gas HVAC repairs in residential applications. The savings calculation requires measurement of steady state furnace efficiency before and after repairs using an electronic combustion analyzer. Alternatively, before and after repair efficiencies may be measured following the method described in ANSI/ASHRAE Standard 103-2007, Method of Testing for Annual Fuel Utilization Efficiency of Residential Central Furnaces and Boilers. Maximum post repair efficiency must not exceed equipment nameplate efficiency. Technicians performing repairs must provide documentation of before- and after-combustion analysis results.

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Heading 3, Indent: First line: 0"

Formatted

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Heading 3, Indent: First line: 0"

Formatted

Formatted: Pattern: Clear (Light Yellow)

Formatted: Body Text, Justified, Right: 0.09", Line spacing: At least 12 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Heading 3

Formatted: Font: Bold, Italic

Formatted: Underline, (none)

Formatted: Indent: First line: 0.25"

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = \text{Cap}_{in} \times \text{EFLH}_h \times (1/\text{SSE}_b - 1/\text{SSE}_q) / 1,000\text{kBtu/MMBtu}$$

Definition of Variables

Cap_{in} = input capacity of existing unit in kBtu/hr

EFLH_h = equivalent full load heating hours

SSE_b = Steady state efficiency of baseline gas HVAC equipment

SSE_q = Steady state efficiency of repaired gas HVAC equipment

Summary of Inputs

Gas HVAC Repairs

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Furnace rating</u>	<u>Variable</u>		<u>Application</u>
<u>EFLH_h</u>	<u>Fixed</u>	<u>965</u>	<u>NJ utility analysis of heating customers, annual gas heating usage</u>
<u>SSE_q</u>	<u>Variable</u>		<u>Application</u>
<u>SSE_b</u>	<u>Variable</u>		<u>Application</u>

Example: If a furnace has a 90 kBtu/hr input capacity, baseline efficiency of 85%, and post repairs efficiency of 90%, the fuel savings would be calculated as $\text{FS} = 90\text{kBtu/hr} \times 965 \text{ hr} \times (1/0.85 - 1/0.90)/1,000\text{kBtu/MMBtu} = 5.67 \text{ MMBtu/yr}$.

Formatted: Level 4, Keep with next

Formatted: (none)

Formatted: Indent: First line: 0.25"

Formatted: Font: 12 pt, Not Bold

Formatted: Normal, Left, Right: 0", Line spacing: single

Formatted: (none)

Formatted: Space After: 1 pt, Don't keep with next

Formatted Table

Formatted: Space After: 1 pt

Formatted: Indent: First line: 0"

Formatted: Heading 3, Indent: Left: 0", First line: 0", Tab stops: Not at 0.5"

Other “Custom” Measures

In addition to the typical measures for which savings algorithms have been developed, it is assumed that there will be niche opportunities that should be identified and addressed. The savings for these custom measures will be reported based on the individual calculations supplied with the reporting. -As necessary the program working group will develop specific guidelines for frequent custom measures for use in reporting and contractor tracking.

Definition of Terms

CFL_{watts} = Average watts replaced for a CFL installation.

CFL_{hours} = Average daily burn time for CFL replacements.

$Fixt_{watts}$ = Average watts replaced for an efficient fixture installation.

$Fixt_{hours}$ = Average daily burn time for CFL replacements.

$Torch_{watts}$ = Average watts replaced for a Torchiere replacement.

$Torch_{hours}$ = Average daily burn time for a Torchiere replacements.

LED_{watts} = Average watts replaced for an LED installation.

LED_{hours} = Average daily burn time for LED replacements.

$LEDN_{watts}$ = Average watts replaced for an LED nightlight installation.

$LEDN_{hours}$ = Average daily burn time for LED nightlight replacements.

Light CF = Summer demand coincidence factor for all lighting measures. Currently fixed at 5%.

HW_{avg} = Average electricity savings from typical electric hot water measure package.

HW_{gavg} = Average natural gas savings from typical electric hot water measure package.

HW_{watts} = Connected load reduction for typical hot water efficiency measures

Formatted: Page break before

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

HW CF = Summer demand coincidence factor for electric hot water measure package. Currently fixed at 75%.

Formatted: Space Before: 3 pt, After: 3 pt

Ref_{old} = Annual energy consumption of existing refrigerator based on on-site monitoring.

Formatted: Space Before: 3 pt, After: 3 pt

Ref_{new} = Rated annual energy consumption of the new refrigerator.

Formatted: Space Before: 3 pt, After: 3 pt

RefDF = kW /kWh of savings. -Refrigerator demand savings factor.

Formatted: Space Before: 3 pt, After: 3 pt

Ref CF = Summer demand coincidence factor for refrigeration. Currently 100%, diversity accounted for in the Ref DF factor.

Formatted: Space Before: 3 pt, After: 3 pt

ESC_{pre} = Pre-treatment electric space conditioning consumption.

Formatted: Space Before: 3 pt, After: 3 pt

ECool_{pre} = Pre-treatment electric cooling consumption.

Formatted: Space Before: 3 pt, After: 3 pt

EFLH = Equivalent full load hours of operation for the average unit. -This value is currently fixed at 650 hours.

Formatted: Space Before: 3 pt, After: 3 pt

AC CF = Summer demand coincidence factor for air conditioning. Currently 85%.

Formatted: Space Before: 3 pt, After: 3 pt

Cap_y = Capacity of Heat Pump in Btuh

Formatted: Space Before: 3 pt, After: 3 pt

EER = Energy Efficiency Ratio of average heat pump receiving charge and air flow service. -Fixed at 9.2

Formatted: Space Before: 3 pt, After: 3 pt

HP CF = Summer demand coincidence factor for heat pump. Currently fixed at 70%.

Formatted: Space Before: 3 pt, After: 3 pt

DSF = Demand savings factor for charge and air flow correction. -Currently fixed at 7%.

Formatted: Space Before: 3 pt, After: 3 pt

GC_{pre} = Pre-treatment gas consumption.

Formatted: Space Before: 3 pt, After: 3 pt

GH_{pre} = Pre-treatment gas space heat consumption (=GC_{pre} less 300 therms if only total gas use is known).

Formatted: Space Before: 3 pt, After: 3 pt

WS = Water Savings associated with water conservation measures. Currently fixed at 3,640 gallons per year per home receiving low-flow showerheads, plus 730 gallons saved per year aerator installed.

Formatted: Space Before: 3 pt, After: 3 pt

Component	Type	Value	Sources
GC _{pre}	Variable		7
GH _{pre}	Variable		7
Time Period Allocation Factors - = Electric	Fixed	Summer/On-Peak 21% Summer/Off-Peak 22% Winter/On-Peak 28% Winter/Off-Peak 29%	11
Time Period Allocation Factors - = Gas	Fixed	Heating: Summer 12% Winter 88% Non-Heating: Summer 50% Winter 50%	13

- Formatted: Table Header
- Formatted: Table Header, Indent: Left: 0"
- Formatted Table
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Font: Bold
- Formatted: Table Cells
- Formatted: Font: Bold
- Formatted: Table Cells

Sources/Notes:

1. Working group expected averages for product specific measures.
2. Efficiency Vermont, [Technical Reference User Manual, 2016](#) – average for lighting products.
3. Experience with average hot water measure savings from low income and direct install programs.
4. VEIC estimate.
5. UI Refrigerator Load Data profile, .16 kW ([5 p.m. July](#)) and 1,147 kWh annual consumption.
6. Diversity accounted for by Ref DF.
7. Billing histories and (for electricity) contractor calculations based on program procedures for estimating space conditioning and cooling consumption.
8. Average EER for SEER 13 units.
9. Analysis of data from 6 utilities by Proctor Engineering
10. From Neme, Proctor and Nadel, 1999.
11. These allocations may change with actual penetration numbers are available.
12. VEIC estimate, assuming 1 GPM reduction for 14 [five-5-minute](#) showers per week for shower heads, and 4 gallons saved per day for aerators.
13. Heating:- Prorated based on 12% of the annual degree days falling in the summer period and 88% of the annual degree days falling in the winter period.
Non-Heating:- Prorated based on 6 months in the summer period and 6 months in the winter period.

- Formatted: Space After: 6 pt
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

14. "NJ Comfort Partners Energy Saving Protocols and Engineering Estimates." ~~Apprise, June 2014. Available at <http://www.njcleanenergy.com/files/file/Protocol%20and%20Engineering%20Estimate%20Summary.pdf>.~~ ~~Apprise, June 2014; available at <http://www.njcleanenergy.com/files/file/Protocol%20and%20Engineering%20Estimate%20Summary.pdf>.~~
15. Pennsylvania Technical Reference Manual. June 2016. ~~Page, p. 27. Available; available at <http://www.puc.pa.gov/pedocs/1370278.docx>~~ ~~<http://www.puc.pa.gov/pdocs/1370278.docx>.~~

Formatted: Indent: Left: 0", Hanging: 0.25"

Residential New Construction Program

Protocols

~~Single-Family, Multi-Single and Low-Rise Multifamily Building Shell~~

~~Energy-Whole building energy~~ savings due to ~~thermal shell and mechanical equipment~~ improvements in residential new construction and “gut” renovation projects are calculated using outputs from ~~REM/Rate™~~RESNET accredited Home Energy Rating System (HERS) modeling software²⁰. -All program homes are modeled ~~in~~ ~~REM/Rate~~using accredited software to estimate annual energy consumption for heating, cooling ~~and~~, hot water~~-, and other end uses within the HERS asset rating. Standards for energy efficient new construction in New Jersey are based on national platforms including IECC 2015, EPA ENERGY STAR® Certified New Homes Program, EPA ENERGY STAR Multifamily High-Rise Program (MFHR), and the DOE Zero Energy Ready Home (ZERH) Program. All of these pathways are based on and incorporate by reference the applicable HERS standards, including but not limited to, the Mortgage Industry National Home Energy Rating System Standard & Addenda and ANSI/RESNET/ICC Standard 30.~~²¹

~~Single-Family, Multi-Single (townhomes), Low-Rise Multifamily~~

The program home is then modeled to a baseline specification using ~~REM/Rate's~~ program-specific reference home (referred to in some software as a User Defined Reference Home ~~or~~ UDRH) feature. -The ~~UDRH~~program reference home specifications are set according to the lowest efficiency specified by applicable codes and standards, thereby representing a New Jersey specific baseline specification ~~is for home against which the improved efficiency of program homes permitted prior is measured.~~

The NJCEP reference home shall be updated as necessary over time to ~~and~~reflect the efficiency values of HERS Minimum Rated Features based on:

- ~~The prescriptive minimum values of the IECC 2015~~version applicable to the home for which savings are being calculated;
- The Federal Minimum Efficiency Standards applicable to each rated feature at the time of permitting (e.g. minimum AFUE and SEER ratings for heating and air conditioning equipment, etc.);
- An assessment of baseline practice, as available, in the event that either of the above standards reference a non-specific value (e.g. “visual inspection”);
- Exclusion of specific rated features from the savings calculation in order to remove penalties for building science based best practice requirements of the

²⁰ Accredited Home Energy Rating Systems (HERS) software,
<http://www.remrate.com/resnet.us/professional/programs/software>

²¹ <http://www.resnet.us/professional/standards>

program (e.g. by setting the reference and rated home to the same value for program-required mechanical ventilation);

- Other approved adjustments as may be deemed necessary.

The RNC program currently specifies three standards for program qualification:

- IECC 2015 Energy Rating Index (for homes permitted on or after March 21, 2016--)
- ENERGY STAR Certified Homes v3.1
- Zero Energy Ready Home & Zero Energy Home + RE

The difference in modeled annual energy consumption between the program and ~~UDRH~~applicable baseline reference home is the ~~project~~projected savings for heating, hot water, cooling, lighting ~~and appliance end uses-, appliances, and other end uses in the~~ HERS Minimum Rated Features, as well as on-site renewable generation, when applicable. Coincident peak demand savings are also derived from ~~REM/Raterated~~ modeled outputs.

~~The algorithms that calculate energy and demand savings are as follows:~~

~~Energy Savings = (Baseline home energy consumption — Program home energy consumption)~~

The following table describes the baseline characteristics of Climate Zone 4 and 5 reference homes for single-family, multi-single and low-rise multifamily buildings.

REM/Rate User Defined Reference Homes Definition			
Applicable to buildings permitted prior to March 21, 2016 -- Reflects IECC 2009			
Note	Data Point	Climate Zone 4	Climate Zone 5
(1)	Ceiling Insulation	U=0.030	U=0.030
	Radiant Barrier	None	None
(1)	Rim/Band Joist	U=0.082	U=0.057
(1)	Exterior Walls - Wood	U=0.082	U=0.057
(1)	Exterior Walls - Steel	U=0.082	U=.057
	Foundation Walls	U=0.059	U=0.059
(1)	Doors	U=0.35	U=0.35
(1)	Windows	U=0.35 , SHGC=NR	U=0.35 , SHGC=NR
(1)	Glass Doors	U=0.35 , SHGC=NR	U=0.35 , SHGC=NR
(1)	Skylights	U=0.60 , SHGC=NR	U=0.60 , SHGC=NR
(2)	Floor	U=0.047	U=.033
	Unheated Slab on Grade	R-10, 2 ft	R-10, 2 ft
	Heated Slab on Grade	R-15, 2 ft	R-15, 2 ft
	Air Infiltration Rate	7 ACH50	7 ACH50
	Duct Leakage	8 cfm25 per 100ft ² CFA	8 cfm25 per 100ft ² CFA
	Mechanical Ventilation	None	None
	Lights and Appliances	Use RESNET Default	Use RESNET Default
	Thermostat	Manual	Manual
	Heating Efficiency		
(3)	Furnace	80% AFUE	80% AFUE
	Boiler	80% AFUE	80% AFUE
	Combo Water Heater	76% AFUE (Recovery Efficiency)	76% AFUE (Recovery Efficiency)
	Air Source Heat Pump	7.7 HSPF	7.7 HSPF
	Cooling Efficiency		
	Central Air Conditioning & Window AC units	13.0 SEER	13.0 SEER
	Air Source Heat Pump	13.0 SEER	13.0 SEER
(4)	Domestic WH Efficiency		
	Electric stand-alone tank	0.90 EF	0.90 EF
	Natural Gas stand-alone tank	0.58 EF	0.58 EF
	Electric instantaneous	0.93 EF	0.93 EF
	Natural Gas instantaneous	0.62 EF	0.62 EF
	Water Heater Tank Insulation	None	None
	Duct Insulation, attic supply	R-8	R-8
	Duct Insulation, all other	R-6	R-6
	Active Solar	None	None
	Photovoltaics	None	None

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Left

Formatted Table

UDRH Table Notes

Formatted: Don't keep with next

(1)	U values represent total wall system U value, including all components (i.e., clear wall, windows, doors). Type A-1 - Detached one and two family dwellings. Type A-2 - All other residential buildings, three stories in height or less.
(2)	All frame floors shall meet this requirement. There is no requirement for floors over basements and/or unvented crawl spaces when the basement and/or unvented crawl space walls are insulated.
(3)	MEC 95 minimum requirement is 78 AFUE. However, 80 AFUE is adopted for New Jersey based on typical minimum availability and practice.
(4)	Based on the Federal Government standard for calculating EF (50 gallon assumed): <ul style="list-style-type: none">•Gas-fired Storage-type EF: $0.67 - (0.0019 \times \text{Rated Storage Volume in gallons})$•Electric Storage-type EF: $0.97 - (0.00132 \times \text{Rated Storage Volume in gallons})$•Instantaneous Gas-fired EF: $0.62 - (0.0019 \times \text{Rated Storage Volume in gallons})$•Instantaneous Electric EF: $0.93 - (0.0013 \times \text{Rated Storage Volume in gallons})$

Formatted: Indent: Left: 0"

REM/Rate User Defined Reference Homes Definition			
Applicable to buildings permitted on or after March 21, 2016 -- Reflects IECC 2015			
Note	Data Point	Climate Zone 4	Climate Zone 5
(1)	Ceiling Insulation	U= 0.026	U=0.026
	Radiant Barrier	None	None
(1)	Rim/Band Joist	U=0.060	U=0.060
(1)	Exterior Walls - Wood	U=0.060	U=0.060
(1)	Exterior Walls - Steel	U=0.060	U=0.060
	Foundation Walls	U=0.059	U=0.050
(1)	Doors	U=0.35	U=0.32
(1)	Windows	U=0.35 , SHGC=40	U=0.32 , SHGC=NR
(1)	Glass Doors	U=0.35 , SHGC=40	U=0.32 , SHGC=NR
(1)	Skylights	U=0.55 , SHGC=40	U=0.55 , SHGC=NR
(2)	Floor	U=0.047	U=.033
	Unheated Slab on Grade	R-10, 2 ft	R-10, 2 ft
	Heated Slab on Grade	R-15, 2 ft	R-15, 2 ft
(3)	Air Infiltration Rate	7 ACH50	7 ACH50
	Duct Leakage	4 cfm25 per 100ft ² CFA	4 cfm25 per 100ft ² CFA
	Mechanical Ventilation	Exhaust only	Exhaust only
	Lighting	75% efficient	75% efficient
	Appliances	Use RESNET Default	Use RESNET Default
(4)	Thermostat	Manual	Manual
	Heating Efficiency		
(5)	Furnace	80% AFUE	80% AFUE
	Boiler	80% AFUE	80% AFUE
	Combo Water Heater	76% AFUE (Recovery Efficiency)	76% AFUE (Recovery Efficiency)
	Air Source Heat Pump Cooling Efficiency	8.2 HSPF	8.2 HSPF
	Cooling Efficiency	-	
	Central Air Conditioning & Window AC units	13.0 SEER	13.0 SEER
	Air Source Heat Pump	14.0 SEER	14.0 SEER
(6)	Domestic WH Efficiency		
	Electric stand-alone tank	0.90 EF	0.90 EF
	Natural Gas stand-alone tank	0.60 EF	0.60 EF
	Electric instantaneous	0.93 EF	0.93 EF
	Natural Gas instantaneous	0.82 EF	0.82 EF
	Water Heater Tank Insulation	None	None
	Duct Insulation, attic	R-8	R-8
	Duct Insulation, all other	R-6	R-6
	Active Solar	None	None

Formatted Table

Formatted: Left

Formatted Table

REM/Rate User Defined Reference Homes Definition		
Applicable to buildings permitted on or after March 21, 2016 -- Reflects IECC 2015		
Photovoltaics	None	None

UDRH Table Notes

(1)	U values represent total system U value, including all components (i.e., clear wall, windows, doors). Type A-1 - Detached one and two family dwellings. Type A-2 - All other residential buildings, three stories in height or less.
(2)	All frame floors shall meet this requirement. There is no requirement for floors over basements and/or unvented crawl spaces when the basement and/or unvented crawl space walls are insulated.
(3)	Based on New Jersey's amendment making the IECC 2015 requirement for air leakage testing optional, there is no empirical evidence that baseline new construction is achieving the 3 ACH50 tightness level through a visual inspection of checklist air sealing items.
(4)	While the code requires a programmable actual programming is an occupant behavior, both the rated home and reference home are set at fixed temperatures of 68 heating and 78 cooling, so that no savings are counted or lost
(5)	MEC 95 minimum requirement is 78 AFUE. However, 80 AFUE is adopted for New Jersey based on typical minimum availability and practice.
(6)	Based on the Federal Government standard for calculating EF (50 gallon assumed): •Gas-fired Storage-type EF: 0.675 - (0.0015 x Rated Storage Volume in gallons) •Electric Storage-type EF: 0.97 - (0.00132 x Rated Storage Volume in gallons) •Instantaneous Gas-fired EF: 0.82 - (0.0019 x Rated Storage Volume in gallons) •Instantaneous Electric EF: 0.93 - (0.0013 x Rated Storage Volume in gallons)

Formatted: Normal

Formatted: Indent: Left: 0"

Multifamily High Rise (MFHR) Protocols

— Multifamily High Rise (MFHR)

Annual energy and summer coincident peak demand savings for qualifying MFHR construction projects (~~4-6 stories~~) shall be calculated from the ~~EPA Project Submittal document, 'As-Built~~ Energy Star Performance Path Calculator (PPC).²² The PPC captures outputs from ~~eQuest~~ EPA approved modeling software. -Coincident peak demand is calculated only for the following end uses: space cooling, lighting, and ventilation. -Clothes washer data cannot be parsed out of the PPC "Misc Equip" field. RNC coincident factors are applied to the MFHR demand savings.

Formatted: Heading 3

Formatted: Space Before: 6 pt, After: 6 pt

Energy and demand savings are calculated using the following equations:

Formatted: Space Before: 6 pt, After: 6 pt

²² https://www.energystar.gov/index.cfm?c=bldrs_lenders_raters.nh_mfhr_guidance

Energy Savings = Average Baseline energy (kWh/yr and/or therms/yr) - Proposed Design energy (kWh/yr and/or therms/yr)

Formatted: Space Before: 3 pt, After: 3 pt

Coincident peak demand = (Average Baseline non-coincident peak demand - Proposed Design non-coincident peak demand) * Coincidence Factor

Formatted: Space Before: 3 pt, After: 3 pt

ENERGY STAR Energy Efficient Products ~~Program~~

Protocols

The following sections detail savings calculations ENERGY STAR Appliances, ENERGY STAR and Lighting, ENERGY STAR Windows, and ENERGY STAR Audit Products in residential and multi-family sectors.

ENERGY STAR Appliances

~~Protocols~~

The general form of the equation for the ENERGY STAR Appliance Program measure savings algorithms is:

Number of Units ~~X~~* Savings per Unit

~~To determine resource savings, the per unit estimates in the protocols will be multiplied by the number of appliance units. To determine resource savings, the per unit estimates in the protocols will be multiplied by the number of appliance units.~~ The number of units will be determined using market assessments and market tracking.

ENERGY STAR Refrigerators – CEE Tier 1

Electricity ~~Impact~~Savings (kWh/yr) = ESav_{REF1}

~~Peak~~ Demand ~~Impact~~Savings (kW) = DSav_{REF1} ~~X~~* CF_{REF}

ENERGY STAR Refrigerators – CEE Tier 2

Electricity ~~Impact~~Savings (kWh/yr) = ESav_{REF2}

~~Peak~~ Demand ~~Impact~~Savings (kW) = DSav_{REF2} ~~X~~* CF_{REF}

ENERGY STAR Clothes Washers – CEE Tier 1

Electricity ~~Impact~~Savings (kWh/yr) = ESav_{CW1}

~~Peak~~ Demand ~~Impact~~Savings (kW) = DSav_{CW1} ~~X~~* CF_{CW}

Gas ~~Impact~~Savings (Therms/yr) = EGSav_{CW1}

Water ~~Impact~~Savings (gallons/yr) = WSav_{CW1}

Formatted: Left: 1.25", Right: 1.25"

Formatted

Formatted: Heading 3

Formatted

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Subscript

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

ENERGY STAR Clothes Washers — CEE Tier 2

Electricity ImpactSavings (kWh/yr) = ESav_{CW2}

Peak Demand ImpactSavings (kW) = DSav_{CW2} * CF_{CW}

Gas ImpactSavings (Therms/yr) = EGSav_{CW2}

Water ImpactSavings (gallons/yr) = WSav_{CW2}

ENERGY STAR Set Top Boxes [Inactive 2017, Not Reviewed]

Electricity Impact (kWh) = ESav_{STB}

Demand Impact (kW) = DSav_{STB} * CF_{STB}

Advanced Power Strip – Tier 1

Electricity Impact (kWh) = ESav_{APS}

Demand Impact (kW) = DSav_{APS} * CF_{APS}

Advanced Power Strip – Tier 2

Electricity Impact (kWh/yr) = ESav_{APS2}

Demand Impact (kW) = DSav_{APS2} * CF_{APS}

ENERGY STAR Electric Clothes Dryers – Tier 1

Electricity ImpactSavings (kWh/yr) = ESav_{CDE1}

Peak Demand ImpactSavings (kW) = DSav_{CDE1} * CF_{CD}

ENERGY STAR Gas Clothes Dryers – Tier 1

Electricity ImpactSavings (kWh/yr) = ESav_{CDG1}

Peak Demand ImpactSavings (kW) = DSav_{CDG1} * CF_{CD}

Gas ImpactSavings (Therms/yr) = GSav_{CDG1}

ENERGY STAR 2014 Emerging Technology Award Electric Clothes Dryers – Tier 2

Electricity ImpactSavings (kWh/yr) = ESav_{CDE2}

Peak Demand ImpactSavings (kW) = DSav_{CDE2} * CF_{CD}

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt, Don't keep with next

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt, Don't keep with next

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt, Don't keep with next

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Subscript

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Normal

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Heading 4

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Heading 4

Formatted: English (U.S.)

Formatted: English (U.S.)

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

ENERGY STAR 2014 Emerging Technology Award Gas Clothes Dryers – Tier 2

Electricity ImpactEnergy Savings (kWh/yr) = ESav_{CDG2}

Peak Demand ImpactSavings (kW) = DSav_{CDG2} * CF_{CD}

Gas ImpactSavings (Therms) = GSav_{CDG1/yr} = GSav_{CDG2}

ENERGY STAR Room AC – Tier 1 [Inactive 2017, Not Reviewed]

Electricity Impact (kWh) = ESav_{RAC1}

Demand Impact (kW) = DSav_{RAC1}

ENERGY STAR Room AC – Tier 2 [Inactive 2017, Not Reviewed]

Electricity Impact (kWh) = ESav_{RAC2}

Demand Impact (kW) = DSav_{RAC2}

ENERGY STAR Room Air Purifier [Inactive 2017, Not Reviewed]

Electricity Impact (kWh) = ESav_{RAP}

Demand Savings (kW) = DSav_{RAC2} is based on the CADR in the table below

Where ESav_{RAP} is based on the CADR in table below

Room Air Purifier Deemed kWh Table				
Clean Air Delivery Rate (CADR)	CADR used in calculation	Baseline Unit Energy Consumption (kWh/year)	ENERGY STAR Unit Energy Consumption (kWh/year)	ESav _{RAP}
CADR 51-100	75	441	148	293
CADR 101-150	125	733	245	488
CADR 151-200	175	1025	342	683
CADR 201-250	225	1317	440	877
CADR Over 250	275	1609	537	1072

Demand Impact (kW) = DSav_{RAC2} is based on the CADR in the table below

- Formatted: Heading 4
- Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt
- Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt
- Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt
- Formatted: Heading 4
- Formatted: Normal, Indent: First line: 0.25", Space After: 3 pt
- Formatted: Indent: First line: 0.25", Space After: 3 pt
- Formatted: Heading 4
- Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt
- Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt
- Formatted: Heading 4
- Formatted: Normal, Indent: First line: 0.25"
- Formatted: Subscript
- Formatted: Left, Indent: First line: 0.25", Space Before: 0 pt, After: 0 pt, Widow/Orphan control, Keep with next
- Formatted: Font: Times New Roman, German (Germany), Not Superscript/ Subscript

Room Air Purifier Deemed kW Table	
Clean Air Delivery Rate	DSav _{RAC2}
CADR 51-100	0.034
CADR 101-150	0.056
CADR 151-200	0.078
CADR 201-250	0.101
CADR Over 250	0.123

ENERGY STAR Freezer [Inactive 2017, Not Reviewed]

-Electricity Impact (kWh) = ESav_{FRZ}

Demand Impact (kW) = DSav_{FRZ} based on table below

ENERGY STAR Soundbar [Inactive 2017, Not Reviewed]

Electricity Impact (kWh) = ESav_{SDB}

Demand Impact (kW) = DSav_{SDB}

Definition of Variables

Definition of Terms

ESav_{REF1} = Electricity savings per purchased ENERGY STAR refrigerator – CEE Tier 1.

DSav_{REF1} = Summer demand savings per purchased ENERGY STAR refrigerator – CEE Tier 1.

ESav_{REF2} = Electricity savings per purchased ENERGY STAR refrigerator – CEE Tier 2.

DSav_{REF2} = Summer demand savings per purchased ENERGY STAR refrigerator – CEE Tier 2.

ESav_{CW1} = Electricity savings per purchased ENERGY STAR clothes washer.

DSav_{CW1} = Summer demand savings per purchased ENERGY STAR clothes washer.

GSav_{CW1} = Gas savings per purchased clothes washer ENERGY STAR clothes washer.

WSav_{CW1} = Water savings per purchased clothes washer ENERGY STAR clothes washer.

ESav_{CW2} = Electricity savings per purchased **CEE** Tier 2 ENERGY STAR clothes washer.

Formatted: (none)

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: English (U.S.)

Formatted: Font: 10 pt, Bold

Formatted: Body Text, Justified, Right: 0.09", Line spacing: At least 12 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{CW2} = Summer demand savings per purchased ~~CEE~~ Tier 2 ENERGY STAR clothes washer.

Formatted: Space Before: 3 pt, After: 3 pt

GSav_{CW2} = Gas savings per purchased ~~CEE~~ Tier 2 ENERGY STAR clothes washer

Formatted: Space Before: 3 pt, After: 3 pt

WSav_{CW2} = Water savings per purchased ~~CEE~~ Tier 2 ENERGY STAR clothes washer.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{STB} = Electricity savings per purchased ENERGY STAR set top box.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{STB} = Summer demand savings per purchased ENERGY STAR set top box.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{APSI} = Electricity savings per purchased advanced power strip.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{APSI} = Summer demand savings per purchased advanced power strip.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{APS2} = Electricity savings per purchased Tier 2 advanced power strip.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{APS2} = Summer demand savings per purchased Tier 2 advanced power strip.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{CDE1} = Electricity savings per purchased ENERGY STAR electric clothes dryer.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{CDE1} = Summer demand savings per purchased ENERGY STAR electric clothes dryer.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{CDG1} = Electricity savings per purchased ENERGY STAR gas clothes dryer.

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{CDG1} = ~~summer~~ Summer demand savings per purchased ENERGY STAR gas clothes dryer.

Formatted: Space Before: 3 pt, After: 3 pt

GSav_{CDG1} = Gas savings per purchased ENERGY STAR gas clothes dryer.

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{CDE2} = Electricity savings per purchased Tier 2 ENERGY STAR electric clothes dryer ~~meeting the ENERGY STAR 2014 Emerging Technology Award criteria.~~

Formatted: Space Before: 3 pt, After: 3 pt

DSav_{CDE2} = Demand savings per purchased Tier 2 ENERGY STAR electric clothes dryer ~~meeting the ENERGY STAR 2014 Emerging Technology Award criteria.~~

Formatted: Space Before: 3 pt, After: 3 pt

ESav_{CDG2} = Electricity savings per purchased Tier 2 ENERGY STAR gas clothes dryer ~~meeting the ENERGY STAR 2014 Emerging Technology Award criteria.~~

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avCDG2} = Demand savings per purchased gas Tier 2 ENERGY STAR gas clothes dryer meeting the ENERGY STAR 2014 Emerging Technology Award criteria.

Formatted: Space Before: 3 pt, After: 3 pt

GS_{avCDG2} = Gas savings per purchased Tier 2 ENERGY STAR gas clothes dryer meeting the ENERGY STAR 2014 Emerging Technology Award criteria.

Formatted: Space Before: 3 pt, After: 3 pt

ES_{avRAC1} = Electricity savings per purchased ENERGY STAR room air conditioner.

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avRAC1} = Summer demand savings per purchased ENERGY STAR room air conditioner.

Formatted: Space Before: 3 pt, After: 3 pt

ES_{avRAC1} = Electricity savings per purchased Tier 2 room air conditioner.

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avRAC2} = Summer demand savings per purchased Tier 2 room air conditioner.

Formatted: Space Before: 3 pt, After: 3 pt

ES_{avRAC1} = Electricity savings per purchased ENERGY STAR room air purifier.

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avRAP} = Summer demand savings per purchased ENERGY STAR room air purifier.

Formatted: Space Before: 3 pt, After: 3 pt

ES_{avFRZ} = Electricity savings per purchased ENERGY STAR freezer.

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avFRZ} = Summer demand savings per purchased ENERGY STAR freezer.

Formatted: Space Before: 3 pt, After: 3 pt

ES_{avSDB} = Electricity savings per purchased ENERGY STAR soundbar.

Formatted: Space Before: 3 pt, After: 3 pt

DS_{avSDB} = Summer demand savings per purchased ENERGY STAR soundbar

Formatted: Space Before: 3 pt, After: 3 pt

TAF = Temperature Adjustment Factor

Formatted: Space Before: 3 pt, After: 3 pt

LSAF = Load Shape Adjustment Factor

Formatted: Space Before: 3 pt, After: 3 pt

$CF_{REF}, CF_{CW}, CF_{DH}, CF_{RAC}, CF_{STB}, CF_{APS}, CF_{CD}$ = Summer demand coincidence factor.

Formatted: Not Superscript/ Subscript

Formatted: Space Before: 3 pt, After: 3 pt

Summary of Inputs

ENERGY STAR Appliances

Component	Type	Value	Sources
ES_{avREF1}	Fixed	59 kWh	5

Formatted: Table Caption, Left, Space Before: 6 pt, Don't keep with next

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Subscript

ENERGY STAR and CEE Tier 2 models. -Demand savings estimated based on a flat 8760 hours of use during the year.- Energy Star Ref:

<https://data.energystar.gov/Active-Specifications/ENERGY-STAR-Certified-Residential-Refrigerators/p5st-her9>

CEE Tier 2 Ref:

~~<http://library.cee1.org/content/qualifying-product-lists-residential-refrigerators>~~
~~<http://library.cee1.org/content/qualifying-product-lists-residential-refrigerators>~~

6. Energy savings represent the difference between the weighted average eligible ENERGY STAR V4.1 models (132 kWh) and minimum requirements of the 2012 voluntary agreement established by the cable industry and tied to ENERGY STAR V3.0 (88 kWh). -Demand savings estimated based on a flat 8760 hours of use during the year. On average, demand savings are the same for both Active and Standby states and is based on 8760 hours usage.
7. Set top box lifetimes: National Resource Defense Counsel, *Cable and Satellite Set-Top Boxes Opportunities for Energy Savings*, 2005.
<http://www.nrdc.org/air/energy/energyeff/stb.pdf>
8. 2010 NYSERDA Measure Characterization for Advanced Power Strips-~~Study;~~ **study** based on review of:
 - a. Smart Strip Electrical Savings and Usability, Power Smart Engineering, October 27, 2008.
 - b. Final Field Research Report, Ecos Consulting, October 31, 2006:
~~Prepared; prepared~~ for California Energy Commission's PIER Program.
 - c. Developing and Testing Low Power Mode Measurement Methods, Lawrence Berkeley National Laboratory (LBNL), September 2004-
~~Prepared; prepared~~ for California Energy Commission's Public Interest Energy Research (PIER) Program.
 - d. 2005 Intrusive Residential Standby Survey Report, Energy Efficient Strategies, March, 2006.
9. Energy savings estimates are based on a California Plug Load Research Center report, "Tier 2 Advanced Power Strip Evaluation for Energy Saving Incentive." Demand savings estimated based on a flat 8760 hours of use during the year. Savings for Tier 2 APS are temporarily included pending additional support.
10. 2011 Efficiency Vermont Load shape for Advanced Power Strips.
11. Advanced Power Strip Measure Life: David Rogers, Power Smart Engineering, October 2008: "Smart Strip electrical savings and usability", ~~p22,~~ **p 22**.
12. ~~Clothes dryer energy and demand savings are based on Mid-Atlantic Technical Reference Manual Version 5.0 April 2015 page 237 available at~~
~~<http://www.neep.org/mid-atlantic-technical-reference-manual-v5>~~. Demand savings are calculated based on 297 annual cycles from 2009 RECS data for New Jersey (See RECS 2009 Table HC3.8 -Home Appliances in Homes in Northeast Region, Divisions, and States) and an average 10.4 lb load based on paired ENERGY STAR washers. **Available at <http://www.neep.org/mid-atlantic-technical-reference-manual-v6>**.

Formatted: Space Before: 3 pt, After: 3 pt

13. Savings for clothes dryers meeting the 2014 Emerging Technology Award criteria assume an average of measured performance and a 50% usage of both normal and most efficient dryer settings for eligible models.

Formatted: Space Before: 3 pt, After: 6 pt

~~14. *NEEP, Mid-Atlantic TRM V5*~~

Formatted: Font: Italic

~~15. *14. Mid-Atlantic TRM Technical Reference Manual, V6 Draft, May 2016.*~~

Formatted: Space Before: 3 pt, After: 3 pt

~~Residential ENERGY STAR Lighting~~

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

~~Protocols~~

Formatted: Table Caption, Space Before: 6

Formatted: Heading 2

Residential ENERGY STAR Lighting

Savings from the installation of screw-in ENERGY STAR CFLs, ENERGY STAR LED lamps, ENERGY STAR fluorescent torchieres, ENERGY STAR ~~indoor-specialty LED~~ fixtures ~~and~~, ENERGY STAR ~~outdoor~~ fixtures are based on a straightforward algorithm that calculates the difference between existing the baseline lamp/fixture wattage and new lamp/fixture wattage, and the average daily hours of usage for the lighting unit being replaced. ~~“An”~~

Using the tables provided in-service” rate- this section, the baseline lamp wattage reflects the input wattage associated with a lamp that is used-compliant with the corresponding standards included in the Energy and Independence and Security Act of 2007.

The coincidence factor (CF) discounts the peak demand savings to reflect the fact that not all lighting products purchased are actually installed kW reduction realized during the summer on-peak demand period. This is based on typical operating schedules for the geographical area covered by the program.

HVAC interactive factors are applied to capture the additional savings or penalty associated with the impact of lighting measures on the building’s HVAC system. A reduction in lighting load will result in additional cooling savings during the summer period, and a gas heating penalty during the winter period.

Algorithms

$$\text{Energy Savings } \left(\frac{\text{kWh}}{\text{yr}} \right) = \frac{(\text{Watts} * \text{Qty})_b - (\text{Watts} * \text{Qty})_q}{1,000 \frac{\text{Watts}}{\text{kW}}} * (\text{Hrs}) * (1 + \text{HVAC}_e)$$

$$\text{Peak Demand Savings } (\text{kW}) = \frac{(\text{Watts} * \text{Qty})_b - (\text{Watts} * \text{Qty})_q}{1,000 \frac{\text{Watts}}{\text{kW}}} * (\text{CF}) * (1 + \text{HVAC}_d)$$

$$\text{Fuel Savings } \left(\frac{\text{MMBtu}}{\text{yr}} \right) = \frac{(\text{Watts} * \text{Qty})_b - (\text{Watts} * \text{Qty})_q}{1,000 \frac{\text{Watts}}{\text{kW}}} * (\text{Hrs}) * (\text{HF}) * \left(\frac{0.003412}{\text{nHeat}} \right)$$

The general form Definition of the equation for the ENERGY STAR Variables

Watts_b = Wattage of baseline connected fixture or other high efficiency lamp

Watts_q = Wattage of qualifying connected fixture or lamp

Qty_b = Quantity of baseline fixtures or lamps

Qty_q = Quantity of energy-efficient fixtures or lamps

Hrs = Annual lighting operating hours

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: English (U.S.)

Formatted: Underline, (none)

CF = Coincidence factor

HVAC_{heat} = HVAC interaction factor for annual cooling energy savings algorithm is:

HVAC_{ecool} = HVAC interaction factor for annual electric heating energy savings

HVAC_d = HVAC interaction factor for peak demand reduction = $1 - ((HF / nHeat) * \%ElecHeat)$

HF = Heating factor, or percentage of lighting savings that must be heated

nHeat = Efficiency of heating system

Summary of Inputs

Residential ENERGY STAR Lighting

Number of Units X Savings per Unit

Per unit savings estimates are derived primarily from a 2004 Nexus Market Research report evaluating similar retail lighting programs in New England (MA, RI and VT). Per unit savings will decrease for CFLs in operation after 2012 due to the effects of federal minimum efficiency standards for incandescent lighting. Because CFLs typically have rated lifespans of 6-8000 hours (5-7 years) and incandescent light bulbs are rated at 1000 hours (1 year), after 2013 there will be less of a difference between CFLs in service and the incandescents that they would have been replacing.

National lighting efficiency standards are being increased according to the Energy Independence and Security Act of 2007 (EISA).²³ EISA pertains to the efficiency of newly manufactured bulbs, not existing stock. Existing *Protocol* baselines and measure lifetimes will remain until the impact of the standard can be fully measured and quantified. The future EISA wattage standards are:

EISA Phase 1

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Watts_b</u>	<u>Variable</u>	<u>See Tables below</u>	<u>1</u>
<u>Watts_q</u>	<u>Variable</u>	<u>Actual Lamp/Fixture Wattage</u>	<u>Application</u>
<u>Qty_b</u>	<u>Variable</u>	<u>Actual Lamp/Fixture Quantity</u>	<u>Application</u>
<u>Qty_q</u>	<u>Variable</u>	<u>Actual Lamp/Fixture Quantity</u>	<u>Application</u>
<u>Hrs</u>	<u>Variable</u>	<u>Interior: 1,205 hrs</u> <u>Exterior: 2,007 hrs</u>	<u>2</u>
<u>CF</u>	<u>Fixed</u>	<u>0.08</u>	<u>3</u>
<u>HVAC_{heat}</u> <u>HVAC_{ecool}</u>	<u>Variable</u>	<u>See Table below</u>	<u>1</u>
<u>HVAC_d</u>	<u>Variable</u>	<u>See Table below</u>	<u>1</u>

²³ EISA information available at <http://www.Lecore.energy.gov/femp/regulations/eisa.html>

Formatted: Space Before: 3 pt, After: 3 pt, Tab stops: 0.69", Left

Formatted: Table Caption, Space Before: 6 pt

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>HF</u>	<u>Fixed</u>	<u>Interior: 0.47</u> <u>Exterior: 0.00</u>	<u>1</u>
<u>nHeat</u>	<u>Fixed</u>	<u>0.72</u>	<u>1</u>
<u>%ElecHeat</u>	<u>Fixed</u>	<u>1.0</u>	<u>Default</u>

HVAC Interactive Factors

	<u>HVAC_{cheat}</u>	<u>HVAC_{cecool}</u>	<u>HVAC_d</u>
<u>Building with cooling</u>	<u>-0.11²⁴</u>	<u>0.12²⁵</u>	<u>0.24²⁶</u>
<u>Building without cooling or exterior</u>	<u>0.0</u>	<u>0.0</u>	<u>0.0</u>
<u>Unknown</u>	<u>-0.11²⁷</u>	<u>0.10²⁸</u>	<u>0.21²⁹</u>

Standard for General Service Bulbs

<u>Rated Lumen Ranges</u>	<u>Maximum Rate Wattage</u>	<u>Minimum Rate Lifetime</u>	<u>Effective Date</u>	<u>Efficacy Ranges (lumens per watt)</u>
1490-2600 (~90W – 150W)	72	1000 hrs	1/1/2012	21 – 36
1050-1489 (~75W – 90W)	53	1000 hrs	1/1/2013	20 – 28
750-1049 (~60W – 75W)	43	1000 hrs	1/1/2014	17 – 24
310-749 (~30W – 60W)	29	1000 hrs	1/1/2014	11 – 26

²⁴ From NEEP Mid-Atlantic TRM V6, pg 23: “Calculated using defaults; $1 - ((0.47 / 1.67) * 0.375)$ ”

²⁵ From NEEP Mid-Atlantic TRM V6, pg 23: “The value is estimated at 1.12 (calculated as $1 + (0.33 / 2.8)$). Based on cooling loads decreasing by 33% of the lighting savings (average result from REMRate modeling of several different building configurations in Wilmington, DE, Baltimore, MD and Washington, DC), assuming typical cooling system operating efficiency of 2.8 COP (starting from standard assumption of SEER 10.5 central AC unit, converted to 9.5 EER using algorithm $(-0.02 * SEER2) + (1.12 * SEER)$ (from Wassmer, M. (2003); A Component-Based Model for Residential Air Conditioner and Heat Pump Energy Calculations. Masters Thesis, University of Colorado at Boulder), converted to $COP = EER / 3.412 = 2.8COP$).”

²⁶ From NEEP Mid-Atlantic TRM V6, pg 23: “The value is estimated at 1.24 (calculated as $1 + (0.66 / 2.8)$). See footnote relating to WHFe for details. Note the 66% factor represents the Residential cooling coincidence factor calculated by dividing average load during the peak hours divided by the maximum cooling load (i.e. consistent with the PJM coincident definition).”

²⁷ From NEEP Mid-Atlantic TRM V6, pg. 23: “Calculated using defaults; $1 - ((0.47 / 1.67) * 0.375)$ ”

²⁸ From NEEP Mid-Atlantic TRM V6, pg. 23: “The value is estimated at 1.10 (calculated as $1 + (0.89 * (0.33 / 2.8))$). Based on assumption that 89% of homes have central cooling (based on KEMA Maryland Energy Baseline Study, Feb 2011.).”

²⁹ From NEEP Mid-Atlantic TRM V6, pg. 23: “The value is estimated at 1.21 (calculated as $1 + (0.89 * 0.66 / 2.8)$).”

ENERGY STAR CFL Standard and Specialty Bulbs

Standard CFL/LED Lamp Wattage Equivalency 1

Formatted: Table Caption

<u>Minimum Lumens</u>	<u>Maximum Lumens</u>	<u>Watts_b</u>
4000	6000	300
3001	3999	200
2550	3000	150
2000	2549	125
1600	1999	72
1100	1599	53
800	1099	43
450	799	29
250	449	25

Formatted: Table Cells

Formatted Table

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Don't keep with next

Formatted: Table Caption, Space Before: 12 pt

Decorative and non-G40 Globe

Specialty CFL and LED Lamp Wattage Equivalency 1

	<u>Minimum Lumens</u>	<u>Maximum Lumens</u>	<u>Watts_b</u>
<u>Decorative</u>	<u>500</u>	<u>699</u>	<u>43</u>
<u>Non-G40 Globe</u>	<u>500</u>	<u>574</u>	<u>43</u>
	<u>575</u>	<u>649</u>	<u>53</u>
	<u>650</u>	<u>1099</u>	<u>72</u>
	<u>1100</u>	<u>1300</u>	<u>150</u>

<u>Specialty Bulb Type</u>	<u>Lower Lumen Range</u>	<u>Upper Lumen Range</u>	<u>WattsBase</u>
3-Way	250	449	25
	450	799	40
	800	1099	60
	1100	1599	75
	1600	1999	100
	2000	2549	125
	2550	2999	150
Globe (medium and intermediate bases less)	90	179	10
	180	249	15

<u>Specialty</u> Bulb-Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
than 750 lumens)	250	349	25
	350	749	40
Decorative (Shapes B, BA, C, CA, DC, F, G, medium and intermediate bases less than 750 lumens)	70	89	10
	90	149	15
	150	299	25
	300	749	40
Globe (candelabra bases less than 1050 lumens)	90	179	10
	180	249	15
	250	349	25
	350	499	40
Decorative (Shapes B, BA, C, CA, DC, F, G, candelabra bases less than 1050 lumens)	500	1049	60
	70	89	10
	90	149	15
	150	299	25
Reflector with medium screw bases w/ diameter <= 2.25"	300	499	40
	500	1049	60
	400	449	40
	450	499	45
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.5" (*see exceptions below)	500	649	50
	650	1199	65
	640	739	40
	740	849	45
	850	1179	50
	1180	1419	65
	1420	1789	75
	1790	2049	90
2050	2579	100	
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.26" and <= 2.5" (*see exceptions below)	2580	3429	120
	3430	4270	150
	540	629	40
	630	719	45
	720	999	50
	1000	1199	65
	1200	1519	75
	1520	1729	90
1730	2189	100	
*ER30, BR30, BR40, or ER40	2190	2899	120
	2900	3850	150
	400	449	40
	450	499	45

Specialty Bulb-Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
	500	649-1179 ³⁰	50
*BR30, BR40, or ER40	650	1419	65
*R20	400	449	40
	450	719	45
*All reflector lamps below lumen ranges specified above	200	299	20
	300	399-639 ³¹	30

$$\text{Energy Savings (kWh)} = (\text{CFL}_{\text{watts}} [\text{CFL}_{\text{base}} - \text{CFL}_{\text{ee}}] / 1000) \times \text{CFL}_{\text{hours}} \times 365 \times \text{CFL}_{\text{ISR}}$$

$$\text{Demand Savings (kW)} = (\text{CFL}_{\text{base}} - \text{CFL}_{\text{ee}}) \text{CFL}_{\text{watts}} / 1000 \times \text{CF} \times \text{CFL}_{\text{ISR}}$$

ENERGY STAR LED Recessed Downlights & Integral Lamps/Fixtures

Formatted: (none)

Some LED products do not allow for a fixture-to-fixture comparison due to unique form factors, such as LED rope lights, sign lighting, and cove lighting.

In these instances, a similar savings and demand algorithm may be used, however with a different metric other than fixture quantity entered. For example, a comparison of watts per linear foot between LED and incandescent technologies would result in accurate energy savings calculations.

Algorithms

Formatted: Underline, (none)

$$\text{Peak Demand Savings (kW)} = (\Delta kW) * (CF) * (1 + HVAC_d)$$

Formatted: English (U.S.)

$$\text{Energy Savings } \left(\frac{\text{kWh}}{\text{yr}} \right) = (\Delta kW) * (Hrs) * (1 + HVAC_e)$$

Formatted: Underline, (none)

$$\text{Fuel Savings } \left(\frac{\text{MMBtu}}{\text{yr}} \right) = \frac{(\text{Watts} * \text{Qty})_b - (\text{Watts} * \text{Qty})_q}{1,000 \frac{\text{Watts}}{\text{kW}}} * (Hrs) * (HF) * \left(\frac{0.003412}{nHeat} \right)$$

where:

$$\begin{aligned} \Delta kW = & \\ & (\text{linear feet of replaced lighting}) * \\ & (\text{baseline fixture wattage of lighting per foot}) - \\ & (\text{linear feet of installed LED lighting}) \\ & * (\text{wattage of new LED lighting per foot}) \end{aligned}$$

³⁰ The upper bounds for these categories depends on the lower bound of the next higher wattage, which varies by bulb type.

³¹ As above.

The remaining variables are unchanged from those presented above in the Summary of Inputs.

Sources

1. NEEP, *Mid-Atlantic Technical Reference Manual*, V6, May 2016., p. 21, pp. 30–31, 38–39, 46–47, 51–52, and 59–60. From the NEEP Mid-Atlantic TRM: “Base wattage is based upon the post first phase of EISA wattage and wattage bins consistent with ENERGY STAR, v1.1.”
2. Efficiency Vermont, *Technical Reference User Manual*, 2016, p. 265. The hours of use for this measure are based on the assumption that these will be installed in the highest use locations due to their high cost. Residential hours of use are based on average daily hours of use of 3.3, from Table 3-5, page 43, value for Living Space for Upstate New York, from NMR Group, Inc., *Northeast Residential Lighting Hours-of-Use Study*, prepared for CT Energy Efficiency Board, Cape Light Compact, Massachusetts Energy Efficiency Advisory Council, National Grid MA, National Grid RI, NYSERDA, Northeast Utilities, May 5, 2014.
3. NY, *Standard Approach for Estimating Energy Savings*, V4, April 2016, p.133. From the NY TRM: “From NY TRM 2016, for NYC due to proximity to NJ. From the NY TRM: “The coincidence factors were derived from an examination of studies throughout New England that calculated coincident factors based on the definition of system peak period at the time, as specified by the New England Power Pool and later, ISO-New England.”

Appliance Recycling Program

Protocols

Formatted: Heading 2

LED Fixture Wattage Equivalency

Bulb-Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
Reflector with medium screw bases w/ diameter <= 2.25"	400	449	40
	450	499	45
	500	649	50
	650	1199	65
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.5" (*see exceptions below)	640	739	40
	740	849	45
	850	1179	50
	1180	1419	65
	1420	1789	75
	1790	2049	90
	2050	2579	100
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.26" and <= 2.5" (*see exceptions below)	2580	3429	120
	3430	4270	150
	540	629	40
	630	719	45
	720	999	50
	1000	1199	65
	1200	1519	75
	1520	1729	90
*ER30, BR30, BR40, or ER40	1730	2189	100
	2190	2899	120
	2900	3850	150
	400	449	40
*BR30, BR40, or ER40	450	499	45
	500	649-1179 ³²	50
*R20	650	1419	65
	400	449	40
*All reflector lamps below lumen ranges specified above	450	719	45
	200	299	20
	300	399-639 ³³	30

³² The upper bounds for these categories depends on the lower bound of the next higher wattage, which varies by bulb type.

³³ As above.

$$\text{Energy Savings (kWh)} = \frac{(\text{LEDF}_{\text{base}} - \text{LEDF}_{\text{ee}}) / 1000 \times \text{LEDF}_{\text{Hours}} \times 365 \times \text{LEDF}_{\text{ISR}}}{\text{LEDF}_{\text{ISR}}}$$

$$\text{Demand Savings (kW)} = (\text{LEDF}_{\text{base}} - \text{LEDF}_{\text{ee}}) / 1000 \times \text{CF} \times \text{LEDF}_{\text{ISR}}$$

$$\text{Energy Savings (kWh)} = (\text{LED}_{\text{watts}} / 1000) \times \text{LED}_{\text{Hours}} \times 365 \times \text{LED}_{\text{ISR}}$$

$$\text{Demand Savings (kW)} = (\text{LED}_{\text{watts}} / 1000) \times \text{CF} \times \text{LED}_{\text{ISR}}$$

The following sections detail savings calculations **ENERGY STAR LED Standard and Specialty Bulbs**

LED Wattage Equivalency

Bulb Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
Standard	250	449	25
	450	799	29
	800	1099	43
	1100	1599	53
	1600	1999	72
	2000	2549	125
	2550	3000	150
	3001	3999	200
3-Way	250	449	25
	450	799	40
	800	1099	60
	1100	1599	75
	1600	1999	100
	2000	2549	125
	2550	2999	150
Globe (medium and intermediate bases less than 750 lumens)	90	179	10
	180	249	15
	250	349	25
	350	749	40
Decorative (Shapes B, BA, C, CA, DC, F, G, medium and intermediate bases less than 750 lumens)	70	89	10
	90	149	15
	150	299	25
	300	749	40
Globe (candelabra bases less than 1050 lumens)	90	179	10
	180	249	15
	250	349	25

Bulb-Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
	350	499	40
	500	1049	60
Decorative (Shapes B, BA, C, CA, DC, F, G, candelabra bases less than 1050 lumens)	70	89	10
	90	149	15
	150	299	25
	300	499	40
	500	1049	60
Reflector with medium screw bases w/ diameter <= 2.25"	400	449	40
	450	499	45
	500	649	50
	650	1199	65
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.5" (*see exceptions below)	640	739	40
	740	849	45
	850	1179	50
	1180	1419	65
	1420	1789	75
	1790	2049	90
	2050	2579	100
	2580	3429	120
R, PAR, ER, BR, BPAR or similar bulb shapes with medium screw bases w/ diameter > 2.26" and <= 2.5" (*see exceptions below)	3430	4270	150
	540	629	40
	630	719	45
	720	999	50
	1000	1199	65
	1200	1519	75
	1520	1729	90
	1730	2189	100
*ER30, BR30, BR40, or ER40	2190	2899	120
	2900	3850	150
	400	449	40
*BR30, BR40, or ER40	450	499	45
	500	649-1179 ³⁴	50
	650	1419	65
*R20	400	449	40
	450	719	45
*All reflector lamps	200	299	20

³⁴ The upper bounds for these categories depends on the lower bound of the next higher wattage, which varies by bulb type.

Bulb-Type	Lower-Lumen Range	Upper-Lumen Range	WattsBase
below lumen ranges specified above	300	399-639 ³⁵	30

$$\text{Energy Savings (kWh)} = ((\text{LED}_{\text{base}} - \text{LED}_{\text{ee}}) / 1000) \times \text{LED}_{\text{Hours}} \times 365 \times \text{LED}_{\text{ISR}}$$

$$\text{Demand Savings (kW)} = ((\text{LED}_{\text{base}} - \text{LED}_{\text{ee}}) / 1000) \times \text{CF} \times \text{LED}_{\text{ISR}}$$

Definition of Terms

~~CF_{base} = Based on lumens of the CFL bulb~~

~~CF_{ee} = Actual wattage of CFL purchased/installed~~

~~CF_{hours} = Average hours of use per day per CFL~~

~~CF_{Bulb} = Summer demand coincidence factor for CFLs and LEDs~~

~~CF_{ISR} = In service rate per CFL~~

~~CF_{Fixtures} = Summer demand coincidence factor for CFL fixtures.~~

~~LED_{base} = Based on lumens of the LED~~

~~LED_{ee} = Actual wattage of LED purchased/installed~~

~~LED_{hours} = Average hours of use per day per LED recessed downlight or integral lamp~~

~~LED_{ISR} = In service rate per LED recessed downlight or integral lamp~~

~~LEDF_{base} = Based on lumens of the LED Fixture~~

~~LEDF_{ee} = Actual wattage of LED Fixture purchased/installed~~

~~LEDF_{hours} = Average hours of use per day per LED Fixture recessed downlight or integral lamp~~

~~LEDF_{ISR} = In service rate per LED Fixture recessed downlight or integral lamp~~

ENERGY STAR Lighting

³⁵ As above.

Component	Type	Value	Sources
CFL _{base}	Variable	Based on lumens	8
CFL _{ee}	Variable	Actual bulb wattage	
CFL _{hours}	Fixed	2.8	6
CFL _{ISR}	Fixed	83.4%	5
CF _{Bulb}	Fixed	9.9%	4
LED _{watts}	Variable	Based on lumens	8
LED _{ee}	Variable	Actual bulb wattage	
LED _{hours}	Fixed	2.8	6
LED _{ISR}	Fixed	100%	7
CF _{LED}	Fixed	8.2%	
LEDE _{watts}	Variable	Based on lumens	8
LEDE _{ee}	Variable	Actual fixture wattage	
LEDE _{hours}	Fixed	2.8	6
LEDE _{ISR}	Fixed	100%	7
CF _{LEDE}	Fixed	8.2%	

Sources:

1. Nexus Market Research, “Impact Evaluation of the Massachusetts, Rhode Island and Vermont 2003 Residential Lighting Programs”, Final Report, October 1, 2004, p. 43 (Table 4-9) The delta watts are reduced by 22.2% in the same proportion to individual CFLs (48.5W to 32.9W) following full enactment of EISA requirements.
2. US Department of Energy, Energy Star Calculator.
3. Nexus Market Research, “Impact Evaluation of the Massachusetts, Rhode Island and Vermont 2003 Residential Lighting Programs”, Final Report, October 1, 2004, p. 42 (Table 4-7). These values reflect both actual installations and the % of units planned to be installed within a year from the logged sample. The logged % is used because the adjusted values (i.e. to account for differences between logging and telephone survey samples) were not available for both installs and planned installs. However, this seems appropriate because the % actual installed in the logged sample from this table is essentially identical to the % after adjusting for differences between the logged group and the telephone sample (p. 100, Table 9-3).
4. RLW Analytics, “Development of Common Demand Impacts for Energy Efficiency Measures/Programs for the ISO Forward Capacity Market (FCM)”, prepared for the New England State Program Working Group (SPWG), March 25, 2007, p. IV.
5. The average wattage (18.4W) of the standard CFL established in the 2009 “NJCEP Residential CFL Impact Evaluation and Protocol Review”, September 28, 2008, p.3-8 (Table 3-6) is adjusted by a post EISA multiplier (1.79) of the 2014 Mid-Atlantic Technical Reference Manual V4.0 for calculating the new delta watts after the incandescent bulb wattage is reduced (from 100W to 72W in 2012, 75W to 53W in 2013 and 60W to 43W and 40W to 29W in 2014).
6. RLW Analytics, *New England Residential Lighting Markdown Impact Evaluation*, January 20, 2009.

- 7. ~~For determining demand savings the baseline was adopted from 2009 KEMA evaluation and represents the replacement of a 65W BR30 downlight and high efficiency is the average of ENERGY STAR qualified downlights (11/10/2009) with lighting output exceeding 475 lumens. Due to the high incremental cost and limited market availability of products, the higher ISR reflects the assumption that every LED downlight purchased is directed towards immediate use.~~
- 8. ~~Mid Atlantic TRM V5~~

Home Energy Reporting System

— Protocols

~~The purpose of the program is to provide information and tools that residential customers can use to make decisions about what actions to take to improve energy efficiency in their homes. The information is mailed in reports separately from a utility’s regular bill to create a neighbor to neighbor comparison where homes of similar size are compared to each other, as well as targeting energy saving tips to individuals. The quantity and timing of mailed reports will vary by utility and fuel type.—~~

Home Energy Reporting System

~~Gas Savings (Therms) = $G_{Sav_{HERS}}$~~

Component	Type	Value	Sources
$G_{Sav_{HERS}}$	Fixed	13.1 therms	1

Sources:

- 1. ~~The average natural gas savings from similar program offered to Puget Sound Energy customers. (Reference: Evidence from Two Large Field Experiments that Peer Comparison Feedback Can Reduce Residential Energy Usage, Ayres, 2009)~~

Refrigerator/Freezer Retirement Program

— Protocols

retirement program. The general form of the equation for the Refrigerator/Freezer Retirement Program savings algorithm is:

Number of Units \times Savings per Unit

To determine resource savings, the per unit estimates in the protocols will be multiplied by the number of appliance units.

Formatted: Underline

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Pattern: Clear (Light Yellow)

Formatted: Body Text, Justified, Right: 0.09", Line spacing: At least 12 pt

Algorithm

~~To determine resource savings, the per unit estimates in the protocols will be multiplied by the number of appliance units.~~

Unit savings are the product of average fridge/freezer consumption (gross annual savings), and a net to gross ratio that adjusts for both free ridership and the portion of retired units that are replaced with more efficient new units.

Algorithm

~~Electricity Impact Energy Savings~~ (kWh/yr) = $ESav_{RetFridge} + ESav_{RAC} - ESav_{DEHRetFreezer}$

~~Peak Demand Impact Savings~~ (kW) = $DSav_{RetFridge} * RetFreezer * CF_{RetFridge}$

Definition of Terms

Definition of Terms

$ESav_{RetFridge}$ = Gross annual energy savings per unit retired refrigerator

$ESav_{RetFreezer}$ = Gross annual energy savings per unit retired freezer

$DSav_{RetFridge}$ = Summer demand savings per retired refrigerator

$DSav_{RetFreezer}$ = Summer demand savings per retired freezer

$CF_{RetFridge}$ = Summer demand coincidence factor.

Summary of Inputs

Refrigerator/Freezer Recycling

Component	Type	Value	Source
$ESav_{RetFridge}$	Fixed	761,098 kWh	1
$ESav_{RetFreezer}$	Fixed	639,715 kWh	1
$ESav_{RAC}$	Fixed	166 kWh	4
$ESav_{DEH}$	Fixed	169 kWh	5
$DSav_{RetFridge}$	Fixed	0.11416 kW	31.2
$DSav_{RetFreezer}$	Fixed	0.114107 kW	31.2
$DSav_{RAC}$	Fixed	0.16 kW	4

Formatted: Heading 4, Space After: 6 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Normal, Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Font: 10 pt, Bold

Formatted: Body Text, Justified, Right: 0.09", Line spacing: At least 12 pt

Formatted: Font: 12 pt, Not Bold

Formatted: Normal, Left, Right: 0", Line spacing: single

Formatted: (none)

Formatted: Normal, Left, Indent: First line: 0.25", Right: 0", Space Before: 3 pt, After: 3 pt, Line spacing: single

Formatted: Normal, Left, Indent: First line: 0.25", Right: 0", Space Before: 3 pt, After: 3 pt, Line spacing: single

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Not Small caps

Formatted: Table Caption, Left, Don't keep with next

Formatted: Table Header

Formatted: Table Cells

Formatted: Table Cells, Left, Indent: Left: 0"

Formatted: Table Cells

Formatted: Table Cells, Left, Indent: Left: 0"

Formatted: Table Cells

Formatted: Table Cells, Left, Indent: Left: 0"

Formatted: Table Cells

Formatted: Table Cells, Left, Indent: Left: 0"

Component	Type	Value	Source
DSav_{DEH}	Fixed	0.114	5
CF _{RetFridge}	Fixed	1	<u>4</u>

Formatted: Table Header

Formatted: Table Cells

Formatted: Table Cells, Left, Indent: Left: 0"

Formatted: Heading 4, Space After: 6 pt

Formatted: Font: Italic

Formatted: Space Before: 3 pt, After: 3 pt

Sources:

- ~~1. Northeast Energy Efficiency Partnerships, "NEEP, Mid-Atlantic Technical Reference Manual", Version 4.0, June, 2014, p. 96. Savings incorporate regression analysis results of EmPower Maryland evaluation of the 2013 Appliance Recycling Program.~~
- ~~2.1. Northeast Energy Efficiency Partnerships, "Mid-Atlantic Technical Reference Manual", Version 4.0, June, 2014, p. 98, V7. May 2017.~~
- ~~3.2. Coincidence factor already embedded in summer peak demand reduction estimates~~
- ~~4. Mid-Atlantic TRM V5~~
- ~~5. Rhode Island TRM 2016 Program Year
<https://www.nationalgridus.com/non-html/cer/ri/PY2016%20RI%20TRM.pdf>
 (pg 20)~~

Formatted: Centered

Home Performance with ENERGY STAR Program

In order to implement Home Performance with Energy Star, there are various standards a program implementer must adhere to in order to deliver the program. -The program implementer must use software that meets a national standard for savings calculations from whole-house approaches such as home performance. ~~-The difference in modeled annual energy consumption between the program and existing home is the project savings for heating, hot water, cooling, lighting and appliance end uses. The software the program implementer uses must adhere to at least one of the following standards:~~

Formatted: Space Before: 6 pt, After: 6 pt

The software the program implementer uses must adhere to at least one of the following standards:

- A software tool whose performance has passed testing according to the National Renewable Energy Laboratory's HERS BESTEST software energy simulation testing protocol.³⁶
- Software approved by the US Department of Energy's Weatherization Assistance Program.³⁷
- RESNET approved rating software.³⁸

There are numerous software packages that comply with these standards. - Some examples of the software packages are REM/Rate, Real Home Analyzer, EnergyGauge, TREAT, and HomeCheck.

Formatted: Space Before: 6 pt

³⁶ Information about BESTEST-EX can be found at

http://www.nrel.gov/buildings/bestest_ex.html-.<http://www.nrel.gov/buildings/bestest-ex.html>

³⁷ A listing of the approved software available at

http://www.waptac.org/data/files/Website_Docs/technical_tools/EnergyAuditMatrixTable2.pdf-.http://www.waptac.org/data/files/Website_Docs/technical_tools/EnergyAuditMatrixTable2.pdf

³⁸ A listing of the approved software available at <http://resnet.us>-

Formatted: Space Before: 3 pt, After: 2 pt

|

Commercial and Industrial Energy Efficient Construction

Formatted: Centered

~~C&I Electric~~ Protocols

~~Baselines and Code Changes~~

In general, efficiency baselines are designed to reflect current market practices - typically, the higher of applicable codes or the minimum efficiency of available new equipment - and are updated periodically to reflect upgrades in code or information from evaluation results. ~~There are exceptions to this approach, as in the Direct Install program (see below).~~

Formatted: Space Before: 6 pt, After: 6 pt

Baseline data reflect ASHRAE 90.1-2007 for existing building retrofit and ASHRAE 90.1-2013 for new construction, ~~replacement of failed equipment, end of useful life, and entire facility rehabilitation unless otherwise noted for applications designated "2011".~~

Formatted: Space Before: 6 pt, After: 6 pt

~~Building Shell~~

Building shell measures identified in an approved Local Government Energy Audit (or equivalent) are eligible for incentives through the Custom and Pay for Performance program. Savings for these measures will vary from project to project based on factors such as building size, existing levels of insulation and infiltration levels. As a result, energy savings for these installed building shell measures will be taken from what is provided in the approved ~~Audit~~ ~~energy Audit and/or energy~~ analysis provided with the application submission.

Formatted: Space Before: 6 pt, After: 6 pt

C&I Electric Protocols

The following measures are outlined in this section: Performance Lighting, Prescriptive Lighting, Refrigerated Case LED Lights, Lighting Controls, ECMs for Refrigeration, Electric HVAC Systems, Fuel Use Economizers, Dual Enthalpy Economizers, Occupancy Controlled Thermostats, Electric Chillers, VFDs, and Commercial Refrigeration.

Performance Lighting

For new construction and entire facility rehabilitation projects, savings are calculated by comparing the lighting power density of fixtures being installed to the baseline ~~power densities from~~ lighting power density, or "lighting power allowance," from the building code. For the state of New Jersey, the applicable building code is ASHRAE 90.1 2013.

Formatted: Normal, Space Before: 6 pt, After: 6 pt

Lighting equipment includes fluorescent fixtures, ballasts, compact fluorescent fixtures, LED fixtures, and lamps, and high-intensity discharge fixtures such as metal halide lamps. The measurement of energy savings is based on algorithms with measurement of key variables (i.e., Coincidence Factor and Operating Hours) through end-use metering data accumulated from a large sample of participating facilities from 1995 through 1999, and high pressure sodium luminaires.

Formatted: Normal, Space Before: 6 pt, After: 6 pt

Algorithms

$$\Delta kW = \frac{(\# \text{ of replaced fixtures}) * (\text{Watts}_b)}{(\# \text{ of fixtures installed}) * (\text{Watts}_q)} = (LPD_b - LPD_q) * (SF)$$

$$\text{Energy Savings} \left(\frac{kWh}{yr} \right) = (\Delta kW) * (\text{Hrs}) * (1 + HVAC_e)$$

$$\text{Peak Demand Savings (kW)} = (\Delta kW) * (CF) * (1 + HVAC_d)$$

$$\text{Fuel Savings} \left(\frac{MMBtu}{yr} \right) = (\Delta kW) * (\text{Hrs}) * (HVAC_g)$$

Formatted: Normal

Definition of Variables

Algorithms

$$\text{Demand Savings} = \Delta kW * CF * (1 + HF)$$

$$\text{Energy Savings} = \Delta kW * EFLH * (1 + HF)$$

$$\Delta kW = (LPD_{base} - LPD_{inst}) * SF$$

Definition of Variables

ΔkW = Change in connected load from baseline to efficient lighting level.

$LPD_{base} - \text{Watts}_{b,q}$ = Wattage of existing baseline and qualifying equipment

LPD_b = Baseline lighting power density in Watt per square foot of space floor area, based on ASHRAE 90.1 Table 9.6.1 (Space-by-Space Method)

LPD_{inst} LPD_q = Lighting power density of installed qualified fixtures, equal to the sum of installed fixture wattage divided by floor area of the space where the fixtures are installed. Wattage of installed fixtures is based on table at http://www.sce.com/NR/rdonlyres/FC51087D-2848-42DF-A52A-BDBA1A09BF8D/0/SCE_B_StandardFixtureWatts010108.pdf.

SF = space = Space floor area, Square Foot in square feet

Formatted: Indent: First line: 0"

Formatted: Underline, (none)

Formatted: Normal, Level 4, Keep with next

Formatted: Normal

Formatted: Font: Bold

Formatted: Indent: Left: 0.25", First line: 0", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Normal, Indent: Left: 0.25", Hanging: 0.75", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Normal, Indent: Left: -0.75", Hanging: 1.75", Space Before: 3 pt, After: 3 pt, Tab stops: 0.25", Left + 0.56", Left + 0.63", Left + 1", Left + 1.91", Left + 2.54", Left + 3.18", Left + 3.82", Left + 4.45", Left + 5.09", Left + 5.73", Left + 6.36", Left + 7", Left + 7.63", Left + 8.27", Left + 8.91", Left + 9.54", Left + 10.18", Left

Formatted: (none)

Formatted: (none)

Formatted: Space Before: 3 pt, After: 3 pt, Tab stops: 0.25", Left + 0.63", Left

CF = Coincidence ~~Factor~~factor

EFLH = Equivalent Full Load Hours

H = Hrs = Annual operating hours

HVAC_d = HVAC Interactive Factor for peak demand savings

HVAC_e = HVAC Interactive Factor for annual energy savings

HVAC_g = HVAC Interactive Factor for annual energy savings

Summary of Inputs

Lighting Verification Performance Lighting

Component	Type	Value	Source
<u>AtkW</u> <u>Watts_{b,q}</u>	<u>Fixed</u> <u>Variable</u>	See <u>California SPENGrid Fixture Wattage Table</u> : http://www.sce.com/NR/rdonlyres/FCS1087D-2848-42DF-A52A-BDBA1A09BF8D/0/SCE_B_StandardFixtureWatts010108.pdf Fixture counts and types, space type, floor area from customer application. <u>And Formula Above.</u>	1 • <u>Baseline LPD from ASHRAE 90.1-2013 Table 9.6.1</u> • <u>Installed LPD; space type and floor area from customer application.</u>
<u>SF</u>	<u>Variable</u>	<u>From Customer Application</u>	<u>Application</u>
<u>CF</u>	<u>Fixed</u>	<u>-See Lighting Table by Building Type</u>	<u>.24</u>
<u>Hrs</u>	<u>Fixed</u>	<u>See Table by Building Type</u>	<u>4</u>
<u>H</u> <u>HVAC_d</u>	<u>Fixed</u>	<u>See Lighting Table by Building Type</u>	<u>3</u> <u>.5</u>
<u>EFLH</u> <u>HVAC_e</u>	<u>Fixed</u>	<u>-See Lighting Table by Building Type</u>	<u>3, 5</u>
<u>HVAC_g</u>	<u>Fixed</u>	<u>See Table by Building Type</u>	<u>6</u>
<u>LPD_b</u>	<u>Variable</u>	<u>Lighting Power Density for, W/SF</u>	<u>2</u>
<u>LPD_q</u>	<u>Variable</u>	<u>Lighting Power Density, W/SF</u>	<u>Application</u>

Formatted: Indent: Left: -0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 0.63", Left + 1", Left

Formatted: Indent: Left: -0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Table Caption, Left

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Subscript

Formatted: Table Cells, No bullets or numbering

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted Table

Formatted: Table Cells, Line spacing: single

Formatted: Table Cells

Formatted Table

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Line spacing: single

Formatted: Table Cells, Line spacing: single

Formatted: Font: Bold

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Building Type	FLH Sector	CF	Hours/F
Storage Conditioned School	4,290 Large Commercial/Industrial & Small Commercial	0.6950	0.062,575
Storage Heated or Unconditioned	4,290	0.69	0.00
Warehouse/ Industrial	4,009 Large Commercial/Industrial	0.697	0.064,116
Average = Miscellaneous	4,268 Small Commercial	0.7268	0.133,799
Unknown ⁴⁰	Large Commercial/Industrial	0.50	2,575

HVAC Interactive Effects

Building Type	Demand Waste Heat Factor (HVAC_d)		Annual Energy Waste Heat Factor by Cooling/Heating Type (HVAC_e)			
	AC (Utility)	AC (PJM)	AC/NonElec	AC/ElecRes	Heat Pump	NoAC/ElecRes
Office	0.35	0.32	0.10	-0.15	-0.06	-0.25
Retail	0.27	0.26	0.06	-0.17	-0.05	-0.23
Education	0.44	0.44	0.10	-0.19	-0.04	-0.29
Warehouse	0.22	0.23	0.02	-0.25	-0.11	-0.27
Other ⁴¹	0.34	0.32	0.08	-0.18	-0.07	-0.26

Interactive Factor (HVAC_g) for Annual Fuel Savings

Project Type	Fuel Type	Impact (MMBtu/ΔkWh)
Large Retrofit	C&I Gas Heat	-0.00023

⁴⁰ Per the NEEP Mid-Atlantic TRM, v7: “The “Other” building type should be used when the building type is known but not explicitly listed above. A description of the actual building type should be recorded in the project documentation. To encourage the use of building type-specific values, the assumed lighting coincidence factors for unknown building types have been set equal to the lowest values from the table.”

⁴¹ Per the NEEP Mid-Atlantic TRM, v7: “The ‘Other’ building type should be used when the building type is known but not explicitly listed above. A description of the actual building type should be recorded in the project documentation.”

- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: Bold, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Don't keep with next
- Formatted: Don't keep with next
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Merged Cells
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Don't keep with next
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black
- Formatted: Font: 12 pt, Font color: Black

<u>Large Retrofit</u>	<u>Oil</u>	<u>-0.00046</u>
<u>Small Retrofit</u>	<u>Gas Heat</u>	<u>-0.001075</u>
<u>Small Retrofit</u>	<u>Oil Heat</u>	<u>-0.000120</u>

Sources ~~—~~ *Note: Figures in italics are

Formatted: Font: Not Bold

1. Device Codes and Rated Lighting System Wattage Table Retrofit Program, National Grid, January 13, 2015.
<https://www1.nationalgridus.com/files/AddedPDF/POA/RILightingRetrofit1.pdf>
2. ASHRAE Standards 90.1-2013, Energy Standard for Buildings Except Low Rise Residential Buildings, Table 9.6.1.; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
3. Average HVAC interactive effects by building type derived from the NEEP Mid-Atlantic TRM 2017, NEEP, *Mid-Atlantic Technical Reference Manual*, V7. May 2017, pp. 464-465. From NEEP TRM: “EmPOWER Maryland DRAFT Final Impact Evaluation Report – July 2014 (source #5) Evaluation Year 4 (June 1, 2012 – May 31, 2013) Commercial & Industrial Prescriptive & Small Business Programs, Navigant, March 31, 2014. Values for Washington, D.C. and Delaware assume values from Maryland, Pepco and Maryland, DPL, respectively.”
4. NEEP Mid-Atlantic TRM 2017, NEEP, *Mid-Atlantic Technical Reference Manual*, V7. May 2017, pp. 462-463.
Massachusetts TRM, 2016-2018 Program Years, October 2015. Original source: DNV KEMA (2013). Impact

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Sources:

Formatted: Font: Bold, Italic

1. California Standard Performance Contracting Program
2. RLW Analytics, *Coincident Factor Study, Residential and Commercial & Industrial Lighting Measures*, 2007.
3. Quantum Consulting, Inc., for Pacific Gas & Electric Company, Evaluation of Pacific Gas & Electric Company’s 1997 Commercial 2010 Prescriptive Lighting Installations. Prepared for Massachusetts Energy Efficiency *Incentives Program: Lighting Technologies*”, March 1, 1999
- 4.5. KEMA. *New Jersey’s Clean Energy Program Energy Impact Evaluation and Protocol Review*. 2009 Administrators and Massachusetts Energy Efficiency Advisory Council.
- 5-6. Northeast Energy Efficiency Partnerships & KEMA for NEEP, C&I Lighting Load Shape Project. July 19, 2011 FINAL Report - Prepared for the Regional Evaluation, Measurement and Verification Forum. July 19, 2011.
http://www.neep.org/sites/default/files/products/NEEP_CI_Lighting_LS_FINAL_Report_ver_5_7_19_11.pdf

Formatted

Formatted: No underline

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: List Paragraph, Indent: Left: 0"

Formatted: Font: Not Italic

Formatted: Font: Not Italic

|

Prescriptive Lighting

This is a fixture replacement program for existing commercial customers targeted for facilities performing efficiency upgrades to their lighting systems.

~~The baseline for linear and U-bend fluorescent measures is standard T8 fixtures with electronic ballasts or actual existing HID fixtures.~~

~~The baseline for LED fixtures is the actual fixture being replaced.~~

~~The baseline for induction lighting is an equivalent pulse-start metal halide fixture (6).~~

~~The baseline for LED refrigerator Case Lighting is that the fixture replaced was 2.63 times the wattage of the replacement LED (7).~~

New fixtures and technologies available after publication will be periodically updated. Baselines will be established based on the guidelines noted below.

Formatted: Space Before: 6 pt

Algorithms

~~Algorithms~~

Formatted: Normal (Web)

Formatted: Font: Bold

$$\text{Demand Savings} = (\Delta kW) \times (CF) \times (1 + IF)$$

$$\text{Energy Savings} = (\Delta kW) \times (1 + IF) \times (EFLH)$$

$$\Delta kW = (\text{Number of fixtures installed} \times \text{baseline wattage for new fixture}) - (\text{number of replaced fixtures} \times \text{wattage from table})$$

~~*For refrigerated case LED fixtures, the following protocols will be applied to account for the lighting and refrigeration energy savings associated with this measure.*~~

Algorithms

Formatted: Heading 4

Formatted: Font: Bold

Formatted: No underline

$$\text{Demand Savings} = (\Delta kW) \times (CF) \times (1 + IF) \times (1 + (0.28 \times \text{Eff}))$$

$$\text{Energy Savings} = (\Delta kW = (\# \text{ of replaced fixtures}) \times (\text{baseline fixture wattage from table}) - (\# \text{ of fixtures installed}) \times (\text{wattage of new fixture})) \times (1 + (0.28 \times \text{Eff}))$$

$$\text{Energy Savings} \left(\frac{\text{kWh}}{\text{yr}} \right) = (\Delta kW) \times (Hrs) \times (1 + HVAC_e)$$

$$\text{Peak Demand Savings (kW)} = (\Delta\text{kW}) * (\text{CF}) * (1 + \text{HVAC}_d)$$

$$\text{Fuel Savings } \left(\frac{\text{MMBtu}}{\text{yr}} \right) = (\Delta\text{kW}) * (\text{Hrs}) * (\text{HVAC}_g)$$

Definition of Variables

$$\Delta\text{kW} = \text{X} * (1 + \text{IF}) * \text{EFLH} * (1 + (0.28 * \text{Eff}))$$

Definition of Variables

ΔkW = Change in connected load from baseline to efficient lighting level.

CF = Coincidence Factor

EFLH = Equivalent Full Load Hours

IF = Interactive Factor

0.28 = Conversion from kW to tons (Refrigeration)

Eff = Efficiency of typical refrigeration system in kW/ton

Hrs = Annual hours of operation

HVAC_d = HVAC interactive factor for peak demand savings

HVAC_e = HVAC interactive factor for annual energy savings

HVAC_g = HVAC interactive factor for annual fuel savings

Summary of Inputs

Prescriptive Lighting for Commercial Customers

Component	Type	Value	Source
ΔkW	Fixed Variable	See Lighting Grid Fixture Wattage Table derived from California SPC Table at: https://www1.nationalgridus.com/files/AddedPDF/POA/RILightingRetrofit1.pdf And http://www.sce.com/NR/rdonlyres/FC51	1 Fixture counts and types, space type, floor area from customer application.

Formatted: Space Before: 9 pt, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Indent: Left: 0", First line: 0", Space Before: 3 pt, After: 3 pt, Tab stops: 0.25", Left

Formatted: Indent: Left: 0", First line: 0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Indent: Left: 0", Keep with next

Formatted: Table Caption, Space Before: 6

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Table Cells, Right: 0"

Formatted: Table Cells

Component	Type	Value	Source
		087D-2848-42DF-A52A-BDBA1A09BF8D/0/SCE_B_StandardFixtureWatts010108.pdf formula above	
<u>CF</u>	<u>Fixed</u>	<u>Table by Building in Performance Lighting Section Above</u>	<u>3</u>
<u>CFHrs</u>	Fixed	See <u>Lighting</u> Table by Building in Performance Lighting Section Above	<u>23</u>
<u>EFLHVAC_d</u>	Fixed	See <u>Lighting</u> Table by Building Type in Performance Lighting Section Above	<u>3, 4, 2</u>
<u>IFHVAC_e</u>	Fixed	See <u>Lighting</u> Table by Building Type in Performance Lighting Section Above	<u>3</u>
<u>E#HVAC_g</u>	Fixed	<u>1.6</u> See Table by Building Type in Performance Lighting Section Above	<u>54</u>

Sources & Notes:

1. Device Codes and Rated Lighting System Wattage Table Retrofit Program, National Grid, January 13, 2015; available at: <https://www1.nationalgridus.com/files/AddedPDF/POA/RILightingRetrofit1.pdf>.
2. Average HVAC interactive effects by building type derived from the NEEP Mid-Atlantic TRM 2017, NEEP, Mid-Atlantic Technical Reference Manual, V7. May 2017, pp. 464-465. From NEEP TRM: "EmPOWER Maryland DRAFT Final Impact Evaluation Report Evaluation Year 4 (June 1, 2012 – May 31, 2013) Commercial & Industrial Prescriptive & Small Business Programs, Navigant, March 31, 2014. Values for Washington, D.C. and Delaware assume values from Maryland, Pepco and Maryland, DPL, respectively.
3. NEEP Mid-Atlantic TRM 2017, NEEP, Mid-Atlantic Technical Reference Manual, V7. May 2017
4. Massachusetts TRM, 2016-2018 Program Years, October 2015. Original source: DNV KEMA (2013). Impact Evaluation of 2010 Prescriptive Lighting Installations. Prepared for Massachusetts Energy Efficiency Program Administrators and Massachusetts Energy Efficiency Advisory Council

Refrigerated Case LED Lights

This measure includes the installation of LED lamps in commercial display refrigerators, coolers or freezers. The display lighting in a typical cooler or freezer add to the load on that unit by increasing power consumption of the unit when the lamp is on, and by adding heat to the inside of the unit that must be overcome through additional cooling.

Replacing fluorescent lamps with low heat generating LEDs reduces the energy consumption associated with the lighting components and reduces the amount of waste heat generated from the lamps that must be overcome by the unit's compressor cycles.

Formatted: Table Header

Formatted Table

Formatted: Font: Not Italic

Formatted: Table Cells

Formatted: Table Cells, Left, Right: 0", Don't keep with next

Formatted Table

Formatted: Table Cells

Formatted: Table Cells, Right: 0", Don't keep with next

Formatted: Table Cells, Right: 0", Don't keep with next

Formatted: Table Cells

Formatted: Table Cells, Right: 0"

Formatted: Table Cells, Right: 0"

Formatted: Table Cells

Formatted: Table Cells, Right: 0"

Formatted: Table Cells, Left, Right: 0"

Formatted: Table Cells

Formatted: Heading 4, Space After: 6 pt

Formatted: Right: 0"

Formatted: (none)

Algorithms

$$\text{Energy Savings } \left(\frac{\text{kWh}}{\text{yr}} \right) = \text{units} * (\text{Lighting kWh}_{\text{base}} - \text{lighting kWh}_{\text{ee}}) + \text{Refrig}_{\text{sav}}$$

$$\text{Peak Demand Savings (kW)} = \text{units} * (\text{kW}_{\text{base}} - \text{kW}_{\text{ee}}) * (1 + \text{Comp}_{\text{factor}}) * \text{CF}$$

$$\text{Refrig}_{\text{sav}} = \text{units} * (\text{lighting kWh}_{\text{base}} - \text{lighting kWh}_{\text{ee}}) * \text{Comp}_{\text{eff}}$$

Definition of Variables

Units = Number of LED linear lamps or fixtures installed

kW_b = Baseline fixture wattage

kW_q = Qualified LED fixture wattage

Lighting kWh_{base} = Total energy usage of lighting fixtures being replaced

Lighting kWh_{ee} = Total energy usage of new LED lighting fixtures are being installed

Comp_{factor} = Compressor factor for cooler or freezer, depending on location of install

Comp_{eff} = Compressor efficiency for cooler or freezer; the efficiency factors in portion of saved energy eliminated via the compressor

CF = Coincidence factor

Summary of Inputs

Refrigerated Case Assumptions

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Methodology</u>	<u>Source</u>
<u>Lighting kWh_{base}</u>	<u>Variable</u>	<u>Variable</u>	<u>Total lighting operating hours per year × wattage of baseline lighting; use 2 × LED watts as default</u>	<u>Application</u>
<u>Lighting kWh_{ee}</u>	<u>Variable</u>	<u>Variable</u>	<u>Total lighting operating hours per year × wattage of LED lighting.</u>	<u>Application</u>
<u>Hrs</u>	<u>Fixed</u>	<u>6,205</u>		<u>2</u>
<u>Comp_{eff} – cooler</u>	<u>Fixed</u>	<u>0.41</u>	<u>Value is calculated by multiplying 0.51 (compressor efficiency for cooler) by 0.80 (portion of saved energy eliminated via the compressor).</u>	<u>1, 3</u>
<u>Comp_{eff} – freezer</u>	<u>Fixed</u>	<u>0.52</u>	<u>Value is calculated by multiplying 0.65 (compressor efficiency for cooler) × 0.80 (portion of saved energy eliminated via the compressor).</u>	<u>1</u>

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Methodology</u>	<u>Source</u>
<u>Comp_{factor} = cooler</u>	<u>Fixed</u>	<u>0.40</u>	<u>Based on EER value of 1.8 kW/ton × 0.285 ton/kW × 0.8 (20% of case lighting load not converted into case cooling load) = 0.40</u>	<u>1</u>
<u>Comp_{factor} = freezer</u>	<u>Fixed</u>	<u>0.51</u>	<u>Based on EER value of 2.3 kW/ton × 0.285 ton/kW × 0.8 (20% of case lighting load not converted into case cooling load) = 0.51</u>	<u>1</u>
<u>CF</u>	<u>Fixed</u>	<u>0.92</u>		<u>2</u>

Sources

1. NY, Standard Approach for Estimating Energy Savings, V4, April 2016, pages 223-22
2. Pennsylvania PUC, Technical Reference Manual, June 2016, page 258. From PA TRM: “Methodology adapted from Kuiken et al, “State of Wisconsin Public Service Commission of Wisconsin Focus on Energy Evaluation Business Programs: Deemed Savings Parameter Development”, KEMA, November 13, 2009, assuming summer coincident peak period is defined as June through August on weekdays between 3:00 p.m. and 6:00 p.m., unless otherwise noted. https://focusonenergy.com/sites/default/files/bpdeemedavingsmanuav10_evaluationreport.pdf”
3. PA TRM, p.258. Values adopted from Hall, N. et al, New York Standard Approach for Estimating Energy Savings from Energy Efficiency Measures in Commercial and Industrial Programs, TecMarket Works, September 1, 2009. [http://www3.dps.ny.gov/W/PSCWeb.nsf/0/06f2fee55575bd8a852576e4006f9af7/\\$FILE/TechManualNYRevised10-15-10.pdf](http://www3.dps.ny.gov/W/PSCWeb.nsf/0/06f2fee55575bd8a852576e4006f9af7/$FILE/TechManualNYRevised10-15-10.pdf)

Specialty LED Fixtures

Some LED fixtures do not adhere to the Prescriptive Lighting algorithm due to unique form factors that do not lend to a fixture-to-fixture comparison, such as LED rope lights, cove lighting, and so on.

In these instances, a similar algorithm may be used, with a different metric other than fixture quantity entered. For example, a comparison of watts per linear foot between LED and incandescent technologies would result in accurate energy savings calculations.

Algorithms

Formatted: Font: Bold, Italic

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted

Formatted: Right: 0"

$$\Delta kW = (\text{linear feet of replaced cove lighting}) * (\text{baseline fixture wattage of cove lighting per foot}) - (\text{linear feet of installed LED cove lighting}) * (\text{wattage of new LED cove lighting per foot})$$

$$\text{Energy Savings } \left(\frac{\text{kWh}}{\text{yr}} \right) = (\Delta kW) * (1 + HVAC_e) * (Hrs)$$

$$\text{Peak Demand Savings (kW)} = (\Delta kW) * (CF) * (1 + HVAC_d)$$

$$\text{Fuel Savings } \left(\frac{\text{MMBtu}}{\text{yr}} \right) = (\Delta kW) * (Hrs) * (HVAC_g)$$

Definition of Variables

- ~~1. California Standard Performance Contracting Program~~
- ~~2. RLW Analytics, *Coincident Factor Study, Residential and Commercial & Industrial Lighting Measures*, 2007.~~
- ~~3. Quantum Consulting, Inc., for Pacific Gas & Electric Company, *Evaluation of Pacific Gas & Electric Company's 1997 Commercial Energy Efficiency Incentives Program: Lighting Technologies*, March 1, 1999~~
- ~~4. KEMA for NEEP. *C&I Lighting Load Shape Project*. July 19, 2011
http://www.neep.org/sites/default/files/products/NEEP_CI_Lighting_LS_FINAL_Report_ver_5_7-19-11.pdf~~
- ~~5. Select Energy Services, Inc. *Cooler Control Measure Impact Spreadsheet User's Manual*. 2004.~~

Formatted: English (U.S.)

Formatted: List Paragraph, Space Before: 6 pt, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0.25" + Indent at: 0.5"

The remaining variables are unchanged from those presented in the Prescriptive Lighting section:

Summary of Inputs

Specialty Lighting for Commercial Customers

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>ΔkW</u>	<u>Variable</u>	<u>See algorithm above</u>	<u>Application</u>
<u>CF</u>	<u>Fixed</u>	<u>See Lighting Table by Building in Performance Lighting Section Above</u>	<u>1</u>
<u>Hrs</u>	<u>Variable</u>	<u>See Lighting Table by Building Type in Performance Lighting Section Above</u>	<u>1</u>
<u>HVAC_d</u>	<u>Fixed</u>	<u>See Lighting Table by Building Type in Performance Lighting Section Above</u>	<u>2</u>
<u>HVAC_e</u>	<u>Fixed</u>	<u>See Lighting Table by Building</u>	<u>2</u>

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
		<u>Type in Performance Lighting Section Above</u>	
<u>HVAC_g</u>	<u>Fixed</u>	<u>See Lighting Table by Building Type in Prescriptive Lighting Section Above</u>	<u>3</u>

6. Sources For induction Lighting, used the lowest PSMH that would produce a 30% reduction in wattage to the induction fixture, which is the minimum requirement for incentives replacing HID with induction lighting. Assume 5% increase for input wattage vs nominal wattage.

7. Based on assuming LED is 62% more efficient than replacement as per RPI study: <http://www.lrc.rpi.edu/programs/solidstate/pdf/SPIE4776-13-Raghavan.pdf>

1. NEEP, *Mid-Atlantic Technical Reference Manual*, V7. May 2017.

2. Average HVAC interactive effects by building type derived from the NEEP Mid-Atlantic TRM 2017, NEEP, *Mid-Atlantic Technical Reference Manual*, V7. May 2017, pp. 464-465. From NEEP TRM: “EmPOWER Maryland DRAFT Final Impact Evaluation Report Evaluation Year 4 (June 1, 2012 – May 31, 2013) Commercial & Industrial Prescriptive & Small Business Programs, Navigant, March 31, 2014. Values for Washington, D.C. and Delaware assume values from Maryland, Pepco and Maryland, DPL, respectively.

3. Massachusetts TRM, 2016-2018 Program Years, October 2015. Original source: DNV KEMA (2013). *Impact Evaluation of 2010 Prescriptive Lighting Installations*. Prepared for Massachusetts Energy Efficiency Program Administrators and Massachusetts Energy Efficiency Advisory Council

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Lighting Controls

Lighting controls include occupancy sensors, daylight dimmer systems, and occupancy controlled hi-low controls for fluorescent, LED and HID fixtures. -The measurement of energy savings is based on algorithms with key variables (i.e., coincidence factor, equivalent full load hours) provided through existing end-use metering of a sample of facilities or from other utility programs with experience with these measures (i.e., % of annual lighting energy saved by lighting control). -For lighting controls, the baseline is a manual switch, based on the findings of the New Jersey Commercial Energy Efficient Construction Baseline Study.

Algorithms

$$\text{Energy Savings } \left(\frac{\text{kWh}}{\text{yr}}\right) = kW_c * SVG * \text{Hrs} * (1 + HVAC_e)$$

$$\text{Peak Demand Savings (kW)} = kW_c * SVG * CF * (1 + HVAC_d)$$

$$\text{Fuel Savings } \left(\frac{\text{MMBtu}}{\text{yr}}\right) = kW_c * SVG * (\text{Hrs}) * (HVAC_g)$$

Definition of Variables

$$\text{Demand Savings} = kW_e * SVG * CF * (1 + IF)$$

$$\text{Energy Savings} = kW_e * SVG * EFLH * (1 + IF)$$

Definition of Variables

SVG = % of annual lighting energy saved by lighting control; refer to table by control type

kW_c = kW lighting load connected to control

~~IF~~ $HVAC_d$ = Interactive Factor – This applies to C&I interior lighting only. -This represents the secondary demand and in reduced HVAC consumption resulting from decreased indoor lighting wattage.

~~$HVAC_e$~~ = Interactive Factor – This applies to C&I interior lighting only. This represents the secondary energy savings in reduced HVAC consumption resulting from decreased indoor lighting wattage. -This value will be fixed at 5%.

~~CF~~ = Coincidence ~~$HVAC_g$~~ = Interactive Factor – This value applies to C&I interior lighting only. This represents the percentage of the total load which is on during electric system's peak window. secondary energy savings in

Formatted: Page break before

Formatted: Space Before: 6 pt

Formatted: Right: 0"

Formatted: Underline

Formatted: Normal

Formatted: Indent: Left: 0.25", Hanging: 0.75", Space Before: 3 pt, After: 3 pt, Tab stops: 0", Left

Formatted: Subscript

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Indent: Left: 0.25", Hanging: 0.75", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

Formatted: Indent: Left: 0.25", Hanging: 0.75", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left

reduced HVAC consumption resulting from decreased indoor lighting wattage.

EFLH = Equivalent full load hours.

CF = Coincidence factor

Hrs = Annual hours of operation prior to installation of controls

Summary of Inputs

Lighting Controls

Component	Type	Value	Source
kW _c	Variable	Load connected to control	Application
<u>SVG</u>	<u>Fixed</u>	<u>Occupancy Sensor, Controlled Hi-Low Fluorescent Control, LED and controlled HID = 30% Daylight Dimmer System=50%</u>	<u>See sources below</u>
<u>CF</u>	<u>Fixed</u>	<u>See Lighting Table by Building in Performance Lighting Section Above</u>	<u>1</u>
<u>EFLH</u>	<u>Fixed</u>	<u>See Lighting Table by Building in Performance Lighting Section Above</u>	<u>2, 3</u>
<u>IF</u>	<u>Fixed</u>	<u>See Lighting Table by Building in Performance Lighting Section Above</u>	<u>2</u>

Formatted: Keep with next, Tab stops: 1", Left

Formatted: Table Caption

Formatted: Table Header, Keep with next

Formatted: Table Cells, Keep with next

Formatted: Table Cells, Right: 0", Keep with next

<u>SVG</u>	<u>Fixed</u>	<u>Occupancy Sensor, Controlled Hi-Low Fluorescent Control, LED and controlled HID = 31% Daylight Dimmer System= 40%</u>	<u>4, 5, 6</u>
<u>CF</u>	<u>Fixed</u>	<u>See Table by Building in Performance Lighting Section Above</u>	<u>1</u>
<u>Hrs</u>	<u>Fixed</u>	<u>See Table by Building in Performance Lighting Section Above</u>	<u>1</u>
<u>HVAC_d</u>	<u>Fixed</u>	<u>See Table by Building Type in Performance Lighting Section Above</u>	<u>2</u>
<u>HVAC_e</u>	<u>Fixed</u>	<u>See Table by Building Type in Performance Lighting Table Above</u>	<u>2</u>

<u>HVAC_g</u>	<u>Fixed</u>	<u>See Table by Building Type in Performance Lighting Table Above</u>	<u>3</u>
-------------------------	--------------	---	----------

Sources:

- ~~1. RLW Analytics, *Coincident Factor Study, Residential and Commercial & Industrial Lighting Measures*, 2007.~~
- ~~1. Quantum Consulting, Inc., for Pacific Gas & Electric Company, *NEEP, Mid-Atlantic Technical Reference Manual*, V7. May 2017.~~
- ~~2. Average HVAC interactive effects by building type derived from the NEEP Mid-Atlantic TRM 2017. NEEP, *Mid-Atlantic Technical Reference Manual*, V7. May 2017, pp. 464-465. From NEEP TRM: “EmPOWER Maryland DRAFT Final Impact Evaluation Report Evaluation Year 4 (June 1, 2012 – May 31, 2013) Commercial & Industrial Prescriptive & Small Business Programs, Navigant, March 31, 2014. Values for Washington, D.C. and Delaware assume values from Maryland, Pepco and Maryland, DPL, respectively.~~
- ~~3. Massachusetts TRM, 2016-2018 Program Years, October 2015. Original source: DNV KEMA (2013). *Impact Evaluation of Pacific Gas & Electric Company’s 1997 Commercial-2010 Prescriptive Lighting Installations*. Prepared for Massachusetts Energy Efficiency *Incentives Program*: Program Administrators and Massachusetts Energy Efficiency Advisory Council~~
- ~~2.4. A Meta-Analysis of Energy Savings from *Lighting Technologies*”, March 1, 1999 *Controls in Commercial Buildings*, Lawrence Berkeley National Laboratory, September 2011.~~
- ~~3. KEMA for NEEP. *C&I Lighting Load Shape Project*. July 19, 2011 http://www.neep.org/sites/default/files/products/NEEP_CI_Lighting_LS_FINAL_Report_ver_5_7_19_11.pdf~~
- ~~5. LBNL, *Quantifying National Energy Savings Potential of Lighting Controls in Commercial Buildings*, May 2012.~~
- ~~6. Unified Facilities Criteria (UFC), *Design: Interior, Exterior, Lighting and Controls*, UFC 3-530-01. September 2012.~~

Motors [Inactive 2017, Not Reviewed]

For premium efficiency motors 1-200 HP.

Algorithms

From application form calculate ΔkW where:

$$\Delta kW = 0.746 * HP * IF_{VFD} * (1/\eta_{base} - 1/\eta_{prem})$$

Demand Savings = (ΔkW) ~~X~~* CF

Formatted: Heading 4, Space After: 6 pt

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Don't add space between paragraphs of the same style, Line spacing: Multiple 1.08 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Font: Not Italic

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Normal

Formatted: English (U.S.)

Formatted: Keep with next

$$\text{Energy Savings} = (\Delta kW) * \text{HRS} * \text{LF}$$

Definition of Variables

ΔkW = kW Savings at full load

HP = Rated horsepower of qualifying motor, from nameplate/manufacturer specs.

LF = Load Factor, percent of full load at typical operating condition

IF_{VFD} = VFD Interaction Factor, 1.0 without VFD, 0.9 with VFD

η_{base} = Efficiency of the baseline motor

η_{prem} = Efficiency of the energy-efficient motor

HRS = Annual operating hours

CF = Coincidence Factor

Motors

Component	Type	Value	Source
HP	Variable	Nameplate/Manufacturer Spec. Sheet	Application
LF	Fixed	0.75	1
hp_{base}	Fixed	ASHRAE 90.1-2013 Baseline Efficiency Table	ASHRAE
hp_{prem}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
IF_{VFD}	Fixed	1.0 or 0.9	3
Efficiency - η_{ec}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
CF	Fixed	0.74	1
HRS	Fixed	Annual Operating Hours Table	1

Formatted: Indent: Left: 0", First line: 0"

Formatted: Normal, Indent: Left: 0", Hanging: 1"

Formatted Table

Baseline Motor Efficiency Table

Formatted: Keep with next

Motor Horsepower	1200 RPM (6 pole)		1800 RPM (4 pole)		3600 RPM (2 pole)	
	ODP	TEFC	ODP	TEFC	ODP	TEFC
1	0.8	0.8	0.825	0.825	na	0.755
1.5	0.84	0.855	0.84	0.84	0.825	0.825
2	0.855	0.865	0.84	0.84	0.84	0.84
3	0.865	0.875	0.865	0.875	0.84	0.855
5	0.875	0.875	0.875	0.875	0.855	0.875
7.5	0.885	0.895	0.885	0.895	0.875	0.885
10	0.9002	0.895	0.895	0.895	0.885	0.895
15	0.902	0.902	0.91	0.91	0.895	0.902
20	0.91	0.902	0.91	0.91	0.902	0.902
25	0.917	0.917	0.917	0.924	0.91	0.91
30	0.924	0.917	0.924	0.924	0.91	0.91
40	0.93	0.93	0.93	0.93	0.917	0.917
50	0.93	0.93	0.93	0.93	0.924	0.924
60	0.936	0.936	0.936	0.936	0.93	0.93
75	0.936	0.936	0.941	0.941	0.93	0.93
100	0.941	0.941	0.941	0.945	0.93	0.936
125	0.941	0.941	0.945	0.945	0.936	0.945
150	0.945	0.95	0.95	0.95	0.936	0.945
200	0.945	0.95	0.95	0.95	0.945	0.95

*Note: For the Direct Install Program, different baseline efficiency values are used.

NEMA ASHRAE 90.1-2013 Motor Efficiency Table – General Purpose Subtype I

Motor Horsepower	1200 RPM (6 pole)		1800 RPM (4 pole)		3600 RPM (2 pole)	
	ODP	TEFC	ODP	TEFC	ODP	TEFC
1	0.825	0.825	0.855	0.855	0.77	0.77
1.5	0.865	0.875	0.865	0.865	0.84	0.84
2	0.875	0.885	0.865	0.865	0.855	0.855
3	0.885	0.895	0.895	0.895	0.855	0.865
5	0.895	0.895	0.895	0.895	0.865	0.885
7.5	0.902	0.91	0.91	0.917	0.885	0.895
10	0.917	0.91	0.917	0.917	0.895	0.902
15	0.917	0.917	0.93	0.924	0.902	0.91
20	0.924	0.917	0.93	0.93	0.91	0.91
25	0.93	0.93	0.936	0.936	0.917	0.917
30	0.936	0.93	0.941	0.936	0.917	0.917
40	0.941	0.941	0.941	0.941	0.924	0.924
50	0.941	0.941	0.945	0.945	0.93	0.93
60	0.945	0.945	0.95	0.95	0.936	0.936
75	0.945	0.945	0.95	0.954	0.936	0.936
100	0.95	0.95	0.954	0.954	0.936	0.941
100	0.95	0.95	0.954	0.954	0.941	0.95
150	0.954	0.958	0.958	0.958	0.941	0.95
200	0.954	0.958	0.958	0.962	0.95	0.954

Annual Operating Hours Table

Motor Horsepower	Operating Hours, HRS
1 to 5 HP	2,745
6 to 20 HP	3,391
21 to 50 HP	4,067
51 to 100 HP	5,329
101 to 200 HP	5,200

Formatted: Keep with next

Electronically Commutated Motors for Refrigeration

This measure is applicable to existing walk-in, multi-deck and free standing coolers and freezers with shaded pole or permanent split capacitor (PSC) motors. -These fractional horsepower motors are significantly more efficient than mechanically commutated, brushed motors, particularly at low speeds or partial load. -By employing variable-speed technology, EC motors are able to optimize fan speeds for changing load requirements. Because these motors are brushless and utilize DC power, losses due to friction and phase shifting are eliminated. -Calculations of savings for this measure take into account both the increased efficiency of the motor as well as the reduction in refrigeration load due to motor heat loss.

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Page break before, Don't keep with next

EC Motor retrofits in Walk-in Coolers and Freezers

Formatted: Font: Not Bold, Italic, No

Algorithms

Formatted: Font: Not Bold, Italic, No

Formatted: Heading 4

$$\Delta kW = ((Amps_{EF} * Volts_{EF} * (Phase_{EF})^{1/2})/1000) * PF_{EF} * LR65\%$$

Formatted: Indent: First line: 0.25"

$$\text{Gross kWh Energy Savings (kWh/yr)} = kWh Savings_{EF} + kWh Savings_{RH}$$

Formatted: Indent: First line: 0.25"

$$kWh Savings_{EF} = ((Amps_{EF} * Volts_{EF} * (Phase_{EF})^{1/2})/1000) * PF_{EF} * \text{Operating Hours} * LR65\%$$

Formatted: Indent: Left: 0.25"

$$kWh Savings_{RH} = kWh Savings_{EF} * 0.28 * 1.6$$

Formatted: Indent: First line: 0.25"

PLEASE NOTE:

"((Amps_{EF} * Volts_{EF} * (Phase_{EF})^{1/2})/1000) * PF_{EF}" is equivalent to "HP * 0.746"

Definition of Variables

Formatted: Heading 4

ΔkW - _____ = Demand Savings due to EC Motor Retrofit

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

$kWh Savings_{EF}$ = Savings due to Evaporator Fan Motors being replaced

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

$kWh Savings_{RH}$ = Savings due to reduced heat from Evaporator Fans

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Amps_{EF} _____ = Nameplate Amps of Evaporator Fan

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Volts_{EF} _____ = Nameplate Volts of Evaporator Fan

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Phase_{EF} _____ = Phase of Evaporator Fan

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

PF_{EF} _____ = Evaporator Fan Power Factor

Formatted: Indent: Left: 0", First line: 0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 0.25", Left

Operating Hours _____ = Annual operating hours if Evaporator Fan Control

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

LR _____ = Percent reduction of load by replacing motors

Formatted: Indent: Left: 0", First line: 0.25", Space Before: 3 pt, After: 3 pt, Tab stops: 1", Left + 1.94", Left + Not at 1.25"

0.28 _____ = Conversion from kW to tons (Refrigeration)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

1.6 _____ = Efficiency of typical refrigeration system in kW/ton

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Case Motor Replacement

Algorithms

Gross kWh Energy Savings (kWh/yr) = kWh Savings_{CM} + kWh Savings_{RH}

kWh Savings_{CM} = kW * ER * RT8, 500

kWh Savings_{RH} = kWh Savings_{EF} * 0.28 * Eff

Definition of Variables

kWh Savings_{CM} = Savings due to Case Motors being replaced

kWh Savings_{RH} = Savings due to reduced heat from Case Motors

kW = Metered load of Case Motors

ER = Energy reduction if a motor is being replaced

RT = Average runtime of Case Motors

0.28 = Conversion from kW to tons (Refrigeration)

Eff = Efficiency of typical refrigeration system in kW/ton

Summary of Inputs

ECM Fraction HP Motors

Component	Type	Value	Source
Amps _{EF}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
Volts _{EF}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
Phase _{EF}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
PF _{EF}	Fixed	0.55	1
Operating Hours	Fixed	Not Installed = 8,760 Installed = 5,600	

Formatted: Font: Italic, No underline

Formatted: Page break before, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Keep with next

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Table Caption

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Component	Type	Value	Source
LR	Fixed	65%	2
ER	Fixed	Shaded Pole Motor Replaced = 53% PSC Motor Replaced = 29%	3
RT	Fixed	8500	
Eff	Fixed	1.6	

- Formatted: Table Header
- Formatted Table
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells

Sources:

1. Select Energy Services, Inc. *Cooler Control Measure Impact Spreadsheet User's Manual*, 2004.
2. This value is an estimate by NRM based on several pre- and post- meter readings of installations. - This is supported by RLW report for National Grid, "Small Business Services, Custom Measure Impact Evaluation", March 23, 2007.
3. Based on numerous pre- and post- meterings conducted by NRM.

- Formatted: English (U.S.)
- Formatted: Heading 4, Don't keep with next
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt, Keep with next
- Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Electric HVAC Systems

~~The measurement of This measure provides energy and demand savings for C/I Efficient HVAC program for Room AC, Central AC, and air cooled DX is based on algorithms. (Includes for C&I Electric HVAC systems. The type of systems included in this measure are: split systems, single package systems, air to air cooled heat pumps, packaged terminal systems, (PTAC and PTHP), single package vertical systems, (SPVAC and SPVHP), central DX AC systems, water source heat pumps, ground water source heat pumps, and/or ground source heat pumps).~~

Formatted: Space Before: 6 pt, After: 6 pt

~~This measure applies to new construction, replacement of failed equipment, or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by ASHRAE Std. 90.1 – 2013, which is the current code adopted by the state of New Jersey.~~

Algorithms

Air Conditioning Algorithms:

Formatted: Font: Italic

~~Demand Energy Savings = (BtuH/1000) X (kWh/yr) = N * Tons * 12 kBtuh/Ton * (1/EER_b-1/EER_q) X CF * EFLH_c~~

Formatted: Indent: First line: 0.25"

Formatted: Subscript

~~Energy Peak Demand Savings = (BtuH/1000) X (kW) = N * Tons * 12 kBtuh/Ton * (1/EER_b-1/EER_q) X EFLH * CF~~

Formatted: Indent: Left: 0", First line: 0.25"

Heat Pump Algorithms:

Formatted: Font: Italic

~~Cooling Energy Savings - Cooling = (BtuH_c/1000) X (kWh/yr) = N * Tons * 12 kBtuh/Ton * (1/EER_b-1/EER_q) X EFLH_c~~

Formatted: Font: Italic

Formatted: Indent: First line: 0.25"

~~Heating Energy Savings - Heating = BtuH_h/1000 X (Btu/yr) = N * Tons * 12 kBtuh/Ton * ((1/ (COP_b X 3.412)) - (1/ (COP_q X 3.412))) X EFLH_h~~

Formatted: Indent: Left: 0.25"

Where *c* is for cooling and *h* is for heating.

Formatted: Indent: Hanging: 0.75"

Definition of Variables

~~BtuH = Cooling N = Number of units~~

~~Tons = Rated cooling capacity in Btu/Hour of unit. This value comes from ARI/AHRI or AHAM rating or manufacturer data.~~

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

~~EER_b = Energy Efficiency Ratio of the baseline unit. This data is found in the HVAC and Heat Pumps table below. For units < 65,000 BtuH, (5.4 tons), SEER should be used in place of EER.~~

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

COP_b = Coefficient of Performance of the baseline unit. -This data is found in the HVAC and Heat Pumps table below. -For units < 65,000 BtuH₇ (5.4 tons), SEER and HSPF/3.412 should be used in place of COP ~~X~~* 3.412 for cooling and heating savings, respectively.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

EER_q = Energy Efficiency Ratio of the high efficiency unit. This value comes from the ARI/AHRI or AHAM directories or manufacturer data. For units < 65,000 (5.4 tons) BtuH, SEER should be used in place of EER.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

COP_q = Coefficient of Performance of the high efficiency unit. This value comes from the ARI/AHRI or AHAM directories or manufacturer data. -For units < 65,000 BtuH₇ (5.4 tons), SEER and HSPF/3.412 should be used in place of COP ~~X~~* 3.412 -for cooling and heating savings, respectively.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

CF = Coincidence Factor – This value represents the percentage of the total load which is on during electric system’s Peak Window. -This value will be based on existing measured usage and determined as the average number of operating hours during the peak window period.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

~~$EFLH$ $EFLH_{c \text{ or } h}$ = Equivalent Full Load Hours – This represents a measure of energy use by season during the on-peak and off-peak periods. This value will be determined by existing measured data of kWh during the period divided by kW at design conditions-peak periods.~~

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Summary of Inputs

HVAC and Heat Pumps

Formatted: Table Caption

Component	Type	Value	Source
BtuHTons	Variable	ARI/AHRI or AHAM or Manufacturer Data Rated Capacity, Tons	Application
EER _b	Variable	See Table below	Collaborative agreement and C/I baseline study₁
EER _q	Variable	ARI/AHRI or AHAM Values	Application
CF	Fixed	67.50%	Engineering estimate₂
EFLH_(c or h)	Fixed Variable	HVAC 1,495 HP cooling 384	1, JCP&L metered data^{42,3}

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Subscript

⁴² ~~Results reflect metered use from 1995–1999.~~

Component	Type	Value	Source
		HP heating - 800 See Tables below	

Formatted: Table Header

Formatted Table

Formatted: Table Cells

Formatted: Normal

HVAC Baseline Table—New Construction

Equipment Type	Baseline = ASHRAE Std. 90.1 – 2013
<u>Unitary HVAC/Split Systems and Single Package, Air Cooled</u> ≤5.4 tons, split ≤5.4 tons, single >5.4 to 11.25 tons >11.25 to 20 tons >21 to 63 tons >63 Tons	13 SEER 14 SEER 11.0 EER, 12.7 IEER 10.8 EER, 12.2 IEER 9.8 EER, 11.4 IEER 9.5 EER, 11.0 IEER
<u>Air Cooled Heat Pump Systems, Split System and Single Package</u> ≤5.4 tons, split ≤5.4 tons, single >5.4 to 11.25 tons >11.25 to 20 tons >= 21	14 SEER, 8.2 HSPF 14 SEER, 8.0 HSPF 10.8 EER, 11.0 IEER, 3.3 heating COP 10.4 EER, 11.4 IEER, 3.2 heating COP 9.3 EER, 10.4 IEER, 3.2 heating COP
▲ Water Source Heat Pumps (water to air, water loop) ▲ ≤1.4 tons ▲ >1.4 to 5.4 tons ▲ >5.4 to 11.25 tons	12.2 EER, 4.3 heating COP 13.0 EER, 4.3 heating COP 13.0 EER, 4.3 heating COP
▲ Ground Water Source Heat Pumps ▲ ≤11.25 tons	▲ 18.0 EER, 3.7 heating COP
▲ Ground Source Heat Pumps (brine to air, ground loop) ▲ ≤11.25 tons	▲ 14.1 EER, 3.2 heating COP
▲ Package Terminal Air Conditioners ^{#43}	▲ 14.0 – (0.300 * Cap/1,000), EER
▲ Package Terminal Heat Pumps [#]	▲ 14.0 – (0.300 * Cap/1,000), EER ▲ 3.7 – (0.052 * Cap/1,000), heating COP
▲ Single Package Vertical Air Conditioners ▲ ≤5.4 tons ▲ >5.4 to 11.25 tons ▲ >11.25 to 20 tons	10.0 EER 10.0 EER 10.0 EER

- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Font: 12 pt
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Font: 12 pt
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Font: 12 pt, No underline
- Formatted: Font: 12 pt
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt, No underline
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Font: 12 pt
- Formatted: Font: 12 pt

⁴³ Cap means the rated cooling capacity of the product in Btu/h.

Equipment Type	Baseline = ASHRAE Std. 90.1 – 2013
Single Package Vertical Heat Pumps	
-<=5.4 tons	10.0 EER, 3.0 heating COP
->5.4 to 11.25 tons	10.0 EER, 3.0 heating COP
->11.25 to 20 tons	10.0 EER, 3.0 heating COP

Formatted: Font: 12 pt, No underline

Formatted: Table Cells

Formatted: Font: 12 pt

Formatted: Table Cells, Left

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Font: 12 pt

Formatted: Table Cells, Left, Space After: 3 pt

a—Cap means the rated cooling capacity of the product in BtuH. If the unit's capacity is less than 7,000 BtuH, use 7,000 BtuH in the calculation. If the unit's capacity is greater than 15,000 BtuH, use 15,000 BtuH in the calculation

EFLH Table

Facility Type	Heating EFLH_h	Cooling EFLH_c
<u>Assembly</u>	<u>603</u>	<u>669</u>
<u>Auto repair</u>	<u>1910</u>	<u>426</u>
<u>Dormitory</u>	<u>465</u>	<u>800</u>
<u>Hospital</u>	<u>3366</u>	<u>1424</u>
<u>Light industrial</u>	<u>714</u>	<u>549</u>
<u>Lodging – Hotel</u>	<u>1077</u>	<u>2918</u>
<u>Lodging – Motel</u>	<u>619</u>	<u>1233</u>
<u>Office – large</u>	<u>2034</u>	<u>720</u>
<u>Office – small</u>	<u>431</u>	<u>955</u>
<u>Other</u>	<u>681</u>	<u>736</u>
<u>Religious worship</u>	<u>722</u>	<u>279</u>
<u>Restaurant – fast food</u>	<u>813</u>	<u>645</u>
<u>Restaurant – full service</u>	<u>821</u>	<u>574</u>
<u>Retail – big box</u>	<u>191</u>	<u>1279</u>
<u>Retail – Grocery</u>	<u>191</u>	<u>1279</u>
<u>Retail – large</u>	<u>545</u>	<u>882</u>
<u>Retail – large</u>	<u>2101</u>	<u>1068</u>
<u>School – Community college</u>	<u>1431</u>	<u>846</u>
<u>School – postsecondary</u>	<u>1191</u>	<u>1208</u>
<u>School – primary</u>	<u>840</u>	<u>394</u>
<u>School – secondary</u>	<u>901</u>	<u>466</u>

<u>Facility Type</u>	<u>Heating EFLH_h</u>	<u>Cooling EFLH_c</u>
<u>Warehouse</u>	<u>452</u>	<u>400</u>

Multi-family EFLH by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Cooling</u>	<u>507</u>	<u>550</u>	<u>562</u>
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Cooling</u>	<u>793</u>	<u>843</u>	<u>954</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Sources:

1. EFLH of ASHRAE Standards 90.1, 495 hours-2013, Energy Standard for Unitary HVAC is represented in the “Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
2. C&I Unitary HVAC Load Shape Project Report”, Table O-2, Final Report. August 2011, v.1.1, p. 12, Table O-5. The CF reported here is a center point for NJ chosen between the CF for urban NY and for the Mid-Atlantic region. This report was published August 2, 2011 and was performed by KEMA for NEEP. in the PJM peak periods. Available at: http://www.neep.org/sites/default/files/resources/NEEP_HVAC_Load_Shape_Report_Final_August2_0.pdf
3. New York State Joint Utilities, New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.

Formatted: English (U.S.)

Formatted: Heading 4, Space After: 6 pt, Don't keep with next

Formatted: Font: Not Bold, Not Italic

Formatted: Font: Italic

Formatted: Indent: Left: 0", Space Before: 3 pt, After: 3 pt

Fuel Use Economizers

Algorithms

Electric Algorithms

$$\text{Energy Savings (kWh/yr)} = (\text{AEU} * 0.13)$$

Definition of Variables

Definition of Variables

AEU = Annual Electric Usage for an uncontrolled AC or refrigeration unit (kWh) = (Input power in kW) * (annual run time)

0.13 = Approximate energy savings factor related to installation of fuel use economizers

Sources:

1. Approximate energy savings factor of 0.13 based on average % savings for test sites represented in Table 2 (page 3) of NYSERDA Study: A Technology Demonstration and Validation Project for Intellidyne Energy Saving Controls; Intellidyne LLC & Brookhaven National Laboratories; 2006
(http://www.cleargreenpartners.com/attachments/File/NYSERDA_Report.pdf); available at:
http://www.cleargreenpartners.com/attachments/File/NYSERDA_Report.pdf.

Dual Enthalpy Economizers

Algorithms

$$\text{Energy Savings (kWh)} = \text{OTF} * \text{SF} * \text{Cap/Eff}$$

$$\text{Demand Savings (kW)} = \text{Savings/Operating Hours}$$

Definition of Variables

OTF = Operational Testing Factor

SF = Approximate savings factor based on regional temperature bin data (assume 4576 for equipment under 5.4 tons where a fixed damper is assumed for the baseline and 3318 for larger equipment where a dry bulb economizer is assumed for the baseline). (Units for savings factor are in kWh x rated EER per ton of cooling or kWh*EER/Ton)

Cap = Capacity of connected cooling load (tons)

Formatted: Page break before

Formatted: Normal

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.5"

Formatted: Indent: First line: 0"

Formatted: Normal, Level 4, Keep with next

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Heading 4, Space Before: 12 pt, After: 6 pt

Formatted: Indent: Left: 0"

Formatted: Font: Bold, Font color: Black

Eff = Cooling equipment energy efficiency ratio (EER)

Operating Hours = 4,438 = Approximate number of economizer operating hours

Dual Enthalpy Economizers

The following algorithm details savings for dual enthalpy economizers. They are to be used to determine electric energy savings between baseline standard units and the high efficiency units promoted in the program. The baseline condition is assumed to be a rooftop unit with fixed outside air (no economizer). The high efficiency units are equipped with sensors that monitor the enthalpy of outside air and return air and modulate the outside air damper to optimize energy performance.

Algorithms

Electric energy savings (kWh/yr) = N * Tons * (ΔkWh/ton)

Peak Demand Savings (kW) = 0⁴⁴ kW

Definition of Variables

N = Number of units

Tons = Rated capacity of the cooling system retrofitted with an economizer

ΔkWh/ton = Stipulated per building type electricity energy savings per ton of cooling system retrofitted with an economizer

Summary of Inputs

Dual Enthalpy Economizers

Component	Type	Value	Source
<u>N</u>	<u>Variable</u>		<u>Application</u>
<u>Tons</u>	<u>Variable</u>	<u>Rated Capacity, Tons</u>	<u>Application</u>
<u>ΔkWh/ton</u>	<u>Fixed</u>	<u>See Table Below</u>	<u>1</u>

Savings per Ton of Cooling System

Building Type	Savings (ΔkWh/ton)
<u>Assembly</u>	<u>27</u>

⁴⁴ Economizer savings occur when outdoor air enthalpy is relatively low, and these conditions mostly exist outside of defined system peak demand periods, therefore, the seasonal peak demand savings for this measure are assumed to be negligible.

Formatted: Font: Italic
Formatted: Left, Don't keep with next, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto
Formatted: Heading 3, Left, Don't keep with next

Formatted: Normal
Formatted: English (U.S.)
Formatted: Font: Not Bold
Formatted: Normal

Formatted: Underline, (none)
Formatted: Normal, Level 4, Keep with next

Formatted: Table Caption

Formatted: Table Header, Left, Don't keep with next
Formatted Table
Formatted: Table Header, Left

<u>Building Type</u>	<u>Savings (ΔkWh/ton)</u>
<u>Big Box Retail</u>	<u>152</u>
<u>Fast Food Restaurant</u>	<u>39</u>
<u>Full Service Restaurant</u>	<u>31</u>
<u>Light Industrial</u>	<u>25</u>
<u>Primary School</u>	<u>42</u>
<u>Small Office</u>	<u>186</u>
<u>Small Retail</u>	<u>95</u>
<u>Religious</u>	<u>6</u>
<u>Warehouse</u>	<u>2</u>
<u>Other</u>	<u>61</u>

1. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix J – Commercial HVAC Unit Savings. P.565. Values for NYC due to proximity to NJ, the input values are based on data provided on the application form and stipulated savings values derived from DOE 2.2 simulations of a series of prototypical small commercial buildings.

Occupancy Controlled Thermostats

The program has received a large amount of custom electric applications for the installation of Occupancy Controlled Thermostats in hotels, motels, and, most recently, university dormitories.

Standard practice today is thermostats which are manually controlled by occupants to regulate temperature within a facility. An occupancy controlled thermostat is a thermostat paired with a sensor and/or door detector to identify movement and determine if a room is occupied or unoccupied. If occupancy is sensed by the sensor, the thermostat goes into an occupied mode (i.e., programmed setpoint). If a pre-programmed time frame elapses (i.e., 30 minutes) and no occupancy is sensed during that time, the thermostat goes into an unoccupied mode (e.g., setback setpoint or off) until occupancy is sensed again. This type of thermostat is often used in hotels to conserve energy.

The occupancy controlled thermostat reduces the consumption of electricity and/or gas by requiring less heating and/or cooling when a room or a facility is vacant or unoccupied.

Algorithms

$$\text{Cooling Energy Savings (kWh/yr)} = (((T_c * (H+5) + S_c * (168 - (H+5)))/168 - T_c) * (P_c * \text{Cap}_{hp} * 12 * \text{EFLH}_c / \text{EER}_{hp})$$

$$\text{Heating Energy Savings (kWh/yr)} = (T_h - ((T_h * (H+5) + S_h * (168 - (H+5)))/168)) * (P_h * \text{Cap}_{hp} * 12 * \text{EFLH}_h / \text{EER}_{hp})$$

$$\text{Heating Energy Savings (Therms/yr)} = (T_h - ((T_h * (H+5) + S_h * (168 - (H+5)))/168)) * (P_h * \text{Cap}_h * \text{EFLH}_h / \text{AFUE}_h / 100,000)$$

Definition of Variables

T_h = Heating Season Facility Temp. (°F)

T_c = Cooling Season Facility Temp. (°F)

S_h = Heating Season Setback Temp. (°F)

S_c = Cooling Season Setup Temp. (°F)

H = Weekly Occupied Hours

Cap_{hp} = Connected load capacity of heat pump/AC (Tons) – Provided on Application.

Cap_h = Connected heating load capacity (Btu/hr) – Provided on Application.

EFLH_c = Equivalent full load cooling hours

EFLH_h = Equivalent full load heating hours

P_h = Heating season percent savings per degree setback

P_c = Cooling season percent savings per degree setup

AFUE_h = Heating equipment efficiency – Provided on Application.

EER_{hp} = Heat pump/AC equipment efficiency – Provided on Application

Formatted: Heading 3, Left, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Don't keep with next

Formatted: Indent: Left: 0.25"

Formatted: Font: Not Bold

<u>Facility Type</u>	<u>Heating EFLH_h</u>	<u>Cooling EFLH_c</u>
<u>Office – small</u>	<u>431</u>	<u>955</u>
<u>Other</u>	<u>681</u>	<u>736</u>
<u>Religious worship</u>	<u>722</u>	<u>279</u>
<u>Restaurant – fast food</u>	<u>813</u>	<u>645</u>
<u>Restaurant – full service</u>	<u>821</u>	<u>574</u>
<u>Retail – big box</u>	<u>191</u>	<u>1279</u>
<u>Retail – Grocery</u>	<u>191</u>	<u>1279</u>
<u>Retail – large</u>	<u>545</u>	<u>882</u>
<u>Retail – large</u>	<u>2101</u>	<u>1068</u>
<u>School – Community college</u>	<u>1431</u>	<u>846</u>
<u>School – postsecondary</u>	<u>1191</u>	<u>1208</u>
<u>School – primary</u>	<u>840</u>	<u>394</u>
<u>School – secondary</u>	<u>901</u>	<u>466</u>
<u>Warehouse</u>	<u>452</u>	<u>400</u>

Multi-family EFLH by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Cooling</u>	<u>507</u>	<u>550</u>	<u>562</u>
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Cooling</u>	<u>793</u>	<u>843</u>	<u>954</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Sources:

1. DOE-2 Simulation Modeling
2. ClimateQuest Economizer Savings Calculator

1. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.
2. ENERGY STAR Products website.

Formatted: Heading 4, Space Before: 9 pt, After: 6 pt

|

Electric Chillers

The measurement of energy and demand savings for C&I chillers is based on algorithms with key variables (i.e., kW/ton, Coincidence Factor, Equivalent Full Load Hours) measured through existing end-use metering of a sample of facilities.

Formatted: Right: -0.13", Space Before: 6 pt, After: 6 pt

This measure applies to new construction, replacement of failed equipment, or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by ASHRAE Std. 90.1 – 2013, which is the current code adopted by the state of New Jersey.

Formatted: Right: -0.13"

Algorithms

Formatted: Font: Not Bold

Algorithms

Formatted: Right: 0"

For IPLV:

Formatted: (none)

Formatted: Font: Italic

~~Demand~~Energy Savings $= (\text{kWh/yr}) = N * \text{Tons} * \text{PDC} * \text{EFLH} * (\text{IPLV}_b - \text{IPLV}_q)$

Formatted: Indent: Left: 0.25", Hanging: 0.75", Right: -0.13"

~~Energy~~Peak Demand Savings $= (\text{kW}) = N * \text{Tons} * \text{EFLH} * \text{PDC} * (\text{IPLV}_b - \text{IPLV}_q)$

Formatted: Indent: Left: 0", First line: 0.25", Right: -0.13"

For FLV:

Formatted: Font: Italic

~~Demand~~Energy Savings $= (\text{kWh/yr}) = N * \text{Tons} * \text{PDC} * \text{EFLH} * (\text{FLV}_b - \text{FLV}_q)$

Formatted: Indent: First line: 0.25"

~~Energy~~Peak Demand Savings $= (\text{kW}) = N * \text{Tons} * \text{EFLH} * \text{PDC} * (\text{FLV}_b - \text{FLV}_q)$

Formatted: Indent: Left: 0", First line: 0.25", Right: -0.13"

Definition of Variables

Formatted: Normal, Right: -0.13"

Definition of Variables

Formatted: Right: 0"

N = Number of units

Tons = Rated ~~capacity of cooling~~ ~~cooling capacity~~

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

EFLH = Equivalent Full Load Hours – This represents a measure of ~~chiller energy~~ use by season ~~determined by measured kWh~~ during the ~~period divided by kW at design conditions from JCP&L measurement data~~ on-peak and off peak periods.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

PDC = Peak Duty Cycle: fraction of time the compressor runs during peak hours

Formatted: Space Before: 3 pt, After: 3 pt

IPLV_b = Integrated Part Load Value of baseline equipment, kW/Ton. -The efficiency of the chiller under partial-load conditions.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

$IPLV_q$ ____ = Integrated Part Load Value of qualifying equipment, kW/Ton. -The efficiency of the chiller under partial-load conditions.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

FLV_b ____ = Full Load Value of baseline equipment, kW/Ton. -The efficiency of the chiller under full-load conditions.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

FLV_q ____ = Full Load Value of qualifying equipment, kW/Ton. The efficiency of the chiller under full-load conditions.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Summary of Inputs

Electric Chiller Assumptions

<u>Electric Chillers Component</u>	<u>Type</u>	<u>Situation</u>	<u>Value</u>	<u>Source</u>
Tons	<u>Variable</u> <u>Rated Capacity, Tons</u>	All	Varies	From Application
<u>$IPLV_b$ (kW/ton)</u>	<u>Variable</u>	<u>See table below</u>	<u>Varies</u>	<u>1</u>
$IPLV_q$ (kW/ton)	Variable	All	Varies	From Application (per AHRI Std. 550/590)
<u>FLV_b (kW/ton)</u>	<u>Variable</u>	<u>See table below</u>	<u>Varies</u>	<u>1</u>
<u>FLV_q (kW/ton)</u>	<u>Variable</u>	<u>All</u>	<u>Varies</u>	<u>From Application (per AHRI Std. 550/590)</u>
PDC	Fixed	All	67%	Engineering Estimate
EFLH	<u>Fixed</u> <u>Variable</u>	All	<u>1,360</u> <u>See Table Below</u>	<u>California DEER2</u>

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Font: Times New Roman Bold, Condensed by 0.2 pt

Formatted: Table Header, Left, Don't keep with next

Formatted Table

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted Table

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted Table

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next

Formatted: Table Cells, Space After: 1 pt, Don't keep with next

Electric Chillers—Existing Buildings

Type	Capacity	ASHRAE 90.1 2007 ^a			
		Full Load COP	IPLV COP	Full Load kW/ton	IPLV kW/ton
Air-Cooled	tons < 150	2.80	3.05	1.256	1.153
	tons ≥ 150	2.80	3.05	1.256	1.153
Water-Cooled Positive Displacement (rotary screw and scroll)	tons < 75	4.45	5.20	0.790	0.676
	75 ≤ tons < 150	4.45	5.20	0.790	0.676
	150 ≤ tons < 300	4.90	5.60	0.718	0.628
	300 ≤ tons < 600	5.50	6.15	0.639	0.572
	tons ≥ 600	5.50	6.15	0.639	0.572
Water-Cooled Centrifugal	tons < 150	5.00	5.25	0.703	0.670
	150 ≤ tons < 300	5.55	5.90	0.634	0.596
	300 ≤ tons < 400	6.10	6.40	0.576	0.549
	400 ≤ tons < 600	6.10	6.40	0.576	0.549
	tons ≥ 600	6.10	6.40	0.576	0.549

^a—The 90.1 2007 efficiencies were used in the 90.1 2013 capacity categories for consistency between tables. The 2007 water-cooled reciprocating category was removed and the 90.1 2007 water-cooled screw and scroll efficiencies were used in the appropriate 90.1 2013 water-cooled positive displacement capacity categories (the water-cooled reciprocating category was removed from ASHRAE 90.1 in 2010).

Electric Chillers – New Construction

Type	Capacity	ASHRAE 90.1 2013 effective 1/1/2015 ^a			
		Path A		Path B	
		Full Load kW/ton	IPLV kW/ton	Full Load kW/ton	IPLV kW/ton
Air Cooled	tons < 150	10.1 1.188	13.7 0.876	9.7 1.237	15.8 0.759
	tons ≥ 150	10.1 1.188	14.0 0.857	9.7 1.237	16.1 0.745
Water-Cooled Positive Displacement (rotary screw and scroll)	tons < 75	0.750	0.600	0.780	0.500
	75 ≤ tons < 150	0.720	0.560	0.750	0.490
	150 ≤ tons < 300	0.660	0.540	0.680	0.440
	300 ≤ tons < 600	0.610	0.520	0.625	0.410
	tons ≥ 600	0.560	0.500	0.585	0.380

Formatted: Table Caption, Don't keep with next

Formatted: Table Caption, Left, Don't keep with next

Formatted: Table Header, Left, Don't keep with next, Don't keep lines together

Formatted: Table Header, Left, Don't keep with next, Don't keep lines together

Formatted: Table Header, Left, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted

Water Cooled Centrifugal	tons < 150	0.610	0.550	0.695	0.440
	150 ≤ tons < 300	0.610	0.550	0.635	0.400
	300 ≤ tons < 400	0.560	0.520	0.595	0.390
	400 ≤ tons < 600	0.560	0.500	0.585	0.380
	tons ≥ 600	0.560	0.500	0.585	0.380

a – Values in italics are EERs.

EFLH Table

<u>Facility Type</u>	<u>Cooling EFLH</u>
<u>Assembly</u>	<u>669</u>
<u>Auto repair</u>	<u>426</u>
<u>Dormitory</u>	<u>800</u>
<u>Hospital</u>	<u>1424</u>
<u>Light industrial</u>	<u>549</u>
<u>Lodging – Hotel</u>	<u>2918</u>
<u>Lodging – Motel</u>	<u>1233</u>
<u>Office – large</u>	<u>720</u>
<u>Office – small</u>	<u>955</u>
<u>Other</u>	<u>736</u>
<u>Religious worship</u>	<u>279</u>
<u>Restaurant – fast food</u>	<u>645</u>
<u>Restaurant – full service</u>	<u>574</u>
<u>Retail – big box</u>	<u>1279</u>
<u>Retail – Grocery</u>	<u>1279</u>
<u>Retail – large</u>	<u>882</u>
<u>Retail – large</u>	<u>1068</u>
<u>School – Community college</u>	<u>846</u>
<u>School – postsecondary</u>	<u>1208</u>
<u>School – primary</u>	<u>394</u>
<u>School – secondary</u>	<u>466</u>
<u>Warehouse</u>	<u>400</u>

Multi-family EFLH by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Cooling</u>	<u>507</u>	<u>550</u>	<u>562</u>
<u>High-rise, Cooling</u>	<u>793</u>	<u>843</u>	<u>954</u>

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Table Cells, Left, Space After: 1 pt, Don't keep with next, Don't keep lines together

Formatted: Don't keep with next

Sources

1. ASHRAE Standards 90.1-2013. *Energy Standard for Buildings Except Low Rise Residential Buildings*. <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
2. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.

Formatted: Keep with next, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: English (U.S.)

Variable Frequency Drives

~~The measurement~~ This section provides algorithms and assumptions for reporting of energy and demand savings for C/I Variable Frequency Drive ~~for (VFD applications is are for constant and variable air volume system)~~ installations for HVAC systems including: supply air fans, return air fans, chilled water and condenser water pumps, hot water circulation pumps, water source heat pump circulation pumps, cooling tower fans, ~~kitchen hood fans, and boiler feed water pumps, and boiler draft fans only.~~ VFD applications for other ~~than this use~~ end uses should follow the custom path.

Algorithms

Algorithms

$$\text{Energy Savings (kWh)} = 0.746 * \text{yr} = N * \text{HP} * \text{HRS} * (\text{ESF} / \eta_{\text{motor}})$$

$$\text{Peak Demand Savings (kW)} = 0.746 * N * \text{HP} * (\text{DSF} / \eta_{\text{motor}})$$

Definitions of Variables

N = Number of motors controlled by VFD(s) per application
HP = ~~nameplate~~ = Nameplate motor horsepower or manufacturer ~~specification~~ sheet per application

η_{motor} = Motor efficiency at the peak load. Motor efficiency varies with load. At low loads relative to the rated hp (usually below 50%) efficiency often drops dramatically.

ESF = Energy Savings Factor. ~~The energy savings factor is calculated by determining the ratio of the power requirement for baseline and VFD control at peak conditions.~~ (kWh/year per HP)

DSF = Demand Savings Factor. ~~The demand savings factor is calculated by determining the ratio~~ (kW per HP)

Summary of the power requirement for baseline and VFD control at peak conditions Inputs

HRS = annual operating hours

Variable Frequency Drives

Component	Type	Value	Source
Motor HP	Variable	Nameplate/Manufacturer	Application

Formatted: Page break before

Formatted: Right: 0"

Formatted: Font: Italic

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Font: Italic

Formatted: Underline, (none)

Formatted: Normal, Level 4, Keep with next

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Heading 4, Right: 0", Tab stops: Not at 0.25"

Formatted: English (U.S.)

Formatted: Normal

Formatted: Table Header, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

		Spec. Sheet	
η_{motor}	Variable	Nameplate/Manufacturer Spec. Sheet	Application
ESF	Variable	See Table Below	Connecticut Light and Power Derived value based on the following sources: 1, 2, 3
DSF	Variable	See Table Below	Connecticut Light and Power Derived value based on the following sources: 1, 2, 3
HRS	Variable	>2,000	Application

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

The ESF for the supply and return fans and circulating pumps are derived from a 2014 NEEP-funded study of 400 VFD installations in eight northeast states. The derived values are based on actual logged input power data and reflect average operating hours, load factors, and motor efficiencies for the sample. Savings factors representing cooling tower fans and boiler feed water pumps are not reflected in the NEEP report. Values representing these applications are taken from April 2018 New York TRM, Appendix K, and represent average values derived from DOE2.2 simulation of various building types and climate zones, supplemented with results from an earlier analysis of actual program data completed by NSTAR in 2010.

The DSF are derived from the same sources. The NEEP values reflect the actual average impact for the category occurring in the PJM defined peak demand period. The NY values are based on a similar but not identically defined peak period. In all cases the values are expressed in kW/HP rating of the controlled motor and reflect average load factors during the peak period and motor efficiencies for the sample.

Formatted: Font: Bold

Formatted: Right: 0", Space Before: 6 pt, After: 6 pt, Tab stops: Not at 0.25"

Formatted: Table Caption

VFD Savings Factors

<u>Application</u>	<u>ESF (kWh/Year-HP)</u>	<u>DSF (kW/HP)</u>	<u>Source</u>
<u>Supply Air Fan</u>	<u>2,033</u>	<u>0.286</u>	<u>1</u>
<u>Return Air Fan</u>	<u>1,788</u>	<u>0.297</u>	<u>1</u>
<u>CHW or CW Pump</u>	<u>1,633</u>	<u>0.185</u>	<u>1</u>
<u>HHW Pump</u>	<u>1,548</u>	<u>0.096</u>	<u>1</u>
<u>WSHP Pump</u>	<u>2,562</u>	<u>0.234</u>	<u>1</u>
<u>CT Fan</u>	<u>290</u>	<u>-0.025</u>	<u>2, 3</u>
<u>Boiler Feedwater Pump</u>	<u>1,588</u>	<u>0.498</u>	<u>2, 3</u>

Formatted: Indent: Left: 0.5", Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Component	Energy Savings Factor, ESF	Demand Savings Factor, DSF
Airfoil/Backward Inclined Fans	0.475	0.448
Forward Curved Fans	0.240	0.216
Chilled Water Pumps	0.580	0.201
Cooling Tower Fans	0.580	0.000

Formatted: No underline

Sources

1. Cadmus, NEEP – Variable Speed Drive Loadshape Project, August 2014; available at: <http://www.neep.org/variable-speed-drive-loadshape-study-final-report>.
2. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix K – VFD savings factors derived from DOE2.2 simulations reflecting a range of building types and climate zones.
3. Chan, Tumin Formulation of Prescriptive Incentive for VFD, and Motors and VFD Impact Tables, NSTAR 2010.

Variable Speed Air Compressors with Variable Frequency Drives

This measure applies to the installation of variable speed air compressors in retrofit installations where they replace fixed speed compressor with either inlet vane modulation, load no load, or variable displacement flow control. The measure also applies to “lost opportunity” installations including new construction, the expansion of existing facilities, or replacement of existing equipment at end of life. In all cases the baseline is assumed to be a fixed speed compressor with one of the flow control methods described above.

The measure applies to variable speed air compressor up to 75 HP. For larger installations, the implementation cost and energy savings varies significantly between installations and the deemed savings factors provided here are not applicable. Custom protocols should be applied to derive savings and incentive levels for installations larger than 75 HP.

Algorithms

The measurement of energy and demand savings for variable frequency drive (VFD) air compressors:

Algorithms

Energy Savings (kWh/yr) = HRS * ~~(*(Maximum kW/HP Savings) *)~~ * Motor HPSF * HP * 0.746

Peak Demand Savings (kW) = PDC * ~~(*(Maximum kW/HP Savings) *)~~ * Motor HPHP * CF * 0.746

Maximum kW/HP Savings = Percent Energy Savings * (0.746 / EFF_b)

Definitions/Definition of Variables

HRS _____ = Annual compressor ~~runtime (hours)~~ run time from application (hours/year).

PDC = Peak Duty Cycle: fraction of time the compressor runs during peak hours

EFF_b = Efficiency of the industry standard compressor at average load

0.746 = kW to HP conversion = Conversion factor = HP to kW

Formatted: Normal, Level 3, Space Before: 12 pt, After: 3 pt, Page break before, Keep with next

Formatted: English (U.S.)

Formatted: Don't keep lines together

Formatted: Underline, (none)

Formatted: Indent: First line: 0.25", Don't keep lines together

Formatted: Right: 0", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Indent: First line: 0.25", Right: 0", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Underline, (none)

Formatted: English (U.S.)

Formatted: Indent: First line: 0.25", Right: 0", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto, Tab stops: Not at 0.25"

Formatted: Indent: Left: 0.25", Hanging: 0.75", Right: 0", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto, Tab stops: Not at 0.25"

SF = Deemed Savings factor from savings factor table, kW/nameplate HP.

HP = Nameplate motor HP for variable speed air compressor, HP.

CF = Coincidence factor applicable to commercial compressed air installations

Summary of Inputs

Air Compressors with VFDs

Component	Type	Value	Source
<i>Motor HP</i>	Variable	Nameplate	Application
<i>Maximum kW/HP Savings</i>	Fixed	0.274	Calculated
<i>PDCSF</i>	Fixed	0.865186	1
<i>HRS</i>	Fixed Variable	49576.978 hours/year	2 Application, default value from source 1
<i>Percent Energy Savings CF</i>	Fixed	22%1.05	31
<i>EEF_b</i>	Fixed	0.60	3

Sources:

1. Aspen Systems Corporation, Impact Evaluation of 2014 RI Prescriptive Variable Speed Drive Incentive Program Support for Industrial Air Compressors, June 20, 2005.
2. Xenergy, Assessment of the Market for Compressed Air Efficiency Systems, 2001.
- 3.1. ACEEE, Modeling and Simulation of Air Compressor Energy Use, 2005 Installations, National Grid, Prepared by KEMA, July 15, 2016.

Formatted: Table Caption, Left

Formatted: Table Header, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: (none)

Formatted: English (U.S.)

Formatted: Heading 4

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Sources, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

New and Retrofit Kitchen Hoods with Variable Frequency Drives

Kitchen Hoods with Variable Frequency Control utilize optical and temperature sensors at the hood inlet to monitor cooking activity. -Kitchen hood exhaust fans are throttled in response to real time ventilation requirements.- Energy savings result from fan power reduction during part load operation as well as a decrease in heating and cooling requirement of make-up air.

Algorithms

Electric Fan Savings (kWh) = $Q/yr = N * (HP * LF * 0.746/FEFF) * RH * PR$

Heating Savings (MMBtu/yr) = $SF * CFM/SF * OF * FR * HDD * 24 * 1.08 / (HEFF * 1,000,000)$

Cooling Savings (kWh/yr) = $SF * CFM/SF * OF * FR * CDD * 24 * 1.08 / (CEFF * 3,412)$

Definition of Variables

N = Number

Definition of Variables

Q = Quantity of Kitchen Hood Fan Motors

HP = Kitchen Hood Fan Motor HP

LF = Existing Motor Loading Factor

0.746 = Conversion ~~from~~ factor = HP to kW

F_{EFF} = Efficiency of Kitchen Hood Fan Motors (%)

RH = Kitchen Hood Fan Run Hours

PR = Fan Motor Power Reduction resultant from VFD/Control Installation

SF = Kitchen Square Footage

CFM/SF = Code required ventilation rate per square foot for Commercial Kitchen spaces

Formatted: Page break before

Formatted: Font: Not Bold

Formatted: Indent: First line: 0.25"

Formatted: Indent: Left: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Underline, (none)

Formatted: Normal, Level 4, Keep with next

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Subscript

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

OF ___ = Ventilation rate oversize factor (compared to code requirement)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

FR ___ = Flow Reduction resultant from VFD/Control Installation

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

HDD_{mod} = Modified Heating Degree Days based on location and facility type

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

CDD_{mod} = Modified Cooling Degree Days based on location and facility type

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

24 = Hours per Day

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

1.08 = Sensible heat factor for air ((Btu/hr) / (CFM * Deg F))

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

H_{EFF} = Efficiency of Heating System (AFUE %)

Formatted: Subscript

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

C_{EFF} = Efficiency of Cooling System (COP)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

3,412 = Conversion factor from Btu to kWh (3,412 Btu = 1 kWh)

Formatted: Subscript

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

1,000,000 = Btu/MMBtu

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Summary of Inputs

Formatted: Keep with next

Kitchen Hoods with VFDs

Formatted: Table Caption, Left, Don't keep with next

Component	Type	Value	Source
QN	Variable	Quantity	Application
HP	Variable	Nameplate	Application
LF	Fixed	0.9	Melink Analysis Sample ^{Sample⁴⁵}
F_{EFF}	Variable	Based on Motor HP	NEMA Premium Efficiency, TEFC 1800 RPM
RH	Variable	Based on Facility Type See Table Below	Facility Specific Value Table 2

Formatted: Table Header, Right: 0", Tab stops: Not at 0.25"

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Formatted: Font: Not Italic, Subscript

Formatted: Font: Not Italic

Formatted: Font: Not Italic

Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

⁴⁵ To assist with development of this protocol, Melink Corporation provided several sample analyses performed on typical facilities utilizing Intelli-Hood control systems. The analysis performed is used nationwide by Melink to develop energy savings and financial reports related to installation of these systems for interested building owners. Melink's analysis is mirrored in this protocol and includes several of the assumed values utilized here, including an average 0.9 load factor on hood fan motors, as well as operating hours for typical campus, lodging, restaurant and supermarket facility types.

PR	Variable	See Table Below	Facility Specific Value Table 2	Formatted: Font: Not Italic
SF	Variable	Kitchen Square Footage	Application	Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
CFM / SF	Fixed	0.7	ASHRAE 62.1 2013 Table 6.5.1	Formatted: Font: Not Italic
OF	Fixed	1.4	Estimated Typical Kitchen Design ⁴⁶	Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
FR	Variable	Based on Facility Type	Facility Specific Value Table 2	Formatted: Font: Not Italic
HDD _{mod}	Variable	See Table Below	Heating Degree Day Table 3	Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
CDD _{mod}	Variable	See Table Below	Cooling Degree Day Table 4	Formatted: Font: Not Italic
H _{EFF}	Fixed	0.8	8.1F ³ Estimated Heating System Efficiency ⁴⁷	Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
C _{EFF}	Fixed	3.00	Estimated Cooling System Efficiency ⁴⁸	Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"

Facility-Specific Values Table 5

Facility Type	Run Hours	Power Reduction (PR)	Flow Reduction (FR)
Campus	5250	0.568	0.295
Lodging	8736	0.618	0.330
Restaurant	5824	0.552	0.295
Supermarket	5824	0.597	0.320
Other	5250	0.584	0.310

- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic, Subscript
- Formatted: Font: Not Italic
- Formatted: Font: Not Italic
- Formatted: Table Cells, Right: 0", Tab stops: Not at 0.25"
- Formatted: Font: Not Italic, Subscript
- Formatted: Font: Not Italic
- Formatted: Table Caption
- Formatted: Centered

⁴⁶ Oversize factor of 1.4 is a best estimate based on past experience, assessments conducted at facilities with commercial food service equipment and approximations based on Melink sample analyses, which lead to average commercial kitchen ventilation rate of 1 CFM/SF (0.7 * 1.4). While exact ventilation rate is dependent on installed equipment and other factors, this figure is meant to represent average ventilation across potential retrofit and new installation projects.

⁴⁷ A typical heating system efficiency of 80% AFUE is assumed based on estimates of average facility size, heating system age, and past and present code requirements, as well as assumptions indicated in Melink sample analyses. This figure is meant to represent average heating system efficiency across potential retrofit and new installation projects.

⁴⁸ A typical cooling system efficiency of 3.00 COP (10.24 EER, 1.17 kW/Ton) is assumed based on estimates of average facility size, cooling system age, and past and present code requirements, as well as assumptions indicated in Melink sample analyses. This figure is meant to represent average cooling system efficiency across potential retrofit and new installation projects.

Modified Heating Degree Days ~~Table~~⁶Table

Building Type	Heating Energy Density (kBtu/sf)	Degree Day Adjustment Factor	Atlantic City (HDD)	Newark (HDD)	Philadelphia (HDD)	Monticello (HDD)
Education	29.5	0.55	2792	2783	2655	3886
Food Sales	35.6	0.66	3369	3359	3204	4689
Food Service	39.0	0.73	3691	3680	3510	5137
Health Care	53.6	1.00	5073	5057	4824	7060
Lodging	15.0	0.28	1420	1415	1350	1976
Retail	29.3	0.55	2773	2764	2637	3859
Office	28.1	0.52	2660	2651	2529	3701
Public Assembly	33.8	0.63	3199	3189	3042	4452
Public Order/Safety	24.1	0.45	2281	2274	2169	3174
Religious Worship	29.1	0.54	2754	2745	2619	3833
Service	47.8	0.89	4524	4510	4302	6296
Warehouse/Storage	20.2	0.38	1912	1906	1818	2661

Formatted: Table Caption, Space Before: 12 pt

Formatted: Centered

Formatted: Table Caption, Space Before: 12 pt

Modified Cooling Degree Days Table⁷Table

Building Type	Degree Day Adjustment Factor	Atlantic City (CDD)	Newark (CDD)	Philadelphia (CDD)	Monticello (CDD)
Education	0.55	824	893	806	625
Food Sales	0.66	989	1071	967	750
Food Service	0.73	1094	1185	1069	830
Health Care	1.00	1499	1623	1465	1137
Lodging	0.28	420	454	410	318
Retail	0.55	824	893	806	625
Office	0.52	779	844	762	591
Public Assembly	0.63	944	1022	923	716
Public Order/Safety	0.45	675	730	659	512
Religious Worship	0.54	809	876	791	614
Service	0.89	1334	1444	1304	1012
Warehouse/Storage	0.38	570	617	557	432

Formatted: Centered

Sources:

1. ~~To assist with development of this protocol, Melink Corporation provided several sample analyses performed on typical facilities utilizing Intelli Hood control systems. The analysis performed is used nationwide by Melink to develop energy savings and financial reports related to installation of these systems for interested building owners. Melink's analysis is mirrored in this protocol and includes several of the assumed values utilized here, including an average 0.9 load factor on hood fan motors, as well as operating hours for typical campus, lodging, restaurant and supermarket facility types.~~
2. ~~Oversize factor of 1.4 is a best estimate based on past experience, assessments conducted at facilities with commercial food service equipment and approximations based on Melink sample analyses, which lead to average commercial kitchen ventilation rate of 1 CFM/SF (0.7 * 1.4). While exact ventilation rate is dependent on installed equipment and other factors, this figure is meant to represent average ventilation across potential retrofit and new installation projects.~~
3. ~~A typical heating system efficiency of 80% AFUE is assumed based on estimates of average facility size, heating system age, and past and present code requirements, as well as assumptions indicated in Melink sample analyses. This figure is meant to represent average heating system efficiency across potential retrofit and new installation projects.~~
4. ~~A typical cooling system efficiency of 3.00 COP (10.24 EER, 1.17 kW/Ton) is assumed based on estimates of average facility size, cooling system age, and past and present code requirements, as well as assumptions indicated in Melink sample analyses. This figure is meant to represent average cooling system efficiency across potential retrofit and new installation projects.~~

Formatted: English (U.S.)

Formatted: Heading 4, Space After: 6 pt

1. ASHRAE Standards 62.1-2013, Standards for Ventilation and IAQ.

<https://www.ashrae.org/standards-research--technology/standards--guidelines>, Table 6.5.

~~5.2.~~ Facility Specific Values table constructed based on consolidation of Melink sample analysis data. -Facility run hours were averaged across all like sample analyses.- Fan power and flow reductions were calculated utilizing fan power profiles included in each sample analysis.

~~6.~~ KEMA, *Smartstart Program Protocol Review.* – 2009.

3. KEMA, June 2009, New Jersey’s Clean Energy Program Smartstart Program Protocol Review; available at:

<http://www.njcleanenergy.com/files/file/Library/HVAC%20Evaluation%20Report%20-%20Final%20June%2011%202009.pdf>.

~~7.4.~~ Modified Cooling Degree Days table utilizes Degree Day Adjustment factors from Heating Degree Days table and cooling degree days for each of the four representative cities as indicated by degreedays.net.

Formatted: Sources, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Sources, No bullets or numbering

Commercial Refrigeration Measures

For Aluminum Night Curtains, Door Heater Controls, Electric Defrost Controls, Evaporator Fan Controls, and Novelty Cooler Shutoff, see applicable protocols for the commercial Direct Install program.

For Energy Efficient Glass Doors for Vertical Open Refrigerated Cases:

This measure applies to retrofitting vertical, open, refrigerated display cases with high efficiency glass doors that have either no anti-sweat heaters (“zero energy doors”), or very low energy anti-sweat heaters. The deemed savings factors are derived from the results of a controlled test designed to measure the impact of this measure. The results of the test were presented at the 2010 International Refrigeration and Air Conditioning conference.

Algorithms

Energy Savings (kWh/yr): $\Delta kWh = ESF \times CL$

Peak Algorithms

Demand Savings (kW): $\Delta kW = (HG \times EF \times CL) / (EER \times 1000) \Delta kWh / Hours$

Annual Heating Energy Savings: $\Delta Therms = HSF * CL$

Definition of Variables

$\Delta kWh = \frac{\text{Gross customer annual kWh savings for the measure}}{\Delta kW \times Usage}$

Definitions of Variables

$\Delta kW = \frac{\text{Gross customer connected load kW savings for the measure}}{\text{gross}}$ (kW)

HG = Loss of cold air or heat gain for refrigerated cases with no cover (Btu/hr-ft opening)

EF = Efficiency Factor, fraction of heat gain prevented by case door

$ESF = \text{Stipulated annual electric savings per linear foot of case}$

$HSF = \text{Stipulated annual heating savings factor per linear foot of case}$

$CL = \text{Case Length, open length of the refrigerated case in feet (from application)}$

EER = Compressor efficiency (Btu/hr-watt)

1000 = Conversion from watts to kW (W/kW).

$\Delta kWh = \text{gross customer annual kWh savings for the measure (kWh)}$

Formatted: Heading 3, Space After: 6 pt, Page break before

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: No underline

Formatted: Space Before: 6 pt, After: 3 pt

Formatted: Underline

Formatted: Indent: First line: 0.25"

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Usage = hours per year

Hours = Hours per year that case is in operation, use 8,760 unless otherwise indicated.

Summary of Inputs

Glass Doors - Commercial Refrigeration

Component	Type	Value	Source
HG	Fixed	760	PG&E study by ENCON Mechanical & Nuclear Engineering, 1992
EF	Fixed	0.85	PG&E study by ENCON Mechanical & Nuclear Engineering, 1992
<u>ESF</u>	<u>Fixed</u>	<u>395 kWh/year-foot</u>	<u>Derived from the following sources: 1,2,3,4,5</u>
<u>HSF</u>	<u>Fixed</u>	<u>10.5 Therms/year-foot</u>	<u>Derived from the following sources: 1,2,3,4,5</u>
CL	Variable		Rebate Application or Manufacturer Data
<u>Hours</u>	<u>Fixed</u>	<u>8,760 Default</u>	<u>3</u>

Formatted: Table Caption, Left

Formatted: Table Header, Left

Formatted Table

Formatted: Table Cells

Formatted Table

Formatted: No underline

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li

Formatted: English (U.S.)

Sources

1. Energy Use of Doored and Open Vertical Refrigerated Display, Brian Fricke and Bryan Becker, University of Missouri – Kansas City, 2010; presented at the 2010 International Refrigeration and Air Conditioning Conference, School of Mechanical Engineering, Purdue University, Paper #1154; available at: <http://docs.lib.purdue.edu/cgi/viewcontent.cgi?article=2153&context=iracc> <http://docs.lib.purdue.edu/iracc/1154>
2. Refrigeration COP of 2.2 used in derivation of savings factors – Kuiken et al, Focus on Energy Evaluation, Business Program: Deemed Savings Manual V 1.0, KEMA, March 22, 2010.
3. HVAC COP of 3.2 used in derivation of savings factors – ASHRAE Standards 90.1-2007 and 2013, Energy Standard for Buildings Except Low Rise Residential Buildings. <https://www.ashrae.org/standards-research--technology/standards--guidelines>, Table 6.8.1A.
4. Gas boiler efficiency of 80% used in derivation of savings factors – ASHRAE Standards 90.1-2007 and 2013, Energy Standard for Buildings Except Low Rise

Residential Buildings. <https://www.ashrae.org/standards-research--technology/standards--guidelines>, Table 6.8.1F.

5. DOE Typical Meteorological Year (TMY3) data for Trenton, Newark, and Atlantic City.

Aluminum Night Covers

This measure is applicable to existing open-type refrigerated display cases where considerable heat is lost through an opening that is directly exposed to ambient air. These retractable aluminum woven fabric covers provide a barrier between the contents of the case and the outside environment. They are employed during non-business hours to significantly reduce heat loss from these cases when contents need not be visible.

Savings approximations are based on the report, "Effects of the Low Emissivity Shields on performance and Power use of a refrigerated display case," by Southern California Edison, August 8, 1997. Southern California Edison (SCE) conducted this test at its state-of-the-art Refrigeration Technology and Test Center (RTTC), located in Irwindale, CA. The RTTC's sophisticated instrumentation and data acquisition system provided detailed tracking of the refrigeration system's critical temperature and pressure points during the test period. These readings were then utilized to quantify various heat transfer and power related parameters within the refrigeration cycle. The results of SCE's test focused on three typical scenarios found mostly in supermarkets: low, medium and high temperature cases.

Algorithms

$$\text{Energy Savings (kWh/yr)} = W * H * F$$

Definition of Variables

W = Width of protected opening in ft.

H = Hours per year covers are in place

F = Savings factor based on case temperature

Summary of Inputs

Aluminum Night Covers - Commercial Refrigeration

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>W</u>	<u>Variable</u>		<u>Application</u>
<u>H</u>	<u>Variable</u>		<u>Application</u>
<u>F</u>	<u>Variable</u>	<u>Low temperature (-35F to -5F) F = 0.1 kW/ft</u> <u>Medium temperature (0F to 30F) F = 0.06 kW/ft</u> <u>High temperature (35F to 55F) F = 0.04 kW/ft</u>	<u>1</u>

Sources

1. Southern California Edison (SCE). "Effects of the Low Emissivity Shields on performance and Power use of a refrigerated display case," August 8, 1997.

Formatted: Font: Not Bold, Not Italic

Formatted: Heading 3, None, Space Before: 0 pt, After: 6 pt, Page break before, Don't keep with next

Formatted: Allow hanging punctuation, Font Alignment: Auto

Formatted: Underline, (none)

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: English (U.S.)

Formatted: Heading 4

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: English (U.S.)

Walk-in Cooler/Freezer Evaporator Fan Control

This measure is applicable to existing walk-in coolers and freezers that have evaporator fans which run continuously. The measure adds a control system feature to automatically shut off evaporator fans when the cooler's thermostat is not calling for cooling. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein. These savings take into account evaporator fan shut off and associated savings as a result of less heat being introduced into the walk-in, as well as the savings from the compressor, which is now being controlled through electronic temperature control.

Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field-tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.⁴⁹

Algorithms

$$\text{Gross Energy Savings (kWh/yr)} = kWh \text{ Savings}_{EF} + kWh \text{ Savings}_{RH} + kWh \text{ Savings}_{SEC}$$

$$kWh \text{ Savings}_{EF} = ((\text{Amps}_{EF} * \text{Volts}_{EF} * (\text{Phase}_{EF})^{1/2}) / 1000) * 0.55 * 8,760 * 35.52\%$$

$$kWh \text{ Savings}_{RH} = kWh \text{ Savings}_{EF} * 0.28 * 1.6$$

$$kWh \text{ Savings}_{SEC} = (((\text{Amps}_{CP} * \text{Volts}_{CP} * (\text{Phase}_{CP})^{1/2}) / 1000) * 0.85 * ((35\% * \text{WH}) + (55\% * \text{NWH})) * 5\%) + (((\text{Amps}_{EF} * \text{Volts}_{EF} * (\text{Phase}_{EF})^{1/2}) / 1000) * 0.55 * 8,760 * 35.52\% * 5\%)$$

$$\text{Gross kW Savings} = ((\text{Amps}_{EF} * \text{Volts}_{EF} * (\text{Phase}_{EF})^{1/2}) / 1000) * 0.55 * D$$

Definition of Variables

kWh Savings_{EF} = Savings due to Evaporator Fan being off

kWh Savings_{RH} = Savings due to reduced heat from Evaporator Fans

kWh Savings_{SEC} = Savings due to the electronic controls on compressor and evaporator

Amps_{EF} = Nameplate Amps of Evaporator Fan

Volts_{EF} = Nameplate Volts of Evaporator Fan

Phase_{EF} = Phase of Evaporator Fan

0.55 = Evaporator Fan Motor power factor

8,760 = Annual Operating Hours

⁴⁹ Several case studies related to NRM's Cooltrol system can be found at: http://www.nrminc.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html.

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: (none)

Formatted: Level 4, Keep with next

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: Left: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

- 35.52% = Percent of time Evaporator Fan is turned off
- 0.28 = Conversion from kW to tons (Refrigeration)
- 1.6 = Efficiency of typical refrigeration system in kW/ton [3]
- Amps_{CP} = Nameplate Amps of Compressor
- Volts_{CP} = Nameplate Volts of Compressor
- Phase_{CP} = Phase of Compressor
- 0.85 = Compressor power factor.
- 35% = Compressor duty cycle during winter months
- WH = Compressor hours during winter months
- 55% = Compressor duty cycle during non-winter months
- NWH = Compressor hours during non-winter months (6,565)
- 5% = Reduced run time of Compressor and Evaporator due to electronic controls
- D = Diversity Factor

Summary of Inputs

Evaporator Fan Control - Commercial Refrigeration

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Amps_{EF}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Volts_{EF}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Phase_{EF}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>0.55</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>8.760</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>35.52%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate⁵⁰</u>
<u>0.28</u>	<u>Variable</u>	<u>Conversion</u>	
<u>1.6</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate. 1</u>
<u>Amps_{CP}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Volts_{CP}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Phase_{CP}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>0.85</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>35%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>

⁵⁰ This value is an estimate by NRM based on hundreds of downloads of hours of use data from the electronic controller. It is an ‘average’ savings number and has been validated through several Third Party Impact Evaluation Studies including study performed by HEC. “Analysis of Walk-in Cooler Air Economizers,” p. 22, Table 9, October 10, 2000 for National Grid.

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>WH</u>	<u>Variable</u>	<u>2,195 - Default</u>	<u>Estimate</u>
<u>55%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>NWH</u>	<u>Variable</u>	<u>6,565 - Default</u>	<u>Estimate</u>
<u>5%</u>	<u>Variable</u>	<u>Default</u>	<u>2</u>
<u>D</u>	<u>Variable</u>	<u>0.228</u>	<u>3</u>

Sources

1. Select Energy Services, Inc. Cooler Control Measure Impact Spreadsheet User's Manual. 2004.
2. This percentage has been collaborated by several utility sponsored 3rd Party studies including study conducted by Select Energy Services for NSTAR, March 9, 2004.
3. Based on the report "Savings from Walk-In Cooler Air Economizers and Evaporator Fan Controls." HEC, June 28, 1996.

Formatted: No underline, (none)

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: English (U.S.)

Formatted: Sources, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Font: Not Italic

Cooler and Freezer Door Heater Control

This measure is applicable to existing walk-in coolers and freezers that have continuously operating electric heaters on the doors to prevent condensation formation. This measure adds a control system feature to shut off the door heaters when the humidity level is low enough such that condensation will not occur if the heaters are off. This is performed by measuring the ambient humidity and temperature of the store, calculating the dewpoint, and using PWM (pulse width modulation) to control the anti-sweat heaters based on specific algorithms for freezer doors. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field-tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.⁵¹

Low Temperature (Freezer) Door Heater Control

Algorithms

$$\text{Energy Savings (kWh/yr)} = (\text{kW}_{\text{DH}} * 8,760) - ((40\% * \text{kW}_{\text{DH}} * 4,000) + (65\% * \text{kW}_{\text{DH}} * 4,760))$$

$$\text{Peak Demand Savings (kW)} = \text{kW}_{\text{DH}} * 46\% * 75\%$$

Definition of Variables

kW_{DH} = Total demand (kW) of the freezer door heaters, based on nameplate volts and amps.

8,760 = Annual run hours of Freezer Door Heater before controls.

40% = Percent of total run power of door heaters with controls providing maximum reduction

4,000 = Number of hours door heaters run at 40% power.

65% = Percent of total run power of door heaters with controls providing minimum reduction

4,760 = Number of hours door heaters run at 65% power.

46% = Freezer Door Heater off time

75% = Adjustment factor to account for diversity and coincidence at peak demand

⁵¹ Several case studies related to NRM's Cooltrol system can be found at: http://www.nrminc.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html

Formatted: Heading 3, None, Space Before: 0 pt, After: 6 pt, Page break before, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font: Bold, Italic, No underline

Formatted: Space Before: 18 pt

Formatted: Heading 4

Formatted: Heading 4

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Medium Temperature (Cooler) Door Heater Control

Algorithms

$$\text{Energy Savings (kWh/yr)} = (\text{kW}_{\text{DH}} * 8,760) - (60\% * \text{kW}_{\text{DH}} * 3,760)$$

$$\text{Peak Demand Savings (kW)} = \text{kW}_{\text{DH}} * 74\% * 75\%$$

Definition of Variables

kW_{DH} = Total demand (kW) of the cooler door heaters, based on nameplate volts and amps.

8,760 = Annual run hours of Cooler Door Heater before controls.

60% = Percent of total run power of door heaters with controls providing minimum reduction

3,760 = Number of hours door heaters run at 60% power.

74% = Cooler Door Heater off time

75% = Adjustment factor to account for diversity and coincidence at peak demand

Summary of Inputs

Door Heater Controls - Commercial Refrigeration

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>kW_{DH}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>8,760</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>40%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 1</u>
<u>4,000</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>65%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 2</u>
<u>4,760</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>46%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 2</u>
<u>75%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 1</u>
<u>60%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>3,760</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>74%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 2</u>

Sources

1. Estimated by NRM based on their experience of monitoring the equipment at various sites.
2. This value is an estimate by National Resource Management based on hundreds of downloads of hours of use data from Door Heater controllers. This supported by 3rd Party Analysis conducted by Select Energy for NSTAR. "Cooler Control Measure Impact Spreadsheet Users' Manual," P.5, March 9, 2004.

Formatted: Heading 4

Formatted: Heading 4

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: English (U.S.)

Formatted: Space Before: 3 pt, After: 3 pt, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Font: 12 pt

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Electric Defrost Control

This measure is applicable to existing evaporator fans with a traditional electric defrost mechanism. This control system overrides defrost of evaporator fans when unnecessary, reducing annual energy consumption. The estimates for savings take into account savings from reduced defrosts as well as the reduction in heat gain from the defrost process.

Independent Testing was performed by Intertek Testing Service on a Walk-in Freezer that was retrofitted with Smart Electric Defrost capability. A baseline of 28 electric defrosts per week were established as the baseline for a two week period without the Smart Electric Defrost capability. With Smart Electric Defrost capability an average skip rate of 43.64% was observed for the following two week period.

Algorithms

$$\text{Gross Energy Savings (kWh/yr)} = kWh \text{ Savings}_{\text{Defrost}} + kWh \text{ Savings}_{\text{RH}}$$

$$kWh \text{ Savings}_{\text{Defrost}} = KW_{\text{Defrost}} * 0.667 * 4 * 365 * 35\%$$

$$kWh \text{ Savings}_{\text{RH}} = kWh \text{ Savings}_{\text{Defrost}} * 0.28 * 1.6$$

Definition of Variables

$kWh \text{ Savings}_{\text{Defrost}}$ = Savings due to reduction of defrosts

$kWh \text{ Savings}_{\text{RH}}$ = Savings due to reduction in refrigeration load

KW_{Defrost} = Nameplate Load of Electric Defrost

0.667 = Average Length of Electric Defrost in hours

4 = Average Number of Electric Defrosts per day

365 = Conversion factor = Days per Year

35% = Average Number of Defrosts that will be eliminated in year

0.28 = Conversion factor = kW to tons (Refrigeration)

1.6 = Efficiency of typical refrigeration system in kW/ton

Summary of Inputs

Electric Defrost Controls - Commercial Refrigeration

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>kW_{DH}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>0.667</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>4</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>35%</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>1.6</u>	<u>Variable</u>	<u>Default</u>	<u>1</u>

Sources

1. Select Energy Services, Inc. Cooler Control Measure Impact Spreadsheet User's Manual. 2004.

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 12 pt, After: 12

Formatted: Heading 4

Formatted: Indent: First line: 0.25", Space Before: 6 pt, After: 6 pt

Formatted: Heading 4

Formatted: List Paragraph, Space Before: 6 pt, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0.25" + Indent at: 0.5"

Novelty Cooler Shutoff

This measure is applicable to existing reach-in novelty coolers which run continuously. The measure adds a control system feature to automatically shut off novelty coolers based on pre-set store operating hours. Based on programmed hours, the control mechanism shuts off the cooler at end of business, and begins operation on reduced cycles. Regular operation begins the following day an hour before start of business. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field-tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.⁵²

Algorithms

$$\text{Energy Savings (kWh/yr)} = \frac{((\text{Amps}_{\text{NC}} * \text{Volts}_{\text{NC}} * (\text{Phase}_{\text{NC}})^{1/2}) / 1000) * 0.85) * ((0.45 * ((\text{CH} - 1) * 91)) + (0.5 * ((\text{CH} - 1) * 274)))}$$

Definition of Variables

- Amps_{NC} = Nameplate Amps of Novelty Cooler
- Volts_{NC} = Nameplate Volts of Novelty Cooler
- Phase_{NC} = Phase of Novelty Cooler
- 0.85 = Novelty Cooler power factor
- 0.45 = Duty cycle during winter month nights
- CH = Closed Store hours
- 91 = Number of days in winter months
- 0.5 = Duty cycle during non-winter month nights [3]
- 274 = Number of days in non-winter months

Summary of Inputs

Novelty Cooler - Commercial Refrigeration

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Amps_{NC}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Volts_{NC}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>
<u>Phase_{NC}</u>	<u>Variable</u>	<u>Manufacturer data</u>	<u>Application</u>

⁵² Several case studies related to NRM's Cooltrol system can be found at: http://www.nrminc.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html.

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Page break before, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4, Space Before: 6 pt

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>0.85</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 1</u>
<u>0.45</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate, 2</u>
<u>CH</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>91</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>0.5</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>
<u>274</u>	<u>Variable</u>	<u>Default</u>	<u>Estimate</u>

Sources

1. Estimated by NRM based on their experience of monitoring the equipment at various sites.
2. Duty Cycles are consistent with third-party study done by Select Energy for NSTAR "Cooler Control Measure Impact Spreadsheet Users Manual," p. 5, March 9, 2004.

Formatted: Indent: Left: 0.5", Space Before: 3 pt, After: 3 pt, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Sources, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Sources, No bullets or numbering

Food Service Measures Protocols

Energy efficient electric or natural gas cooking equipment of the following listed types utilized in commercial food service applications which have performance rated in accordance with the listed ASTM standards:

- Electric and gas combination oven/steamer – ASTM F2861
- Gas convection ovens – ASTM F1496
- Gas conveyor ovens – ASTM F1817
- Gas rack ovens – ASTM F2093
- Electric and gas small vat fryers – ASTM F1361
- Electric and gas large vat fryers – ASTM F2144
- Electric and gas steamers – ASTM F1484
- Electric and gas griddles – ASTM F1275
- Hot food holding cabinets –CEE Tier II
- Commercial dishwashers – ENERGY STAR Refrigerators, Freezers – ENERGY STAR
- Ice Machines – ARI Standard 810

Electric and Gas Combination Oven/Steamer

The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

Energy Savings (kWh/yr or Therms/yr) = $D * (E_p + E_{ic} + E_{is} + E_{cc} + E_{cs})$

Peak Demand Savings (kW) = kWh Savings / (D * H)

Preheat Savings[†]: $E_p = P * (PE_b - PE_q)$

Convection Mode Idle Savings[†]: $E_{ic} = (I_{cb} - I_{cq}) * ((H - (P * P_t)) - (I_{cb} / PC_{cb} - I_{cq} / PC_{cq}) * Lbs) * (1 - S_t)$

Steam Mode Idle Savings[†]: $E_{is} = (I_{sb} - I_{sq}) * ((H - (P * P_t)) - (I_{sb} / PC_{sb} - I_{sq} / PC_{sq}) * Lbs) * S_t$

Convection Mode Cooking Savings: $E_{cc} = Lbs * (1 - S_t) * Heat_c * (1 / Eff_{cb} - 1 / Eff_{cq}) / C$

Formatted: Right: -0.38", Space Before: 6 pt, After: 6 pt

Formatted: Tab stops: 1.03", Left

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: Left: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Steam Mode Cooking Savings: $E_{cs} = Lbs * St * Heat_s * (1/Eff_{sb} - 1/Eff_{sq}) / C$

Formatted: Indent: First line: 0.25"

† – For gas equipment, convert these intermediate values to therms by dividing the result by 100,000 Btu/therm

Definition of Variables

(See tables of values below for more information)⁵³

C = Conversion Factor from Btu to kWh or Therms

D = Operating Days per Year

Effcb = Baseline Equipment Convection Mode Cooking Efficiency

Effcq = Qualifying Equipment Convection Mode Cooking Efficiency

Effsb = Baseline Equipment Steam Mode Cooking Efficiency

Effsq = Qualifying Equipment Steam Mode Cooking Efficiency

H = Daily Operating Hours

Heatc = Convection Mode Heat to Food

Heats = Steam Mode Heat to Food

Icb = Baseline Equipment Convection Mode Idle Energy Rate

Icq = Qualifying Equipment Convection Mode Idle Energy Rate

Isb = Baseline Equipment Steam Mode Idle Energy Rate

Isq = Qualifying Equipment Steam Mode Idle Energy Rate

Lbs = Total Daily Food Production

P = Number of Preheats per Day

PCcb = Baseline Equipment Convection Mode Production Capacity

PCcq = Qualifying Equipment Convection Mode Production Capacity

PCsb = Baseline Equipment Steam Mode Production Capacity

PCsq = Qualifying Equipment Steam Mode Production Capacity

PEb = Baseline Equipment Preheat Energy

PEq = Qualifying Equipment Preheat Energy

Pt = Preheat Duration

St = Percentage of Time in Steam Mode

⁵³ Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission. Values for Tables 1 and 2 from PG&E Work Paper PGEFST100, "Commercial Combination Ovens/Steam –Electric and Gas," Revision 6, 2016.

Summary of Inputs

Table 1: Electric Combination Oven/Steamers						
Variable	Baseline			Qualifying		
	<15 Pans	15-28 Pans	>28 Pans	<15 Pans	15-28 Pans	>28 Pans
D - Operating Days per Year	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P - Number of Preheats per Day	1	1	1	1	1	1
PE _b & PE _q - Preheat Energy (kWh)	3.00	3.75	5.63	1.50	2.00	3.00
I _{cb} & I _{cq} - Convection Mode Idle Energy Rate (kW)	3.00	3.75	5.25	Application	Application	Application
H - Operating Hours per Day	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25	0.25	0.25
PC _{cb} & PC _{cq} - Convection Mode Prod. Capacity (lbs/hr)	80	100	275	100	125	325
Lbs - Total Daily Food Production (lbs)	200	250	400	200	250	400
S _t - Percentage of Time in Steam Mode	50%	50%	50%	50%	50%	50%
I _{sb} & I _{sq} - Steam Mode Idle Energy Rate (kW)	10.0	12.5	18.0	Application	Application	Application
PC _{sb} & PC _{sq} - Steam Mode Prod. Capacity (lbs/hr)	100	150	350	120	200	400
Heat _c - Convection Heat to Food (Btu/lb)	250	250	250	250	250	250
Eff _{cb} & Eff _{cq} - Convection Mode Cooking Efficiency	65%	65%	65%	Application	Application	Application
C - Btu/kWh	3,412	3,412	3,412	3,412	3,412	3,412
Heat _s - Steam Heat to Food (Btu/lb)	105	105	105	105	105	105
Eff _{sb} & Eff _{sq} - Steam Mode Cooking Efficiency	40%	40%	40%	Application	Application	Application

Table 2: Gas Combination Oven/Steamers						
Variable	Baseline			Qualifying		
	<15 Pans	15-28 Pans	>28 Pans	<15 Pans	15-28 Pans	>28 Pans
D - Operating Days per Year	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P - Number of Preheats per Day	1	1	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	18,000	22,000	32,000	13,000	16,000	24,000
I _{cb} & I _{cq} - Convection Mode Idle Energy Rate (Btu/h)	15,000	20,000	30,000	Application	Application	Application
H - Operating Hours per Day	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P _t - Preheat Duration (h)	0.25	0.25	0.25	0.25	0.25	0.25
PC _{cb} & PC _{cq} - Convection Mode Prod. Capacity (lbs/h)	80	100	275	100	125	325
Lbs - Total Daily Food Production (lbs)	200	250	400	200	250	400
S _t - Percentage of Time in Steam Mode	50%	50%	50%	50%	50%	50%
I _{sb} & I _{sq} - Steam Mode Idle Energy Rate (kW)	45,000	60,000	80,000	Application	Application	Application
PC _{sb} & PC _{sq} - Steam Mode Prod. Capacity (lbs/h)	100	150	350	120	200	400
Heat _c - Convection Heat to Food (Btu/lb)	250	250	250	250	250	250
Eff _{cb} & Eff _{cq} - Convection Mode Cooking Efficiency	35%	35%	35%	Application	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000	100,000	100,000
Heat _s - Steam Heat to Food (Btu/lb)	105	105	105	105	105	105
Eff _{sb} & Eff _{sq} - Steam Mode Cooking Efficiency	20%	20%	20%	Application	Application	Application

Table 3: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Electric and Gas Convection Ovens, Gas Conveyor and Rack Ovens, Steamers, Fryers, and Griddles

The measurement of energy savings for these measures are based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

Energy Savings (kWh/yr or Therms/yr) = D * (E_p + E_i + E_c)

Peak Demand Savings (kW) = kWh Savings / (D * H)

Preheat Savings[†]: E_p = P * (PE_b - PE_q)

Idle Savings[†]: E_i = (I_b - I_q) * ((H - (P*P_t)) - (I_b/PC_b - I_q/PC_q) * Lbs)

Cooking Savings: E_c = Lbs * Heat * (1/Eff_b - 1/Eff_q) / C

† – For gas equipment, convert these intermediate values to therms by dividing the result by 100,000 Btu/therm

Definition of Variables

(See tables of values below for more information)⁵⁴

D = Operating Days per Year

P = Number of Preheats per Day

PE_b = Baseline Equipment Preheat Energy

PE_q = Qualifying Equipment Preheat Energy

I_b = Baseline Equipment Idle Energy Rate

I_q = Qualifying Equipment Idle Energy Rate

H = Daily Operating Hours

P_t = Preheat Duration

PC_b = Baseline Equipment Production Capacity

PC_q = Qualifying Equipment Production Capacity

Lbs = Total Daily Food Production

Heat = Heat to Food

Eff_b = Baseline Equipment Convection Mode Cooking Efficiency

Eff_q = Qualifying Equipment Convection Mode Cooking Efficiency

⁵⁴ Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission. Values for Tables 1 and 2 from PG&E Work Paper PGEFST100, "Commercial Combination Ovens/Steam –Electric and Gas," Revision 6, 2016.

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

C = Conversion Factor from Btu to kWh or Therms

Summary of Inputs

Table 1: Electric Convection Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Full Size</i>	<i>Half Size</i>	<i>Full Size</i>	<i>Half Size</i>
D - Operating Days per Year	Table 11	Table 11	Table 11	Table 11
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.50	1.00	1.00	0.90
I _b & I _q - Idle Energy Rate (kW)	2.00	1.50	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	70	45	82	53
Lbs - Total Daily Food Production (lbs)	100	100	100	100
Heat - Heat to Food (Btu/lb)	250	250	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	65%	65%	Application	Application
C - Btu/kWh	3,412	3,412	3,412	3,412

Source: PGECOFST101 R6, "Commercial Convection Oven – Electric and Gas," 2016.

Table 2: Gas Convection Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Full Size</i>	<i>Half Size</i>	<i>Full Size</i>	<i>Half Size</i>
D - Operating Days per Year	Table 11	Table 11	Table 11	Table 11
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	19,000	13,000	11,000	7,500
I _b & I _q - Idle Energy Rate (Btu/h)	18,000	12,000	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	70	45	83	55
Lbs - Total Daily Food Production (lbs)	100	100	100	100
Heat - Heat to Food (Btu/lb)	250	250	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	30%	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000

Source: PGECOFST101 R6, "Commercial Convection Oven – Electric and Gas," 2016.

Table 3: Gas Conveyor Ovens		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	35,000	18,000
I _b & I _q - Idle Energy Rate (Btu/hr)	70,000	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	114	167
Lbs - Total Daily Food Production (lbs)	190	190
Heat - Heat to Food (Btu/lb)	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	20%	Application
C - Btu/Therm	100,000	100,000

Source: PGECOFST117 R5, “Commercial Conveyor Oven– Gas,” 2014.

Table 4: Gas Rack Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Double Rack</i>	<i>Single Rack</i>	<i>Double Rack</i>	<i>Single Rack</i>
D - Operating Days per Year	Table 11	Table 11	Table 5	Table 5
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	100,000	50,000	85,000	44,000
I _b & I _q - Idle Energy Rate (Btu/h)	65,000	43,000	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 5	Table 5
P _t - Preheat Duration (hrs)	0.33	0.33	0.33	0.33
PC _b & PC _q - Production Capacity (lbs/hr)	250	130	280	140
Lbs - Total Daily Food Production (lbs)	1200	600	1200	600
Heat - Heat to Food (Btu/lb)	235	235	235	235
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	30%	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000

Source: PGECOFST109, “Commercial Rack Oven– Gas,” 2016.

Table 5: Electric Steamers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.50	1.50
I _b & I _q - Idle Energy Rate (kW)	0.167 x No. of Pans	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	11.7 x No. of Pans	14.7 x No. of Pans
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	105	105
Eff _b & Eff _q - Heavy Load Cooking Efficiency	26%	Application
C - Btu/kWh	3,412	3,412

Source: PGECOFST104 R6, “Commercial Steam Cooker – Electric and Gas,” 2016.

Table 6: Gas Steamers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	20,000	9,000
I _b & I _q - Idle Energy Rate (Btu/h)	2,500 x No. of Pans	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	23.3 x No. of Pans	20.8 x No. of Pans
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	105	105
Eff _b & Eff _q - Heavy Load Cooking Efficiency	15%	Application
C - Btu/Therm	100,000	100,000

Source: PGECOFST104 R6, “Commercial Steam Cooker – Electric and Gas,” 2016.

Table 7: Electric Fryers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	2.40	1.90
I _b & I _q - Idle Energy Rate (kW)	1.2	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	71	71
Lbs - Total Daily Food Production (lbs)	150	150
Heat - Heat to Food (Btu/lb)	570	570
Eff _b & Eff _q - Heavy Load Cooking Efficiency	75%	Application
C - Btu/kWh	3,412	3,412

Source: PGECOFST102 R6, "Commercial Fryer – Electric and Gas," 2016.

Table 8: Gas Fryers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	18,500	16,000
I _b & I _q - Idle Energy Rate (Btu/h)	17,000	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	75	75
Lbs - Total Daily Food Production (lbs)	150	150
Heat - Heat to Food (Btu/lb)	570	570
Eff _b & Eff _q - Heavy Load Cooking Efficiency	35%	Application
C - Btu/Therm	100,000	100,000

Source: PGECOFST102 R6, "Commercial Fryer – Electric and Gas," 2016.

Table 9: Electric Griddles		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.3 x Griddle Width (ft)	0.7 x Griddle Width (ft)
I _b & I _q - Idle Energy Rate (kW)	0.8 x Griddle Width (ft)	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	11.7 x Griddle Width (ft)	13.3 x Griddle Width (ft)
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	475	475
Eff _b & Eff _q - Heavy Load Cooking Efficiency	60%	Application
C - Btu/kWh	3,412	3,412

Source: PGECOFST103 R7, "Commercial Griddle – Electric and Gas," 2016.

Table 10: Gas Griddles		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	7,000 x Griddle Width (ft)	5,000 x Griddle Width (ft)
I _b & I _q - Idle Energy Rate (Btu/h)	7,000 x Griddle Width (ft)	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	8.3 x Griddle Width (ft)	15 x Griddle Width (ft)
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	475	475
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	Application
C - Btu/Therm	100,000	100,000

Source: PGECOFST103 R7, "Commercial Griddle – Electric and Gas," 2016.

Table 11: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Insulated Food Holding Cabinets

The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

Energy Savings (kWh/yr) = D * H * (I_b - I_q)

Peak Demand Savings (kW) = I_b - I_q

Definition of Variables

(See tables of values below for more information)⁵⁵

D = Operating Days per Year

H = Daily Operating Hours

I_b = Baseline Equipment Idle Energy Rate

I_q = Qualifying Equipment Idle Energy Rate

Summary of Inputs

Table 1: Insulated Food Holding Cabinets						
Variable	Baseline			Qualifying		
	<i>Full Size</i>	<i>3/4 Size</i>	<i>1/2 Size</i>	<i>Full Size</i>	<i>3/4 Size</i>	<i>1/2 Size</i>
D - Operating Days per Year	Table 2	Table 2	Table 2	Table 2	Table 2	Table 2
I _b & I _q - Idle Energy Rate (kW)	1.00	0.69	0.38	Application	Application	Application
H - Operating Hours per Day	Table 2	Table 2	Table 2	Table 2	Table 2	Table 2

Source: PGECOFST105 R5, "Insulated Holding Cabinet – Electric," 2016.

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Underline

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

⁵⁵ Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.

Table 2: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Commercial Dishwashers

This measure is applicable to replacement of existing dishwashers with energy efficient under counter, door type, single-rack and multi-rack conveyor machines testing in accordance with NSF/ANSI 3-2007, ASTM F1696, and ASTM F1920 standards. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

$$\text{Energy Savings (kWh/yr or Therms/yr)} = E_{\text{Build}} + E_{\text{Boost}} + E_{\text{Idle}}$$

$$\text{Peak Demand Savings (kW)} = \text{kWh Savings}/8760$$

Note: Depending on water heating system configuration (e.g. gas building water heater with electric booster water heater), annual energy savings may be reported in both therms and kWh.

Definition of Variables

EER	Fixed	9.0	Average based on custom applications for the NJCEP C&I Program in 2010
Usage	Fixed	8,760	365 days/year, 24 hours/day

(See tables below for more information)⁵⁶

E_{Build} = Annual Building Water Heater Energy Savings, in kWh or Therms (from tables below)

E_{Boost} = Annual Booster Water Heater Energy Savings, in kWh or Therms (from tables below)

E_{Idle} = Annual Dishwasher Idle Energy Savings, in kWh (from tables below)

8760 = Hours per Year

Summary of Inputs

⁵⁶ Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission and from the Savings Calculator for ENERGY STAR Qualified Commercial Kitchen Equipment.

Table 1: Low Temperature Dishwasher Savings					
Dishwasher Type	Electric Building Water Heater Savings (kWh)	Gas Building Water Heater Savings (Therms)	Electric Booster Water Heater Savings (kWh)	Gas Booster Water Heater Savings (Therms)	Idle Energy Savings (kWh)
Under Counter	1,213	56.2	0	0.0	0
Door Type	12,135	562.1	0	0.0	0
Single Tank Conveyor	11,384	527.3	0	0.0	0
Multi Tank Conveyor	17,465	809.0	0	0.0	0

Table 2: High Temperature Dishwasher Savings					
Dishwasher Type	Electric Building Water Heater Savings (kWh)	Gas Building Water Heater Savings (Therms)	Electric Booster Water Heater Savings (kWh)	Gas Booster Water Heater Savings (Therms)	Idle Energy Savings (kWh)
Under Counter	4,754	220.2	2,717	110.1	0
Door Type	8,875	411.1	5,071	205.5	198
Single Tank Conveyor	11,126	515.3	6,358	257.7	1,752
Multi Tank Conveyor	21,734	1,006.7	12,419	503.3	0

Formatted: Font: Italic

Formatted: Normal, Space Before: 6 pt, After: 6 pt

Commercial Refrigerators and Freezers

This measure is applicable to replacement of existing commercial grade refrigerators and freezers with energy efficient glass and solid door units complying with ANSI/ASHRAE Standard 72-2005, Method of Testing Commercial Refrigerators and Freezers. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

Annual Algorithms

$$\text{Energy Savings (kWh/yr)} = D * (E_b - E_q)$$

$$\text{Peak Demand Savings (kW)} = \text{kWh Savings} / (D * H)$$

Definition of Variables

(See tables below for more information)⁵⁷

D = Operating Days per Year (assume 365)

H = Daily Operating Hours (assume 24)

E_b = Daily kWh Consumption of Baseline Equipment (from Table 1 below)

E_q = Daily kWh Consumption of Qualifying Equipment (from Application)

Table 1: Baseline Equipment Daily kWh Consumption	
Proposed Equipment Type	kWh Consumption (V = Unit Volume in ft ³)
Glass Door Freezer	0.75V + 4.1
Glass Door Refrigerator	0.12V + 3.34
Solid Door Freezer	0.4V + 1.38
Solid Door Refrigerator	0.1V + 2.04

Summary of Inputs

Table 1: Baseline Equipment Daily kWh Consumption	
Proposed Equipment Type	kWh Consumption (V = Unit Volume in ft ³)
Glass Door Freezer	0.75V + 4.1
Glass Door Refrigerator	0.12V + 3.34
Solid Door Freezer	0.4V + 1.38
Solid Door Refrigerator	0.1V + 2.04

⁵⁷ Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.

Sources:

~~Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.~~

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: No underline

Commercial Ice Machines

This measure is applicable to replacement of existing ice makers with energy efficient, air-cooled ice machines tested in accordance with ARI Standard 810. ~~The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.~~

Formatted: Heading 3, Space After: 0 pt, Line spacing: single

Formatted: Space Before: 6 pt, After: 6 pt, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Algorithms

~~Annual Energy Savings (kWh) = D * DC * (IHR/100) * (E_b - E_q)~~

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

~~Demand Savings (kW) = kWh Savings / (D * 24 * DC)~~

Definition of Variables

- ~~D = Operating Days per Year (assume 365)~~
- ~~DC = Duty Cycle, defined as Ice Harvest Rate/Actual Daily Ice Production (assume 75%)~~
- ~~IHR = Proposed Equipment Ice Harvest Rate in lbs/day (from Application)~~
- ~~E_b = kWh Consumption of Baseline Equipment in kWh/100 lbs (from Table 1 below)~~
- ~~E_q = kWh Consumption of Qualifying Equipment in kWh/100 lbs (from Application)~~
- ~~24 = Hours per Day~~

Table 1: Baseline Energy Consumption	
Ice Harvest Rate (lbs/day)	Baseline Energy Consumption (kWh/100 lbs)
0-100	18.0
101-200	16.0
201-300	11.0
301-400	8.5
401-500	7.6
501-1000	6.9
1001-1500	6.4
1501	6.1

Formatted: Keep with next, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: No underline

Sources:

~~Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website,~~

~~www.fishnick.com, by Fisher Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.~~

Commercial Dishwashers

~~This measure is applicable to replacement of existing dishwashers with energy efficient under counter, door type, single rack and multi rack conveyor machines testing in accordance with NSF/ANSI 3-2007, ASTM F1696, and ASTM F1920 standards. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.~~

Algorithms

$$\text{Annual Energy Savings (kWh or Therms)} = E_{\text{Build}} + E_{\text{Boost}} + E_{\text{Idle}}/\text{yr} = D * DC * (\text{IHR}/100) * (E_b - E_q)$$

$$\text{Peak Demand Savings (kW)} = \text{kWh Savings} / (D * 24 * DC)$$

Definition of Variables

$$\text{Demand Savings (kW)} = \text{kWh Savings}/8760$$

~~Note: Depending on water heating system configuration (e.g. gas building water heater with electric booster water heater), annual energy savings may be reported in both therms and kWh.~~

Definition of Variables

~~E_{Build} = Annual Building Water Heater Energy Savings, in kWh or Therms (from tables below)~~

~~E_{Boost} = Annual Booster Water Heater Energy Savings, in kWh or Therms (See tables below for more information)⁵⁸~~

~~D = Operating Days per Year (assume 365)~~

~~DC = Duty Cycle, defined as Ice Harvest Rate/Actual Daily Ice Production (assume 75%)~~

~~IHR = Proposed Equipment Ice Harvest Rate in lbs/day (from Application)~~

~~E_b = kWh Consumption of Baseline Equipment in kWh/100 lbs (from tables Table 1 below)~~

⁵⁸ ~~Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.~~

Formatted: Heading 4

Formatted: Indent: First line: 0.25"

Formatted: Not Superscript/ Subscript

Formatted: Don't keep with next, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Indent: First line: 0.25"

Formatted: Heading 4

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

$E_{idle} = \text{Annual Dishwasher Idle Energy Savings, } E_{eq} = \text{kWh Consumption of Qualifying Equipment in kWh/100 lbs (from tables below Application)}$
 $8760 \cdot 24 = \text{Hours per Year/Day}$

Formatted: Not Superscript/ Subscript

Table 1: Low Temperature Dishwasher Savings					
Dishwasher Type	Electric Building Water Heater Savings (kWh)	Gas Building Water Heater Savings (Therms)	Electric Booster Water Heater Savings (kWh)	Gas Booster Water Heater Savings (Therms)	Idle Energy Savings (kWh)
Under Counter	1,213	56.2	0	0.0	0
Door Type	12,135	562.1	0	0.0	0
Single Tank Conveyor	11,384	527.3	0	0.0	0
Multi Tank Conveyor	17,465	809.0	0	0.0	0

Table 2: High Temperature Dishwasher Savings					
Dishwasher Type	Electric Building Water Heater Savings (kWh)	Gas Building Water Heater Savings (Therms)	Electric Booster Water Heater Savings (kWh)	Gas Booster Water Heater Savings (Therms)	Idle Energy Savings (kWh)
Under Counter	4,754	220.2	2,717	110.1	0
Door Type	8,875	411.1	5,071	205.5	198
Single Tank Conveyor	11,126	515.3	6,358	257.7	1,752
Multi Tank Conveyor	21,734	1,006.7	12,419	503.3	0

Summary of Inputs

Table 1: Baseline Energy Consumption	
Ice Harvest Rate (lbs/day)	Baseline Energy Consumption (kWh/100 lbs)
0-100	18.0
101-200	16.0
201-300	11.0
301-400	8.5
401-500	7.6
501-1000	6.9
1001-1500	6.4
1501	6.1

Sources:

Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher-Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission and from the Savings Calculator for ENERGY STAR Qualified Commercial Kitchen Equipment.

Formatted: Indent: Left: 0.5", Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: No underline

C&I ~~Construction~~ Gas Protocols

~~For The following~~ measures installed as part of the Direct Install program, different baselines will be utilized to estimate savings as defined further~~are outlined~~ in the Direct Install~~this~~ section of these Protocols.

The following fuel conversions will be used to calculate energy savings for propane and oil equipment for all eligible C&I programs including C&I Construction, Direct Install, and Pay for Performance.

1 therm of gas = 1.087 gal of propane = 0.721 gal of #2 oil

1 therm = 100,000 Btu

1 gal of propane = 92,000 Btu

1 gal of #2 oil = 138,700 Btu

: Gas Chillers, Gas Fired Dessicants, Water Heating Equipment, Space Heating Equipment, and Fuel Use Economizers.

Gas Chillers

The measurement of energy savings for C&I gas fired chillers and chiller heaters is based on algorithms with key variables (i.e., Equivalent Full Load Hours, Vacuum Boiler Efficiency, Input Rating, Coincidence Factor) provided by manufacturer data or measured through existing end use metering of a sample of facilities captured on the application form or from manufacturer's data sheets and collaborative/utility studies.

For certain fixed components, studies and surveys developed by the utilities in the State or based on a review of manufacturer's data, other utilities, regulatory commissions or consultants' reports will be used to update the values for future filings.

Algorithms

Algorithms

Winter Gas Savings (MMBtu/yr) = $(VBE_q - BE_b) / VBE_q \times IR \times EFLH_c$

~~Electric Demand~~Energy Savings (kWh/yr) = Tons $\times (kW/Ton_b - kW/Ton_{gc}) \times CF_c$
EFLH_c

~~Electric Energy~~ Savings = Tons $\times (kW/Ton_b - kW/Ton_{gc}) \times EFLH_c$

Summer Gas Usage (MMBtu/yr) = MMBtu Output Capacity / COP $\times EFLH_c$

Formatted: Normal, Space Before: 6 pt, After: 6 pt

Formatted: Heading 3

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Underline

Formatted: Underline, (none)

Formatted: Indent: First line: 0.25"

Formatted: Underline

Formatted: Normal, Level 4, Keep with next

Formatted: (none)

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Font: Italic

Formatted: Indent: First line: 0.25"

Net Energy Savings = ~~Electric~~(kWh/yr) = Energy Savings + Winter Gas Savings – Summer Gas Usage

Formatted: Indent: First line: 0.25"

$$\text{Peak Demand Savings (kW)} = \text{Tons} * (\text{kW/Ton}_b - \text{kW/Ton}_{gc}) * \text{CF}$$

Definition of Terms

VBE_q ____ = Vacuum Boiler Efficiency

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

BE_b ____ = Efficiency of the baseline gas boiler

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

IR ____ = Input Rating = ~~Therms~~MMBtu/hour

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Tons ____ = The rated capacity of the chiller (in tons) at site design conditions accepted by the program-

Formatted: Indent: Left: 0.25", Hanging: 0.75", Space Before: 3 pt, After: 3 pt

kW/Ton_b _ = The baseline efficiency for electric chillers, as shown in the Gas Chiller Verification Summary table below.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

kW/Ton_{gc} = Parasitic electrical requirement for gas chiller.

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

COP = Efficiency of the gas chiller

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

MMBtu Output Capacity = Cooling Capacity of gas chiller in MMBtu.

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

CF = Coincidence Factor. -This value represents the percentage of the total load that is on during electric system peak.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

~~EFL~~EFLH_c = Equivalent Full Load Hours. -This represents a measure of chiller use by cooling season.

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

~~Gas Chillers~~

Formatted: Heading 3

Summary of Inputs

Gas Chillers

Formatted: Table Caption, Left, Don't keep with next

Component	Type	Value	Source
VBE _q	Variable		Rebate Application or Manufacturer Data

Formatted: Table Header, Left

Formatted: Table Cells

Component	Type	Value	Source
BE _b	Fixed	75% 80% Et	ASHRAE 90.1-2013 Table 6.8.1-6 Assumes a baseline hot water boiler with rated input >300 MBh and ≤ 2,500 MBh.
IR	Variable		Rebate-Application or Manufacturer Data
Tons	Variable <u>Rated Capacity, Tons</u>		Rebate-Application
MMBtu	Variable		Rebate-Application
kW/Ton _b	Fixed	<100 tons 1.25 kW/ton ▲ 100 to < 150 tons 0.703 kW/ton ▲ 150 to <300 tons: 0.634 kW/Ton ▲ 300 tons or more: 0.577 kW/ton	Collaborative agreement and C/I baseline study Assumes new electric chiller baseline using air cooled unit for chillers less than 100 tons; water cooled for chillers greater than 100 tons
kW/Ton _{gc}	Variable		Manufacturer Data
COP	Variable		Manufacturer Data
CF	Fixed	67%	Engineering estimate
EFLHEFLH_g	Fixed <u>Variable</u>	1,360 <u>See Table Below</u>	JCP&L Measured <u>data</u> ⁵⁹

Formatted: Table Header, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Subscript

Formatted: Table Cells

~~Variable data will be captured on the application form or from manufacturer's data sheets and collaborative/utility studies.~~

⁵⁹ ~~Results reflect metered use from 1995—1999.~~

~~For certain fixed components, studies and surveys developed by the utilities in the State or based on a review of manufacturer's data, other utilities, regulatory commissions or consultants' reports will be used to update the values for future filings.~~

Formatted: Space Before: 6 pt, After: 6 pt

EFLH_c Table

<u>Facility Type</u>	<u>Cooling EFLH_c</u>
<u>Assembly</u>	<u>669</u>
<u>Auto repair</u>	<u>426</u>
<u>Dormitory</u>	<u>800</u>
<u>Hospital</u>	<u>1424</u>
<u>Light industrial</u>	<u>549</u>
<u>Lodging – Hotel</u>	<u>2918</u>
<u>Lodging – Motel</u>	<u>1233</u>
<u>Office – large</u>	<u>720</u>
<u>Office – small</u>	<u>955</u>
<u>Other</u>	<u>736</u>
<u>Religious worship</u>	<u>279</u>
<u>Restaurant – fast food</u>	<u>645</u>
<u>Restaurant – full service</u>	<u>574</u>
<u>Retail – big box</u>	<u>1279</u>
<u>Retail – grocery</u>	<u>1279</u>
<u>Retail – large</u>	<u>882</u>
<u>Retail – large</u>	<u>1068</u>
<u>School – community college</u>	<u>846</u>
<u>School – postsecondary</u>	<u>1208</u>
<u>School – primary</u>	<u>394</u>
<u>School – secondary</u>	<u>466</u>
<u>Warehouse</u>	<u>400</u>

Multi-family EFLH by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Cooling</u>	<u>507</u>	<u>550</u>	<u>562</u>
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Cooling</u>	<u>793</u>	<u>843</u>	<u>954</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Sources

1. ASHRAE Standards 90.1-2013, *Energy Standard for Buildings Except Low Rise Residential Buildings*; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>. Table 6.8.1 – 6
2. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.

Gas Fired ~~Desiccants~~ Desiccants

Gas-fired desiccant systems employ a desiccant wheel (a rotating disk filled with a dry desiccant such as silica gel, titanium gel, or dry lithium chloride) which adsorbs outside air moisture, reducing the air's latent heat content. This air is then conditioned by the building's cooling system, before being delivered to the occupied space. By reducing the relative humidity of the air, the operating temperature of the building can be increased, as comfort levels are maintained at higher temperatures when air moisture content is decreased. Electric savings are realized from a reduction in the required cooling load as a result of decreased humidity.

In order to maintain the usefulness of the desiccant (to keep it dry) hot air must be passed through the desiccant that has been used to remove moisture from the outside air. To supply this hot air, a gas-fired heater is employed to heat "regeneration" air, which picks up moisture from the saturated desiccant and exhausts it to the outside. As a result, in addition to electric benefits, these systems will also incur a natural gas penalty.

Electric savings and natural gas consumption will vary significantly from system to system depending on regional temperature and humidity, facility type, occupancy, site processes, desiccant system design parameters, ventilation requirements and cooling load and system specifications. Due to the multitude of site and equipment specific factors, along with the relative infrequency of these systems, gas-fired desiccant systems will be treated on a case-by-case basis.

Gas Booster Water Heaters

~~Gas Booster Water Heaters~~

C&I gas booster water heaters are substitutes for electric water heaters. The measurement of energy savings is based on engineering algorithms with key variables (i.e., Input Rating Coincidence Factor, Equivalent Full Load Hours) provided by manufacturer data or measured through existing end-use metering of a sample of facilities.

Algorithms

$$\text{Energy Savings (kWh/yr)} = \text{IR} * \text{EFF}/3,412 * \text{EFLH}$$

$$\text{Peak Demand Savings (kW)} = \text{IR} * \text{EFF}/3,412 * \text{CF}$$

$$\text{Energy Savings (kWh)} = \text{IR} * \text{EFF}/3,412 * \text{EFLH} * \text{CF}$$

$$\text{Gas Usage Increase (MMBtu/yr)} = \text{IR} * \text{EFLH}$$

Formatted: Page break before

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font color: Auto

Formatted: Heading 3, Left, Don't keep with next

Formatted: Table Caption

Formatted: Space After: 3 pt

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Net Energy Savings (kWh/yr) = Electric Energy Savings – Gas Usage Increase/3,412

Formatted: Indent: First line: 0.25"

Definition of Variables

(Calculated in MMBtu)

Definition of Variables

Formatted: Underline, (none)

IR ___ = Input Rating in ~~Btu~~MMBtu/hr

Formatted: Normal, Level 4, Keep with next

EFF-__ = Efficiency

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

CF ___ = Coincidence Factor

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

EFLH _ = Equivalent Full Load Hours

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

The 3412 used in the denominator is used to convert Btus to kWh.

Formatted: Indent: First line: 0.25", Space Before: 6 pt, After: 6 pt

Summary of Inputs

Gas Booster Water Heaters

Formatted: Table Caption

~~Gas Booster Water Heaters~~

Formatted: Heading 3, Left, Don't keep with next

Component	Type	Value	Source
IR	Variable		Application Form or Manufacturer Data
CF	Fixed	30%	Summit Blue NJ Market Assessment
EFLH	Fixed	1,000	PSE&G
EFF	Variable		Application Form or Manufacturer Data

Formatted: Table Header, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Stand Alone Storage Water Heaters

This prescriptive measure ~~targets solely the use of smaller scale domestic~~ is intended for stand alone storage water heaters (50 gallons or less per unit) installed in all commercial facilities. ~~Larger gas~~ The savings algorithms are based on installed equipment specifications and data from the Commercial Building Energy Consumption Survey (CBECS).

Baseline efficiencies are set by current and previous equipment performance standards. In New Jersey ASHRAE 90.1 defines the commercial energy code requirements. For new buildings, ASHRAE 90.1-2013 standards apply, and for existing buildings, ASHRAE 90.1-2007 standards are assumed.

~~Note, that for stand alone storage~~ water heaters ~~are treated under the custom measure path.~~ The measurement with a rated input capacity greater than 75 kBtu/hr, equipment standards are defined in terms of thermal efficiency. Equipment below this input capacity is rated in terms of energy savings for C&I gas water heaters is based on algorithms with key variables (i.e., energy factor) provided by manufacturer data. Energy factor is determined on a 24 hour basis and includes standby or storage loss effects, while thermal efficiency does not. Therefore, if the equipment is large enough to be rated in terms of thermal efficiency, a percent standby loss factor must be included in the calculation as shown in the algorithms.

Formatted: Normal, Space Before: 6 pt, After: 6 pt

Algorithms

Formatted: Normal

Formatted: Font: Not Bold

Formatted: Normal

Gas Algorithms

$$\text{Fuel Savings} = ((\text{EFF}_q - (\text{MMBtu}/\text{yr})) / \text{EFF}_q) \times \text{SLF}^{60} * \text{Energy Use Density} \times (\text{Area}) / 1000 \text{ kBtu/MMBtu}$$

Formatted: Indent: Left: 0.25"

Formatted: Font: 12 pt, Subscript

where,

$$\text{SLF} = (\text{SL}_b - \text{SL}_q) / \text{Cap}_q$$

Definition of Variables

Formatted: English (U.S.)

EFF_q = Efficiency of the qualifying ~~energy efficient~~ water heater.

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

EFF_b = Efficiency of the baseline water heater, commercial grade.

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

⁶⁰ Standby losses only apply if the stand alone storage water heater is rated for more than 75 kBtu/hr

EF_b = Energy Factor of the baseline water heater, commercial grade.

Energy Use Density = Annual baseline water heater energy use per square foot of commercial space served (MMBtu/sq.ft./yr)

Area = Square feet of building area served by the water heater

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

SLF = Standby loss factor for savings of qualifying water heater over baseline

SL_{b or q} = Standby losses in kBtu/hr of the baseline and qualifying storage water heater respectively. The baseline standby losses is calculated assuming the baseline water heater has the same input capacity rating as the qualifying unit's input capacity using ASHRAE equipment performance standards. The qualifying unit's standby losses are available on the AHRI certificate provided with the application.

Cap_q = Rated input capacity of the qualifying water heater

Summary of Inputs

Stand Alone Storage Water Heaters Heater Assumptions

Formatted: Table Caption, Left, Don't keep with next

Component	Type	Value	Source
EFF _q	Variable		Application
EFF _b	Fixed	<50 gal or <75,000 BtuH: EF >50 gal or >75,000 BtuH: TE EF = Energy Factor TE = Thermal Efficiency	From ASHRAE 90.1-2007
Energy Use Density	Variable	See Table Below	4
Fluid Capacity	Variable		Application

Formatted: Table Header, Left, Don't keep with next

Formatted Table

Formatted: Table Header, Left

Formatted: Table Cells

EFF _b	Variable	See Table Below	1, 2
EF _b	Variable	See Table Below	1, 2
Energy Use Density	Variable	See Table Below	3
Area	Variable		Application
Cap _q	Variable		Application
SL _b	Variable	See Table Below	1 & Application
SL _q	Variable		Application

Efficiency of Baseline Stand Alone Storage Water Heaters—Existing Buildings

Formatted: Table Caption, Left, No page break before

ASHRAE 90.1-2007			
Equipment Type	Size Category (Input)	Subcategory or Rating Condition	Performance Required ^a
Gas Storage Water Heaters	≤ 75,000 BtuH	≥ 20 gal	0.62—0.0019V EF

Gas Storage Water Heaters	>75,000 BtuH	<4,000 (BtuH)/gal	80% Et (Q/800 + 110 √V) SL, BtuH
Gas Instantaneous Water Heaters	>50,000 BtuH and <200,000 BtuH	≥4,000 (BtuH)/gal and <2 gal	0.62 – 0.0019V EF
Gas Instantaneous Water Heaters	≥200,000 BtuH ^b	≥4,000 (BtuH)/gal and <10 gal	80% E _t
Gas Instantaneous Water Heaters	≥200,000 BtuH	≥4,000 (BtuH)/gal and ≥10 gal	80% Et (Q/800 + 110 √V) SL, BtuH

ASHRAE 90.1-2007 and 2013^a

<u>Equipment Type</u>	<u>Size Category (Input)</u>	<u>Existing Building Baseline Efficiency (ASHRAE 90.1-2007)</u>	<u>New Building Baseline Efficiency (ASHRAE 90.1-2013)</u>
Gas Storage Water Heaters	<75 kBtu/hr	EF = 0.62 – 0.0019 × V	EF = 0.67 – 0.0005 × V
Gas Storage Water Heaters	≥75 kBtu/hr	TE = 0.80 SL = (Cap _g / 0.8 + 110 × √V) / 1000	TE = 0.80 SL = (Cap _g / 0.799 + 16.6 × √V) / 1000

a – ~~Energy~~ EF is energy factor (EF) and TE is thermal efficiency (Et) are minimum requirements, while standby loss (SL) is maximum BtuH based on a 70°F temperature difference between stored water and ambient requirements. In the EF equation, V, V is the volume of the installed storage water heater, and Cap_g is the rated volume in gallons. In the SL equation, V is the rated volume in gallons and Q is the nameplate input rate in BtuH.

b – Instantaneous water heaters with input rates below 200,000 BtuH must comply with these requirements if the water heater is designed to heat water to temperatures of 180°F or higher.
of the proposed storage

~~Water Heaters~~ – New Construction

ASHRAE 90.1-2013 (most current requirement as of February 2016)

Equipment Type	Size Category (Input)	Subcategory or Rating Condition	Performance Required^a
Gas Storage Water Heaters	≤75,000 BtuH	≥20 gal	0.67 – 0.0005V EF
Gas Storage Water Heaters	>75,000 BtuH	<4,000 (BtuH)/gal	80% Et (Q/799 + 16.6 √V) SL, BtuH
Gas Instantaneous Water Heaters	>50,000 BtuH and <200,000 BtuH	≥4,000 (BtuH)/gal and <2 gal	0.62 – 0.0005V EF

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: Not Bold

Gas Instantaneous Water Heaters	$\geq 200,000 \text{ BtuH}^b$	$\geq 4,000$ (BtuH)/gal and < 10 gal	$80\% E_t$
Gas Instantaneous Water Heaters	$\geq 200,000 \text{ BtuH}$	$\geq 4,000$ (BtuH)/gal and ≥ 10 gal	$80\% E_t (Q/799 + 16.6 \sqrt{V})$ SL, BtuH

a—Energy factor (EF) and thermal efficiency (E_t) are minimum requirements, while standby loss (SL) is maximum BtuH based on a 70°F temperature difference between stored water and ambient requirements. In the EF equation, V is the rated volume in gallons. In the SL equation, V is the rated volume in gallons and Q is the nameplate input rate in BtuH.

b—Instantaneous water heaters with input rates below 200,000 BtuH must comply with these requirements if the water heater is designed to heat water to temperatures of 180°F or higher.

- Formatted: Font: 10 pt
- Formatted: Font: 10 pt
- Formatted: Font: Bold
- Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Energy Use Density ~~Lookup~~Look-up Table

Formatted: Table Caption

<u>Building Type</u>	<u>Energy Use Density (kBtu/SF/yr)</u>
<u>Education</u>	<u>7.0</u>
<u>Food sales</u>	<u>4.4</u>
<u>Food service</u>	<u>39.2</u>
<u>Health care</u>	<u>23.7</u>
<u>Inpatient</u>	<u>34.3</u>
<u>Outpatient</u>	<u>3.9</u>
<u>Lodging</u>	<u>26.5</u>
<u>Retail (other than mall)</u>	<u>2.5</u>
<u>Enclosed and strip malls</u>	<u>14.1</u>
<u>Office</u>	<u>4.8</u>
<u>Public assembly</u>	<u>2.1</u>
<u>Public order and safety</u>	<u>21.4</u>
<u>Religious worship</u>	<u>0.9</u>
<u>Service</u>	<u>15</u>
<u>Warehouse and storage</u>	<u>2.9</u>
<u>Other</u>	<u>2.3</u>

Example: If a water heater of 150 kBtu/hr input capacity and 100 gallons storage capacity is installed in an existing building, the baseline standby losses would be calculated as $SL = (150 \text{ kBtu/hr} / 0.8 + 110 \times \sqrt{100}) / 1000 = 1.29 \text{ kBtu/hr}$. If the proposed equipment's standby losses were rated for 1.0 kBtu/hr, the standby loss factor for savings would be $SLF = (1.29 - 1.0) / 150 = 0.0019$.

In the above example, if the unit was rated for 96% thermal efficiency, and installed in an office building space of 10,000 ft², the annual energy savings would be $((1 - 0.8/0.96) + 0.0019) \times 4.8 \times 10000 / 1000 = 8.1 \text{ MMBtus/yr}$

Building Type	Energy Use Density (kBtu/SF/yr)
Education	5.2
Food Sales	3.2
Food Service	40.0
Health Care	28.9
- Inpatient	39.4
- Outpatient	3.5
Lodging	29.2
Retail (Other Than Mall)	1.0
Office	1.6
Public Assembly	0.9
Public Order and Safety	15.1
Religious Worship	0.9
Service	0.9
Warehouse and Storage	0.7
Other	1.7

Sources

Sources:

3. ASHRAE Standards 90.1-2007, Energy Standard for Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
4. ASHRAE Standards 90.1-2013, Energy Standard for Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
- 4.5. Energy Information Administration, Commercial Building Energy Consumption Survey--2003, Data, 2012; available at: <https://www.eia.gov/consumption/commercial/data/2012/c&e/cfm/e7.cfm>.

Formatted: Sources, No bullets or numbering

Instantaneous Gas Water Heaters

This prescriptive measure is intended for instantaneous water heaters installed in commercial facilities. This measure assumes that the baseline water heater is either a code stand alone storage water heater, or a code instantaneous water heater. The savings algorithms are based on installed equipment specifications and data from the Commercial Building Energy Consumption Survey (CBECS).

Baseline efficiencies are set by current and previous equipment performance standards. In New Jersey ASHRAE 90.1 defines the commercial energy code requirements. For new buildings, ASHRAE 90.1-2013 standards apply, and for existing buildings, ASHRAE 90.1-2007 standards are assumed.

If the qualifying instantaneous water heater is greater than 200 kBtu/hr and replacing a stand alone storage water heater, use a baseline storage water heater efficiency greater than 75 kBtu/hr. Similarly, if the qualifying instantaneous water heater is less than 200 kBtu/hr, and replacing a stand alone storage water heater, use an efficiency for equipment less than 75 kBtu/hr.

Note, that for stand alone storage tank water heaters rated above 75 kBtu/hr, and instantaneous water heaters above 200 kBtu/hr, equipment standards are defined in terms of thermal efficiency. Equipment below these levels is rated in terms of energy factor. Energy factor is determined on a 24 hour basis and includes standby or storage loss effects, while thermal efficiency does not. Therefore, if the equipment is large enough to be rated in terms of thermal efficiency, a percent standby loss factor must be included in the calculation as shown in the algorithms.

Algorithms

Fuel Savings (MMBtu/yr) = ((1 – (EFF_b / EFF_q) + SLF⁶¹) * Energy Use Density * Area

Where,

SLF = 0.775 × Cap_q^{-0.778}

Definition of Variables

EFF_q = Efficiency of the qualifying instantaneous water heater.

EFF_b = Efficiency of the baseline water heater, commercial grade.

EF_b = Efficiency of the baseline water heater, commercial grade.

SLF = Standby loss factor of the baseline water heater fuel usage. This was calculated from standby loss and input capacity data for commercial water heaters exported from the AHRI database.

Energy Use Density = Annual baseline water heater energy use per square foot of commercial space served (MMBtu/sq.ft./yr)

Area = Square feet of building area served by the water heater

Cap_q = Rated input capacity of the qualifying water heater

Summary of Inputs

Water

Heater Assumptions

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>EFF_q</u>	<u>Variable</u>		<u>Application</u>
<u>EFF_b</u>	<u>Variable</u>	<u>See Table Below</u> <u>If storage water heater < 75</u> <u>kBtu/Hhr or instantaneous water</u>	<u>1, 2</u>

⁶¹ Standby losses only apply if the baseline water heater is a stand alone storage water heater rated for more than 75 kBtu/hr

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
		heater < 200 kBtu/hr: EF Otherwise TE. EF = Energy Factor TE = Thermal Efficiency	
<u>EF_b</u>	<u>Variable</u>	<u>See Table Below</u>	<u>1, 2</u>
<u>Energy Use Density</u>	<u>Variable</u>	<u>See Table Below</u>	<u>3</u>
<u>Area</u>	<u>Variable</u>		<u>Application</u>

Efficiency of Baseline Water Heaters

ASHRAE 90.1-2007 and 2013^a

<u>Equipment Type</u>	<u>Size Category (Input)</u>	<u>Existing Building Baseline Efficiency (ASHRAE 90.1-2007)</u>	<u>New Building Baseline Efficiency (ASHRAE 90.1-2013)</u>
<u>Gas Storage Water Heaters⁶²</u>	<u>≤ 75 kBtu/hr</u>	<u>EF = 0.54</u>	<u>EF = 0.65</u>
<u>Gas Storage Water Heaters</u>	<u>> 75 kBtu/hr</u>	<u>TE = 0.80</u>	<u>TE = 0.80</u>
<u>Gas Instantaneous Water Heaters⁶³</u>	<u>< 200 kBtu/hr</u>	<u>EF = 0.62</u>	<u>EF = 0.62</u>
<u>Gas Instantaneous Water Heaters</u>	<u>≥ 200 kBtu/hr</u>	<u>TE = 0.80</u>	<u>TE = 0.80</u>

a – EF means energy factor and TE means thermal efficiency

Energy Use Density Look-up Table

<u>Building Type</u>	<u>Energy Use Density (kBtu/SF/yr)</u>
<u>Education</u>	<u>7.0</u>
<u>Food sales</u>	<u>4.4</u>
<u>Food service</u>	<u>39.2</u>
<u>Health care</u>	<u>23.7</u>
<u>Inpatient</u>	<u>34.3</u>
<u>Outpatient</u>	<u>3.9</u>
<u>Lodging</u>	<u>26.5</u>

⁶² Note, for qualifying instantaneous water heaters less than 200kBtu/hr, the storage water heater tank size is assumed to be 40 gallons.

⁶³ For instantaneous water heaters rated for less than 200 kBtu/hr, the tank size is assumed to be 1 gallon.

<u>Retail (other than mall)</u>	<u>2.5</u>
<u>Enclosed and strip malls</u>	<u>14.1</u>
<u>Office</u>	<u>4.8</u>
<u>Public assembly</u>	<u>2.1</u>
<u>Public order and safety</u>	<u>21.4</u>
<u>Religious worship</u>	<u>0.9</u>
<u>Service</u>	<u>15</u>
<u>Warehouse and storage</u>	<u>2.9</u>
<u>Other</u>	<u>2.3</u>

Sources

1. ASHRAE Standards 90.1-2007, *Energy Standard for Buildings Except Low Rise Residential Buildings*; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
2. ASHRAE Standards 90.1-2013, *Energy Standard for Buildings Except Low Rise Residential Buildings*; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
3. Energy Information Administration, *Commercial Building Energy Consumption Survey Data, 2012*; available at: <https://www.eia.gov/consumption/commercial/data/2012/c&e/cfm/e7.cfm>.

Prescriptive Boilers

This prescriptive measure targets the use of smaller-scale boilers (less than or equal to 4000 MBH) and furnaces (no size limitation) in all commercial facilities. ~~Larger sized boilers are treated under the custom measure path. The measurement of energy savings for C&I gas, oil, and propane fired furnaces and boilers is based on algorithms with key variables (i.e. Annual Fuel Utilization Efficiency, capacity of the furnace, EFLH) provided by manufacturer data or utility data. Savings are calculated for four zones throughout the state by heating degree days and for twelve different building types. Larger sized boilers are treated under the custom measure path.~~

Algorithms

$$\text{Gas Savings for Boilers (Therms)} = \frac{OF * HDD_{mod} * 24}{\Delta T * HC_{fuel}} * IR_B * \left[1 - \left(\frac{Eff_B}{Eff_Q} \right) \right]$$

Definition of Variables

OF = Oversize factor of standard boiler (OF=0.8)

HDD_{mod} = HDD by zone and building type

ΔT = design temperature difference

HC_{fuel} = Conversion from Btu to Therms of gas (100,000 Btu/Therm)

IR_B = Boiler Baseline Input Rating (BtuH)

Eff_B - This measure applies to new construction, replacement of failed equipment, or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by ASHRAE Std. 90.1 – 2013, which is the current code adopted by the state of New Jersey.

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = Cap_m * EFLH_h * ((Eff_q/Eff_b)-1) / 1000 \text{ kBtu/MMBtu}$$

Definition of Variables

Cap_m = Input capacity of qualifying unit in kBtu/hr

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season in hours

Eff_b = Boiler Baseline Efficiency

Eff_q-Eff_q = Boiler Proposed Efficiency

1000 = Conversion from kBtu to MMBtu

Formatted: Page break before

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Don't keep with next

Formatted: Normal, Right: -0.13"

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Summary of Inputs

Prescriptive Boilers

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>Cap_{in}</u>	<u>Variable</u>		<u>Application</u>
<u>EFLH_h</u>	<u>Fixed</u>	<u>See Table Below</u>	<u>1</u>
<u>Eff_b</u>	<u>Variable</u>	<u>See Table Below</u>	<u>2</u>
<u>Eff_q</u>	<u>Variable</u>		<u>Application</u>

Formatted: Table Caption, Left, Don't keep with next

Formatted: Table Header, Left

EFLH_h Table

<u>Facility Type</u>	<u>Heating EFLH</u>
<u>Assembly</u>	<u>603</u>
<u>Auto repair</u>	<u>1910</u>
<u>Dormitory</u>	<u>465</u>
<u>Hospital</u>	<u>3366</u>
<u>Light industrial</u>	<u>714</u>
<u>Lodging – Hotel</u>	<u>1077</u>
<u>Lodging – Motel</u>	<u>619</u>
<u>Office – large</u>	<u>2034</u>
<u>Office – small</u>	<u>431</u>
<u>Other</u>	<u>681</u>
<u>Religious worship</u>	<u>722</u>
<u>Restaurant – fast food</u>	<u>813</u>
<u>Restaurant – full service</u>	<u>821</u>
<u>Retail – big box</u>	<u>191</u>
<u>Retail – Grocery</u>	<u>191</u>
<u>Retail – large</u>	<u>545</u>
<u>Retail – large</u>	<u>2101</u>
<u>School – Community college</u>	<u>1431</u>
<u>School – postsecondary</u>	<u>1191</u>
<u>School – primary</u>	<u>840</u>
<u>School – secondary</u>	<u>901</u>
<u>Warehouse</u>	<u>452</u>

Multi-family EFLH by Vintage

Facility Type	Prior to 1979	From 1979 to 2006	From 2007 through Present
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Baseline Boiler Efficiencies (Eff_b)

Formatted: Table Caption

OF	Fixed	0.8	
IR_B	Variable		Application
HC_{Fuel}	Fixed	100,000-Btu/Therm	
Eff_B	Variable	See Table Below	±
Eff_Q	Variable		Application
ΔT	Variable	See Table Below	±
HDD_{mod}	Fixed	See Table Below	±

Adjusted Heating Degree Days by Building Type

Building Type	Heating Energy Density (kBtu/sf)	Degree Day Adjustment Factor	Atlantic City (HDD)	Newark (HDD)	Philadelphia (HDD)	Monticello (HDD)
Education	29.5	0.55	2792	2783	2655	3886
Food Sales	35.6	0.66	3369	3359	3204	4689
Food Service	39.0	0.73	3691	3680	3510	5137
Health Care	53.6	1.00	5073	5057	4824	7060
Lodging	15.0	0.28	1420	1415	1350	1976
Retail	29.3	0.55	2773	2764	2637	3859
Office	28.1	0.52	2660	2651	2529	3701
Public Assembly	33.8	0.63	3199	3189	3042	4452
Public Order/Safety	24.1	0.45	2281	2274	2169	3174
Religious Worship	29.1	0.54	2754	2745	2619	3833
Service	47.8	0.89	4524	4510	4302	6296
Warehouse/Storage	20.2	0.38	1912	1906	1818	2661

Boiler Type	Size Category (kBtu input)		Standard 90.1-2013
<u>Hot Water – Gas fired</u>	<u>< 300</u>		<u>82% AFUE</u>
	<u>> 300 and < 2,500</u>		<u>80% Et</u> <u>82% Ec</u>
<u>Hot Water – Oil fired</u>	<u>< 300</u>	<u>84% AFUE</u>	
	<u>> 300 and < 2,500</u>	<u>82% Et</u> <u>84% Ec</u>	
<u>Steam – Gas fired</u>	<u>< 300</u>	<u>80% AFUE</u>	
<u>Steam – Gas fired, all except natural draft</u>	<u>> 300 and < 2,500</u>	<u>79% Et</u>	
<u>Steam – Gas fired, all except</u>	<u>> 2,500</u>		<u>79% Ec</u>
<u>Steam – Gas fired, natural draft</u>	<u>> 300 and <</u>		<u>77% Et</u>

<u>Boiler Type</u>	<u>Size Category (kBtu input)</u>		<u>Standard 90.1-2013</u>
<u>Steam – Gas fired, natural draft</u>	<u>> 2,500</u>		<u>77% Ec</u>
<u>Steam – Oil fired</u>	<u>< 300</u>	<u>82% AFUE</u>	
	<u>> 300 and < 2,500</u>	<u>81% Et</u>	
		<u>81% Ec</u>	

Formatted: Indent: Left: 0.25"

Formatted: Font: Not Bold

Heating Degree Days and Outdoor Design Temperature by Zone

<u>Weather Station</u>	<u>HDD</u>	<u>Outdoor Design Temperature (F)</u>
Atlantic City	5073	13
Newark	5057	14
Philadelphia, PA	4824	15
Monticello, NY	7060	8

Baseline Boiler Efficiencies (Eff_b)

<u>Boiler Type</u>	<u>Size Category (MBh input)</u>	<u>Existing Buildings Standard 90.1-2007</u>	<u>New Construction Standard 90.1-2013</u>
<u>Hot Water</u>	<u><300</u>	<u>80% AFUE</u>	<u>82% AFUE</u>
<u>Hot Water</u>	<u>≥ 300 and ≤ 2,500</u>	<u>75% Et</u>	<u>80% Et</u>
<u>Hot Water</u>	<u>> 2,500</u>	<u>80% Ec</u>	<u>82% Ec</u>
<u>Steam</u>	<u><300</u>	<u>75% AFUE</u>	<u>80% AFUE</u>
<u>Steam, all except natural draft</u>	<u>≥ 300 and ≤ 2,500</u>	<u>75% Et</u>	<u>79% Et</u>
<u>Steam, all except natural draft</u>	<u>> 2,500</u>	<u>80% Ec</u>	<u>79% Et</u>
<u>Steam, natural draft</u>	<u>≥ 300 and ≤ 2,500</u>	<u>75% Et</u>	<u>77% Et</u>
<u>Steam, natural draft</u>	<u>> 2,500</u>	<u>80% Ec</u>	<u>77% Et</u>

Sources:

Formatted: Heading 4, Space After: 6 pt

1. KEMA, Smartstart Program Protocol Review. 2009.
2. ASHRAE 90.1 2007

1. Infrared Heaters, New York State Joint Utilities, New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.
2. ASHRAE Standards 90.1-2013. Energy Standard for Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.

Prescriptive Furnaces and Direct Install Boilers

Formatted: Heading 3, Page break before

The methodology outlined below shall be adopted for estimating savings for installation of qualifying furnaces and infrared heaters as well as Direct Install boilers in order to accommodate resizing.

Formatted: Space Before: 6 pt, After: 6 pt

Algorithms

Formatted: Right: -0.13"

Formatted: Font: Not Bold

Gas Savings (Therms)

$$= \frac{[OF \times HDD_{mod} \times 24 \times ((CAPY_{B.out} \times Eff_{AFUE_q}) - (CAPY_{Q.out} \times AFUE_{eff_b} \times ICF))]}{\Delta T \times HC_{fuel} \times AFUE_{eff_b} \times AFUE_{eff_q} \times ICF}$$

This measure applies to new construction, replacement of failed equipment, or end of useful life. The baseline unit is a code compliant unit with an efficiency as required by ASHRAE Std. 90.1 – 2013, which is the current code adopted by the state of New Jersey.

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = Cap_{in} * EFLH_h * ((Eff_q/Eff_b)-1) / 1000 \text{ kBtu/MMBtu}$$

Formatted: Normal

Definition of Variables

Formatted: English (U.S.)

OF = Oversize factor of standard furnace/boiler/heater (OF=0.8)

CAPY_{B.out} = Total output capacity of the baseline furnace/boiler/heater(s) in Btu/hour

Eff_{AFUE_Q} = Efficiency of qualifying furnace/boiler/heater(s) (AFUE %)

CAPY_{Q.out} = Total output Cap_{in} = Input capacity of the qualifying furnace/boiler/heater(s) unit in kBtu/hr

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season in Btu/hour hours

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Eff_B = Eff_b = Furnace Baseline Efficiency

Eff_q = Furnace Proposed Efficiency of baseline furnace/boiler/heater(s) (AFUE %)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

ICF = Infrared Compensation Factor (ICF = 0.8 for IR Heaters, 1.0 for Furnaces/Boilers)²

HDD_{mod} = HDD by zone and building type

24 = Hours/Day

ΔT = design temperature difference

$\frac{HC_{fuel} \cdot 1000}{Btu/Therm} =$ Conversion from Btu to Therms of gas (100,000 Btu/Therm) kBtu to MMBtu

IR Heaters, Summary of Inputs

Prescriptive Furnaces and Boilers

Component	Type	Value	Source
ϕ_f	Fixed	0.8	
HC_{fuel}	Fixed	100,000 Btu/Therm	
Cap_{in}	Variable		Application
$EFLH_h$	Fixed	See Table Below	1
Eff_q	Variable		Application
Eff_b	Fixed	See Table Below	2

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

Formatted: Indent: First line: 0.25"

Formatted: Table Caption, Left, Don't keep with next

Formatted: Table Header, Left

Formatted Table

Formatted: Table Cells

Formatted Table

EFLH_h Table

Facility Type	Heating EFLH
Assembly	603
Auto repair	1910
Dormitory	465
Hospital	3366
Light industrial	714
Lodging – Hotel	1077
Lodging – Motel	619
Office – large	2034
Office – small	431
Other	681
Religious worship	722
Restaurant – fast food	813
Restaurant – full service	821
Retail – big box	191
Retail – Grocery	191
Retail – large	545
Retail – large	2101

<u>Facility Type</u>	<u>Heating EFLH</u>
<u>School – Community college</u>	<u>1431</u>
<u>School – postsecondary</u>	<u>1191</u>
<u>School – primary</u>	<u>840</u>
<u>School – secondary</u>	<u>901</u>
<u>Warehouse</u>	<u>452</u>

Multi-family EFLH by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Baseline Furnace Efficiencies (Eff_b)

<u>Furnace Type</u>	<u>Size Category (kBtu input)</u>	<u>Standard 90.1-2013</u>
<u>Gas Fired</u>	<u>< 225</u>	<u>78% AFUE</u>
	<u>≥ 225</u>	<u>80% Ec</u>
<u>Oil Fired</u>	<u>< 225</u>	<u>78% AFUE</u>
	<u>≥ 225</u>	<u>81% Et</u>

Sources

1. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix G – Equivalent Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.
2. ASHRAE Standards 90.1-2013, *Energy Standard for Buildings Except Low Rise Residential Buildings*; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.

Infrared Heaters

This measures outlines the deemed savings for the installation of a gas-fired low intensity infrared heating system in place of unit heater, furnace, or other standard efficiency equipment. The deemed savings are based on a Massachusetts Impact Evaluation Study.

Summary of Assumptions

<u>Variable</u>	<u>Value</u>	<u>Source</u>
<u>Deemed Savings</u>	<u>12.0 MBtu/yr</u>	<u>1</u>

<u>Sources</u> _{Eff_b}	Fixed	Furnaces: 78% Boilers: 80%^a Infrared: 78%	EPACT Standard for furnaces and boilers
CAPY _{B/Q-Out}	Variable		Application
ΔT	Variable	See Table Below	1
HDD _{mod}	Fixed	See Table Below	1

Formatted: No underline

a—80% efficiency used for Direct Install protocols only. SmartStart gas boiler efficiencies referenced in Boiler Baseline Efficiency table.

Sources:

1. KEMA, *Smartstart Program Protocol Review*—2009.
2. http://www.spaceray.com/1_space_ray_faqs.php

Adjusted Heating Degree Days by Building Type

Building Type	Heating Energy Density (kBtu/sf)	Degree Day Adjustment Factor	Atlantic City (HDD)	Newark (HDD)	Philadelphia (HDD)	Monticello (HDD)
Education	29.5	0.55	2792	2783	2655	3886
Food Sales	35.6	0.66	3369	3359	3204	4689
Food Service	39.0	0.73	3691	3680	3510	5137
Health Care	53.6	1.00	5073	5057	4824	7060
Lodging	15.0	0.28	1420	1415	1350	1976
Retail	29.3	0.55	2773	2764	2637	3859
Office	28.1	0.52	2660	2651	2529	3701
Public Assembly	33.8	0.63	3199	3189	3042	4452
Public Order/Safety	24.1	0.45	2281	2274	2169	3174
Religious Worship	29.1	0.54	2754	2745	2619	3833
Service	47.8	0.89	4524	4510	4302	6296
Warehouse/Storage	20.2	0.38	1912	1906	1818	2661

Heating Degree Days and Outdoor Design Temperature by Zone

Weather Station	HDD	Outdoor Design Temperature (F)
Atlantic City	5073	13
Newark	5057	14
Philadelphia, PA	4824	15
Monticello, NY	7060	8

Baseline Boiler Efficiencies (Eff_b)

Size Category (MBh input)		Hot Water	Steam
Min	Max		
0	300	80% AFUE	75% AFUE
300	2500	75% Et	75% Et
2500	4000	80% Ec	76% Et
Baseline ASHRAE 90.1 2007			

Formatted: Table Caption

Sources:

- ~~1. KEMA, Smartstart Program Protocol Review. 2009.~~
- ~~2. <http://www.spaceray.com/1-space-ray-faqs.php>~~

Formatted: No underline

1. KEMA, Impact Evaluation of 2011 Prescriptive Gas Measures; prepared for Massachusetts Energy Efficiency Program Administrators and Massachusetts Energy Efficiency Advisory Council, 2013, pp. 1-5.

Electronic Fuel Use Economizers

Algorithms

Fuel Savings (MMBtu) = (AFU * 0.13)

AFU = Annual Fuel Usage for an uncontrolled (gas, oil, propane) HVAC unit (MMBtu or gallons) = (Input power in MMBtu or gallons) * (annual run time)

0.13 = Approximate energy savings factor related to installation of fuel use economizers¹.

Sources_:

1. Approximate energy savings factor of 0.13 based on average % savings for test sites represented in Table 2 (page 3) of NYSERDA Study: A Technology Demonstration and Validation Project for Intellidyne Energy Saving Controls; Intellidyne LLC & Brookhaven National Laboratories; 2006
(http://www.cleargreenpartners.com/attachments/File/NYSERDA_Report.pdf)(http://www.cleargreenpartners.com/attachments/File/NYSERDA_Report.pdf)

Formatted: Font: Not Bold

Formatted: Normal

Formatted: Font: Not Bold, Underline, (none)

Formatted: Normal, Level 4, Keep with next

Formatted: Font: Bold

Formatted: No underline

Formatted: Space Before: 6 pt, After: 6 pt, No bullets or numbering

Formatted: Normal

Distributed Energy Resource (DER)

Combined Heat & Power Program

Protocols

The measurement of energy and demand savings for Combined Heat and Power (CHP)~~/fuel cell~~ systems is based primarily on the characteristics of the individual systems subject to the general principles set out below. The majority of the inputs used to estimate energy and demand impacts of CHP~~/fuel cell~~ systems will be drawn from individual project applications. Eligible systems include: powered by non-renewable or renewable fuel sources, gas internal combustion engine, gas combustion turbine, microturbine, and fuel cells with heat recovery.

Formatted: Space Before: 6 pt, After: 6 pt

~~CHP/fuel cell~~The NJ Protocol is to follow the National Renewable Energy Laboratory's Combined Heat and Power, The Uniform Methods Project: Methods for Determining Energy-Efficiency Savings for Specific Measures [1]. The product should be all of the below outputs, as applicable:

- a. Annual energy input to the generator, HHV basis (MMBtu/yr)
- b. Annual electricity generated, net of all parasitic loads (kWh/yr)
- c. Annual fossil fuel energy savings from heat recovery (MMBtu/yr)
- d. Annual electric energy savings from heat recovery, including absorption chiller sourced savings if chiller installation is included as part of the system installation (kWh/yr)
- e. Annual overall CHP fuel conversion efficiency, HHV basis (%)
- f. Annual electric conversion efficiency, net of parasitics, HHV basis (%)

CHP systems typically use fossil fuels to generate electricity that displaces electric generation from other sources. Therefore, the electricity generated from a CHP~~/fuel cell~~ system should not be reported as either electric energy savings or renewable energy generation. Alternatively, electric generation and capacity from CHP~~/fuel cell~~ systems should be reported as Distributed Generation (DG) separate from energy savings and renewable energy generation. However, any waste heat recaptured and utilized should be reported as energy savings as discussed below.

Formatted: Space Before: 6 pt, After: 6 pt

Distributed Generation

~~Electric~~Net Electricity Generation (MWh) = Estimated ~~annual and lifetime~~ electric generation in MWh provided on the project application, as adjusted during the project review and approval process.

Formatted: Font: Not Bold

Peak Electric Demand (kW) = Electric demand reduction delivered by the CHP system provided on the project application, as adjusted during the project review and approval process.

Formatted: Space Before: 6 pt, After: 3 pt

~~Electric Demand (kW) = Electric capacity of the CHP/fuel cell system in kW~~
~~Total Fuel Consumption or Fuel Consumed by Prime Mover (MMBtu @HHV) = Total heating value of used by CHP system~~ provided on the project application, as adjusted during the project review and approval process.

Formatted: Space Before: 6 pt, After: 3 pt

Energy Savings Impact

~~Gas Energy Savings or Fuel Offset (MMBtu @HHV):~~ Gas savings should be reported on a consistent basis by all applicants as the reduction in fuel related to the recapture of thermal energy (e.g., reduction in boiler gas associated with the recapture of waste heat from the CHP engine or turbine, or a fuel cell with heat recovery.)

Formatted: Font: Not Bold

Formatted: Space Before: 6 pt, After: 6 pt

~~Electric Energy Savings or Offset Chiller Electricity Use (MWh):~~ Electric energy savings should be reported only in cases where the recapture of thermal energy from the CHP system is used to drive an absorption chiller that would displace electricity previously consumed for cooling.

Formatted: Font: Not Bold

Formatted: Space Before: 6 pt, After: 6 pt

Emission Reductions

For many CHP/~~fuel cell~~ applications there can be substantial emission benefits due to the superior emission rates of many new CHP engines and turbines as compared to the average emission rate of electric generation units on the margin of the grid. However, CHP engines and turbines produce emissions, which should be offset against the displaced emissions from the electricity that would have been generated by the grid.⁶⁴

Formatted: Space Before: 6 pt, After: 6 pt

~~The New Jersey Department of Environmental Protection (DEP) has provided the BPU with emission~~
~~Electric and natural gas emissions~~ factors ~~that are presented in the~~
~~Introduction section of the Protocols and~~ are used to calculate the emission savings from energy efficiency and renewable energy projects. These factors should be used to calculate the base emission factors which the CHP system emission factors would be compared to. The emissions from the CHP system would be subtracted from the base emissions to determine the net emission changes as follows:

Formatted: Space Before: 6 pt, After: 6 pt

CHP Emissions Factors Reduction Associated with PJM Grid

Formatted: Heading 3, Left

CO₂—1015 lbs per MWh

NO_x—0.95 lbs per MWh

SO₂—2.21 lbs per MWh

CHP Emissions Reduction (ER) Formulas

⁶⁴ Summit Blue, Draft Energy Efficiency Market Assessment of New Jersey Clean Energy Program, Book III, Page 196, May 26, 2006

(Assuming that the useful thermal output will displace natural gas)

Formatted: Left

CO₂e Algorithms

CO₂ ER (lbs) = $\frac{1015 * \text{Electrical Output} * \text{CO}_2\text{emission} * \text{Net Electricity Generation}}{(\text{MWh}) + \text{Useful Thermal Output} * \text{Gas Energy Savings (MMBtu)} * \text{CO}_2 \text{ EF}_{\text{NG}}} - [\text{CHP CO}_2 \text{ EF}_f * \text{Total Fuel Consumption (MMBtu)}]$

Formatted: Indent: Hanging: 1.25"

NO_x ER (lbs) = $\frac{0.95 * \text{Electrical Output} * \text{NO}_x\text{emission} * \text{Net Electricity Generation}}{(\text{MWh}) + \text{Useful Thermal Output} * \text{Gas Energy Savings (MMBtu)} * \text{NO}_x \text{ EF}_{\text{NG}}} - [\text{CHP NO}_x \text{ EF}_f * \text{Total Fuel Consumption (MMBtu)}]$

Formatted: Indent: Hanging: 1.25"

SO₂ ER (lbs) = $\frac{2.21 * \text{Electrical Output} * \text{SO}_2\text{emission} * \text{Net Electricity Generation}}{(\text{MWh}) + \text{Useful Thermal Output} * \text{Gas Energy Savings (MMBtu)} * \text{SO}_2 \text{ EF}_{\text{NG}}} - [\text{CHP SO}_2 \text{ EF}_f * \text{Total Fuel Consumption (MMBtu)}]$

Formatted: Indent: Hanging: 1.25"

Note:

Definition of Variables

CO₂emission = See emmissions tables summarized in Introduction section of Protocols

NO_xemission = See emmissions tables summarized in Introduction section of Protocols

SO₂emission = See emmissions tables summarized in Introduction section of Protocols

1- EF_{NG} values associated with boiler fuel displacement :

- CO₂ EF_{NG} = 115 lb/MMBtu
- NO_x EF_{NG} = 0.12 lbs/MMBtu
- SO₂ EF_{NG} = .0006 lb/MMBtu

Formatted: Normal, Indent: First line: 0.25", Space Before: 6 pt, After: 3 pt, Add space between paragraphs of the same style, Line spacing: Multiple 1.15 li, No bullets or numbering

CO₂ EF_{NG} = See emmissions tables summarized in Introduction section of Protocols

NO_x EF_{NG} = See emmissions tables summarized in Introduction section of Protocols

SO₂ EF_{NG} = See emmissions tables summarized in Introduction section of Protocols

2- CHP EF_f (lb/MWh)–MMBtu) = Emission factor of fuel type used in the CHP system, which will vary with different projects based on the types of prime movers and emission control devices used.

Formatted: Normal, Indent: Left: 0.25", Space After: 10 pt, Line spacing: Multiple 1.15 li, No bullets or numbering

~~NJDEP Regulatory Limits for CHP Systems~~

~~NOX: 0.047 lb/MMBtu~~

~~SO2: 0.0006 lb/MMBtu~~

~~CO: 0.157 lb/MMBtu~~

~~VOC: 0.047 lb/MMBtu~~

~~TSP: 0.01 lb/MMBtu~~

~~PM-10: 0.038 lb/MMBtu~~

Emission reductions from any CHP system energy savings, as discussed above, would be treated the same as any other energy savings reported.

Sources

1. Simons, George, Stephan Barsun, and Charles Kurnik. 2016. *Chapter 23: Combined Heat and Power, The Uniform Methods Project: Methods for Determining Energy-Efficiency Savings for Specific Measures*. Golden, CO: National Renewable Energy Laboratory. NREL/ SR-7A40-67307. <http://www.nrel.gov/docs/fy17osti/67307.pdf>.

Sustainable Biomass Biopower

Estimated annual energy generation and peak impacts for sustainable biomass systems will be determined on a case-by-case basis based on the information provided by project applicants and inspection data for verification of -as- installed conditions.

Formatted: Indent: Left: 0.25", Space After: 10 pt, Don't add space between paragraphs of the same style, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Normal, Space After: 10 pt, Don't add space between paragraphs of the same style, Line spacing: Multiple 1.15 li

Formatted: Normal, Level 3, Space Before: 12 pt, After: 3 pt, Keep with next

Formatted: Normal, Space After: 10 pt, Don't add space between paragraphs of the same style, Line spacing: Multiple 1.15 li

Formatted: Font: 12 pt, Not Bold

Pay for Performance Program

Formatted: Centered

Protocols

The Pay for Performance Program is a comprehensive program targeted at existing commercial and industrial (C&I) buildings that have an average annual peak demand of 200 kW or greater; as well as select multifamily buildings with annual peak demand of 100 kW or greater. Participants in the Pay for Performance Program are required to identify and implement energy efficiency improvements that will achieve a minimum of **15% reduction in total source energy consumption savings target.**

Formatted: Font: Bold

Energy Savings Requirements

Formatted: Space Before: 9 pt, After: 3 pt

Existing Buildings

ProjectsFor Existing Buildings, projects are required to identify and implement comprehensive energy efficiency improvements that will achieve a minimum of 15% reduction in total source energy consumption as measured from existing energy use. ~~(for existing buildings) and 15% energy cost savings from the current state energy code (for new construction). Further, no more than 50% of the total savings may be derived from lighting measures. Savings may not come from a single measure and no more than 50% of the total savings may be derived from lighting measures. Lighting savings up to 70% of total projected savings can be considered but the minimum savings required will increase proportionately as demonstrated in the table below~~For New Consturction, including major rehabilitation, projects are required to identify and implement comprehensive energy efficiency measures that achieve a minimum 5% energy cost savings for commercial and industrial buildings, and 15% for multifamily, from the current state energy code.

Formatted: Space Before: 6 pt, After: 6 pt

Existing Buildings projects must include multiple measures, where lighting measures do not exceed 50% of total savings (exceptions apply, see program guidelines). New Construction projects must have at least one measure addressing each envelope, heating, cooling, and lighting systems. Buildings that are not heated (e.g. refrigerated warehouse) or not cooled (e.g. warehouse) will not be required to have a measure addressing the missing building system.

Lighting Savings	Minimum Source Energy Target
51%	16%
52%	17%
53%	18%
54%	19%
55%	20%
56%	21%
57%	22%
58%	23%
59%	24%
60%	25%
61%	26%
62%	27%
63%	28%
64%	29%
65%	30%
66%	31%
67%	32%
68%	33%
69%	34%
70%	35%

~~The~~In both program components, the total package of measures must have ~~at least a 10%,~~ internal rate of return (IRR), and at least 50% of the savings must come from investor-owned electricity and/or natural gas. If 50% of the savings does not meet this criteria, then the project must save a minimum of 100,000 kWh or 2,000 therms from investor-owned utility accounts.

Formatted: Space Before: 6 pt, After: 6 pt

~~An~~For Existing Buildings, an exception to the 15% savings requirement ~~will be limited~~ is available to sectors such as manufacturing, pharmaceutical, chemical, refinery, packaging, food/beverage, data center, transportation, mining/mineral, paper/pulp, biotechnology, etc, as well as hospitals. The manufacturing and/or processing loads use should be equal to or greater than approximately 50% of the total metered energy use. Instead of the 15% savings requirement, the project must deliver a minimum energy savings of ~~100,000 kWh, 350 MMBTU or~~ 4% of total facility consumption, ~~whichever is greater. Exceptions must be pre-approved by Market Manager and currently only apply to existing buildings component of program.~~

Formatted: Space Before: 6 pt, After: 6 pt

~~New Construction and Gut Rehabilitation~~

~~Projects are required to identify and implement energy efficiency improvements that will achieve a minimum of 5% energy cost savings for C&I buildings, and 15% for multifamily, as measured from ASHRAE 90.1-2013 baseline. Equivalent performance targets for ASHRAE Building Energy Quotient (bEQ) As-Designed and ASHRAE 90.1-2013 with Addendum BM are provided in the program guidelines (see Baseline Conditions below).~~

~~Each project must have at least one measure addressing each envelope, heating, cooling, and lighting systems. Buildings that are not heated (e.g. refrigerated warehouse) or not~~

Formatted: Space Before: 6 pt, After: 6 pt

~~cooled (e.g. warehouse) will not be required to have a measure addressing the missing building system.~~

Software Requirements

In order for a project to qualify for incentives under the Pay for Performance Program, the Partner must create a whole-building energy simulation to demonstrate energy savings from recommended energy efficiency measures, as described in detail in the Simulation Guidelines section of the Pay for Performance Program Guidelines. The primary source for developing the Simulation Guidelines is ASHRAE Guideline 14. Simulation software must be compliant with ASHRAE 90.1 -Section 11 or Appendix G. Examples of allowed tools include eQUEST, HAP, EnergyPlus, Trane Trace, DOE 2.1. Approval for use in LEED and Federal Tax Deductions for Commercial Buildings program may serve as the proxy to demonstrate compliance with the requirement.

Formatted: Space Before: 9 pt, After: 3 pt

Baseline Conditions

Existing Buildings

Existing Buildings

Baseline from which energy savings are measured will be based off the most recent ~~twelve~~12 months of energy use from all sources. Site energy use is converted to source energy use following EPA's site-to-source conversion factors⁶⁵.

Formatted: Space Before: 9 pt, After: 3 pt

New Construction

Project may establish building baseline in one of two ways:

- *Path 1* — Under this path, the Partner will develop a single energy model representing the proposed project design using prescribed modeling assumptions that follow *ASHRAE Building Energy Quotient (bEQ) As-Designed*⁶⁶ simulation requirements.
- *Path 2* — Under this option the Partner will develop a baseline building using ASHRAE 90.1-2013 Appendix G *modified by Addendum BM*⁶⁷.

~~-(for existing buildings) or current state energy code, such as ASHRAE 90.1-2007 (for new construction).~~

Formatted: Indent: Left: 0.5", No bullets or numbering

Measure Savings

Formatted: Space Before: 9 pt, After: 3 pt

⁶⁵ <https://portfoliomanager.energystar.gov/pdf/reference/Source%20Energy.pdf>

⁶⁶ <http://buildingenergyquotient.org/asdesigned.html>

⁶⁷ Addendum BM sets a common baseline building approach that will remain the same for ASHRAE 90.1-2013 and all future iterations of ASHRAE 90.1, and is roughly equivalent to ASHRAE 90.1-2004. To comply with ASHRAE 90.1-2013, a proposed building has to have energy cost savings of 11-40% from the Addendum BM baseline, depending on the building type and climate zone.

Formatted: Space Before: 3 pt, After: 3 pt

Measures must be modeled to demonstrate proposed energy/energy cost savings according to Pay for Performance program guidelines, including meeting or exceeding Minimum Performance Standards, or current state or local energy code, whichever is more stringent. Minimum Performance Standards generally align with C&I SmartStart Program equipment requirements.

Existing Buildings

Measures must be modeled within the approved simulation software and modeled incrementally to ensure interactive savings are taken into account.

New Construction

Measures must be modeled based on the baseline path chosen:

- *Path 1* — Modeled within the same proposed design energy model, but as parametric runs or alternatives downgraded to code compliant parameters.
- *Path 2* – Modeled as interactive improvements to the ASHRAE 90.1-2013 Appendix G baseline (with Addendum BM accepted).

In the event that a software tool cannot adequately model a particular measure or component, or in cases where Program Manager permits savings calculations outside of the model, projects are required to use stipulated savings calculations as outlined in the Program Guidelines or within these Protocols as applicable. If stipulated savings do not exist within these documents, the Program Manager will work with the applicant to establish acceptable industry calculations.

Formatted: Space Before: 3 pt, After: 3 pt, Add space between paragraphs of the same style

Measurement & Verification

Existing Buildings

The Program metering requirements are based on the 2010 International Performance Measurement and Verifications Protocol (“IPMVP”) and the 2008 Federal Energy Management Program (“FEMP”) M&V Guidelines, Version 3.0. All projects must follow Option D, Calibrated Simulation, as defined by the IPMVP. Calibrated simulation involves the use of computer software to predict building energy consumption and savings from energy-efficiency measures. Options A and B, as defined by the IPMVP, may be used as guidelines for data collection to help create a more accurate model. Additionally, for the existing buildings component, Option C is used to measure actual savings using twelve months of post-retrofit utility data.

New Construction

Projects are required to commission all energy efficiency measures. Further, projects are required to complete a benchmark through EPA’s *ENERGY STAR Portfolio Manager* to demonstrate operational performance based on the building’s first year of operation. Building types not eligible for ENERGY STAR Score may demonstrate compliance through *ASHRAE Building Energy Quotient (bEQ) In-Operation*.

Energy Savings Reporting

Committed energy savings are reported upon approval of the Energy Reduction Plan and are based on modeling results of recommended measures as described above. Installed energy savings are reported upon installation of recommended measures and are based on modeling results. Unless significant changes to the scope of work occurred during construction, installed savings will be equal to committed savings. Verified savings are reported at the end of the performance period (for Existing Buildings) and are based on twelve (12) months of post-retrofit utility bills compared to pre-retrofit utility bills used during Energy Reduction Plan development. For New Construction, verified savings are not currently ~~reported at the end of the Commissioning process (for new construction) and may vary from committed/installed savings reported.~~ Note that only installed savings are reported on New Jersey’s Clean Energy Quarterly Financial and Energy Savings Reports.

Formatted: Space Before: 12 pt, After: 3 pt

Formatted: Font: Not Bold

Formatted: Space Before: 9 pt, After: 3 pt

Direct Install Program

Protocols

This section identifies the protocols for ~~all~~ measures proposed under the Direct Install Program. ~~This section includes protocols for. Several of the measures that are not included in other sections of the Protocols. In addition, for several of the where Direct Install Protocols uses~~ algorithms and inputs ~~from~~ identical to the “Commercial and Industrial Energy Efficient Construction” section of the Protocols, and as such, the user is directed to that section of the Protocols for the specific protocol. Other measures may have similar algorithms and inputs, but identify different equipment baselines ~~will be used~~ to reflect the Direct Install ~~includes~~ early retirement. ~~Baseline replacement program where equipment efficiency shown in is replaced as a direct result of the program. For those measures, the applicable baseline tables are included in this section is an estimate of existing equipment efficiency rather than currently available standard efficiency., but the user is directed to the C&I section of the Protocols for algorithms and other inputs.~~

Formatted: Font: Italic

Electric HVAC Systems

Replacement of existing electric HVAC equipment with high efficiency units is a proposed measure under the Direct Install Program. (See C&I C&I Energy Efficient Construction Electric HVAC Systems Protocols). The Direct Install savings protocol will be the same as previously stated in this document with the exception of the assumption for baseline efficiency. ~~For the Direct Install program, the following values will be used for the variable identified as EER_b. These age based efficiencies are used in estimating savings associated with the Direct Install Program because as an early replacement program, equipment is replaced as a direct result of the program.~~

Formatted: Heading 3

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font: Italic

Default Values for Mechanical System Efficiencies—Age-Based

Efficiency baselines are designed to reflect current market practices, which in this case reflect ASHRAE 90.1-2007. For the Direct Install program, the following values will be used for the variable identified as SEER_b, EER_b, COP_b, IPLV_b and HSPF_b.

HVAC Baseline Table – Direct Install

System Equipment Type	Units Baseline = ASHRAE Std. 90.1-2007	Pre-1992	1992- present
Unitary HVAC / Split Systems			
≤ 5.4 tons	SEER	9.10	10.00
Unitary HVAC/Split Systems and Single Package, Air Cooled		7.70	8.46
· ≤ 5.4 tons	13 SEER		
· > 5.4 to 11.25 tons	11 EER		
· > 11.25 to 20 tons	10.8 EER		

Deleted Cells

Formatted: Table Header

Deleted Cells

Formatted: Table Header, Indent: Left: 0.1"

Formatted Table

Formatted: Font: Arial, 10 pt, Not Bold

Formatted: Font: Arial, 10 pt, Not Bold

Deleted Cells

Deleted Cells

Formatted Table

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Table Cells

Formatted: Font: Arial, 10 pt

Formatted: Font: Arial, 10 pt

Formatted: Table Cells, Indent: Left: 0.1"

System Equipment Type	Units Baseline = ASHRAE Std. 90.1-2007	Pre-1992	1992-present
11.25 – 20 tons	EER	7.56	8.31
Air-Air Heat Pump Systems			
≤ 5.4 tons	SEER	9.10	10.00
Air-Air Cooled Heat Pump Systems, Split System and Single Package		7.56	8.31
· ≤ 5.4 tons	13 SEER, 7.7 HSPF		
· > 5.4 to 11.25 tons	10.8 EER, 3.3 heating COP		
· > 11.25 to 20 tons	10.4 EER, 3.2 heating COP		
Packaged Terminal Systems			
< 0.74 tons	EER	8.03	8.50
0.75 – 1 ton	EER	7.80	8.26
> 1 ton	EER	7.50	7.94
Water Source Heat Pumps All Capacities	12.0 EER		
All Capacities	EER	9.45	10.00

Source: Based on the 2006 Mortgage Industry National Home Energy Ratings Systems Standards, Table 303.7.1(3) Default Values for Mechanical System Efficiencies (Age-based), RESNET.

NOTE— The age-based efficiencies in the above table have been interpolated from RESNET standards and current baseline figures utilized in NJ C&I Energy Efficiency Rebate programs. With no equivalent resource available specific to small commercial equipment, these combined resources reflect the closest approximation to typical efficiencies of mechanical equipment present in Direct Install project facilities. The Direct Install program is targeted towards small commercial customers. As such, eligible equipment must not exceed a maximum capacity determined to be commonplace in the small C&I sector. In most cases, these capacity ranges correlate well with equipment certified by AHRI under the designation “Residential”.

Motors [Inactive 2017, Not Reviewed]

Replacement of existing motors with high efficiency units is a proposed measure under the Direct Install Program. (See C&I Construction Motors Protocols). The savings protocol will be the same as previously stated in this document with the exception of the assumption for baseline efficiency. For the Direct Install program, the following values will be used for the variable identified as η_{base} . These efficiencies are used in estimating savings associated with the Direct Install Program because as an early replacement program, equipment is replaced as a direct result of the program.

- Deleted Cells
- Formatted: Table Header
- Deleted Cells
- Formatted: Table Header, Indent: Left: 0.1"
- Formatted Table
- Formatted: Font: Arial, 10 pt, Not Bold
- Formatted: Font: Arial, 10 pt, Not Bold
- Deleted Cells
- Deleted Cells
- Formatted Table
- Formatted: Font: Arial, 10 pt
- Formatted: Font: Arial, 10 pt
- Formatted: Font: Arial, 10 pt
- Formatted: Table Cells, Indent: Left: 0.1"
- Formatted: Font: Arial, 10 pt
- Formatted: Table Cells
- Formatted: Font: Arial, 10 pt
- Formatted: Font: Arial, 10 pt
- Formatted Table
- Inserted Cells
- Formatted: Font: Arial, 10 pt, Underline
- Formatted: Table Cells, Right: 0.61"

Formatted: Heading 3

Motor HP	Baseline Efficiency
1	0.75
1.5	0.775
2	0.80
3	0.825
5	0.84
7.5	0.845
10	0.85
>10	Use EPA Act Baseline Motor Efficiency Table on pg. 72

Formatted Table

Source: *Opportunities for Energy Savings in the Residential and Commercial Sectors with High-Efficiency Electric Motors*, US DOE, 1999, Figure 4-4, page 4-5.

Formatted: Font: Not Bold

Variable Frequency Drives

Formatted: Heading 3

Installation of variable frequency motor drive systems is a proposed measure under the ~~the Direct Install Program. (See C&I Commercial and Industrial Energy Efficient Construction Motors Protocols).~~ Because there is no baseline assumption included in the protocols for this measure, the savings protocol will be exactly the same as previously stated in this document.

Refrigeration Measures

Formatted: Heading 3

~~Walk-in Cooler/Freezer Evaporator Fan Control~~

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Don't keep with next

~~This measure is applicable to existing walk-in coolers and freezers that have evaporator fans which run continuously. The measure adds a control system feature to automatically shut off evaporator fans when the cooler's thermostat is not calling for cooling. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein. These savings take into account evaporator fan shut off and associated savings as a result of less heat being introduced into the walk-in, as well as the savings from the compressor, which is now being controlled through electronic temperature control.~~

Formatted: Space Before: 6 pt, After: 6 pt

~~Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field-tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.~~

Algorithms

~~Gross kWh Savings = kWh Savings_{EL} + kWh Savings_{RH} + kWh Savings_{EC}~~

Formatted: Indent: First line: 0.25"

~~kWh Savings_{EF} = ((Amps_{EL} * Volts_{EL} * (Phase_{EL})^{1/2}) / 1000) * 0.55 * 8,760 * 35.52%~~

Formatted: Indent: First line: 0.25"

~~kWh Savings_{RH} = kWh Savings_{EL} * 0.28 * 1.6~~

Formatted: Indent: First line: 0.25"

~~kWh Savings_{EC} = (((Amps_{CF} * Volts_{CF} * (Phase_{CF})^{1/2}) / 1000) * 0.85 * ((35% * WH) + (55% * NWH)) * 5%) + (((Amps_{EL} * Volts_{EL} * (Phase_{EL})^{1/2}) / 1000) * 0.55 * 8,760 * 35.52% * 5%)~~

Formatted: Indent: Left: 0.25"

~~Gross kW Savings = ((Amps_{EL} * Volts_{EL} * (Phase_{EL})^{1/2}) / 1000) * 0.55 * D~~

Formatted: Indent: First line: 0.25"

Definition of Variables

Formatted: Heading 4

kWh Savings_{EF} = Savings due to installation of the following refrigeration measures are proposed under the Commercial and Industrial Energy Efficient Construction Program. Because there is no baseline assumption included in the protocols for these measures, the savings protocol will be exactly the same as previously stated in this document.

Walk-in Cooler/Freezer Evaporator Fan being off Control

Formatted: Heading 4, Indent: Left: 0", Space Before: 3 pt, After: 3 pt

kWh Savings_{RH} = Savings due to reduced heat from Cooler and Freezer Door Heater Control

Electric Defrost Control

Aluminum Night Covers

Novelty Cooler Shutoff

Energy Efficient Glass Doors on Open Refrigerated Cases

ECM on Evaporator Fans

Formatted: Heading 4, Indent: Left: 0", Space Before: 3 pt, After: 3 pt

~~kWh Savings_{EC} = Savings due to the electronic controls on compressor and evaporator~~

~~Amps_{EF} = Nameplate Amps of Evaporator Fan~~

~~Volts_{EF} = Nameplate Volts of Evaporator Fan~~

~~Phase_{EF} = Phase of Evaporator Fan~~

~~0.55 = Evaporator Fan Motor power factor.~~

8,760 = Annual Refrigerated Vending Machine Control

Refrigerated Case LED Lighting (Prescriptive Lighting)

Vending Machine Controls

This measures outlines the deemed savings for the installation of a gas-fired low intensity infrared heating system in place of unit heater, furnace, or other standard efficiency equipment

Algorithms

Electric Savings (kWh/yr) = kW_v * Hrs * SF

Peak Demand Savings (kW) = kW_v * SF

Definition of Variables

kW_v = Connected kW of equipment

Hrs = Operating Hours of equipment

35.52%SF = Percent of time Evaporator Fan is turned off.² savings factor of equipment

0.28 = Conversion from kW to tons (Refrigeration).

1.6 = Efficiency of typical refrigeration system in kW/ton.³

Amps_{CP} = Nameplate Amps of Compressor

Volts_{CP} = Nameplate Volts of Compressor

Phase_{CP} = Phase of Compressor

0.85 = Compressor power factor.

35% = Compressor duty cycle during winter months (estimated)

WH = Compressor hours during winter months (2,195)

55% = Compressor duty cycle during non-winter months (estimated)

NWH = Compressor hours during non-winter months (6,565)

5% = Reduced run-time of Compressor and Evaporator due to electronic controls.⁴

D = 0.228 or Diversity Factor⁵

Formatted: Indent: Left: 0", First line: 0.5", Space Before: 3 pt, After: 3 pt

Summary of Assumptions

<u>Variable</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>kW_v</u>	<u>Refrigerated beverage vending machine</u>	<u>0.4 kW</u>	<u>1</u>
	<u>Non-refrigerated snack vending machine</u>	<u>0.085 kW</u>	
	<u>Glass front refrigerated coolers</u>	<u>0.46 kW</u>	
<u>Hrs</u>	<u>Hours of operating of vending machine</u>	<u>Variable, default 8,760 hours</u>	<u>Application</u>
<u>SF</u>	<u>Refrigerated beverage vending machine</u>	<u>46%</u>	<u>1</u>
	<u>Non-refrigerated snack vending machine</u>	<u>46%</u>	
	<u>Glass front refrigerated coolers</u>	<u>30%</u>	

Sources:

(1) Several case studies related to NRM's Cooltrol system can be found at:
http://www.nrmine.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html

Formatted: Level 4, Space After: 6 pt, Keep with next

Formatted: Underline, (none)

~~(2) This value is an estimate by NRM based on hundreds of downloads of hours of use data from the electronic controller. It is an 'average' savings number and has been validated through several 3rd Party Impact Evaluation Studies including study performed by HEC, "Analysis of Walk in Cooler Air Economizers", Page 22, Table 9, October 10, 2000 for National Grid.~~

~~(3) 1. Select Energy Services, Inc. Cooler Control Measure Impact Spreadsheet User's Manual, 2004.~~

~~(4) 1. This percentage has been collaborated by several utility sponsored 3rd Party studies including study conducted by Select Energy Services for NSTAR, March 9, 2004.~~

~~(5) Based on the report "Savings from Walk In Cooler Air Economizers and Evaporator Fan Controls", HEC, June 28, 1996.~~

Formatted: Sources, Numbered + Level: 1 +
Numbering Style: 1, 2, 3, ... + Start at: 1 +
Alignment: Left + Aligned at: 0" + Indent at:
0.25"

Formatted: Font: Not Italic

~~Cooler and Freezer Door Heater Control~~

Formatted: Font: Not Italic

Formatted: Heading 3, None, Space Before: 0 pt, After: 6 pt, Page break before, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

~~This measure is applicable to existing walk-in coolers and freezers that have continuously operating electric heaters on the doors to prevent condensation formation. This measure adds a control system feature to shut off the door heaters when the humidity level is low enough such that condensation will not occur if the heaters are off. This is performed by measuring the ambient humidity and temperature of the store, calculating the dewpoint, and using PWM (pulse width modulation) to control the anti-sweat heaters based on specific algorithms for freezer doors. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.~~

~~Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field-tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.¹~~

Formatted: Font: Bold, Italic, No underline

Formatted: Space Before: 18 pt

~~*Low Temperature (Freezer) Door Heater Control*~~

Formatted: Heading 4

~~Algorithms~~

$$\text{kWh Savings} = (\text{kW}_{\text{DH}} * 8,760) - ((40\% * \text{kW}_{\text{DH}} * 4,000) + (65\% * \text{kW}_{\text{DH}} * 4,760))$$

$$\text{kW Savings} = \text{kW}_{\text{DH}} * 46\% * 75\%$$

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

~~Definition of Variables~~

Formatted: Heading 4

Formatted: Space Before: 3 pt, After: 3 pt

~~kW_{DH} = Total demand (kW) of the freezer door heaters, based on nameplate volts and amps.~~

~~8,760 = Annual run hours of Freezer Door Heater before controls.~~

~~40% = Percent of total run power of door heaters with controls providing maximum reduction.²~~

~~4,000 = Number of hours door heaters run at 40% power.~~

Formatted: Space Before: 3 pt, After: 3 pt

~~65% = Percent of total run power of door heaters with controls providing minimum reduction.²~~

~~4,760 = Number of hours door heaters run at 65% power.~~

~~46% = Freezer Door Heater off time.³~~

Formatted: Space Before: 3 pt, After: 3 pt

~~75% = Adjustment factor to account for diversity and coincidence at peak demand time.²~~

~~Medium Temperature (Cooler) Door Heater Control~~

Algorithms

$$\text{kWh Savings} = (\text{kW}_{\text{DH}} * 8,760) - (60\% * \text{kW}_{\text{DH}} * 3,760)$$

$$\text{kW Savings} = \text{kW}_{\text{DH}} * 74\% * 75\%$$

Definition of Variables

~~kW_{DH} = Total demand (kW) of the cooler door heaters, based on nameplate volts and amps.~~

~~8,760 = Annual run hours of Cooler Door Heater before controls.~~

~~60% = Percent of total run power of door heaters with controls providing minimum reduction.²~~

~~3,760 = Number of hours door heaters run at 60% power.~~

~~74% = Cooler Door Heater off time.³~~

~~75% = Adjustment factor to account for diversity and coincidence at peak demand time.²~~

Sources:

~~(1) Several case studies related to NRM's Cooltrol system can be found at:
http://www.nrmine.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html~~

~~(2) 1. Estimated by NRM based on their experience of monitoring the equipment at various sites.~~

~~(3) 1. This value is an estimate by National Resource Management based on hundreds of downloads of hours of use data from Door Heater controllers. This supported by 3rd Party Analysis conducted by Select Energy for NSTAR, "Cooler Control Measure Impact Spreadsheet Users' Manual", Page 5, March 9, 2004.~~

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: No underline

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: Space Before: 3 pt, After: 3 pt

Formatted: No underline

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li

Formatted: Space Before: 3 pt, After: 3 pt, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Sources, No bullets or numbering

Aluminum Night Covers

This measure is applicable to existing open type refrigerated display cases where considerable heat is lost through an opening that is directly exposed to ambient air. These retractable aluminum woven fabric covers provide a barrier between the contents of the case and the outside environment. They are employed during non-business hours to significantly reduce heat loss from these cases when contents need not be visible.

Savings approximations are based on the report, "Effects of the Low Emissivity Shields on performance and Power use of a refrigerated display case", by Southern California Edison, August 8, 1997. Southern California Edison (SCE) conducted this test at its state of the art Refrigeration Technology and Test Center (RTTC), located in Irwindale, CA. The RTTC's sophisticated instrumentation and data acquisition system provided detailed tracking of the refrigeration system's critical temperature and pressure points during the test period. These readings were then utilized to quantify various heat transfer and power related parameters within the refrigeration cycle. The results of SCE's test focused on three typical scenarios found mostly in supermarkets: low, medium and high temperature cases.

Algorithms

$$\text{kWh Savings} = W * H * F$$

Definition of Variables

W = Width of protected opening in ft.

H = Hours per year covers are in place

F = Savings factor based on case temperature:

Low temperature (-35F to -5F) F = 0.1 kW/ft

Medium temperature (0F to 30F) F = 0.06 kW/ft

High temperature (35F to 55F) F = 0.04 kW/ft

Electric Defrost Control

This measure is applicable to existing evaporator fans with a traditional electric defrost mechanism. This control system overrides defrost of evaporator fans when unnecessary, reducing annual energy consumption. The estimates for savings take into account savings from reduced defrosts as well as the reduction in heat gain from the defrost process.

Independent Testing was performed by Intertek Testing Service on a Walk-in Freezer that was retrofitted with Smart Electric Defrost capability. A baseline of 28 electric defrosts

Formatted: Font: Not Bold, Not Italic

Formatted: Heading 3, None, Space Before: 0 pt, After: 6 pt, Page break before, Don't keep with next

Formatted: Allow hanging punctuation, Font Alignment: Auto

Formatted: Underline, (none)

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Heading 4

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Heading 4

Formatted: Font: 12 pt

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Don't keep with next

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 12 pt, After: 12

~~per week were established as the baseline for a two week period without the Smart Electric Defrost capability. With Smart Electric Defrost capability an average skip rate of 43.64% was observed for the following two week period.~~

Algorithms

$$\text{Gross kWh Savings} = \text{kWh Savings}_{\text{Defrost}} + \text{kWh Savings}_{\text{RH}}$$

$$\text{kWh Savings}_{\text{Defrost}} = \text{KW}_{\text{Defrost}} * 0.667 * 4 * 365 * 35\%$$

$$\text{kWh Savings}_{\text{RH}} = \text{kWh Savings}_{\text{Defrost}} * 0.28 * 1.6$$

Definition of Variables

kWh Savings_{Defrost} = Savings due to reduction of defrosts

kWh Savings_{RH} = Savings due to reduction in refrigeration load

KW_{Defrost} = Nameplate Load of Electric Defrost

0.667 = Average Length of Electric Defrost in hours

4 = Average Number of Electric Defrosts per day

365 = Number of Days in Year

35% = Average Number of Defrosts that will be eliminated in year

0.28 = Conversion from kW to tons (Refrigeration)

1.6 = Efficiency of typical refrigeration system in kW/ton[†]

Sources:

(1) Select Energy Services, Inc. *Cooler Control Measure Impact Spreadsheet User's Manual*. 2004.

LED Lighting for Coolers and Freezers

~~This measure is applicable to existing walk-in and reach-in coolers and freezers with non-LED lighting. LED lighting is not only more efficient, but also provides higher quality lighting for cooler and freezer displays as they are more suited for cold environments. In addition, LEDs have a longer operating life than fluorescents in cooler and freezer applications, which results in reduced life cycle costs. The estimated savings for this measure take into account both reduced wattage of replacement lighting and reduced refrigeration load from lighting heat loss.~~

Algorithms

$$\text{kWh Savings} = (((\text{Watts}_B - \text{Watts}_{\text{LED}}) / 1000) * H) * (1 + (0.28 * 1.6))$$

$$\text{kW Savings} = ((\text{Watts}_B - \text{Watts}_{\text{LED}}) / 1000) * (1 + (0.28 * 1.6))$$

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: (none)

Formatted: Level 4, Keep with next

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Indent: First line: 0.25", Space Before: 6 pt, After: 6 pt

Formatted: Heading 4

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: No underline

Formatted: Underline, (none)

Formatted: Indent: First line: 0.25"

Formatted: Level 4, Keep with next

Formatted: (none)

Formatted: Indent: First line: 0.25"

Definition of Variables

~~Watts_B = Baseline Lighting Wattage~~

~~Watts_{LED} = LED Lighting Wattage~~

~~1000 = Conversion from W to kW~~

~~H = Lighting Operating Hours~~

~~0.28 = Conversion from kW to tons (Refrigeration)~~

~~1.6 = Efficiency of typical refrigeration system in kW/ton⁶⁸~~

Formatted: Heading 4

⁶⁸ ~~Select Energy Services, Inc. Cooler Control Measure Impact Spreadsheet User's Manual. 2004.~~

Novelty Cooler Shutoff

~~This measure is applicable to existing reach in novelty coolers which run continuously. The measure adds a control system feature to automatically shut off novelty coolers based on pre-set store operating hours. Based on programmed hours, the control mechanism shuts off the cooler at end of business, and begins operation on reduced cycles. Regular operation begins the following day an hour before start of business. The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.~~

~~Several case studies have been performed that verify the accuracy of these savings. The algorithms below are based on field tested approximations of energy savings realized through installation of National Resource Management Inc. (NRM)'s Cooltrol® energy management system.¹~~

Algorithms

$$kWh\ Savings = (((Amps_{NC} * Volts_{NC} * (Phase_{NC})^{1/2}) / 1000) * 0.85) * ((0.45 * ((CH - 1) * 91)) + (0.5 * ((CH - 1) * 274)))$$

Definition of Variables

~~Amps_{NC} = Nameplate Amps of Novelty Cooler~~

~~Volts_{NC} = Nameplate Volts of Novelty Cooler~~

~~Phase_{NC} = Phase of Novelty Cooler~~

~~0.85 = Novelty Cooler power factor²~~

~~0.45 = Duty cycle during winter month nights³~~

~~CH = Closed Store hours~~

~~91 = Number of days in winter months~~

~~0.5 = Duty cycle during non-winter month nights³~~

~~274 = Number of days in non-winter months~~

~~1. Massachusetts Technical Reference Manual, October 2015.~~

Sources:

~~(1) Several case studies related to NRM's Cooltrol system can be found at:
http://www.nrmine.com/national_resource_management_case_studies_cooltrol_cooler_control_systems.html~~

~~(2) 1. Estimated by NRM based on their experience of monitoring the equipment at various sites.~~

~~(3) Duty Cycles are consistent with 3rd Party study done by Select Energy for NSTAR "Cooler Control Measure Impact Spreadsheet Users' Manual", page 5, March 9, 2004.~~

Formatted: Heading 3, None, Space Before: 0 pt, After: 0 pt, Page break before, Don't keep with next

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Heading 4

Formatted: Heading 4

Formatted: No underline, (none)

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: No underline

Formatted: Sources, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0" + Indent at: 0.25"

Formatted: Heading 3

Gas ~~Space and~~ Water Heating Measures

Gas ~~Furnaces and~~ Boilers

Replacement of existing gas, oil, ~~or propane furnaces and~~ propane water heaters with high efficiency units is a proposed measure under the C&I Energy Efficient Construction GasHVAC Systems Protocols. The Direct Install savings protocol will be the same as previously stated in this document with the baselines designed to reflect current market practices, which in this case reflect ASHRAE 90.1-2007. These tables are included in the C&I Protocol.

Gas Space Heating Measures

Boilers

Replacement of existing gas, oil, and propane boilers with high efficiency units is a proposed measure under the Direct Install Program. (See C&I Energy Efficient Construction GasHVAC Systems Protocols). The Direct Install savings protocol will be the same as previously stated in this document with the exception of the assumption for baseline efficiency. ~~For the Direct Install program, the following values will be used for the variable identified as AFUE_b. These age-based efficiencies are used in estimating savings associated with the Direct Install Program because as an early replacement program, equipment is replaced as a direct result of the program.~~

Formatted: Space Before: 6 pt, After: 6 pt

Default Values for Mechanical System Efficiencies — Age-Based

Efficiency baselines are designed to reflect current market practices, which in this case reflect ASHRAE 90.1-2007. For the Direct Install program, the following values will be used for the variable identified as Eff_b.

Baseline Boiler Efficiencies (Eff_b)

<u>SystemBoiler Type</u>	<u>UnitsSize Category (kBtu input)</u>	<u>Pre-1992Standard 90.1-2007</u>	<u>1992-present</u>	
<u>Hot Water – Gas or Propane Furnacefired</u>	<u>< 300</u>	<u>80% AFUE</u>	<u>0.73</u>	<u>0.78</u>
	<u>> 300 and < 2,500</u>	<u>75% Et</u>		
<u>Hot Water – Oil fired</u>	<u>< 300</u>	<u>80% AFUE</u>		
	<u>> 300 and < 2,500</u>	<u>78% Et</u>		
<u>Steam – Gas or Propane</u>	<u>< 300</u>	<u>75% AFUE</u>	<u>0.70</u>	<u>0.80</u>

- Deleted Cells
- Formatted: Table Header
- Formatted Table
- Formatted: Table Header
- Deleted Cells
- Formatted: Table Cells
- Inserted Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted Table
- Inserted Cells
- Formatted: Table Cells
- Deleted Cells
- Deleted Cells

<u>Steam, all except natural draft</u>	<u>> 300 and < 2,500</u>	<u>75% Et</u>		
<u>Steam, natural draft</u>	<u>> 300 and < 2,500</u>	<u>75% Et</u>		
<u>Steam – Oil Furnace or Boiler fired</u>	<u>< 300</u>	<u>80% AFUE</u>	<u>0.77</u>	<u>0.80</u>
	<u>> 300 and < 2,500</u>	<u>78% Et</u>		

~~Source: 2006 Mortgage Industry National Home Energy Ratings Systems Standards, Table 303.7.1(3) Default Values for Mechanical System Efficiencies (Age-based), RESNET.~~

~~NOTE—The age-based efficiencies in the above table have been interpolated from RESNET standards and current baseline figures utilized in NJ C&I Energy Efficiency Rebate programs. With no equivalent resource available specific to small commercial equipment, these combined resources reflect the closest approximation to typical efficiencies of mechanical equipment present in Direct Install project facilities. The Direct Install program is targeted towards small commercial customers. As such, eligible equipment must not exceed a maximum capacity determined to be commonplace in the small C&I sector. In most cases, these capacity ranges correlate well with equipment certified by AHRI under the designation “Residential”.~~

~~Small Commercial Boilers [Inactive 2017, Not Reviewed]~~

~~This section will apply only for boilers that are closed loop and for space heating.~~

~~For Boilers that are under 5000 MBtuH use the calculator from the Federal Energy Management Program at:~~

~~http://www1.eere.energy.gov/femp/technologies/eep_boilers_calc.html~~

~~Gas, Oil, and Propane Infrared Heating Furnaces~~

~~Replacement of existing atmospherically vented heating with gas or oil and propane infrared heating is an available measure under the Direct Install Program. (See C&I Construction Gas Protocols).~~

~~Gas Water Heating~~

~~Replacement of existing gas furnaces and boilers with gas high efficiency units is a proposed measure under the Direct Install Program. (See C&I Energy Efficient Construction Gas HVAC Systems Protocols). The Direct Install savings protocol will be~~

- Formatted: Table Cells
- Deleted Cells
- Formatted Table
- Deleted Cells
- Inserted Cells
- Formatted: Table Cells
- Formatted: Font: Not Bold, Not Italic

- Formatted: Font: Not Bold, Not Italic
- Formatted: Heading 3

- Formatted: Heading 3

- Formatted: Space Before: 6 pt, After: 6 pt

the same as previously stated in this document with the exception of the assumption for baseline efficiency. ~~For the Direct Install program, the following values will be used for the variable identified as EFF_b. These age-based efficiencies are used in estimating savings associated with the Direct Install Program because as an early replacement program, equipment is replaced as a direct result of the program.~~

Default Values for Water Heating System Efficiencies—Age-Based

Efficiency baselines are designed to reflect current market practices, which in this case reflect ASHRAE 90.1-2007. For the Direct Install program, the following values will be used for the variable identified as Eff_b.

Baseline Furnace Efficiencies (Eff_b)

Water Heater/Furnace Type	Units/Size Category (kBtu input)	Pre-1992 Standard 90.1-2007	1992–present
Gas Fired	EF < 225	0.5378%	0.56
Oil Fired	EF < 225	0.578%	0.56

Electric	EF	0.87	0.88
----------	----	------	------

~~Source: 2006 Mortgage Industry National Home Energy Ratings Systems Standards, Table 303.7.1(3) Default Values for Mechanical System Efficiencies (Age-based), RESNET.~~

~~NOTE— The age-based efficiencies in the above table have been interpolated from RESNET standards and current baseline figures utilized in NJ C&I Energy Efficiency Rebate programs. With no equivalent resource available specific to small commercial equipment, these combined resources reflect the closest approximation to typical efficiencies of mechanical equipment present in Direct Install project facilities. The Direct Install program is targeted towards small commercial customers. As such, eligible equipment must not exceed a maximum capacity determined to be commonplace in the small C&I sector. In most cases, these capacity ranges correlate well with equipment certified by AHRI under the designation “Residential”.~~

Food

Infrared Heating

Replacement of existing atmospherically vented heating with infrared heating is a proposed measure under *Commercial and Industrial Energy Efficient Construction*. Because this is a deemed savings measure the protocol will be exactly the same as previously stated in this document.

- Deleted Cells
- Formatted: Table Header
- Formatted Table
- Formatted: Table Header
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells

Programmable Thermostats

This measure provides savings algorithms for programmable thermostats installed through the direct install program in commercial buildings. The baseline for this measure is manual thermostats that require occupant adjustment to change the space temperature. Non-communicating programmable thermostats achieve energy savings over manual thermostats by automatically setting temperatures back in the winter, or up in the summer, per a factory default schedule, or a user modified schedule. Setback/set up schedules achieve heating fuel savings in the winter, and cooling electric savings in the summer.

The savings factors for this measure come from the Michigan Energy Measures Database (MEMD), which shows deemed cooling and heating savings per 1,000 square feet of building space. The MEMD savings values for programmable thermostats were determined through measurement and verification of installed thermostats in a variety of commercial building types. For this measure, values for the Detroit airport locale are used because the ambient temperatures are closest to those for the New Jersey locale, and results are averaged across HVAC equipment types.

There are no peak demand savings for this measure, and motel and auto repair space types are excluded from this measure.

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = \text{SQFT}_{1000} * \text{SF}_{\text{heat}}$$

$$\text{Energy Savings (kWh/yr)} = \text{SQFT}_{1000} * \text{SF}_{\text{cool}}$$

Definition of Variables

~~Energy efficient electric or natural gas cooking equipment of the following listed types utilized in commercial food service applications which have performance rated in accordance with the listed ASTM standards:~~

- ~~• Electric combination and convection ovens — ASTM 1639 F~~
- ~~• Gas combination and convection ovens — ASTM 1639 F~~
- ~~• Gas conveyor and rack ovens — ASTM 1817 F~~
- ~~• Electric and gas small vat fryers — ASTM 1361 F~~
- ~~• Electric and gas large vat fryers — ASTM 2144 F~~
- ~~• Electric and gas steamers — ASTM 1484 F~~

Formatted: (none)

Formatted: Right: -0.38", Space Before: 6 pt, After: 6 pt

- ~~Electric and gas griddles—ASTM 1275-F~~
- ~~Hot food holding cabinets—ATM F2140-11~~

Electric and Gas Combination Oven/Steamer

The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Algorithms

$$\text{Annual Energy Savings (kWh or Therms)} = D * (E_p + E_{ie} + E_{is} + E_{ce} + E_{es})$$

$$\text{Demand Savings (kW)} = \text{kWh Savings} / (D * H)$$

$$\text{Preheat Savings}^\ddagger: E_p = P * (PE_b - PE_q)$$

$$\text{Convection Mode Idle Savings}^\ddagger: E_{ie} = (I_{eb} - I_{eq}) * ((H - (P * P_i)) - (I_{eb} / PC_{eb} - I_{eq} / PC_{eq}) * Lbs) * (1 - S_i)$$

$$\text{Steam Mode Idle Savings}^\ddagger: E_{is} = (I_{sb} - I_{sq}) * ((H - (P * P_i)) - (I_{sb} / PC_{sb} - I_{sq} / PC_{sq}) * Lbs) * S_i$$

$$\text{Convection Mode Cooking Savings: } E_{ce} = Lbs * (1 - S_i) * Heat_c * (1 / Eff_{eb} - 1 / Eff_{eq}) / C$$

$$\text{Steam Mode Cooking Savings: } E_{es} = Lbs * S_i * Heat_s * (1 / Eff_{sb} - 1 / Eff_{sq}) / C$$

‡ For gas equipment, convert these intermediate values to therms by dividing the result by 100,000 Btu/therm

Definition of Variables (See tables of values below for more information)

D = Operating Days per Year

PSQFT₁₀₀₀ = Number of Preheats per Day thousands of square feet of building space⁶⁹

PE_b = Baseline Equipment Preheat Energy

PE_q = Qualifying Equipment Preheat Energy

I_{eb} = Baseline Equipment Convection Mode Idle Energy Rate

I_{eq} = Qualifying Equipment Convection Mode Idle Energy Rate

H = Daily Operating Hours

P_i = Preheat Duration

PC_{eb} = Baseline Equipment Convection Mode Production Capacity

⁶⁹ For example, a 5,000 ft² building would have a SQFT₁₀₀₀ value of 5

Formatted: Heading 4

Formatted: (none)

Formatted: Level 4, Keep with next, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: Left: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: (none)

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt, Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

PC_{cq} = Qualifying Equipment Convection Mode Production Capacity
 Lbs = Total Daily Food Production
 S_t = Percentage of Time in Steam Mode
 I_{sb} = Baseline Equipment Steam Mode Idle Energy Rate
 I_{sq} = Qualifying Equipment Steam Mode Idle Energy Rate
 PC_{sb} = Baseline Equipment Steam Mode Production Capacity
 PC_{sq} = Qualifying Equipment Steam Mode Production Capacity
 $Heat_c$ = Convection Mode Heat to Food
 Eff_{cb} = Baseline Equipment Convection Mode Cooking Efficiency
 Eff_{cq} = Qualifying Equipment Convection Mode Cooking Efficiency
 C = Conversion Factor from Btu to kWh or Therms
 $Heat_s$ = Steam Mode Heat to Food
 Eff_{sb} = Baseline Equipment Steam Mode Cooking Efficiency
 Eff_{sq} = Qualifying Equipment Steam Mode Cooking Efficiency

Table 1: Electric Combination Oven/Steamers						
Variable	Baseline			Qualifying		
	<15 Pans	15-28 Pans	>28 Pans	<15 Pans	15-28 Pans	>28 Pans
D - Operating Days per Year	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P - Number of Preheats per Day	1	1	1	1	1	1
PE _b & PE _q - Preheat Energy (kWh)	3.00	3.75	5.63	1.50	2.00	3.00
I _{cb} & I _{cq} - Convection Mode Idle Energy Rate (kW)	3.00	3.75	5.25	Application	Application	Application
H - Operating Hours per Day	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25	0.25	0.25
PC _{cb} & PC _{cq} - Convection Mode Prod. Capacity (lbs/hr)	80	100	275	100	125	325
Lbs - Total Daily Food Production (lbs)	200	250	400	200	250	400
S _t - Percentage of Time in Steam Mode	50%	50%	50%	50%	50%	50%
I _{sb} & I _{sq} - Steam Mode Idle Energy Rate (kW)	10.0	12.5	18.0	Application	Application	Application
PC _{sb} & PC _{sq} - Steam Mode Prod. Capacity (lbs/hr)	100	150	350	120	200	400
Heat _c - Convection Heat to Food (Btu/lb)	250	250	250	250	250	250
Eff _{cb} & Eff _{cq} - Convection Mode Cooking Efficiency	65%	65%	65%	Application	Application	Application
C - Btu/kWh	3,412	3,412	3,412	3,412	3,412	3,412
Heat _s - Steam Heat to Food (Btu/lb)	105	105	105	105	105	105
Eff _{sb} & Eff _{sq} - Steam Mode Cooking Efficiency	40%	40%	40%	Application	Application	Application

Table 2: Gas Combination Oven/Steamers						
Variable	Baseline			Qualifying		
	<15 Pans	15-28 Pans	>28 Pans	<15 Pans	15-28 Pans	>28 Pans
D - Operating Days per Year	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P - Number of Preheats per Day	1	1	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	18,000	22,000	32,000	13,000	16,000	24,000
I _{cb} & I _{cq} - Convection Mode Idle Energy Rate (Btu/h)	15,000	20,000	30,000	Application	Application	Application
H - Operating Hours per Day	Table 3	Table 3	Table 3	Table 3	Table 3	Table 3
P _t - Preheat Duration (h)	0.25	0.25	0.25	0.25	0.25	0.25
PC _{cb} & PC _{cq} - Convection Mode Prod. Capacity (lbs/h)	80	100	275	100	125	325
Lbs - Total Daily Food Production (lbs)	200	250	400	200	250	400
S _t - Percentage of Time in Steam Mode	50%	50%	50%	50%	50%	50%
I _{sb} & I _{sq} - Steam Mode Idle Energy Rate (kW)	45,000	60,000	80,000	Application	Application	Application
PC _{sb} & PC _{sq} - Steam Mode Prod. Capacity (lbs/h)	100	150	350	120	200	400
Heat _c - Convection Heat to Food (Btu/lb)	250	250	250	250	250	250
Eff _{cb} & Eff _{cq} - Convection Mode Cooking Efficiency	35%	35%	35%	Application	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000	100,000	100,000
Heat _s - Steam Heat to Food (Btu/lb)	105	105	105	105	105	105
Eff _{sb} & Eff _{sq} - Steam Mode Cooking Efficiency	20%	20%	20%	Application	Application	Application

Table 3: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Sources:

Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.

Formatted: No underline

~~Electric and Gas Convection Ovens, Gas Conveyor and Rack Ovens, Steamers, Fryers, and Griddles~~

~~The measurement of energy savings for these measures are based on algorithms with key variables provided by manufacturer data or prescribed herein.~~

~~Algorithms~~

~~Annual Energy Savings SF_{heat} = Heating savings factor (MMBtu per 1,000 ft² of building space)~~

~~SF_{cool} = Cooling savings factor (kWh or Therms) = $D * (E_p + E_i + E_c)$~~

~~Demand Savings (kW) = kWh Savings / (D * H)~~

~~Preheat Savings †: $E_p = P * (PE_b - PE_q)$~~

~~Idle Savings †: $E_i = (I_b - I_q) * ((H - (P * P_i)) - (I_b / PC_b - I_q / PC_q)) * Lbs$~~

~~Cooking Savings: $E_c = Lbs * Heat * (1 / Eff_b - 1 / Eff_q) / C$~~

~~† For gas equipment, convert these intermediate values to therms by dividing the result by 100,000 Btu/therm~~

~~Definition of Variables (See tables of values below for more information)~~

~~D = Operating Days per Year~~

~~P = Number of Preheats per Day~~

~~PE_b = Baseline Equipment Preheat Energy~~

~~PE_q = Qualifying Equipment Preheat Energy~~

~~I_b = Baseline Equipment Idle Energy Rate~~

~~I_q = Qualifying Equipment Idle Energy Rate~~

~~H = Daily Operating Hours~~

~~P_i = Preheat Duration~~

~~PC_b = Baseline Equipment Production Capacity~~

~~PC_q = Qualifying Equipment Production Capacity~~

~~Lbs = Total Daily Food Production~~

~~Heat = Heat to Food~~

~~Eff_b = Baseline Equipment Convection Mode Cooking Efficiency~~

~~Eff_q = Qualifying Equipment Convection Mode Cooking Efficiency~~

~~C = Conversion Factor from Btu to kWh or Therms~~

Formatted: Heading 4, Space Before: 6 pt

Formatted: Don't allow hanging punctuation, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Font Alignment: Baseline

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: Indent: First line: 0.25"

Formatted: No underline

Table 1: Electric Convection Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Full Size</i>	<i>Half Size</i>	<i>Full Size</i>	<i>Half Size</i>
D - Operating Days per Year	Table 11	Table 11	Table 11	Table 11
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.50	1.00	1.00	0.90
I _b & I _q - Idle Energy Rate (kW)	2.00	1.50	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	70	45	82	53
Lbs - Total Daily Food Production (lbs)	100	100	100	100
Heat - Heat to Food (Btu/lb)	250	250	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	65%	65%	Application	Application
C - Btu/kWh	3,412	3,412	3,412	3,412

Table 2: Gas Convection Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Full Size</i>	<i>Half Size</i>	<i>Full Size</i>	<i>Half Size</i>
D - Operating Days per Year	Table 11	Table 11	Table 11	Table 11
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	19,000	13,000	11,000	7,500
I _b & I _q - Idle Energy Rate (Btu/h)	18,000	12,000	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	70	45	83	55
Lbs - Total Daily Food Production (lbs)	100	100	100	100
Heat - Heat to Food (Btu/lb)	250	250	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	30%	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000

Table 3: Gas Conveyor Ovens		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	35,000	18,000
I _b & I _q - Idle Energy Rate (Btu/hr)	70,000	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	114	167
Lbs - Total Daily Food Production (lbs)	190	190
Heat - Heat to Food (Btu/lb)	250	250
Eff _b & Eff _q - Heavy Load Cooking Efficiency	20%	Application
C - Btu/Therm	100,000	100,000

Table 4: Gas Rack Ovens				
<i>Variable</i>	<i>Baseline</i>		<i>Qualifying</i>	
	<i>Double Rack</i>	<i>Single Rack</i>	<i>Double Rack</i>	<i>Single Rack</i>
D - Operating Days per Year	Table 11	Table 11	Table 5	Table 5
P - Number of Preheats per Day	1	1	1	1
PE _b & PE _q - Preheat Energy (Btu)	100,000	50,000	85,000	44,000
I _b & I _q - Idle Energy Rate (Btu/h)	65,000	43,000	Application	Application
H - Operating Hours per Day	Table 11	Table 11	Table 5	Table 5
P _t - Preheat Duration (hrs)	0.33	0.33	0.33	0.33
PC _b & PC _q - Production Capacity (lbs/hr)	250	130	280	140
Lbs - Total Daily Food Production (lbs)	1200	600	1200	600
Heat - Heat to Food (Btu/lb)	235	235	235	235
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	30%	Application	Application
C - Btu/Therm	100,000	100,000	100,000	100,000

Table 5: Electric Steamers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.50	1.50
I _b & I _q - Idle Energy Rate (kW)	0.167 x No. of Pans	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	11.7 x No. of Pans	14.7 x No. of Pans
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	105	105
Eff _b & Eff _q - Heavy Load Cooking Efficiency	26%	Application
C - Btu/kWh	3,412	3,412

Table 6: Gas Steamers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	20,000	9,000
I _b & I _q - Idle Energy Rate (Btu/h)	2,500 x No. of Pans	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	23.3 x No. of Pans	20.8 x No. of Pans
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	105	105
Eff _b & Eff _q - Heavy Load Cooking Efficiency	15%	Application
C - Btu/Therm	100,000	100,000

Table 7: Electric Fryers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	2.40	1.90
I _b & I _q - Idle Energy Rate (kW)	1.2	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	71	71
Lbs - Total Daily Food Production (lbs)	150	150
Heat - Heat to Food (Btu/lb)	570	570
Eff _b & Eff _q - Heavy Load Cooking Efficiency	75%	Application
C - Btu/kWh	3,412	3,412

Table 8: Gas Fryers		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	18,500	16,000
I _b & I _q - Idle Energy Rate (Btu/h)	17,000	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	75	75
Lbs - Total Daily Food Production (lbs)	150	150
Heat - Heat to Food (Btu/lb)	570	570
Eff _b & Eff _q - Heavy Load Cooking Efficiency	35%	Application
C - Btu/Therm	100,000	100,000

Table 9: Electric Griddles		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (kWh)	1.3 x Griddle Width (ft)	0.7 x Griddle Width (ft)
I _b & I _q - Idle Energy Rate (kW)	0.8 x Griddle Width (ft)	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	11.7 x Griddle Width (ft)	13.3 x Griddle Width (ft)
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	475	475
Eff _b & Eff _q - Heavy Load Cooking Efficiency	60%	Application
C - Btu/kWh	3,412	3,412

Table 10: Gas Griddles		
<i>Variable</i>	<i>Baseline</i>	<i>Qualifying</i>
D - Operating Days per Year	Table 11	Table 11
P - Number of Preheats per Day	1	1
PE _b & PE _q - Preheat Energy (Btu)	7,000 x Griddle Width (ft)	5,000 x Griddle Width (ft)
I _b & I _q - Idle Energy Rate (Btu/h)	7,000 x Griddle Width (ft)	Application
H - Operating Hours per Day	Table 11	Table 11
P _t - Preheat Duration (hrs)	0.25	0.25
PC _b & PC _q - Production Capacity (lbs/hr)	8.3 x Griddle Width (ft)	15 x Griddle Width (ft)
Lbs - Total Daily Food Production (lbs)	100	100
Heat - Heat to Food (Btu/lb)	475	475
Eff _b & Eff _q - Heavy Load Cooking Efficiency	30%	Application
C - Btu/Therm	100,000	100,000

Table 11: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Sources:

Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website; www.fishnick.com, by Fisher Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.

Formatted: No underline

Insulated Food Holding Cabinets

The measurement of energy savings for this measure is based on algorithms with key variables provided by manufacturer data or prescribed herein.

Formatted: Tab stops: 1.03", Left

Algorithms

Formatted: Heading 4

Annual Energy Savings (kWh) = D * H * (I_b - I_q)

Demand Savings (kW) = I_b - I_q

Definition of Variables (See tables of values below for more information)

D = Operating Days per Year

H = Daily Operating Hours

I_b = Baseline Equipment Idle Energy Rate

I_q = Qualifying Equipment Idle Energy Rate

Table 1: Insulated Food Holding Cabinets						
Variable	Baseline			Qualifying		
	Full Size	3/4 Size	1/2 Size	Full Size	3/4 Size	1/2 Size
D - Operating Days per Year	Table 2	Table 2	Table 2	Table 2	Table 2	Table 2
I _b & I _q - Idle Energy Rate (kW)	1.00	0.69	0.38	Application	Application	Application
H - Operating Hours per Day	Table 2	Table 2	Table 2	Table 2	Table 2	Table 2

Table 2: Operating Days/Hours by Building Type		
Building Type	Days/Year	Hours/Day
Education - Primary School	180	8
Education - Secondary School	210	11
Education - Community College	237	16
Education - University	192	16
Grocery	364	16
Medical - Hospital	364	24
Medical - Clinic	351	12
Lodging Hotel (Guest Rooms)	229	5
Lodging Motel	364	24
Manufacturing - Light Industrial	330	13
Office - Large	234	12
Office - Small	234	12
Restaurant - Sit-Down	364	12
Restaurant - Fast-Food	364	17
Retail - 3-Story Large	355	12
Retail - Single-Story Large	364	12
Retail - Small	364	11
Storage Conditioned	330	13
Storage Heated or Unconditioned	330	13
Warehouse	325	12
Average = Miscellaneous	303	14

Sources:

Savings algorithm, baseline values, assumed values and lifetimes developed from information on the Food Service Technology Center program's website, www.fishnick.com, by Fisher Nickel, Inc. and funded by California utility customers and administered by Pacific Gas and Electric Company under the auspices of the California Public Utility Commission.

Formatted: No underline

Occupancy Controlled Thermostats

The program has received a large amount of custom electric applications for the installation of Occupancy Controlled Thermostats in hotels, motels, and, most recently, university dormitories. Due to the number of applications, consistent incentive amounts (\$75 per thermostat) and predictable savings of the technology TRC recommends that a prescriptive application be created for this technology.

Standard practice today is thermostats which are manually controlled by occupants to regulate temperature within a facility. An occupancy controlled thermostat is a thermostat paired with a sensor and/or door detector to identify movement and determine if a room is occupied or unoccupied. If occupancy is sensed by the sensor, the thermostat goes into an occupied mode (i.e. programmed setpoint). If a pre-programmed time frame elapses (i.e. 30 minutes) and no occupancy is sensed during that time, the thermostat goes into an unoccupied mode (e.g., setback setpoint or off) until occupancy is sensed again. This type of thermostat is often used in hotels to conserve energy.

Formatted: Space Before: 6 pt, After: 6 pt

The occupancy controlled thermostat reduces the consumption of electricity and/or gas by requiring less heating and/or cooling when a room or a facility is vacant or unoccupied.

Algorithms

$$\text{Cooling Energy Savings (kWh)} = (((T_c * (H+5) + S_c * (168 - (H+5)))/168) T_c) * (P_c * Cap_{hp} * 12 * EFLH_c / EER_{hp})$$

$$\text{Heating Energy Savings (kWh)} = (((T_h * (H+5) + S_h * (168 - (H+5)))/168) T_h) * (P_h * Cap_{hp} * 12 * EFLH_h / EER_{hp})$$

$$\text{Heating Energy Savings (Therms)} = (T_h - (T_h * (H+5) + S_h * (168 - (H+5)))/168) * (P_h * Cap_h * EFLH_h / AFUE_h / 1001,000 \text{ ft}^2 \text{ of building space})$$

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Underline

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

DefinitionSummary of VariablesInputs

Formatted: English (U.S.)

- T_h = Heating Season Facility Temp. (°F)
- T_c = Cooling Season Facility Temp. (°F)
- S_h = Heating Season Setback Temp. (°F)

S_e = Cooling Season Setup Temp. (°F)
 H = Weekly Occupied Hours
 Cap_{hp} = Connected load capacity of heat pump/AC (Tons) — Provided on Application.
 Cap_h = Connected heating load capacity (Btu/hr) — Provided on Application.
 $EFLH_c$ = Equivalent full load cooling hours
 $EFLH_h$ = Equivalent full load heating hours
 P_h = Heating season percent savings per degree setback
 P_e = Cooling season percent savings per degree setup
 $AFUE_h$ = Heating equipment efficiency — Provided on Application.
 EER_{hp} = Heat pump/AC equipment efficiency — Provided on Application
 $\dagger 2$ = Conversion factor from Tons to kBtu/hr to acquire consumption in kWh.
 $\dagger 68$ = Hours per week.
 5 = Assumed weekly hours for setback/setup adjustment period (based on 1 setback/setup per day, 5 days per week).

Occupancy Controlled Thermostats

Programmable Thermostat Assumptions

Component	Type	Value	Source
$SQFT_{1000}$	Variable	Customer specified	Application
SF_{heat}	Fixed	1.68 MMBtu / 1,000 ft ²	1
SF_{cool}	Fixed	74.7 kWh / 1,000 ft ²	1

Sources

T_h	Variable		Application
T_e	Variable		Application
S_h	Fixed	$T_h - 5^\circ$	
S_e	Fixed	$T_e + 5^\circ$	
H	Variable		Application; Default of 56 hrs/week
Cap_{hp}	Variable		Application
Cap_h	Variable		Application
$EFLH_c$	Fixed	381	1
$EFLH_h$	Fixed	900	PSE&G
P_h	Fixed	3%	2
P_e	Fixed	6%	2
$AFUE_h$	Variable		Application
EER_{hp}	Variable		Application

Sources:

1. JCP&L metered data from 1995-1999
2. ENERGY STAR Products website

Formatted: Heading 3, Left, Don't keep with next

Formatted: Table Header, Left, Don't keep with next

Formatted: Table Header, Left

Formatted Table

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Caption

Dual Enthalpy Economizers

Dual enthalpy economizers are used to control a ventilation system's outside air intake in order to reduce a facility's total cooling load. An economizer monitors the outside air to ensure that its temperature (sensible heat) and humidity (latent heat) are low enough to utilize outside air to provide cooling in place of the cooling system's compressor. This reduces the demand on the cooling system, lowering its usage hours, saving energy.

The measurement of energy savings associated with dual enthalpy economizers is based on algorithms with key variables provided through DOE-2 simulation modeling and ClimateQuest's economizer savings calculator. Savings are calculated per ton of connected cooling load. The baseline conditions are fixed damper for equipment under 5.4 tons and dry bulb economizer otherwise.

Algorithms

$$\text{Energy Savings (kWh)} = \text{OTF} * \text{SF} * \text{Cap} / \text{Eff}$$

$$\text{Demand Savings (kW)} = \text{Savings} / \text{Operating Hours}$$

1. Michigan Public Service Commission. *2017 Michigan Energy Measures Database (MEMD) with Weather Sensitive Weighting Tool*. Available for download at: http://www.michigan.gov/mpsc/0,4639,7-159-52495_55129---,00.html

Formatted: Table Caption

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Boiler Reset Controls

The following algorithm detail savings for installation of boiler reset control on commercial boilers. Energy savings are realized through a better control on boiler water temperature. Through the use of software settings, boiler reset controls use outside or return water temperature to control boiler firing and in turn the boiler water temperature.

The input values are based on data supplied by the utilities and customer information on the application form, confirmed with manufacturer data. Unit savings are deemed based on study results.

Algorithms

$$\text{Fuel Savings (MMBtu/yr)} = (\% \text{ Savings}) * (\text{EFLH}_h * \text{Cap}_{in}/\text{hr}) / 1,000 \text{ kBtu/MMBtu}$$

Definition of Variables

OTF = Operational Testing Factor

SF = Approximate savings factor based on regional temperature bin data (assume 4576 for equipment under 5.4 tons where a fixed damper is assumed for the baseline and 3318 for larger equipment where a dry bulb economizer is assumed for the baseline). (Units for savings factor are in kWh x rated EER per ton of cooling or kWh*EER/Ton)

Cap = Capacity of connected cooling load (tons)

Eff = Cooling equipment energy efficiency ratio (EER)

Operating Hours = 4,438 = Approximate number of economizer operating hours

Dual Enthalpy Economizers

% Savings = Estimated percentage reduction in heating load due to boiler reset controls (5%)

EFLH_h = The Equivalent Full Load Hours of operation for the average unit during the heating season

Cap_m = Input capacity of qualifying unit in kBtu/hr

Summary of Inputs

Boiler Reset Control Assumptions

Component	Type	Value	Source
OTF	Fixed	1.0 when operational testing is performed, 0.8 otherwise	
SF		4576 for equipment under 5.4 tons, 3318 otherwise	†

Formatted: Underline, (none)
Formatted: Normal, Level 4, Keep with next

Formatted: Don't keep with next
Formatted Table

Component	Type	Value	Source
Cap	Variable		Application
Eff	Variable		Application
Operating Hours	Fixed	4,438	2
% Savings	Fixed	5%	1
EFLH _h	Variable	See Table Below	2
Cap _{in}	Variable		Application

Formatted: Don't keep with next

Formatted Table

Small Commercial EFLH_h

<u>Building</u>	<u>EFLH_h</u>
<u>Assembly</u>	<u>603</u>
<u>Auto Repair</u>	<u>1910</u>
<u>Fast Food Restaurant</u>	<u>813</u>
<u>Full Service Restaurant</u>	<u>821</u>
<u>Light Industrial</u>	<u>714</u>
<u>Motel</u>	<u>619</u>
<u>Primary School</u>	<u>840</u>
<u>Religious Worship</u>	<u>722</u>
<u>Small Office</u>	<u>431</u>
<u>Small Retail</u>	<u>545</u>
<u>Warehouse</u>	<u>452</u>
<u>Other</u>	<u>681</u>

Multi-family EFLH_h by Vintage

<u>Facility Type</u>	<u>Prior to 1979</u>	<u>From 1979 to 2006</u>	<u>From 2007 through Present</u>
<u>Low-rise, Heating</u>	<u>757</u>	<u>723</u>	<u>503</u>
<u>High-rise, Heating</u>	<u>526</u>	<u>395</u>	<u>219</u>

Formatted: Indent: Left: 0.5", Space Before: 3 pt, After: 3 pt, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Sources:

3. DOE-2 Simulation Modeling
4. ClimateQuest Economizer Savings Calculator

Sources

1. GDS Associates, Inc. Natural Gas Energy Efficiency Potential in Massachusetts, 2009, p. 38 Table 6-4.
2. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Appendix G – Equivalent

Full-Load Hours (EFLH), For Heating and Cooling. Page 535-540. EFLH values for NYC due to proximity to NJ.

Dual Enthalpy Economizers

Installation of Dual Enthalpy Economizers is a proposed measure under the Commercial and Industrial Energy Efficient Construction. Because there is no baseline assumption included in the protocols for this measure, the savings protocol will be exactly the same as previously stated in this document.

Electronic Fuel-Use Economizers (Boilers, Furnaces, AC)

These devices are microprocessor-based fuel-saving controls for commercial HVAC. They optimize energy consumption by adjusting burner or compressor run patterns to match the system's load. They can be used to control gas or oil consumption for any type of boiler or forced air furnace system. ~~There are also fuel use economizers available that control the electric consumption for commercial air conditioning and refrigeration units by optimizing compressor cycles to maximize energy efficiency.~~⁴ Installation of variable Fuel Use Economizers is a proposed measure under the Commercial and Industrial Energy Efficient Construction. Because there is no baseline assumption included in the protocols for this measure, the savings protocol will be exactly the same as previously stated in this document.

Formatted: Heading 3, Space Before: 18 pt

Demand-Controlled Ventilation Using CO₂ Sensors

Maintaining acceptable air quality requires standard ventilation systems designers to determine ventilation rates based on maximum estimated occupancy levels and published CFM/occupant requirements. During low occupancy periods, this approach results in higher ventilation rates than are required to maintain acceptable levels of air quality. This excess ventilation air must be conditioned and therefore results in wasted energy.

Building occupants exhale CO₂, and the CO₂ concentration in the air increases in proportion to the number of occupants. The CO₂ concentration provides a good indicator of overall air quality. Demand control ventilation (DCV) systems monitor indoor air CO₂ concentrations and use this data to automatically modulate dampers and regulate the amount of outdoor air that is supplied for ventilation. DCV is most suited for facilities where occupancy levels are known to fluctuate considerably.

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

~~A recent study of Fuel use economizer controls by the New York State Energy Research and Development Authority (NYSERDA) in conjunction with Brookhaven National Laboratories (BNL) found that the typical energy savings for these devices generally varies between 10.08% and 19.15%, when used under normal operating conditions and normalized for typical annual degree-days in the New York metro area.² The NYSERDA study tested at each of the different models of fuel use economizers manufactured by *Intellidyne, LLC*, (under the brand name *IntelliCon*). Operational data was recorded for various commercial heating, cooling, and refrigeration systems (of different sizes and fuel types) with and without the *IntelliCon* fuel use economizers added. The average energy savings across all system and fuel types and operational conditions was found to be 13%. Another study of *IntelliCon* fuel use economizers by Consolidated Edison, Inc. (ConEd) found a similar range of savings for the devices when the devices were studied as a control option for commercial refrigeration units at supermarkets in New York City and the surrounding area.³~~

~~Test results in both studies showed a very good payback for the devices across all applications studied. However, no discernable pattern was evident to determine which installations are most likely to yield the highest savings. Though actual savings will vary somewhat from project to project, it is reasonable to assume that program wide energy savings across all approved fuel use economizers measures will likely be close to the average savings found in the NYSERDA study. Annual energy savings for each approved fuel use economizer installation (for any *IntelliCon* brand or equivalent devices) can be estimated as simply 13% of the expected annual energy usage for the HVAC (or refrigeration) system without the device.~~

The magnitude of energy savings associated with DCV is a function of the type of facility, hours of operation, occupancy schedule, ambient air conditions, space temperature set points, and the heating and cooling system efficiencies. Typical values representing this factors were used to derive deemed savings factors per CFM of the

design ventilation rate for various space types. These deemed savings factors are utilized in the following algorithms to predict site specific savings.

Algorithms

Electric Energy Savings (kWh) = (AEU * 0.13) / yr = CESF * CFM

Peak Demand Savings (kW) = CDSF * CFM

Fuel Savings (MMBtu) = (AFU * 0.13) / yr = HSF * CFM

Definition of Variables

AEU = Annual Electric Usage for an uncontrolled AC or refrigeration unit (kWh)

AFU = Annual Fuel Usage for an uncontrolled (gas, oil, propane) HVAC unit (MMBtu or gallons)

CESF = Cooling Sources

(1) Some examples of the different types of fuel use economizer controls available on the market can be found at: http://www.intelldynelle.com/02_prods.htm

(2) NYSERDA (2007) "A Technology Demonstration and Validation Project for Intellidyne Energy Saving Controls".

(3) ConEd Solutions (2000) "Report Energy Savings Factor (kWh/CFM)

CDSF = Cooling Demand Savings Factor (kW/CFM)

HSF = Heating Savings Factor (MMBtu/CFM)

CFM = Baseline Design Ventilation Rate of Controlled Space (CFM)

Summary of Inputs

<u>Demand Controlled Ventilation Using CO₂ Sensors Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>CESF</u>	<u>Fixed</u>	<u>0.0484 MMBtu/CFM See Table 2</u>	<u>1</u>
<u>CDSF</u>	<u>Fixed</u>		<u>1</u>
<u>HSF</u>	<u>Fixed</u>		<u>1</u>
<u>CFM</u>	<u>Variable</u>		<u>Application</u>

Formatted: (none)

Formatted: Indent: First line: 0.25", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Subscript

Formatted: Indent: First line: 0", Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font

Formatted: Font: +Body (Calibri), 11 pt

Formatted: English (U.S.)

Formatted: No underline

Savings Factors for Demand-Controlled Ventilation Using CO₂ Sensors

<u>Component</u>	<u>CESF</u>	<u>CDSF</u>	<u>HSF</u>
<u>Assembly</u>	<u>2.720</u>	<u>0.0014</u>	<u>0.074</u>
<u>Auditorium – Community Center</u>	<u>1.500</u>	<u>0.0015</u>	<u>0.043</u>
<u>Gymnasium</u>	<u>2.558</u>	<u>0.0013</u>	<u>0.069</u>
<u>Office Building</u>	<u>2.544</u>	<u>0.0013</u>	<u>0.068</u>
<u>Elementary School</u>	<u>1.079</u>	<u>0.0013</u>	<u>0.029</u>
<u>High School</u>	<u>2.529</u>	<u>0.0015</u>	<u>0.072</u>
<u>Shopping Center</u>	<u>1.934</u>	<u>0.0012</u>	<u>0.050</u>
<u>Other</u>	<u>2.544</u>	<u>0.0013</u>	<u>0.068</u>

Sources on Intellidyne Unit Installation at Six Key Food Supermarkets?

Formatted: No underline

1. ERS spreadsheet derivation of deemed savings factors for demand control ventilation. DCV Deemed savings Analysis. Based on DOE-2 default space occupancy profiles and initially developed for NYSERDA in 2010, revised to reflect typical New Jersey weather data.

Low Flow Devices *Faucet Aerators, Showerheads, and Pre-rinse Spray Valves*

The following algorithm details savings for low-flow showerheads, and faucet aerators in residential, multi-family, and pre-rinse spray valves some public sectors. These devices save water heating energy by reducing the total flow rate from hot water sources.

The measurement of energy savings associated with these low-flow devices is based on algorithms with key variables obtained from analysis by the Federal Energy Management Program (FEMP), published data from the Environmental Protection Agency water conservations studies, and customer information provided through Fisher-Nickel's Life Cycle cost calculators, on the application form. The energy values are in Btu for natural gas fired water heaters or kWh for electric water heaters.

Low Flow Faucet Aerators and Showerheads

Algorithm

Btu or kWh Fuel

Algorithms

$$\text{Savings/yr} = N \times (60 \times H \times D \times (F_{\text{base}} - F_{\text{eff}}) \times (F_b - F_g) \times (8.33 \times DT \times (1/\text{EFF}) / C)$$

Definition of Variables

- 60N = Number of fixtures
- H = Hours per day of device usage
- D = Days per year of device usage
- F_b = Baseline device flow rate (gal/m)
- F_g = Low flow device flow rate (gal/m)
- 8.33 = Heat content of water (Btu/gal/°F)
- DT = Difference in temperature (°F) between cold intake and output
- EFF = Efficiency of water heating equipment
- C = Conversion factor from hoursBtu to minutes therms or kWh = (100,000 for gas water heating (Therms), 3,413 for electric water heating (kWh))

Summary of Inputs

Low Flow Faucet Aerators and Showerheads

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Source</u>
<u>N</u>	<u>Variable</u>		<u>Application</u>
<u>H</u>	<u>Fixed</u>	<u>Aerators</u> <u>30 minutes</u>	<u>1</u>

Formatted: Heading 3, Page break before

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font: 12 pt, Not Bold, Underline, Font color: Auto, (none), Not Small caps

Formatted: English (U.S.)

Formatted: Heading 4, Space After: 6 pt

Formatted: Indent: First line: 0.25"

Formatted: Underline, (none)

Formatted: Normal, Level 4, Keep with next

Formatted: Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

		<u>Shower heads</u> <u>20 minutes</u>	
<u>D</u>	<u>Fixed</u>	<u>Aerators</u> <u>260 days</u>	<u>1</u>
		<u>Shower heads</u> <u>365 days</u>	
<u>E_b</u>	<u>Fixed</u>	<u>Aerators</u> <u>2.2 gpm</u>	
		<u>Showerhead</u> <u>2.5 gpm</u>	
<u>E_q</u>	<u>Fixed</u>	<u>Aerators</u> <u><=1.5 gpm (kitchen)</u> <u><=0.5 gpm (public restroom)</u> <u><=1.5 gpm (private restroom)</u>	<u>2,3,4</u>
		<u>Showerheads</u> <u><=2 gpm</u>	
<u>DT</u>	<u>Fixed</u>	<u>Aerators</u> <u>25°F</u>	<u>5</u>
		<u>Showerheads</u> <u>50°F</u>	<u>6</u>
<u>EFF</u>	<u>Fixed</u>	<u>97% electric</u> <u>80% natural gas</u>	<u>7,8</u>

Sources

1. FEMP Cost Calculator; located at: <https://energy.gov/eere/femp/energy-cost-calculator-faucets-and-showerheads-0#output>.
2. EPA WaterSense requirements for faucet aerators; available at: <https://www.epa.gov/watersense/bathroom-faucets>.
3. Department of Energy, Best Management Practice #7, Faucets and Showerheads; available at: <https://energy.gov/eere/femp/best-management-practice-7-faucets-and-showerheads>
4. EPA WaterSense requirements for showerheads; available at: <https://www.epa.gov/watersense/showerheads>.
5. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Calculated using T_{shower} and T_{main} for Faucet – Low-flow aerator measure in NYC. Values for both T_{faucet} and T_{main} found on p. 81.
6. New York State Joint Utilities, *New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs*, V6, April 2018. Calculated using T_{sh} and T_{main} for Showerhead – Low-flow measure in NYC. Values for both T_{shower} and T_{main} found on p. 92.

7. [New York State Joint Utilities, New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs, V6, April 2018. From “Baseline Efficiencies from which Savings are Calculated section with table on p. 88.](#)
8. [ASHRAE Standards 90.1-2007. Energy Standard for Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research-technology/standards--guidelines>.](#)

Low Flow Pre-rinse Spray Valves

Algorithm

$$\text{Btu or KWh Fuel Savings/yr} = N * H * D * (F_b - F_q) * (8.33 * DT / \text{EFF}) / C$$

Definition of Variables

N = Number of fixtures

H = Hours per day of device usage

D = Days per year of ~~facility operation~~ device usage

~~F_{base}~~~~F_b~~ = Baseline device flow rate (gal/m)

~~F_{eff}~~~~F_q~~ = Low flow device flow rate (gal/m)

8.33 = Heat content of water (Btu/gal/°F-)

DT = Difference in temperature (°F) between cold intake and output

Eff = Percent efficiency of water heating equipment

C = Conversion factor from Btu to Therms or kWh \equiv (100,000 for gas water heating (Therms), 3,413 for electric water heating (kWh))

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Not Superscript/ Subscript

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: First line: 0.25", Space Before: 3 pt, After: 3 pt

← **Formatted:** Indent: Left: 0.25", Space Before: 3 pt, After: 3 pt

Summary of Inputs

Low Flow Devices Pre-Rinse Spray Valves

Component	Type	Value	Source
N	Variable		Application
H	Fixed	3 for pre-rinse spray valves 1.06 hours	1
<u>D</u>	<u>Fixed</u>	344 days	<u>1</u>
<u>HE_p</u>	Fixed	20 minutes for showerheads 30 minutes for aerators 1.6 gpm	2
<u>D</u>	<u>Variable</u>		<u>Application</u>
<u>F_{base}</u>	<u>Variable</u>		<u>Application</u>
<u>F_{eff}E_q</u>	Variable	Max of 1.0 gpm for lavatory aerators, 2.2 for kitchen aerators and 2.0 gpm for showerheads per EPA's Water Sense Label ≤ 1.28 gpm	<u>Application 3</u>
DT	Fixed	50°F for showerheads and faucet aerators, 70°F for pre-rinse spray valves 75°F	<u>14</u>
Eff	Variable	default of <u>97%</u> electric <u>80%</u> for natural gas water heaters and <u>95%</u> for electric water heaters	<u>Application 5, 6</u>

Sources:

1. Fisher Nickel Life Cycle cost calculator
2. FEMP Cost Calculator located at http://www1.eere.energy.gov/femp/technologies/cep_faucets_showerheads_calculator.html

Demand Control Ventilation Using CO₂ Sensors

Demand control ventilation (DCV) monitors indoor air CO₂ content as a result of occupancy production levels and uses this data to regulate the amount of outdoor air that is permitted for ventilation. In order to ensure adequate air quality, standard ventilation systems permit outside air based on estimated occupancy levels in CFM/occupant. However, during low occupancy hours, the space may become over-ventilated due to decreased CO₂ levels. This air must be conditioned and, therefore, unnecessary ventilation results in wasted energy. DCV reduces unnecessary outdoor air intake by

Formatted: Font: Not Bold

Formatted: Left, Don't keep with next

Formatted: Table Header, Left, Don't keep with next

Formatted Table

Formatted: Table Header, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells

Formatted Table

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted Table

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Table Cells, Left

Formatted: Table Cells

Formatted: Table Cells

Formatted: Font: Bold

Formatted: Centered, Keep with next

Formatted: Heading 4, Space After: 6 pt

Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

~~regulating ventilation based on actual CO₂ levels, saving energy. DCV is most suited for facilities where occupancy levels are known to fluctuate considerably.~~

The measurement of energy savings associated with DCV is based on hours of operation, occupancy schedule, return air enthalpy, return air dry bulb temperature, system air flow, outside air reduction, cooling system efficiency, and other factors. As a conservative simplification of complex algorithms, DCV is assumed to save 5% of total facility HVAC load in appropriate building types based on FEMP DCV documentation.

Algorithms

Electric Savings (kWh) = 0.05 * HVAC_E

Gas Savings (Therms) = 0.05 * HVAC_G

Definition of Variables

HVAC_E = Total electric HVAC consumption (kWh)

HVAC_G = Total gas HVAC consumption (Therms)

Demand Control Ventilation Using CO₂ Sensors

Component	Type	Value	Source
HVAC _E	Variable		Application
HVAC _G	Variable		Application

Pipe Insulation

~~Un-insulated hot water carrying pipes lose considerable heat to outside air due to high thermal conductivity. In order to reduce this heat loss, pipes can be covered with a layer of fiberglass insulation, which will reduce source heating demand, resulting in significant energy savings.~~

The measurement of energy savings associated with pipe insulation is based on the length of the supply pipe, pipe diameter, relative thermal conductivity of bare and insulated piping and the temperature difference between supplied water and outside air temperature as indicated in the EPRI report referenced below. The baseline case is un-insulated copper pipe and the default proposed case is 0.5" of fiberglass insulation.

Algorithms

Energy Savings (kWh) = (L * (HLC_{base} - HLC_{ee}) / C) * ΔT * 8,760

Formatted: Underline, (none)

Formatted: Underline, (none)

Formatted: Don't keep with next, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Formatted: Space After: 1 pt, Don't keep with next

Formatted Table

Formatted: Space After: 1 pt

Formatted: Underline

Definition of Variables

L = Length of pipe from water heating source to hot water application (ft)

HLC_{base} = Pipe heat loss coefficient by pipe diameter (baseline) (BtuH⁻¹°F-ft)

HLC_{ee} = Pipe heat loss coefficient by pipe diameter (proposed) (BtuH⁻¹°F-ft)

C = Conversion from Btu to kWh or Therms (3,413 for kWh (Electric Water Heating); 100,000 for Therms (Gas Water Heating))

ΔT = Average temperature difference between supplied water and outside air temperature (°F)

8,760 = Hours per year

1. EPA WaterSense Specification for Commercial Pre-Rinse Spray Valves Supporting Statement, September 19, 2013, Appendix A, Page 7.
2. EPA Energy Policy Act of 2005, p. 40, Title I, Subtitle C.
3. EPA WaterSense Specification for Commercial Pre-Rinse Spray Valves, available at: <https://www.epa.gov/watersense/pre-rinse-spray-valves>.
4. NY, *Standard Approach for Estimating Energy Savings*, V4, April 2016. Calculated using T_{heater} and T_{main} for Low-flow Pre-rinse spray valve measure. Values for both T_{sh} and T_{main} found on p. 184, Table 1 and p. 184, Table 2, respectively.
5. NY, *Standard Approach for Estimating Energy Savings*, V4, April, p. 177, Table 1.
6. ASHRAE Standards 90.1-2007, *Energy Standard for Buildings Except Low Rise Residential Buildings*; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.

Pipe Insulation

Formatted: Heading 3, Left, Page break before, Don't keep with next

This measure applies to insulation installed on previously bare hot water distribution piping located in unconditioned spaces. Deemed savings factors were derived using the North American Insulation Manufacturers Association, 3E Plus Version 4.1 heat loss calculation tool. The savings factors represent average values for copper or steel pipe with mineral fiber or polyolefin tube pipe insulation. Savings are a function of pipe size and insulation thickness. A table of savings factors for nominal pipe size ranging from ½ inch to 4 inches, with insulation ranging from ½ inch to 2 inches thick is provided.

The savings factors are based on a fluid temperature of 180°F, and an ambient temperature of 50°F, resulting in a temperature differential of 130°F. If the actual temperature differential varies significantly from this value, the reported savings should be scaled proportionally.

The default value for annual operating hours represents the average annual hours when space heating is required. For non-space heating applications, the value should be adjusted to reflect the annual hours when the hot fluid is circulated.

Algorithms

Fossil Fuel Source:

Fuel Savings (MMBtu/yr) = SF * L * Oper Hrs / EFF

Electric Source:

Energy Savings (kWh/yr) = SF * L * Oper Hrs / EFF / C

Scaling: Only applicable if differential between the fluid temperature and space temperature is significantly different than 130°F. If this is the case, the fuel or electric savings calculated with the above formulas should be multiplied by the resulting scaling factor derived as:

Scaling Factor (unitless) = (FT – ST)/130

Fuel or electric savings calculated using the derived savings factors should be multiplied by the scaling factor.

Scaled Savings (MMBtu/year or kWh/yr) = Calculated Savings * Savings Factor

Definition of Variables

SF = Savings factor derived from #E Plus Version 4.1 tool, Btu/hr-ft see table below

L = Length of pipe from water heating source to hot water application, ft

Oper Hrs = hours per year fluid flows in pipe, hours

EFF = Efficiency of equipment providing heat to the fluid

C = Conversion factor from Btu to kWh = 3.413 for electric water heating (kWh)

FT = Fluid Temperature (°F)

ST = Space temperature (°F)

Summary of Inputs

Pipe Insulation

Component	Type	Value	Source
<u>SF</u>	<u>Fixed</u>	<u>See Table Below</u>	<u>1</u>
L	Variable		Application
<u>HLC_{base}Oper Hrs</u>	Fixed	<u>4,282 hrs/year (default value reflects average heating season hours) See Table Below</u>	<u>2</u>
<u>HLC_{ee}EFF</u>	Fixed	<u>97% electric</u> <u>80% natural gas See Table Below</u>	<u>3, 4</u>
<u>ATFT</u>	Variable	<u>Default is 65°F</u>	<u>EPRI</u> <u>Study Application</u>
<u>ST</u>	<u>Variable</u>		<u>Application</u>

- Formatted: Table Header, Left, Don't keep with next
- Formatted: Table Header, Left
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Table Cells
- Formatted: Table Cells, Left
- Formatted: Table Cells
- Formatted: Space After: 10 pt, Line spacing: Multiple 1.15 li, Allow hanging punctuation, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Font Alignment: Auto

Pipe Heat Loss Coefficient Table

Pipe Diam. (in.)	HLC _{base}	HLC _{ee}
0.75	0.43	0.25
1.00	0.54	0.29
1.25	0.64	0.33
1.50	0.76	0.36
2.00	0.94	0.42
2.50	1.00	0.48
3.00	1.30	0.56
4.00	1.70	0.69

Savings Factor

Nominal Pipe Size, Inches	Savings, Btu/hr-ft			
	0.5" Insulation	1.0" Insulation	1.5" Insulation	2.0" Insulation
0.50	47	53	56	57
0.75	58	64	68	70
1.00	72	82	85	87
1.25	89	100	107	108
1.50	100	115	120	125
2.00	128	143	148	153
2.50	153	171	182	185
3.00	195	221	230	236
3.50	224	241	248	253
4.00	232	263	274	281

Sources:

Engineering Methods for Estimating the Impacts of Demand Side Management Programs, Volume 2, EPRI, 1993

1. North American Insulation Manufacturers Association, 3E Plus, Version 4.1, heat loss calculation tool, August 2012.
2. NOAA, Typical Meteorological Year (TMY3) weather data – Newark, Trenton, and Atlantic City averaged.
3. ASHRAE Standards 90.1-2007. Energy Standard for Buildings Except Low Rise Residential Buildings; available at: <https://www.ashrae.org/standards-research--technology/standards--guidelines>.
4. New York State Joint Utilities, New York Standard Approach for Estimating Energy Savings from Energy Efficiency Programs, V6, April 2018. From “Baseline Efficiencies from which Savings are Calculated section with table on p. 88.

Formatted: Heading 4, Space After: 6 pt

Lighting and Lighting Controls

For lighting and lighting control projects performed by Direct Install programs, use the C&I prescriptive lighting tables for the lighting types identified within those tables. For any fixtures not listed on the table, go to the source table for that fixture. If the fixture is not on the source table, then use manufacture cut sheets for replacement kW to calculate the savings.

Eligible measures include:

Prescriptive Lighting

T8

T5

CFL Screw-In

LED Screw-In

LED Linear Tubes

LED Hard-Wired Fixtures

Lighting Controls

Occupancy Sensors

High-Bay Occupancy Sensors

Photocell with Dimmable Ballast

Formatted: Page break before

Formatted: Space Before: 6 pt, After: 6 pt

C&I Large Energy Users Incentive Program

The purpose of the program is to foster self-investment in energy-efficiency, and combined heat and power projects while providing necessary financial support to large commercial and industrial utility customers in New Jersey.

Protocols

Please refer to the Pay for Performance Existing Buildings protocols to calculate demand and energy savings for the Large Energy Users Program. ~~If a project addresses a specific end-use technology, protocols for that technology should be used.~~

Formatted: Indent: Left: 0"

C&I Customer-Tailored Energy Efficiency Pilot Program

The purpose of the program is to better serve the needs of specific commercial and industrial customers whose usage is too large for them to qualify for the Direct Install program, but too low for the Large Energy Users Program.

Protocols

Please refer to the Pay for Performance Existing Buildings protocols to calculate demand and energy savings for ~~the Large Energy Users~~ comprehensive projects in the Customer Tailored Pilot Program. ~~If a project addresses a specific end-use technology, protocols for that technology should be used.~~

Formatted: Indent: Left: 0"

Renewable Energy Program Protocols

SREC Registration Program (SRP)

The energy and demand impacts for customer sited solar PV generation systems participating in the program are based on fixed assumptions which are applied to the total project system capacity. The annual electricity generation is derived by multiplying the estimated annual production factor of 1,200 kWh per kW by the total system capacity (kW) to yield the estimated annual output (kWh).⁷⁰ The combined values for all projects participating in a specified period are then summed up and converted to MWh for reporting purposes.

~~Renewable Non-SRP~~

~~Renewable Electric Storage~~

~~The impact of Renewable Electric Storage, if any on net renewable energy generation will be analyzed over the coming year based upon quarterly performance reporting that is required of participants in this program.~~

⁷⁰ Estimated annual production factor is based on combined average calculation of the PV Watts estimated annual output for the Newark and Atlantic City weather stations.

Appendix A Measure Lives

NEW JERSEY STATEWIDE ENERGY-EFFICIENCY PROGRAMS Measure Lives Used in Cost-Effectiveness Screening

April 2012

If actual measure lives are available through nameplate information or other manufacturing specifications with proper documentation, those measure lives should be utilized to calculate lifetime savings.- In the absence of the actual measure life, Protocol measure lives listed below should be utilized. Measure life values listed below are from the California Database of Energy Efficient Resources⁷¹ (DEER) unless otherwise noted.

PROGRAM/Measure	Measure Life
Residential ProgramsSector,	
Energy Star AppliancesLighting End Use	
ES Refrigerator post 2004CFL	125
ES Refrigerator 2004LED	1215
HVAC End Use	
Central Air Conditioner (CAC)	15
CAC QIV	15
Air Source Heat Pump (ASHP)	15
Mini-Split (AC or HP)	17
Ground Source Heat Pumps (GSHP)	25
Furnace High Efficiency Fan	15
Heat Pump Hot Water (HPHW)	10
Furnaces	20
Boilers	20
Combination Boilers	20
Boiler Reset Controls	10
Heating and Cooling Equipment Maintenance Repair/Replacement	10
Thermostat Replacement	11
Hot Water End-Use	
Storage Water Heaters	11
Instantaneous Water Heaters	20
Building Shell End-Use	

Formatted: Left

Formatted: Space Before: 6 pt, After: 6 pt

Formatted: Font color: Black

Formatted: Left, Space After: 1 pt

Formatted: Space After: 1 pt

Deleted Cells

Formatted: Font: Not Italic, No underline

Formatted Table

Formatted: No underline

Formatted: Centered, Space After: 1 pt

Formatted: Space After: 1 pt

Formatted: Font: Bold, Font color: Auto

Formatted: Font color: Auto

Formatted: Indent: First line: 0 ch, Space After: 1 pt

Formatted: Font: 10 pt, Font color: Auto

Formatted: Centered, Space After: 1 pt

Formatted: Font: 10 pt

Formatted: Indent: First line: 0 ch, Space After: 1 pt

Formatted: Font: 10 pt, Font color: Auto

Formatted: Centered, Space After: 1 pt

Formatted: Font: 10 pt

⁷¹ <http://www.deeresources.com/>

PROGRAM/Measure	Measure Life
<u>Air Sealing</u>	<u>15⁷²</u>
<u>Duct Sealing and Repair</u>	<u>18</u>
<u>Insulation Upgrades</u>	<u>20</u>

Formatted: Left, Space After: 1 pt

Formatted: Font color: Black

Formatted: Space After: 1 pt

⁷² Mid-Atlantic TRM V7, <http://www.neep.org/mid-atlantic-technical-reference-manual-v7> and NY TRM V6, <http://www3.dps.ny.gov/W/PSCWeb.nsf/All/72C23DECFE52920A85257F1100671BDD>

E-star T-stat (HP)	15
GSHP	30
CAC-15	15
ASHP-15	15
Residential Gas HVAC	-
High Efficiency Furnace	20
High Efficiency Boiler	20
High Efficiency Gas DHW	10
E-Star T-stat	15
Boiler Reset Controls	7
Low Income Program	-
Air sealing electric heat	30
Duct Leak Fossil Heat & CAC	15
typical fossil fuel heat	17
typical electric DHW pkg	10
typical fossil fuel DHW pkg	10
screw in CFLs	6.4
high performance fixtures	20
fluorescent torchieres	10
TF-14	20
TF-16	20
TF-18	20
SS-20	20
TF-24	20
SS-22	20
TF-25	20
audit fees	20
Attic Insulation-ESH	30
Duct Leak-ESH	15
T-Stat-ESH	5
HP charge air flow	8
electric arrears reduction	4
gas arrears reduction	4
Home Performance with ENERGY STAR	-
Blue Line Innovations — PowerCost Monitor™	5

PROGRAM/Measure	Measure Life
Non-Residential Programs	-
C&I Construction	-
Commercial Lighting — New	15
Commercial Lighting — Remodel/Replacement	15

Commercial Lighting Controls — Remodel/Replacement	18
Commercial Custom — New	48
Commercial Chiller Optimization	48
Commercial Unitary HVAC — New — Tier 1	45
Commercial Unitary HVAC — Replacement — Tier 1	45
Commercial Unitary HVAC — New — Tier 2	45
Commercial Unitary HVAC — Replacement Tier 2	45
Commercial Chillers — New	25
Commercial Chillers — Replacement	25
Commercial Small Motors (1-10 HP) — New or Replacement	20
Commercial Medium Motors (11-75 HP) — New or Replacement	20
Commercial Large Motors (76-200 HP) — New or Replacement	20
Commercial VSDs — New	15
Commercial VSDs — Retrofit	15
Commercial Air Handlers Units	20
Commercial Heat Exchangers	24
Commercial Burner Replacement	20
Commercial Boilers	25
Commercial Controls (electric/electronic)	45
Commercial Controls (Pneumatic)	40
Commercial Comprehensive New Construction Design	48
Commercial Custom — Replacement	48
Industrial Lighting — New	15
Industrial Lighting — Remodel/Replacement	15
Industrial Unitary HVAC — New — Tier 1	45
Industrial Unitary HVAC — Replacement - Tier 1	45
Industrial Unitary HVAC — New — Tier 2	45
Industrial Unitary HVAC — Replacement Tier 2	45
Industrial Chillers — New	25
Industrial Chillers — Replacement	25
Industrial Small Motors (1-10 HP) — New or Replacement	20
Industrial Medium Motors (11-75 HP) — New or Replacement	20
Industrial Large Motors (76-200 HP) — New or Replacement	20
Industrial VSDs — New	45
Industrial VSDs — Retrofit	45
Industrial Custom — Non-Process	48
Industrial Custom — Process	40
Industrial Air Handler Units	20
Industrial Heat Exchangers	20
Industrial Burner Replacements	20
Small Commercial Gas Furnace — New or Replacement	20

Infrared Heating	17
Small Commercial Gas Boiler — New or Replacement	20
Small Commercial Gas DHW — New or Replacement	10
C&I Gas Absorption Chiller — New or Replacement	25
C&I Gas Custom — New or Replacement (Engine Driven Chiller)	25
C&I Gas Custom — New or Replacement (Gas Efficiency Measures)	18

PROGRAM/Measure	Measure Life
Non-Residential Programs	-
Building O&M	-
O&M savings	3
Compressed Air	-
Compressed Air (GWh participant)	8
Refrigeration	-
Evaporator Fan Control	10
Cooler and Freezer Door Heater Control	10
Polyethylene Strip Curtains	4
Food Service	-
Fryers	12
Steamers	10
Griddles	12
Ovens	12

PROGRAM/Measure	Measure Life
Solar Panels	25
Combined Heat & Power (CHP) System ≤ 1 MW ⁷⁶	15
Combined Heat & Power (CHP) System > 1 MW ⁷⁷	20
Fuel Cells	20

* For custom applications, projects will be evaluated upon industry/multiplier data but not to exceed value in above table unless authorized by the Market Manager. Reported savings will be calculated per measure life indicated in this table.

⁷⁶ Size of individual prime-mover, not the overall system. For example, a project with three 75kW internal combustion engines should be assigned a 17-year measure life for small systems.

⁷⁷ Size of individual prime-mover, not the overall system. For example, a project with three 75kW internal combustion engines should be assigned a 17-year measure life for small systems.

- Formatted: Font color: Black
- Formatted: Space After: 1 pt
- Formatted Table
- Formatted: Space After: 1 pt
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Space After: 1 pt
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Font color: Black
- Formatted: Space After: 1 pt
- Formatted: Font color: Black