New Jersey's Clean Energy Program - Refrigerator/Freezer Recycling Program

Glossary of Terms

CFC-11

This chlorofluorocarbon was used as a blowing agent for polyurethane foam insulation for refrigerators and freezers manufactured between 1965 and 1993.

• CFC-12

Commonly known by its trade name Freon,[®] this chlorofluorocarbon was used as a refrigerant in the sealed cooling system for units manufactured before 1993. Both CFC-11 and CFC-12 are extreme ozone depleters with high global warming potential.

HFC-134a

Hydrofluorocarbon replaced CFC-12 as the refrigerant after 1993, in accordance with the U.S. schedule for phase-out under the guidelines of the Montreal Protocol. This chemical is non-ozone depleting, but is still a global warmer.



HCFC-141b

Hydrochlorofluorocarbon replaced CFC-II as the blowing agent for polyurethane foam insulation for units manufactured after 1993.

PCBs

Polychlorinated Biphenyls are hazardous materials sometimes found in starting capacitors of large refrigerators and freezers manufactured before 1979, when PCBs were banned.

ABS

Acrylonitrile Butadiene Styrene is a flexible molded plastic commonly used for interior linings of appliances and for shelves and drawers.

HIPS

High Impact Polystyrene is also used for the same purpose of ABS but is about 50 percent less expensive.

• LEXAN®

Lexan is a trade name for a clear or tinted plastic used for drawers in high-end model refrigerators.



